

SUBMITTAL STANDARD ITEM	ITEM TYPE SLIDE GATE OPERATOR	TITLE HEAVY DUTY HDL24UL	LAST UPDATED DECEMBER 22, 2021
----------------------------	----------------------------------	-----------------------------	-----------------------------------



OPERATOR OVERVIEW:

MODEL:

HDSL24UL

GATE LENGTH MAX:

75 FEET

GATE WEIGHT MAX:

3000 LBS

RATE OF TRAVEL:

.5 FT/SEC TO 1 FT/SEC

TEMPERATURE:

W/O HEATER: -4°F to 140°F (-20°C to 60°C)

W/ OPTIONAL HEATER: -40°F to 140°F (-40°C to 60°C)

WARRANTY:

5 YEAR COMMERCIAL; 7 YEAR RESIDENTIAL

ETL LISTED UL35:

SPECIFIC TO LOCATION : I, II, III, IV AVAILABLE

USER CONTROLS:

BUILT IN RADIO RECEIVER, FULL SYSTEM COMPATIBLE

POWER SPECS:

VOLTAGE:

INPUT: 4A AT 120V

ACCESSORY POWER:

INPUT: 6A AT 120V

MAIN AC SUPPLY:

120 V

MAIN SUPPLY (MOTOR):

24VDC

HEATER DRAW (OPTIONAL):

325W (120 VAC ONLY)

DAILY CYCLE RATE AC POWER:

CONTINUOUS

FUSE PROTECTION BATTERY:

30A

FUSE PROTECTION DC POWER:

30A

BATTERY BACKUP:

RUN GATE TO OPEN

RUN GATE UP TO 100 CYCLES

MAXIMUM WIRE LENGTH		
AMERICAN WIRE GAUGE (AWG)	STANDARD OPERATOR	
	120 VAC, 10A (includes fully loaded outlets)	120 VAC, 4A
14	75	150
12	125	225
10	200	360
8	300	600
6	500	900
4	800	1,500
Chart assumes: copper wire, 65°C, 5% drop		



2525 NE COLUMBIA BLVD | PORTLAND, OR 97211

SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1-888.813.6772

SERVING THE PORTLAND/VANCOUVER METRO AREA SINCE 1984