

SUBMITTAL STANDARD ITEM	ITEM TYPE SWING GATE OPERATOR	TITLE HEAVY DUTY HDSW24UL	LAST UPDATED DECEMBER 22, 2021
----------------------------	----------------------------------	------------------------------	-----------------------------------



OPERATOR OVERVIEW:

MODEL:

HDSW24UL

GATE LENGTH MAX:

22 FEET

GATE WEIGHT MAX:

4500 LBS

RATE OF TRAVEL:

13 TO 36 SECONDS TO 90 DEGREE OPEN

TEMPERATURE:

W/O HEATER: -4°F to 140°F (-20°C to 60°C)

W/ OPTIONAL HEATER: -40°F to 140°F (-40°C to 60°C)

WARRANTY:

5 YEAR COMMERCIAL; 7 YEAR RESIDENTIAL


ETL LISTED UL35:

SPECIFIC TO LOCATION : I, II, III, IV AVAILABLE

USER CONTROLS:

BUILT IN RADIO RECEIVER, FULL SYSTEM COMPATIBLE

CAPACITIES STANDARD ARM



CAPACITIES LONG ARM



POWER SPECS:

VOLTAGE:

INPUT: 4A AT 120V

ACCESSORY POWER:

INPUT: 6A AT 120V

MAIN AC SUPPLY:

120 V

MAIN SUPPLY (MOTOR):

24VDC

HEATER DRAW (OPTIONAL):

325W (120 VAC ONLY)

DAILY CYCLE RATE AC POWER:

CONTINUOUS

FUSE PROTECTION BATTERY:

30A

FUSE PROTECTION DC POWER:

30A

BATTERY BACKUP:

RUN GATE TO OPEN

RUN GATE UP TO 100 CYCLES

MAXIMUM WIRE LENGTH

AMERICAN WIRE GAUGE (AWG)	STANDARD OPERATOR	
	120 VAC, 10A (includes fully loaded outlets)	120 VAC, 4A
14	75	150
12	125	225
10	200	360
8	300	600
6	500	900
4	800	1,500

Chart assumes: copper wire, 65°C, 5% drop



2525 NE COLUMBIA BLVD | PORTLAND, OR 97211
 SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1-888.813.6772
 SERVING THE PORTLAND/VANCOUVER METRO AREA SINCE 1984