

SUBMITTAL STANDARD ITEM	ITEM TYPE SLIDE GATE OPERATOR	TITLE HEAVY DUTY IHSL24UL	09/16/2024
----------------------------	----------------------------------	------------------------------	------------



OPERATOR OVERVIEW:

MODEL:
 IHSL24UL
 GATE WEIGHT MAX:
 5500 LBS
 RATE OF TRAVEL:
 1 FT/SEC
 TRAVEL DISTANCE:
 4 - 90 FEET
 TEMPERATURE:
 W/O HEATER: -4°F to 140°F (-20°C to 60°C)
 W/ HTR HEATER: -40°F to 140°F (-40°C to 60°C)
 WARRANTY:
 5 YEAR COMMERCIAL
 ETL LISTED UL35:
 SPECIFIC TO LOCATION : II, III, IV AVAILABLE

POWER SPECS:

VOLTAGE:
 24VDC TRANSFORMER RUN/ BATTERY
 BACKUP
 ACCESSORY POWER:
 24 VDC, 1A MAX FOR ON + SW
 MAIN AC SUPPLY:
 120V, 13.0 AMPS
 DAILY CYCLE RATE AC POWER:
 CONTINUOUS

IHSL24UL MAXIMUM WIRE LENGTH							
AMERICAN WIRE GAUGE (AWG)	STANDARD OPERATOR			3PHCONV kit powering operator + heater + 1 Amp on outlets			
	120 VAC, 13 A (includes fully loaded outlets)	120 VAC, 7 A	240 VAC, 3.5 A	208 VAC, 5.2 A	240 VAC, 4.5 A	480 VAC, 2.3A	575 VAC, 1.9 A
14	75	140	600	330	440	1,700	2,500
12	120	225	900	525	700	2,700	4,000
10	200	360	1,440	840	1,100	4,400	6,300
8	300	600	2,300	1,300	1,800	6,900	10,000
6	500	900	3,600	2,100	2,800	11,000	16,000
4	800	1,400	5,800	3,400	4,500	17,000	25,000

Chart assumes: copper wire, 65°C, 5% drop