

SUBMITTAL	ITEM TYPE	TITLE	LAST UPDATED
KEYPAD	WIRELESS KEYPAD	KPW250	APRIL 12, 2018



KPW250



FEATURE	KPW250
Code and Radio Frequency	• LiftMaster® Security+ 2.0® (default) – Delivered on tri-band 310/315/390 MHz • LiftMaster Security+® 315 MHz • LiftMaster Security+ 390 MHz • Linear® Multi-Code® 300 MHz
PIN Capacity	• Up to 250 permanent 4-digit PINs • Up to 10 unique temporary PINs
Power	9V lithium battery with battery life up to 5 years (based on 25 activations per day)
Operating Temperature	–4°F to 140°F (–20°C to 60°C)
Storage and Shipping Temperature Range	–40°F to 140°F (–40°C to 60°C)
Operating Humidity	5% to 95% (non-condensing)
Weatherization	Electronics meet NEMA 4X water protection requirements; housings meet or exceed NEMA 3R
Enclosure	Zinc-alloy metal front cover; high-impact polycarbonate back housing
Lockable Housing	Restricts access to the reset button
Memory	Non-volatile (codes are saved when battery is replaced)
Mounting	Compatible for surface mount or standard pedestal mount (4 x 4 in.)
Operating Range	Up to 500 ft. (open field)
Dimensions	4.3" W x 6" H x 1.75" D
Shipping Weight	1.2 lbs.
Warranty	1 Year limited

4.3"



1.75"



2525 NE COLUMBIA BLVD | PORTLAND, OR 97211
SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1-888.813.6772

"SERVING THE PORTLAND/VANCOUVER METRO AREA SINCE 1984"