

SUBMITTAL	ITEM TYPE	TITLE
ACCESS CONTROL	READERS & KEYPADS	LIFTMASTER SRDRST/ SRDRKP

FEATURES

COMMUNICATION

MOBILE BLE; 125 KHz PROXIMITY; 13.56 MHz SMART

COMPATIBILITY

WORKS WITH MYQ COMMUNITY (iOS, ANDROID)

CREDENTIAL RANGE

TAP: WITHIN 3" OF READER

TOUCH: PHONE MUST BE WITHIN 2' OF READER. USER MUST PHYSICALLY TOUCH THE READER

ALERT: WILL POP UP ON PHONE WITHIN 10' OF THE READER

USER FEEDBACK

LED BAR (RED, GREEN, AMBER) & BEEPER

SPECS

CONNECTIVITY

DEPENDS ON DOOR CONTROLLER

POWER SUPPLY VOLTAGE

5-16VDC

COMMUNICATIONS

OSDP AUTODETECT - COMMUNICATION WITH UP TO 4 READERS W/ CAPXLV2

WIEGAND INPUT FORMAT

26 BIT, 30 BIT, 37 BIT (HID)/ (TRANSCORE)

OPERATING TEMPERATURE

-35° to 66°C, 95% HUMIDITY



Cable Length Recommendations

Weigand	
Feet	AWG
200	22
300	20
500	18

SRDRKP

- STANDARD 10-KEY KEYPAD
- 145 mA AVERAGE
- 195 mA PEAK

SRDRST

- STANDARD SINGLE GANG
- 120 mA AVERAGE
- 170 mA PEAK



2525 NE COLUMBIA BLVD PORTLAND, OR 97211
SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1.800.813.6772

"SERVING THE PORTLAND/ VANCOUVER METRO AREA SINCE 1984"