

STAR1000 COMMERCIAL ACCESS CONTROL RECEIVER

High-Capacity Gate and Commercial
Door Operator Access Control.



KEY FEATURES

HIGH CAPACITY

Holds up to 1,000 remote controls

NEVER LOSE YOUR DATA

Removable backup memory module

DELETE SINGLE REMOTE CONTROL

Easy to add, block and delete individual remotes

SMART

1,000 REMOTE CONTROL CAPACITY.

EASY TO PROGRAM USING THE LCD PROGRAMMING DISPLAY.

QUICKLY BLOCK LEARN PASSPORT LITE REMOTE CONTROLS (10 OR 100) A BOX AT A TIME.

TEMPORARILY SUSPEND USERS WITHOUT DELETING THEIR REMOTE CONTROL FROM MEMORY.

DELETE A SINGLE REMOTE CONTROL WITH ABILITY TO RE-USE THE MEMORY SLOT.

FUNCTIONS AS A STAND-ALONE CONTROLLER.

RELIABLE

DESIGNED FOR OUTDOOR ENVIRONMENTS RATED IP44 HOUSING.

BACKUP MEMORY MODULE – **NEVER LOSE YOUR PROGRAMMED REMOTE CONTROL DATA** AND EASILY UPDATE A NEW RADIO USING THE REMOVABLE BACKUP MEMORY MODULE. ALSO IDEAL FOR COPYING INTO A SECOND RECEIVER FOR ANOTHER ACCESS POINT.

SECURE

SECURITY+ 2.0® RECEIVER COMPATIBLE WITH ALL LIFTMASTER® SECURITY+ 2.0 REMOTE CONTROLS AND SAFEGUARDS ACCESS TO PROPERTY WITH ENCRYPTED SIGNAL TO OFFER EXTENDED RANGE WITH SECURITY+ 2.0

TOTAL SOLUTION ACCESSORIES:

3-BUTTON PASSPORT MAX REMOTE CONTROLS**

Visor, keychain and keychain w/proximity sensor 3-button remotes with unique credentialed IDs. Available individual or 100 pack.



PPV3M / PPK3M / PPK3PHM

1-BUTTON PASSPORT LITE REMOTE CONTROLS**

Cost-effective, credentialed 1-button access solutions for gate access only. Visor, keychain and keychain w/proximity sensor. Available in 10 or 100 pack.



PLV1-10 / PPLK1-10 / PPLK1PH-10 / PPLV1-100 / PPLK1-100 / PPLK1PH-100

LEARNING REMOTE CONTROLS

2- and 4-button remote controls compatible with Security+ 2.0 technology.



892LT / 894LT

AC TRANSFORMER

24VAC transformer.



95LM

REMOTE ANTENNA EXTENSION WITH MOUNTING KIT

Additional 15' and 25' coaxial cables to mount antenna away from metal for optimal range.



86LM / 86LMT

* Special order available for 100 packs that require specific facility code and start IDs.

†Passport Lite Remote Controls with Security+ 2.0 are specifically designed for gate access control and are not compatible with LiftMaster Garage Door Openers.

‡Passport MAX Remote Controls are compatible with LiftMaster Security+ 2.0 and backwards compatible Security+® (315 MHz or 390 MHz) Residential Garage Door Openers and Commercial Door Operators.

MASTERFUL ENGINEERING.

CAPACITIES



- 1,000 Device Capacity

POWER



- 9-30VAC, 9-42VDC Supply Voltage
- 50mA Maximum Operating Current
- 30mA Maximum Standby Current
- 6.0kV Minimum Surge Suppression

MECHANICS



- IP44 Rated Housing

DIMENSIONS



- 4" W x 6" H x 1.875" D

6"



4"

STANDARD SPECS.

WARRANTY

- 1-Year Limited

RADIO

- Code Format: Security+ 2.0®

OUTPUTS

- One Form C Relay Output. N/O and COM
- 1 Amp @ 24VAC/DC Relay Contact Rating

OPERATING TEMPERATURE **-40°F to 149°F**
(-40°C to 65°C)

OPERATING HUMIDITY

- 50% Rh

SHIPPING.

SHIPPING WEIGHT (in lbs.)



1.05

CARTON (1)

- 4.5" W x 9.75" H x 2.0" D
- Receiver
- Antenna
- Mounting Bracket with Two Screws
- Instruction Sheet

STORAGE/SHIP TEMPERATURE RANGE

- 40°F to 185°F @ 50% Rh
- 40°C to 85°C @ 50% Rh

For Support Tools and Training Videos, Visit
LiftMasterTraining.com

For More Information, Visit
LiftMaster.com/AccessControl

Sales Support: **800.282.6225**
Technical Support Center: **800.528.2806**
LiftMasterDealer.CustHelp.com/App/Ask