

APeX II Control Board

The Linear OSCO APeX II Gate Operator Control Board has been designed to operate with Linear's OSCO brand of slide, swing gate operators and barrier gate operators. It features on-board, low-voltage surge protection for lightning protection on all inputs. It also has plug-in loop detector capability (open, shadow/reset, reversing), as well as pluggable, European-style field wiring connectors. There are LED diagnostic lights and a built-in MegaCode radio that can program up to 40 handheld transmitters and two MGT gate edge transmitters, as well as an integrated three-button station (momentary contact: Open, Close, Stop). To simplify dual gate installation and operation, the APeX II is networkable, and allows accessory devices to be wired to either machine in a dual gate application. The APeX II Control Board also features automatically resetting fuses, and there are not dip switches or potentiometers to set. It has a dual seven segment LED display for programming and diagnostics. The APeX II Control Board will also bring soft-start/soft-stop capability to OSCO's line of commercial DC battery backup gate operators. The APeX II Control Board meets UL 325 (Pre January 2016 UL) Requirements and is CUL listed.

Features:

- Power: 24 VAC/VDC
- Easy-To-Set Current Sensing
- Built-In Paired Mode Capability
- Plug-In Loop Detector Capability
- Low Voltage Surge Protection For All Inputs
- Integral 3-Button, OPEN-CLOSE-STOP Controls
- UL325/991 Compliant And Canadian UL (CSA) Listed
- Pluggable Field Wire Connections And Diagnostic LEDs
- Two MGT Safety Edge Transmitters For Obstacle Sensing
- Integral MegaCode® Radio Receiver Supports 40 Transmitters
- DC Motor Board With Full PWM Soft-Start/Soft-Stop Functionality
- Single Module Design For 115V/230V, For Single Phase Applications
- Works With UL Approved 10K Resistance Entrapment Protection Devices
- *No Proprietary Entrapment Devices Are Required*

