

SUBMITTAL	ITEM TYPE	TITLE	LAST UPDATED
SAFETY DEVICE	TRANSMITTER DETECTOR	SG 10	AUGUST 20, 2018



FEATURES

- 1-10 m sensing range
- 34 to 274 cross scanning beams
- Active height of 650 mm to 2535 mm
- Detector length of 850 mm to 2800 mm
- Cable or plug connection
- Automatic sensitivity adjustment
- Water-resistant, slim line (12x30 mm) detector housing
- Power, output and signal status indicators
- 12 - 36 V DC supply voltage
- 5 wire, solid state relay output
- Test input
- Light/dark function via wire connection

Technical Data						
			46 mm channel spacing		92 mm channel spacing	
			SGT	SGR	SGT	SGR
Supply voltage			12-36 V dc			
Current consumption			Max. 100 mA	50 mA	Max. 100 mA	50 mA
Output rating Solid state			–	200 mA	–	200 mA
Short circuit protected			–	Yes	–	Yes
Reverse polarity protected			Yes			
Light source			Infrared (880 nm)	–	Infrared (880 nm)	–
Number of channels (diodes per detector)			16, 24, 32, 40, 48 or 56		8, 12, 16, 20, 24 or 28	
Number of cross scanning beams			74, 114, 154, 194, 234 or 274		34, 54, 74, 94, 114 or 134	
Active height			695, 1065, 1430, 1800, 2165 or 2535 mm		650, 1020, 1385, 1755, 2120 or 2490 mm	
Channel spacing			46 mm		92 mm	
Bottom spacing to Ch 1			25 mm			
Pinch point beam spacing			23 mm		46 mm	
Response time			–	< 165 ms	–	< 85 ms
Power on indicator			Green LED			
Output indicator			–	Yellow LED	–	Yellow LED
System status indicator			–	Red LED	–	Red LED
Time-out function			–			
Housing dimensions (w x d) Slim Line C			12 x 30 mm			
Housing material Profile Lens cover			Aluminium (black anodised)			
			Polycarbonate			
Connection			5 m fixed cable or 0,5 m cable with 5 pin, M12 plug			
Cable, PVC Ø 4,9 mm			3 x 0,20 mm²	5 x 0,20 mm²	3 x 0,20 mm²	5 x 0,20 mm²