

SUBMITTAL	ITEM TYPE	TITLE	LAST UPDATED
SAFETY DEVICE	EDGE CONTACT SENSOR	MILLER GATE EDGE CONTACT SENSORS	October 2, 2014 1:24 PM

MGO20, MGR20

COLOR:

BLACK (MGO), YELLOW (MGR)

LEAD WIRE:

SJTO, 18GA, 2' LENGTH

SENSITIVITY:

NORMAL 4PSI

ELECTRICAL DIAGRAM:

2 WIRE N.O. CONFIGURATION

ELECTRICAL REQUIREMENTS:

24 VOLT AC OR DC, 1/2 AMP

CONTACT ELEMENT:

ALUMAGLAS

MATERIALS:




BLACK EXTRUDED PVC OR ALUMINUM

TEMPERATURE RANGE:

-30°F TO 155°F

WIRE OUTLET LOCATION:

SPECIFY RIGHT, LEFT, OR END



CODE COMPLIANCE

GATE EDGE CONTACT SENSORS ARE REQUIRED WHEREVER A PINCH POINT IS CREATED BY A MOVING GATE. A PINCH POINT IS CONSIDERED TO BE ANY OBJECT BETWEEN 4" AND 16" AWAY FROM ANY MOVING PORTION OF THE GATE.