

PART NUMBER 714310VNQ

UL Listed and Rated Type TC, PLTC, NPLF or FPL Multi-Conductor Shielded Non-Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 4 Conductor twisted Bare Copper, Shielded with Water Block Tape and overall jacket. Inner Conductors are Thermoplastic Insulated, Nylon Sheathed, Heat, Oil & Gasoline Resistant 600 Volt TFFN Rated. Material suitable for underground use and indoor trays, "sunlight resistant". (Low voltage industrial process control circuits, Power-Limited circuits, Power-Limited fire alarm circuits, Power-Limited try cable PLTC)
CONDUCTOR	18 (7/26 Bare Copper)
INSULATION	PVC with Nylon
COLOR CODE	Black/Red/Orange/Blue
SHIELD	Aluminum Mylar
DRAIN WIRE	22 AWG 7 Strand Tinned Copper
JACKET	PVC .040"
JACKET COLOR	Black Jacket
MARKING	WINDY CITY WIRE A B C D E 0 1 2 3 4 5 6 7 8 9 18AWG (UL) TYPE TC-ER 600V 90C DRY 75C WET "DIR BUR" "SUN RES" PLTC, FPL OR NPLF MADE IN THE USA "SMARTWIRE WATERWARRIOR Â®"
OVERALL DIAMETER	.345" Nom.
CABLE WEIGHT	59 Lbs/Mft.
CAPACITANCE	68 pF/Ft. Nom.
IMPEDANCE	28 Ohms/Mft.
TEMPERATURE RATING	-20 C to 105 C / 600 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS	UL Standard 1277, UL 1424 Power limited fire alarm cables, UL 1425 Non-power limited fire alarm cables, UL 13 power limited circuit cables, NEC Articles 340, 725, 760, Made in the USA
------------------	---



All specifications referenced are nominal measurements unless otherwise noted.