

SUBMITTAL	ITEM TYPE	TITLE
GATE AUTOMATION	SWING GATE OPERATOR	VIKING X-390

FEATURES:

- COMPATIBLE WITH VIKING WIRELES PRODUCTS
- BATTERY BACKUP INCLUDED
- LIGHTENING PROTECTION
 - UP TO 20K VOLTS/ 10K AMPS
- EASY ADJUSTMENT OS LIMITS & RELIABLE OPERATION
- INTEGRATED HEATER
- LCD DIAGNOSTICS DISPLAY

SPECIFICATIONS:

OPERATIONAL VOLTAGE

24VDC

MAIN POWER SOURCE

120/240 VAC, 1PH

ACCESSORY POWER

24VDC (750mA)

MAX TORQUE

184 LB/FT (250Nm)

BATTERY BACKUP

UP TO 400 CONTINOUS CYCLES

OPERATING SPEED

10-13 SEC/ 90°

OPERATING TEMPERATURE

-20°F (-28°C) to 131°F (55°C)

MAX GATE CAPACITY

600LBS/ 14FT

MAX DUTY CYCLE

100% CONTINOUS CYCLE

UL 325 CLASSIFICATION

I,II,III,IV AVAILABLE

DEPENDANT ON LOCATION TYPE



MOTOR CABLE LENGTH/ GAUGE

40 FT	16 AWG
60 FT	14 AWG
80 FT	12 AWG
120FT	10 AWG
MORE THAN 120 FT	NOT RECOMMENDED

IMPORTANT: CABLE SHALL BE SHIELDED WITH DRAIN WIRE.
CONNECT DRAIN WIRE TO CHASSIS GROUND OF BOTH THE
OPERATOR AND THE ECU



2525 NE COLUMBIA BLVD PORTLAND, OR 97211
SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1.800.813.6772

"SERVING THE PORTLAND/ VANCOUVER METRO AREA SINCE 1984"