

M-Track Solo

48-KHz, 2-channel USB Audio Interface with 1 Crystal Preamp, Phantom Power and Instrument Input

OVERVIEW () FEATURES () [SPECS] ()
VIDEOS & PHOTOS ()

Technical Specifications

Mic Input (balanced XLR)

Signal-to-Noise Ratio	109 dB (A-weighted)
THD+N	0.003% (min. gain, 0 dBu out, A-weighted)
Preamp EIN	-128 dBu (max. gain, 40 Ω source, A-weighted)
Gain Range	0 dB to +54 dB

Line Input (balanced 1/4" [6.35 mm] TRS)	
Frequency Response	20 Hz – 20 kHz (+0.1 dB)
Sensitivity	-43 dBu
THD+N	0.002% (min. gain, 0 dBu out, A-weighted)
Gain Range	-10 dB to +44 dB

Instrument Input (unbalanced 1/4" [6.35 mm] TS)	
Frequency Response	20 Hz – 20 kHz (+0.1 dB)
THD+N	0.005% (min. gain, 0 dBu output, A-weighted)
Input Impedance	1 MΩ
Gain Range	-10 dB to +44 dB

Frequency Response	20 Hz – 20 kHz (+0.1 dB)
Signal-to-Noise Ratio	109 dB (A-weighted)
THD+N	0.002% (0 dBu output, A-weighted)
Max Output Level	+4 dBu

Headphone Output (1/8" [3.5 mm] TRS)	
Power	60 mW/Ch, 32 Ω
Frequency Response	20 Hz – 20 kHz (+0.5 dB)
THD+N	0.02% (A-weighted)
Signal-to-Noise Ratio	100 dB (A-weighted)

What's In The Box

M-Track Solo

USB-B–to–USB-A Cable

Software Download Cards

User Guide

Safety & Warranty Manual

DISTRIBUTORS

(/distributors)

© 2026 inMusic, LLC. All Rights Reserved

Cookie Preferences