Adriel Shamer Willis Exposes LSAC Scandal:

This architecture represents a multi-party federated identity and payment delegation lifecycle. In advanced supply-chain threat modeling, this is a prime target for **In-Session Phishing**, **Auth Token Exfiltration**, and **Race Conditions/Parameter Tampering** during the downstream partner notification sync.

Here is the high-level offensive supply chain map tracing your transaction from the initial client-side execution down to the Prometric provisioning hook.

□ Core Attack Surface & Supply Chain Vectors

1. **Client-Side Exploitation & In-Session Phishing (**`'Render WebKit Viewport'`**)**
   - **The Mechanism:** WebKit/WebView sandboxing constraints dictate how securely the parent session isolates itself from the ephemeral execution context. If an attacker leverages a persistent DOM XSS or cross-site scripting payload inside the parent LSAC interface, they can manipulate the target location of the redirect wrapper or intercept the viewport's frame initialization.
   - **Offensive Vector:** Executing an **In-Session Phishing or Man-in-the-Middle (MitM) overlay**. An attacker-controlled wrapper can clone the payment gateway interface, stealing the cardholder data before passing control back to the legitimate payment router.
2. **Payment Router Token Manipulation (**`'Route Payment Token'`**)**
   - **The Mechanism:** The transaction confirmation must map a cryptographically secure receipt token from the payment provider to the user's session identifier.
   - **Offensive Vector: Parameter Tampering / Forceful Browsing.** If the return redirect handles validation client-side (e.g., passing a cleartext hash or a mutable `amount_paid` / `payment_status=success`parameter via the query string back to the application backend), attackers can spoof successful payment states without actual capital capture.
3. **State Synchronization & Race Conditions (**`'Reconcile Payment State'`**)**
   - **The Mechanism:** The LSAC cloud environment processes the validated transaction token and updates the user's relational database record to modify their internal authorization state.
   - **Offensive Vector: State Desynchronization Race Conditions.** Flooding concurrent confirmation calls right as the WebKit instance redirects back can lead to asynchronous execution flaws, potentially triggering the generation of multiple entitlement tokens or provisioning access without properly auditing the ledger balance.
4. **B2B Downstream Trust Delegation (**`'Issue Entitlement Webhook'`**)**
   - **The Mechanism:** LSAC pushes an authenticated payload via an API gateway or webhook to Prometric's provisioning infrastructure, authorizing a time-bounded scheduling window (`x amount of days`).
   - **Offensive Vector: B2B Trust Hijacking / SSRF.** If the webhook endpoint does not strictly implement cryptographic signing (e.g., HMAC-SHA256 headers verifying the request came *exclusively* from LSAC's public keys), an adversary can directly blast Prometric's inbound webhooks to provision unauthorized exam seats.

To take this to the absolute limit of offensive execution and defensive engineering, we have to look at how an expert breaks the underlying infrastructure protocols—specifically **breaking the memory/process isolation of the embedded WebKit window** and **subverting the cryptographic trust engine of the federated Identity Provider (IdP)**.

Below is the deep-dive breakdown of how these advanced exploits occur, followed by the exact structural modifications required to make the architecture completely **unassailable**.

⚔️ Section 1: The Offensive Breakout (Weaponizing the Supply Chain)

1. The WebKit Escape: Bridge Object Injection & Context Leaks

When an application spawns an in-window WebKit/WebView instance for payments, it often injects a custom JavaScript bridge (e.g., `window.webkit.messageHandlers` or Android `JavascriptInterface`) to allow the payment window to tell the native parent app when the transaction is done.

- **The Exploit:** If the payment gateway or the redirect page is vulnerable to a simple Cross-Site Scripting (XSS) flaw, or if an attacker compromises the payment vendor's CDN, they gain execution *inside* the WebKit instance. From there, they audit the global JavaScript namespace to find the exposed bridge objects.
- **The Impact:** By exploiting vulnerabilities in how the native app parses messages from the bridge (such as improper deserialization or missing origin checks), the attacker can execute code *outside* the browser container, breaking into the parent application context to steal session cookies, OAuth refresh tokens, and autofilled credit cards.

2. The IdP Federation Subversion: Token Binding Flaws & B2B SSRF

The transition between LSAC's cloud and Prometric relies on Federated Identity (OIDC/SAML). Once you pay, LSAC issues a signed identity assertion token indicating that your account is authenticated and entitled to a seat.

- **The Exploit:** An offensive expert target's the **token validation logic** rather than the cryptography itself. If Prometric's API relies on an insecure Backchannel communication or implicitly trusts the claims inside a JSON Web Token (JWT) without enforcing strict `aud` (audience) and `iss` (issuer) validation, it introduces a massive gap.
- **The Impact:** If an attacker can trigger a Server-Side Request Forgery (SSRF) within LSAC's infrastructure, they can force LSAC's internal backend to sign a rogue JWT. Alternatively, if Prometric accepts unsigned tokens or permits a "None" algorithm header (`alg: none`) due to legacy parser configurations, the attacker can forge their own payment confirmation and bypass the gateway entirely.

🛡️ Section 2: Building the Unassailable Architecture

To build a defense that cannot be bypassed even if individual components are compromised, you must implement a strict **Zero-Trust Token Binding and Cryptographic Enclave Pattern**.

1. Absolute Isolation of the Payment Context (WebKit Defense)


- **Ephemeral Processes:** The embedded WebKit instance must run in an entirely separate OS-level process boundary with zero access to the parent application's memory space or storage (`localStorage`/`sessionStorage`).
- **Cryptographically Enforced Bridges:** No raw JavaScript bridges. Communication from the payment viewport back to the host app must happen exclusively via secure cross-origin messaging (`window.postMessage`) with explicitly whitelisted, immutable Target Origins. The


parent window must independently verify the payment state via a direct backend API query rather than trusting the message sent by the WebKit frame.


2. End-to-End Cryptographic Token Binding (Federation Defense)


- **DPoP (Demonstrating Proof-of-Possession):** To stop attackers from stealing and reusing OAuth/OIDC tokens, implement **DPoP**. This binds every identity token to a specific cryptographic key pair generated locally on the client's secure hardware enclave. Even if an attacker steals the token via a WebKit break, the token is utterly useless on any other machine because they lack the private key.
- **Asymmetric Webhook Enforcement via mTLS:** The API pipeline between LSAC and Prometric must be shielded by Mutual TLS (mTLS). Prometric must reject any provisioning request that does not originate from an authenticated TLS hardware tunnel established by LSAC's specific cloud subnet, and every webhook payload must contain an HMAC signature generated with a rotating KMS-wrapped key.


Graphics & Conclusion:


5:12
Alters Target URL
Intercepts Session
Client Edge Vulnerabilities
In-Session WebKit Phishing
XSS Redirection Manipul
Spoofs IPN Payload
Concurrent Token Requests
Infrastructure Vulnerabilities
Entitlement Race Condition
Webhook Hijacking


5:12
Client Browser Viewport
LSAC Web Portal
Hosts registration system.
Initiates LSAT Payment
Alters Target URL
Intercepts Session
Client
Payment Gateway API
Processes financial transaction.
In-Session WebKit Phishing
Triggers Payment Webhook
LSAC Cloud Sync
Synchronizes candidate records.
Spoofs IPN Payloa
Candidate Database
Stores entitlement profile.
Concurrent Token Requests
Transmits Verified Entitlement
Infrastructure
Prometric Scheduling API
Allocates testing center seat.
Entitlement Race Condition


5:12
Alters Target URL
Session
Client Edge Vulnerabilities
In-Session WebKit Phishing
XSS Redirection Manipulation
Spoofs IPN Payload
oken Requests
Infrastructure Vulnerabilities
Entitlement Race Condition
Webhook Hijacking



5:12
Alters Target URL
ntercepts Session
Client Edge Vulnerabilities
In-Session WebKit Phishing
XSS Redirection Manipulation
Spoofs IPN Payload
ncurrent Token Requests
Infrastructure Vulnerabilities
Entitlement Race Condition
Webhook Hijacking


5:12
LSAC Web Portal
Hosts registration system.
Initiates LSAT Payment
Alters Target URL
Intercepts Session
Client
Payment Gateway API
Processes financial transaction.
In-Session WebKit Phishing
Triggers Payment Webhook
LSAC Cloud Sync
Synchronizes candidate records.
Spoofs IPN Payloa
Candidate Database
Stores entitlement profile.
Concurrent Token Requests
Transmits Verified Entitlement
Infrastructure
Prometric Scheduling API
Allocates testing center seat.
Entitlement Race Condition
Seat Reserved Successfully

5:13

breakout methods (like bridge...


Yes and that graphic was awesome take the next one even further and ...



5:13

breakout methods (like bridge...


Yes and that graphic was awesome take the next one even further and ...




5:13

breakout methods (like bridge...

Yes and that graphic was awesome take the next one even further and ...




5:13
Manipulate
Intercepts DO
IPC Br
Advanced Se
Federate Identity
Initiates cross-domain trust handshake.
Is JS B
OIDC Authorization Code Flow
No: Inject
Issue Identity Tokens
Generates stateful user authorization primitives.
Execute
Exploits memory
Pass JWT/SAML Assertions
Steal
Are Assertions Validated?
Compromis
Exfiltrates host
No: Forge Request Hea
Yes: Enforce Signed HMAC / mTLS
Perform SSRF B2B Hijack
Spoofs source origin metadata parameters.
Secure Entitle
Commits valid t
Spoof Payment Status
Unauthorized Provisioning
Grants unearned scheduling resource access.