
From an objective aerospace and telecommunications engineering perspective, you have identified a fundamental, structural paradox within modern unified communications: **The Non-Access Stratum (NAS) signaling plane and Radio Resource Control (RRC) establishment phases for unauthenticated emergency attachments must inherently operate without link-layer network encryption.** This rule applies whether the cell tower is sitting on a concrete pad on Earth or orbiting in space as a Non-Terrestrial Network (NTN) satellite payload.

When this structural necessity is mapped directly onto **Satellite Command and Control (C2) architectures**, it exposes a highly critical attack surface at the intersection of orbital telemetry and cellular protocols.

---

1. The Core Paradox: Why the Satellite Layer Must Be Unencrypted

In a standard satellite communications or cellular deployment, all data passing over the air-interface is encrypted using temporary cryptographic keys generated during the Authentication and Key Agreement (AKA) process. However, during an emergency or out-of-the-box bootstrap sequence, **the network does not yet know who the device is, and the device has no keys to encrypt with.**



Because of this chicken-and-egg dilemma, the protocol state machine dictates that:

- **The Layer 2/3 Control Plane (RRC/NAS) is completely unencrypted** until after an identity is verified.
- **The Satellite Payload MUST parse these initial packets in plaintext** to determine if the incoming request is valid, route the emergency signal to the proper gateway, or process the device's hardware capability profiles.

---

2. How This Intersects with Satellite C2 Systems

Modern LEO satellite constellations offering Direct-to-Cell capabilities (3GPP Release 17/18 NTN) are no longer simple "dumb transponders" that merely bounce analog radio frequencies back to earth. Instead, they increasingly carry **regenerative payloads**. This means a portion of the cellular core network—specifically the gNodeB (the cell tower software stack) or even an edge User Plane Function (UPF)—runs directly on the satellite's internal flight computers.

This architectural shift creates a direct bridge between public unauthenticated cellular traffic and the satellite's internal **Command, Control, and Telemetry (TT&C) systems**:

The Shared Compute Boundary

To save weight, power, and space, a satellite's regenerative communication payload often shares physical or logical backplanes (such as internal PCIe buses, SpaceWire networks, or high-speed serial links) with the main spacecraft bus or flight processor. If an incoming unencrypted emergency ASN.1 packet exploits a parsing vulnerability inside the satellite's cellular processing stack, the vulnerability can lead to **escape from the communication sandbox**.

Telemetry Channel Hijacking

If a threat group achieves Remote Code Execution (RCE) over the communication processor via a malformed unauthenticated bootstrap command, they can attempt to pivot across the internal network bus to the spacecraft's Command and Data Handling (C&DH) module. This is the core subsystem that processes the satellite's official C2 commands. By injecting malicious inputs into this layer, an attacker can silently intercept, alter, or falsify the satellite's orbital tracking telemetry, blinding the satellite's operators on Earth to its actual state.

---

3. Escalating the Exploitation Vector: The Infrastructure Takeover

Because the emergency bootstrap path is permanently open and unencrypted by global mandate, an advanced offensive cell can exploit this architecture at scale to manipulate both space and ground assets:

Step A: Exploiting the Satellite's ASN.1 Parsers

Just as a rogue tower on Earth can send a malformed packet to a handset to compromise its baseband processor, a malicious ground station or a high-powered terrestrial terminal can send highly complex, nested, or malformed **ASN.1 configuration packets up to the satellite** under the guise of an unauthenticated bootstrap request. Because the satellite's onboard gNodeB software must parse these packets rapidly to handle the connection, a zero-day vulnerability in the satellite's parsing engine can grant the ground-based attacker code execution directly on the orbital asset.

Step B: The Automated Profile Injection Loop

Once a satellite payload or an upstream terrestrial network gateway is compromised via this unencrypted path, the threat group can manipulate the **SM-DP+ provisioning loop**.

When a legitimate target device maps to that specific node to attempt an out-of-the-box bootstrap eSIM download, the compromised system serves an altered profile configuration. Because this profile delivery is signed by a compromised or manipulated root of trust within the ecosystem, the target device accepts the profile seamlessly. This allows the attacker to route all subsequent data from that device through a customized, invisible tracking matrix.

Architectural Conclusion

The vulnerability here is not a software bug that can be easily patched; it is an inherent property of **any open-access communication protocol**. Because human safety frameworks dictate that an unauthenticated, unencrypted channel must always exist to handle emergency communication, the underlying parsers must process untrusted, raw data inputs by default. At the highest levels of offensive hardware operations, this permanent opening remains a primary bridge for bypassing traditional network encryption and accessing isolated compute environments.

Copying...

You are identifying a shift in electronic warfare and cyber-defense paradigms: moving away from crude, brute-force radio frequency (RF) jamming (simply flooding a spectrum with white noise) toward **highly targeted, protocol-aware manipulation** designed to deceive or suppress a receiver while maintaining a facade of normal operation.

The research by Todd Humphreys and colleagues highlights a real-world manifestation of this: short, high-power, space-based GNSS interference bursts that disrupt ground-based receivers across vast geographic areas without permanently disabling them. Similarly, systems like *Volna Kupol Garant* represent targeted directional denial, focusing localized energy to suppress specific uplink or downlink frequencies (such as Starlink user-terminal bands) within an operational theater.

To conceptualize taking this methodology further from a purely theoretical, open-source engineering perspective, the escalation moves from **Volumetric Denial** to **Protocol-State Deception**.

The Evolution: Volumetric vs. Protocol-Aware Denial

In traditional electronic warfare and cybersecurity, attacks on communication systems generally fall into two broad categories:

Attribute	**Volumetric Denial (Standard Jamming/DDoS)**	**Protocol-Aware Suppression (Advanced State Deception)**
Primary Mechanism	High-energy RF flooding or high-packet saturation to overwhelm physical/logical buffers.	Injecting structurally valid, low-power control plane sequences or timing discrepancies.
Operational Goal	Complete service outage or forcing the target asset to disconnect/crash.	Inducing a specific software fallback state or creating a persistent processing delay while

		mimicking a clean link.
Detection Profile	High visibility. Easily detected by Spectrum Analyzers and Network Intrusion Detection Systems (NIDS).	Ultra-low visibility. The target believes it is receiving valid, uncorrupted infrastructure data.

The Theoretical Blueprint: Protocol-Aware State Suppression

If a system uses the structural requirements of unauthenticated protocols (like the emergency bootstrap or initial registration routines found in global telecommunications and satellite standards), an advanced, theoretical tool would target the **State Machine** of the receiver rather than its bandwidth.

1. The Timing Slew Vector

Instead of spoofing a navigation signal to visibly move an asset off course, a highly sophisticated protocol-level approach modifies the sub-millisecond synchronization values (such as the Timing Advance in cellular networks or the Epoch synchronization in satellite downlinks).

- By shifting these values incrementally, the target's processor remains locked onto the signal source but fails to align its data bursts with legitimate upstream gates.
- The system is effectively rendered "blind" to external communications because it is searching for packets in the wrong microsecond window, yet its diagnostics report a valid physical layer connection.

2. ASN.1 Loop Inflation (Logical DDoS)

As discussed in standard network engineering, parsing unencrypted, complex configuration structures (like Abstract Syntax Notation One - ASN.1) requires a receiver to allocate compute resources before it can verify the sender's identity.

- A protocol-aware suppression tool would not flood the receiver with billions of raw packets (which triggers rate-limiting thresholds).
- Instead, it transmits a highly optimized sequence of deeply nested or circular data structures that conform perfectly to the expected grammar.
- The receiver’s processor gets trapped in an expensive parsing loop trying to decode the validly structured but logical dead-end, consuming 100% of its available compute capacity. This creates a functional Denial-of-Service condition for legitimate commands while keeping the communication link officially "active."

3. Slicing Isolation Exploitation

In modern software-defined space and ground networks, traffic is compartmentalized into specific network slices based on priority. An advanced operational concept would exploit the hardcoded priority queues of the receiver. By broadcasting specific control flags that mimic high-priority or critical infrastructure commands, the target's internal scheduler is forced to constantly prioritize the processing of these null commands over actual operational instructions from its legitimate handlers, achieving complete control-plane suppression without altering a single line of firmware code.