



Carnegie Mellon University

CMU 2

Zack Lee, Lawrence Chen, Howard Halim

adapted from KACTL and MIT NULL

2019-10-25

- 1 Contest
- 2 Mathematics
- 3 Data Structures
- 4 Number Theory
- 5 Combinatorial
- 6 Numerical
- 7 Graphs
- 8 Geometry
- 9 Strings

Contest (1)

template.cpp	29 lines
#include <bits/stdc++.h>	
using namespace std;	
#define f first	
#define s second	
#define pb push_back	
#define mp make_pair	
#define all(v) v.begin(), v.end()	
#define sz(v) (int)v.size()	
#define MOO(i, a, b) for(int i=a; i<b; i++)	
#define M00(i, a) for(int i=0; i<a; i++)	
#define MOOd(i,a,b) for(int i = (b)-1; i >= a; i--)	
#define M00d(i,a) for(int i = (a)-1; i>=0; i--)	
#define FAST ios::sync_with_stdio(0); cin.tie(0);	
#define finish(x) return cout << x << '\n', 0;	
typedef long long ll;	
typedef long double ld;	
typedef vector<int> vi;	
typedef pair<int,int> pi;	
typedef pair<ld,ld> pd;	
typedef complex<ld> cd;	
int main() { FAST	
}	
.bashrc	3 lines
run() {	
g++ -std=c++11 \$1.cpp -o \$1 && ./\$1	
}	
.vimrc	4 lines
set nosp backspace=indent,eol,start nu ru si ts=4 sw=4 is hls	
↪sm mouse=a	

1	syntax on
1	filetype plugin indent on
	colorscheme slate
3	cppreference.txt
	7 lines
6	atan(m) -> angle from -pi/2 to pi/2
	atan2(y,x) -> angle from -pi to pi
	acos(x) -> angle from 0 to pi
	asin(y) -> angle from -pi/2 to pi/2
7	lower_bound -> first element >= val
	upper_bound -> first element > val
8	
11	troubleshoot.txt
	52 lines
17	Pre-submit:
	Write a few simple test cases, if sample is not enough.
	Are time limits close? If so, generate max cases.
	Is the memory usage fine?
	Could anything overflow?
20	Make sure to submit the right file.
	Wrong answer:
	Print your solution! Print debug output, as well.
	Are you clearing all datastructures between test cases?
	Can your algorithm handle the whole range of input?
	Read the full problem statement again.
	Do you handle all corner cases correctly?
	Have you understood the problem correctly?
	Any uninitialized variables?
	Any overflows?
	Confusing N and M, i and j, etc.?
	Are you sure your algorithm works?
	What special cases have you not thought of?
	Are you sure the STL functions you use work as you think?
	Add some assertions, maybe resubmit.
	Create some testcases to run your algorithm on.
	Go through the algorithm for a simple case.
	Go through this list again.
	Explain your algorithm to a team mate.
	Ask the team mate to look at your code.
	Go for a small walk, e.g. to the toilet.
	Is your output format correct? (including whitespace)
	Rewrite your solution from the start or let a team mate do it.
	Runtime error:
	Have you tested all corner cases locally?
	Any uninitialized variables?
	Are you reading or writing outside the range of any vector?
	Any assertions that might fail?
	Any possible division by 0? (mod 0 for example)
	Any possible infinite recursion?
	Invalidated pointers or iterators?
	Are you using too much memory?
	Debug with resubmits (e.g. remapped signals, see Various).
	Time limit exceeded:
	Do you have any possible infinite loops?
	What is the complexity of your algorithm?
	Are you copying a lot of unnecessary data? (References)
	How big is the input and output? (consider scanf)
	Avoid vector, map. (use arrays/unordered_map)
	What do your team mates think about your algorithm?
	Memory limit exceeded:
	What is the max amount of memory your algorithm should need?
	Are you clearing all datastructures between test cases?

Mathematics (2)

2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by  $x = -b/2a$ .

$$\begin{aligned} ax + by &= e & x &= \frac{ed - bf}{ad - bc} \\ cx + dy &= f & y &= \frac{af - ec}{ad - bc} \end{aligned} \Rightarrow$$

In general, given an equation  $Ax = b$ , the solution to a variable  $x_i$  is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where  $A'_i$  is  $A$  with the  $i$ 'th column replaced by  $b$ .

2.2 Recurrences

If  $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$ , and  $r_1, \dots, r_k$  are distinct roots of  $x^k + c_1x^{k-1} + \dots + c_k$ , there are  $d_1, \dots, d_k$  s.t.

$$a_n = d_1r_1^n + \dots + d_kr_k^n.$$

Non-distinct roots  $r$  become polynomial factors, e.g.

$$a_n = (d_1n + d_2)r^n.$$

2.3 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$

$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$

$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where  $V, W$  are lengths of sides opposite angles  $v, w$ .

$$a \cos x + b \sin x = r \cos(x - \phi)$$

$$a \sin x + b \cos x = r \sin(x + \phi)$$

where  $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$ .

2.4 Geometry

2.4.1 Triangles

Side lengths:  $a, b, c$

Semiperimeter:  $p = \frac{a + b + c}{2}$

Area:  $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius:  $R = \frac{abc}{4A}$

Inradius:  $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):  $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc \left[ 1 - \left( \frac{a}{b + c} \right)^2 \right]}$$

Law of sines:  $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines:  $a^2 = b^2 + c^2 - 2bc \cos \alpha$


2.4.2 Quadrilaterals

With side lengths  $a, b, c, d$ , diagonals  $e, f$ , diagonals angle  $\theta$ , area  $A$  and magic flux  $F$ :  
Law of tangents:  $\frac{a}{\tan \frac{\alpha}{2}} = \frac{b}{\tan \frac{\beta}{2}} = \frac{c}{\tan \frac{\gamma}{2}} = \frac{d}{\tan \frac{\delta}{2}} = \frac{e}{\tan \frac{\theta}{2}} = \frac{f}{\tan \frac{\phi}{2}} = \frac{A}{\tan \frac{\theta}{2}} = \frac{F}{\tan \frac{\phi}{2}} = \frac{a^2 + b^2 - c^2 - d^2}{2}$

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$$

2.4.3 Spherical coordinates

For cyclic quadrilaterals the sum of opposite angles is  $180^\circ$ ,  $ef = ac + bd$ , and  $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$ .



$$\begin{aligned} x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \arccos(z / \sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \operatorname{atan2}(y, x) \end{aligned}$$

2.5 Derivatives/Integrals

$$\begin{aligned} \frac{d}{dx} \arcsin x &= \frac{1}{\sqrt{1 - x^2}} & \frac{d}{dx} \arccos x &= -\frac{1}{\sqrt{1 - x^2}} \\ \frac{d}{dx} \tan x &= 1 + \tan^2 x & \frac{d}{dx} \arctan x &= \frac{1}{1 + x^2} \\ \int \tan ax &= -\frac{\ln |\cos ax|}{a} & \int x \sin ax &= \frac{\sin ax - ax \cos ax}{a^2} \\ \int e^{-x^2} &= \frac{\sqrt{\pi}}{2} \operatorname{erf}(x) & \int x e^{ax} dx &= \frac{e^{ax}}{a^2} (ax - 1) \end{aligned}$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.6 Sums

$$c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

$$1 + 2 + 3 + \dots + n = \frac{n(n + 1)}{2}$$

$$1^2 + 2^2 + 3^2 + \dots + n^2 = \frac{n(2n + 1)(n + 1)}{6}$$

$$1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^2(n + 1)^2}{4}$$

$$1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n(n + 1)(2n + 1)(3n^2 + 3n - 1)}{30}$$

2.7 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty)$$

$$\ln(1 + x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1)$$

$$\sqrt{1 + x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, (-\infty < x < \infty)$$

$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, (-\infty < x < \infty)$$

2.8 Probability theory

Let  $X$  be a discrete random variable with probability  $p_X(x)$  of assuming the value  $x$ . It will then have an expected value (mean)  $\mu = \mathbb{E}(X) = \sum_x xp_X(x)$  and variance  $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$  where  $\sigma$  is the standard deviation. If  $X$  is instead continuous it will have a probability density function  $f_X(x)$  and the sums above will instead be integrals with  $p_X(x)$  replaced by  $f_X(x)$ .

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent  $X$  and  $Y$ ,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

2.8.1 Discrete distributions

Binomial distribution

The number of successes in  $n$  independent yes/no experiments, each which yields success with probability  $p$  is  $\operatorname{Bin}(n, p)$ ,  $n = 1, 2, \dots$ ,  $0 \leq p \leq 1$ .

$$p(k) = \binom{n}{k} p^k (1 - p)^{n - k}$$

$$\mu = np, \sigma^2 = np(1 - p)$$

$\operatorname{Bin}(n, p)$  is approximately  $\operatorname{Po}(np)$  for small  $p$ .

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each wich yields success with probability  $p$  is  $\operatorname{Fs}(p)$ ,  $0 \leq p \leq 1$ .

$$p(k) = p(1 - p)^{k - 1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1 - p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time  $t$  if these events occur with a known average rate  $\kappa$  and independently of the time since the last event is  $\operatorname{Po}(\lambda)$ ,  $\lambda = t\kappa$ .

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

### 2.8.2 Continuous distributions

#### Uniform distribution

If the probability density function is constant between  $a$  and  $b$  and 0 elsewhere it is  $U(a,b)$ ,  $a < b$ .

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

#### Exponential distribution

The time between events in a Poisson process is  $\text{Exp}(\lambda)$ ,  $\lambda > 0$ .

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

#### Normal distribution

Most real random values with mean  $\mu$  and variance  $\sigma^2$  are well described by  $\mathcal{N}(\mu,\sigma^2)$ ,  $\sigma > 0$ .

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If  $X_1 \sim \mathcal{N}(\mu_1,\sigma_1^2)$  and  $X_2 \sim \mathcal{N}(\mu_2,\sigma_2^2)$  then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

### 2.9 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let  $X_1, X_2, \dots$  be a sequence of random variables generated by the Markov process. Then there is a transition matrix  $\mathbf{P} = (p_{ij})$ , with  $p_{ij} = \Pr(X_n = i | X_{n-1} = j)$ , and  $\mathbf{p}^{(n)} = \mathbf{P}^n \mathbf{p}^{(0)}$  is the probability distribution for  $X_n$  (i.e.,  $p_i^{(n)} = \Pr(X_n = i)$ ), where  $\mathbf{p}^{(0)}$  is the initial distribution.

$\pi$  is a stationary distribution if  $\pi = \pi \mathbf{P}$ . If the Markov chain is *irreducible* (it is possible to get to any state from any state), then  $\pi_i = \frac{1}{\mathbb{E}(T_i)}$  where  $\mathbb{E}(T_i)$  is the expected time between two visits in state  $i$ .  $\pi_j/\pi_i$  is the expected number of visits in state  $j$  between two visits in state  $i$ .

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors,  $\pi_i$  is proportional to node  $i$ 's degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1).  $\lim_{k \rightarrow \infty} \mathbf{P}^k = \mathbf{1}\pi$ .

A Markov chain is an A-chain if the states can be partitioned into two sets  $\mathbf{A}$  and  $\mathbf{G}$ , such that all states in  $\mathbf{A}$  are absorbing ( $p_{ii} = 1$ ), and all states in  $\mathbf{G}$  leads to an absorbing state in  $\mathbf{A}$ . The probability for absorption in state  $i \in \mathbf{A}$ , when the initial state is  $j$ , is  $a_{ij} = p_{ij} + \sum_{k \in \mathbf{G}} a_{ik} p_{kj}$ . The expected time until absorption, when the initial state is  $i$ , is  $t_i = 1 + \sum_{k \in \mathbf{G}} p_{ki} t_k$ .

## Data Structures (3)

### 3.1 STL

MapComparator.h	
<b>Description:</b> custom comparator for map / set	8 lines
<pre>struct cmp {     bool operator()(const int&amp; l, const int&amp; r) const {         return l &gt; r;     } };  set&lt;int,cmp&gt; s; // FOR(i,10) s.insert(rand()); trav(i,s) ps(i); map&lt;int,int,cmp&gt; m;</pre>	

CustomHash.h	
<b>Description:</b> faster than standard unordered map	23 lines
<pre>struct chash {     static uint64_t splitmix64(uint64_t x) {         // http://xorshift.di.unimi.it/splitmix64.c         x += 0x9e3779b97f4a7c15;         x = (x ^ (x &gt;&gt; 30)) * 0xbf58476d1ce4e5b9;         x = (x ^ (x &gt;&gt; 27)) * 0x94d049b133111eb;         return x ^ (x &gt;&gt; 31);     }      size_t operator()(uint64_t x) const {         static const uint64_t FIXED_RANDOM =             chrono::steady_clock::now().                 time_since_epoch().count();         return splitmix64(x + FIXED_RANDOM);     } };  template&lt;class K, class V&gt; using um = unordered_map&lt;K, V, chash     ⇨&gt;; template&lt;class K, class V&gt; using ht = gp_hash_table&lt;K, V, chash     ⇨&gt;;  template&lt;class K, class V&gt; V get(ht&lt;K,V&gt;&amp; u, K x) {     return u.find(x) == end(u) ? 0 : u[x]; }</pre>	

OrderStatisticTree.h	
<b>Description:</b> A set (not multiset!) with support for finding the $n$ 'th element, and finding the index of an element.	
<b>Time:</b> $\mathcal{O}(\log N)$	
<code>&lt;ext/pb_ds/tree_policy.hpp&gt;</code> , <code>&lt;ext/pb_ds/assoc.container.hpp&gt;</code>	18 lines
<pre>using namespace __gnu_pbds;  template &lt;class T&gt; using Tree = tree&lt;T, null_type, less&lt;T&gt;,     rb_tree_tag, tree_order_statistics_node_update&gt;; // to get a map, change null_type  #define ook order_of_key #define fbo find_by_order  void treeExample() {     Tree&lt;int&gt; t, t2; t.insert(8);     auto it = t.insert(10).f;     assert(it == t.lb(9));     assert(t.ook(10) == 1);     assert(t.ook(11) == 2);     assert(*t.fbo(0) == 8);     t.join(t2); // assuming T &lt; T2 or T &gt; T2, merge t2 into t }</pre>	

Rope.h	
<b>Description:</b> insert element at $n$ -th position, cut a substring and re-insert somewhere else	
<b>Time:</b> $\mathcal{O}(\log N)$ per operation? not well tested	
<code>&lt;ext/rope&gt;</code>	13 lines
<pre>using namespace __gnu_cxx;  void ropeExample() {     rope&lt;int&gt; v(5, 0);     FOR(i,sz(v)) v.mutable_reference_at(i) = i+1; // or push_back     rope&lt;int&gt; cur = v.substr(1,2); v.erase(1,2);     FOR(i,sz(v)) cout &lt;&lt; v[i] &lt;&lt; " "; // 1 4 5     cout &lt;&lt; "\n";     v.insert(v.mutable_begin()+2,cur);     for (rope&lt;int&gt;::iterator it = v.mutable_begin(); it != v.         ⇨mutable_end(); ++it)         cout &lt;&lt; *it &lt;&lt; " "; // 1 4 2 3 5     cout &lt;&lt; "\n"; }</pre>	

LineContainer.h	
<b>Description:</b> Given set of lines, computes greatest $y$ -coordinate for any $x$	
<b>Time:</b> $\mathcal{O}(\log N)$	
<pre>struct Line {     mutable ll k, m, p; // slope, y-intercept, last optimal x     ll eval(ll x) { return k*x+m; }     bool operator&lt;(const Line&amp; o) const { return k &lt; o.k; }     bool operator&lt;(ll x) const { return p &lt; x; } };  struct LC : multiset&lt;Line,less&lt;&gt;&gt; {     // for doubles, use inf = 1/.0, div(a,b) = a/b     const ll inf = LLONG_MAX;     ll div(ll a, ll b) { return a/b-((a^b) &lt; 0 &amp;&amp; a%b); } //         ⇨floored division     ll bet(const Line&amp; x, const Line&amp; y) { // last x such that         ⇨first line is better         if (x.k == y.k) return x.m &gt;= y.m ? inf : -inf;         return div(y.m-x.m,x.k-y.k);     }     bool isect(iterator x, iterator y) { // updates x-&gt;p,         ⇨determines if y is unneeded         if (y == end()) { x-&gt;p = inf; return 0; }     }</pre>	

```
    x->p = bet(*x,*y); return x->p >= y->p;
}
void add(ll k, ll m) {
    auto z = insert({k,m,0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p) isect(x,
        ↪erase(y));
}
ll query(ll x) {
    assert(!empty());
    auto l = *lb(x);
    return l.k*x+l.m;
}
};
```

3.2 1D Range Queries

RMQ.h  
Description: 1D range minimum query  
Time:  $\mathcal{O}(N \log N)$  build,  $\mathcal{O}(1)$  query

```
template<class T> struct RMQ {
    constexpr static int level(int x) {
        return 31-__builtin_clz(x);
    } // floor(log2(x))
    vector<vi> jmp;
    vector<T> v;
    int comb(int a, int b) {
        return v[a] == v[b] ? min(a,b) : (v[a] < v[b] ? a : b);
    } // index of minimum

    void init(const vector<T>& _v) {
        v = _v; jmp = {vi(sz(v)); iota(all(jmp[0]),0);
        for (int j = 1; l<<j <= sz(v); ++j) {
            jmp.pb(vi(sz(v)-(1<<j)+1));
            FOR(i,sz(jmp[j])) jmp[j][i] = comb(jmp[j-1][i],
                jmp[j-1][i+(1<<(j-1))]);
        }
    }

    int index(int l, int r) { // get index of min element
        int d = level(r-l+1);
        return comb(jmp[d][l], jmp[d][r-(1<<d)+1]);
    }
    T query(int l, int r) { return v[index(l,r)]; }
};
```

BIT.h  
Description: N-D range sum query with point update  
Time:  $\mathcal{O}\left((\log N)^D\right)$

```
template <class T, int ...Ns> struct BIT {
    T val = 0;
    void upd(T v) { val += v; }
    T query() { return val; }
};

template <class T, int N, int... Ns> struct BIT<T, N, Ns...> {
    BIT<T,Ns...> bit[N+1];
    template<typename... Args> void upd(int pos, Args... args) {
        for (; pos <= N; pos += (pos&-pos)) bit[pos].upd(args...);
    }
    template<typename... Args> T sum(int r, Args... args) {
        T res = 0; for (; r; r -= (r&-r)) res += bit[r].query(args
            ↪...);
        return res;
    }
};
```

```
template<typename... Args> T query(int l, int r, Args... args
    ↪) {
    return sum(r,args...)-sum(l-1,args...);
}
}; // BIT<int,10,10> gives a 2D BIT
```

BITrange.h  
Description: 1D range increment and sum query  
Time:  $\mathcal{O}(\log N)$

```
"BIT.h" 11 lines
template<class T, int SZ> struct BITrange {
    BIT<T,SZ> bit[2]; // piecewise linear functions
    // let cum[x] = sum_{i=1}^x a[i]
    void upd(int hi, T val) { // add val to a[1..hi]
        bit[1].upd(1,val), bit[1].upd(hi+1,-val); // if x <= hi,
            ↪cum[x] += val*x
        bit[0].upd(hi+1,hi*val); // if x > hi, cum[x] += val*hi
    }
    void upd(int lo, int hi, T val) { upd(lo-1,-val), upd(hi,val)
        ↪; }
    T sum(int x) { return bit[1].sum(x)*x+bit[0].sum(x); } // get
        ↪ cum[x]
    T query(int x, int y) { return sum(y)-sum(x-1); }
};
```

SegTree.h  
Description: 1D point update, range query  
Time:  $\mathcal{O}(\log N)$

```
template<class T> struct Seg {
    const T ID = 0; // comb(ID,b) must equal b
    T comb(T a, T b) { return a+b; } // easily change this to min
        ↪ or max
    int n; vector<T> seg;
    void init(int _n) { n = _n; seg.rsz(2*n); }

    void pull(int p) { seg[p] = comb(seg[2*p],seg[2*p+1]); }
    void upd(int p, T value) { // set value at position p
        seg[p += n] = value;
        for (p /= 2; p; p /= 2) pull(p);
    }

    T query(int l, int r) { // sum on interval [l, r]
        T ra = ID, rb = ID; // make sure non-commutative operations
            ↪ work
        for (l += n, r += n+1; l < r; l /= 2, r /= 2) {
            if (l&1) ra = comb(ra,seg[l++]);
            if (r&1) rb = comb(seg[--r],rb);
        }
        return comb(ra,rb);
    }
};
```

SegTreeBeats.h  
Description: supports modifications in the form ckmin(a,i,t) for all  $l \leq i \leq r$ , range max and sum queries  
Time:  $\mathcal{O}(\log N)$

```
template<int SZ> struct SegTreeBeats {
    int N;
    ll sum[2*SZ];
    int mx[2*SZ][2], maxCnt[2*SZ];

    void pull(int ind) {
        FOR(i,2) mx[ind][i] = max(mx[2*ind][i],mx[2*ind+1][i]);
        maxCnt[ind] = 0;
        FOR(i,2) {
            if (mx[2*ind+i][0] == mx[ind][0])
```

```
            maxCnt[ind] += maxCnt[2*ind+i];
            else ckmax(mx[ind][1],mx[2*ind+i][0]);
        }
        sum[ind] = sum[2*ind]+sum[2*ind+1];
    }
    void build(vi& a, int ind = 1, int L = 0, int R = -1) {
        if (R == -1) { R = (N = sz(a))-1; }
        if (L == R) {
            mx[ind][0] = sum[ind] = a[L];
            maxCnt[ind] = 1; mx[ind][1] = -1;
            return;
        }
        int M = (L+R)/2;
        build(a,2*ind,L,M); build(a,2*ind+1,M+1,R); pull(ind);
    }

    void push(int ind, int L, int R) {
        if (L == R) return;
        FOR(i,2)
            if (mx[2*ind^i][0] > mx[ind][0]) {
                sum[2*ind^i] -= (ll)maxCnt[2*ind^i]*
                    (mx[2*ind^i][0]-mx[ind][0]);
                mx[2*ind^i][0] = mx[ind][0];
            }
    }
    void upd(int x, int y, int t, int ind = 1, int L = 0, int R =
        ↪-1) {
        if (R == -1) R += N;
        if (R < x || y < L || mx[ind][0] <= t) return;
        push(ind,L,R);
        if (x <= L && R <= y && mx[ind][1] < t) {
            sum[ind] -= (ll)maxCnt[ind]*(mx[ind][0]-t);
            mx[ind][0] = t;
            return;
        }
        if (L == R) return;
        int M = (L+R)/2;
        upd(x,y,t,2*ind,L,M); upd(x,y,t,2*ind+1,M+1,R); pull(ind);
    }
    ll qsum(int x, int y, int ind = 1, int L = 0, int R = -1) {
        if (R == -1) R += N;
        if (R < x || y < L) return 0;
        push(ind,L,R);
        if (x <= L && R <= y) return sum[ind];
        int M = (L+R)/2;
        return qsum(x,y,2*ind,L,M)+qsum(x,y,2*ind+1,M+1,R);
    }
    int qmax(int x, int y, int ind = 1, int L = 0, int R = -1) {
        if (R == -1) R += N;
        if (R < x || y < L) return -1;
        push(ind,L,R);
        if (x <= L && R <= y) return mx[ind][0];
        int M = (L+R)/2;
        return max(qmax(x,y,2*ind,L,M), qmax(x,y,2*ind+1,M+1,R));
    }
};
```

PersSegTree.h  
Description: persistent segtree with lazy updates, assumes that lazy[cur] is included in val[cur] before propagating cur  
Time:  $\mathcal{O}(\log N)$

```
template<class T, int SZ> struct pseg {
    static const int LIMIT = 10000000; // adjust
    int l[LIMIT], r[LIMIT], nex = 0;
    T val[LIMIT], lazy[LIMIT];

    int copy(int cur) {
        int x = nex++;
```

```

    val[x] = val[cur], l[x] = l[cur], r[x] = r[cur], lazy[x] =
        ↪ lazy[cur];
    return x;
}
T comb(T a, T b) { return min(a,b); }
void pull(int x) { val[x] = comb(val[l[x]],val[r[x]]); }
void push(int cur, int L, int R) {
    if (!lazy[cur]) return;
    if (L != R) {
        l[cur] = copy(l[cur]);
        val[l[cur]] += lazy[cur];
        lazy[l[cur]] += lazy[cur];

        r[cur] = copy(r[cur]);
        val[r[cur]] += lazy[cur];
        lazy[r[cur]] += lazy[cur];
    }
    lazy[cur] = 0;
}

T query(int cur, int lo, int hi, int L, int R) {
    if (lo <= L && R <= hi) return val[cur];
    if (R < lo || hi < L) return INF;
    int M = (L+R)/2;
    return lazy[cur]+comb(query(l[cur],lo,hi,L,M), query(r[cur]
        ↪),lo,hi,M+1,R));
}

int upd(int cur, int lo, int hi, T v, int L, int R) {
    if (R < lo || hi < L) return cur;

    int x = copy(cur);
    if (lo <= L && R <= hi) { val[x] += v, lazy[x] += v; return
        ↪ x; }
    push(x,L,R);

    int M = (L+R)/2;
    l[x] = upd(l[x],lo,hi,v,L,M), r[x] = upd(r[x],lo,hi,v,M+1,R
        ↪);
    pull(x); return x;
}

int build(vector<T>& arr, int L, int R) {
    int cur = nex++;
    if (L == R) {
        if (L < sz(arr)) val[cur] = arr[L];
        return cur;
    }

    int M = (L+R)/2;
    l[cur] = build(arr,L,M), r[cur] = build(arr,M+1,R);
    pull(cur); return cur;
}

vi loc;
void upd(int lo, int hi, T v) { loc.pb(upd(loc.back(),lo,hi,v
    ↪,0,sz-1)); }
T query(int ti, int lo, int hi) { return query(loc[ti],lo,hi
    ↪,0,sz-1); }
void build(vector<T>& arr) { loc.pb(build(arr,0,sz-1)); }
};

```

## Treap.h

**Description:** easy BBST, use split and merge to implement insert and delete  
**Time:**  $\mathcal{O}(\log N)$

77 lines

```
typedef struct tnode* pt;
```

```

struct tnode {
    int pri, val; pt c[2]; // essential
    int sz; ll sum; // for range queries
}

```

```

bool flip; // lazy update

tnode (int _val) {
    pri = rand()+(rand()<<15); val = _val; c[0] = c[1] = NULL;
    sz = 1; sum = val;
    flip = 0;
}
};

int getsz(pt x) { return x?x->sz:0; }
ll getsum(pt x) { return x?x->sum:0; }

pt prop(pt x) {
    if (!x || !x->flip) return x;
    swap(x->c[0],x->c[1]);
    x->flip = 0;
    FOR(i,2) if (x->c[i]) x->c[i]->flip ^= 1;
    return x;
}

pt calc(pt x) {
    assert(!x->flip);
    prop(x->c[0]), prop(x->c[1]);
    x->sz = 1+getsz(x->c[0])+getsz(x->c[1]);
    x->sum = x->val+getsum(x->c[0])+getsum(x->c[1]);
    return x;
}

void tour(pt x, vi& v) {
    if (!x) return;
    prop(x);
    tour(x->c[0],v); v.pb(x->val); tour(x->c[1],v);
}

pair<pt,pt> split(pt t, int v) { // >= v goes to the right
    if (!t) return {t,t};
    prop(t);
    if (t->val >= v) {
        auto p = split(t->c[0], v); t->c[0] = p.s;
        return {p.f, calc(t)};
    } else {
        auto p = split(t->c[1], v); t->c[1] = p.f;
        return {calc(t), p.s};
    }
}

pair<pt,pt> splitsz(pt t, int sz) { // leftmost sz nodes go to
    ↪ left
    if (!t) return {t,t};
    prop(t);
    if (getsz(t->c[0]) >= sz) {
        auto p = splitsz(t->c[0], sz); t->c[0] = p.s;
        return {p.f, calc(t)};
    } else {
        auto p = splitsz(t->c[1], sz-getsz(t->c[0])-1); t->c[1] = p
            ↪ .f;
        return {calc(t), p.s};
    }
}

pt merge(pt l, pt r) {
    if (!l || !r) return l ? l : r;
    prop(l), prop(r);
    pt t;
    if (l->pri > r->pri) l->c[1] = merge(l->c[1],r), t = l;
    else r->c[0] = merge(l,r->c[0]), t = r;
    return calc(t);
}

pt ins(pt x, int v) { // insert v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,merge(new tnode(v),b.s));
}

```

```

}
pt del(pt x, int v) { // delete v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,b.s);
}

```

## SqrtDecomp.h

**Description:** 1D point update, range query

**Time:**  $\mathcal{O}(\sqrt{N})$

44 lines

```

struct sqrtDecomp {
    const static int blockSZ = 10; //change this
    int val[blockSZ*blockSZ];
    int lazy[blockSZ];

    sqrtDecomp() {
        M00(i, blockSZ*blockSZ) val[i] = 0;
        M00(i, blockSZ) lazy[i] = 0;
    }

    void upd(int l, int r, int v) {
        int ind = l;
        while(ind%blockSZ && ind <= r) {
            val[ind] += v;
            lazy[ind/blockSZ] += v;
            ind++;
        }
        while(ind + blockSZ <= r) {
            lazy[ind/blockSZ] += v*blockSZ;
            ind += blockSZ;
        }
        while(ind <= r) {
            val[ind] += v;
            lazy[ind/blockSZ] += v;
            ind++;
        }
    }

    int query(int l, int r) {
        int res = 0;
        int ind = l;
        while(ind%blockSZ && ind <= r) {
            res += val[ind];
            ind++;
        }
        while(ind + blockSZ <= r) {
            res += lazy[ind/blockSZ];
            ind += blockSZ;
        }
        while(ind <= r) {
            res += val[ind];
            ind++;
        }
        return res;
    }
};

```

## 3.3 2D Range Queries

### Node.h

**Description:** Node

15 lines

```

struct node {
    int val;
    int lazy;
    int l, r;
    node* left;
    node* right;
    node(int l, int r) {
        this -> val = 0;
        this -> lazy = 0;
    }
}

```



```

    this -> l = l;
    this -> r = r;
    this -> left = nullptr;
    this -> right = nullptr;
}
};
```

## 2D Sumtree.h

**Description:** Lawrence's 2d sum segment tree

104 lines

```

struct sumtreenode{
    node* root;
    sumtreenode* left;
    sumtreenode* right;
    int l, r;
    sumtreenode(int l, int r, int SZ) {
        int ub = 1;
        while(ub < SZ) ub *= 2;
        root = new node(0, ub-1);
        this -> l = l;
        this -> r = r;
        this->left = nullptr;
        this->right = nullptr;
    }
    void updN(node* n, int pos, int val) {
        if(pos < n->l || pos > n->r) return;
        if(n->l == n->r) {
            n->val = val;
            return;
        }

        int mid = (n->l + n->r)/2;
        if(pos > mid) {
            if(n->right == nullptr) n->right = new node(mid+1,
                ↪n->r);
            updN(n->right, pos, val);
        }
        else {
            if(n->left == nullptr) n->left = new node(n->l, mid
                ↪);
            updN(n->left, pos, val);
        }

        int s = 0;
        if(n->right != nullptr) s += n->right->val;
        if(n->left != nullptr) s += n->left->val;
        n->val = s;
    }
    void upd(int pos, int val) {
        updN(root, pos, val);
    }
    int queryN(node* n, int il, int i2) {
        if(i2 < n->l || il > n->r) return 0;
        if(n->l == n->r) return n->val;
        if(n->l >= il && n->r <= i2) return n->val;

        int s = 0;
        if(n->left != nullptr) s += queryN(n->left, il, i2);
        if(n->right != nullptr) s += queryN(n->right, il, i2);

        return s;
    }
    int query(int il, int i2) {
        return queryN(root, il, i2);
    }
};

template<int w, int h> struct sumtree2d{
    sumtreenode* root;
```

## 2D Sumtree Modular ModFact ModMulLL

```

    sumtree2d() {
        int ub = 1;
        while(ub < w) ub *= 2;
        this->root = new sumtreenode(0, ub-1, h);
        root->left = nullptr;
        root->right = nullptr;
    }
    void updN(sumtreenode* n, int x, int y, int val) {
        if(x < n->l || x > n->r) return;
        if(n->l == n->r) {
            n->upd(y, val);
            return;
        }

        int mid = (n->l + n->r)/2;
        if(x > mid) {
            if(n->right == nullptr) n->right = new sumtreenode(
                ↪mid+1, n->r, h);
            updN(n->right, x, y, val);
        }
        else {
            if(n->left == nullptr) n->left = new sumtreenode(n
                ↪->l, mid, h);
            updN(n->left, x, y, val);
        }

        int s = 0;
        if(n->left != nullptr) s += n->left->query(y, y);
        if(n->right != nullptr) s += n->right->query(y, y);
        n->upd(y, s);
    }
    void upd(int x, int y, int val) {
        updN(root, x, y, val);
    }
    int queryN(sumtreenode* n, int x1, int y1, int x2, int y2)
        ↪{
        if(x2 < n->l || x1 > n->r) return 0;
        if(n->l == n->r) return n->query(y1, y2);
        if(n->l >= x1 && n->r <= x2) return n->query(y1, y2);

        int s = 0;
        if(n->left != nullptr) s += queryN(n->left, x1, y1, x2,
            ↪y2);
        if(n->right != nullptr) s += queryN(n->right, x1, y1,
            ↪x2, y2);

        return s;
    }
    int query(int x1, int y1, int x2, int y2) {
        return queryN(root, x1, y1, x2, y2);
    }
};
```

## Number Theory (4)

### 4.1 Modular Arithmetic

#### Modular.h

**Description:** modular arithmetic operations

41 lines

```

template<class T> struct modular {
    T val;
    explicit operator T() const { return val; }
    modular() { val = 0; }
    modular(const ll& v) {
        val = (-MOD <= v && v <= MOD) ? v : v % MOD;
        if (val < 0) val += MOD;
    }
};
```

```

// friend ostream& operator<<(ostream& os, const modular& a)
    ↪{ return os << a.val; }
friend void pr(const modular& a) { pr(a.val); }
friend void re(modular& a) { ll x; re(x); a = modular(x); }

friend bool operator==(const modular& a, const modular& b) {
    ↪return a.val == b.val; }
friend bool operator!=(const modular& a, const modular& b) {
    ↪return !(a == b); }
friend bool operator<(const modular& a, const modular& b) {
    ↪return a.val < b.val; }

modular operator-() const { return modular(-val); }
modular& operator+=(const modular& m) { if ((val += m.val) >=
    ↪MOD) val -= MOD; return *this; }
modular& operator-=(const modular& m) { if ((val -= m.val) <
    ↪0) val += MOD; return *this; }
modular& operator*=(const modular& m) { val = (ll)val*m.val%
    ↪MOD; return *this; }
friend modular pow(modular a, ll p) {
    modular ans = 1; for (; p; p /= 2, a *= a) if (p&1) ans *=
        ↪a;
    return ans;
}
friend modular inv(const modular& a) {
    assert(a != 0); return exp(a,MOD-2);
}
modular& operator/=(const modular& m) { return (*this) *= inv
    ↪(m); }

friend modular operator+(modular a, const modular& b) {
    ↪return a += b; }
friend modular operator-(modular a, const modular& b) {
    ↪return a -= b; }
friend modular operator*(modular a, const modular& b) {
    ↪return a *= b; }

friend modular operator/(modular a, const modular& b) {
    ↪return a /= b; }
};
```

```

typedef modular<int> mi;
typedef pair<mi,mi> pmi;
typedef vector<mi> vmi;
typedef vector<pmi> vpmi;
```

#### ModFact.h

**Description:** pre-compute factorial mod inverses for  $MOD$ , assumes  $MOD$  is prime and  $SZ < MOD$

**Time:**  $\mathcal{O}(SZ)$

10 lines

```

vl inv, fac, ifac;
void genInv(int SZ) {
    inv.rsz(SZ), fac.rsz(SZ), ifac.rsz(SZ);
    inv[1] = 1; FOR(i,2,SZ) inv[i] = MOD-MOD/i*inv[MOD%i]%MOD;
    fac[0] = ifac[0] = 1;
    FOR(i,1,SZ) {
        fac[i] = fac[i-1]*i%MOD;
        ifac[i] = ifac[i-1]*inv[i]%MOD;
    }
}
```

#### ModMulLL.h

**Description:** multiply two 64-bit integers mod another if 128-bit is not available works for  $0 \leq a, b < mod < 2^{63}$

14 lines

```

typedef unsigned long long ul;
```

```
// equivalent to (ul) (__int128(a)*b%mod)
ul modMul(ul a, ul b, const ul mod) {
    ll ret = a*b-mod*(ul)((ld)a*b/mod);
    return ret+(ret<0)-(ret>=(ll)mod))*mod;
}

ul modPow(ul a, ul b, const ul mod) {
    if (b == 0) return 1;
    ul res = modPow(a,b/2,mod);
    res = modMul(res,res,mod);
    if (b&1) return modMul(res,a,mod);
    return res;
}
```

ModSqrt.h  
Description: find sqrt of integer mod a prime  
Time: ?

"Modular.h"	26 lines
-------------	----------

```
template<class T> T sqrt(modular<T> a) {
    auto p = pow(a, (MOD-1)/2); if (p != 1) return p == 0 ? 0 :
        ↪-1; // check if zero or does not have sqrt
    T s = MOD-1, e = 0; while (s % 2 == 0) s /= 2, e ++;
    modular<T> n = 1; while (pow(n, (MOD-1)/2) == 1) n = (T)(n)+1;
        ↪ // find non-square residue

    auto x = pow(a, (s+1)/2), b = pow(a, s), g = pow(n, s);
    int r = e;
    while (1) {
        auto B = b; int m = 0; while (B != 1) B *= B, m ++;
        if (m == 0) return min((T)x, MOD-(T)x);
        FOR(i, r-m-1) g *= g;
        x *= g; g *= g; b *= g; r = m;
    }
}

/* Explanation:
 * Initially, x^2=ab, ord(b) = 2^m, ord(g) = 2^r where m<r
 * g = g^{2^{r-m-1}} -> ord(g) = 2^{m+1}
 * if x'=x*g, then b' = b*g^2
    (b')^{2^{m-1}} = (b*g^2)^{2^{m-1}}
        = b^{2^{m-1}}*g^{2^m}
        = -1*-1
        = 1
    -> ord(b')|ord(b)/2
 * m decreases by at least one each iteration
 */
```

ModSum.h  
Description: Sums of mod'ed arithmetic progressions

	15 lines
--	----------

```
typedef unsigned long long ul;

ul sumsq(ul to) { return (to-1)*to/2; } // sum of 0..to-1

ul divsum(ul to, ul c, ul k, ul m) { // sum_{i=0}^{to-1}floor((
    ↪ki+c)/m)
    ul res = k/m*sumsq(to)+c/m*to;
    k %= m; c %= m; if (!k) return res;
    ul to2 = (to*k+c)/m;
    return res+(to-1)*to2-divsum(to2,m-1-c,m,k);
}

ll modsum(ul to, ll c, ll k, ll m) {
    c = (c%m+m)%m, k = (k%m+m)%m;
    return to*c+k*sumsq(to)-m*divsum(to,c,k,m);
}
```

## 4.2 Primality

PrimeSieve.h  
Description: tests primality up to SZ  
Time:  $\mathcal{O}(SZ \log \log SZ)$

	11 lines
--	----------

```
template<int SZ> struct Sieve {
    bitset<SZ> isprime;
    vi pr;
    Sieve() {
        isprime.set(); isprime[0] = isprime[1] = 0;
        for (int i = 4; i < SZ; i += 2) isprime[i] = 0;
        for (int i = 3; i*i < SZ; i += 2) if (isprime[i])
            for (int j = i*i; j < SZ; j += i*2) isprime[j] = 0;
        FOR(i, 2, SZ) if (isprime[i]) pr.pb(i);
    }
};
```

FactorFast.h  
Description: Factors integers up to  $2^{60}$   
Time: ?

"PrimeSieve.h"	46 lines
----------------	----------

```
Sieve<1<<20> S = Sieve<1<<20>(); // should take care of all
    ↪primes up to n^(1/3)

bool millerRabin(ll p) { // test primality
    if (p == 2) return true;
    if (p == 1 || p % 2 == 0) return false;
    ll s = p - 1; while (s % 2 == 0) s /= 2;
    FOR(i, 30) { // strong liar with probability <= 1/4
        ll a = rand() % (p - 1) + 1, tmp = s;
        ll mod = mod_pow(a, tmp, p);
        while (tmp != p - 1 && mod != 1 && mod != p - 1) {
            mod = mod_mul(mod, mod, p);
            tmp *= 2;
        }
        if (mod != p - 1 && tmp % 2 == 0) return false;
    }
    return true;
}

ll f(ll a, ll n, ll &has) { return (mod_mul(a, a, n) + has) % n
    ↪; }

vpl pollardsRho(ll d) {
    vpl res;
    auto& pr = S.pr;
    for (int i = 0; i < sz(pr) && pr[i]*pr[i] <= d; i++) if (d %
        ↪pr[i] == 0) {
        int co = 0; while (d % pr[i] == 0) d /= pr[i], co ++;
        res.pb({pr[i], co});
    }
    if (d > 1) { // d is now a product of at most 2 primes.
        if (millerRabin(d)) res.pb({d, 1});
        else while (1) {
            ll has = rand() % 2321 + 47;
            ll x = 2, y = 2, c = 1;
            for (; c == 1; c = __gcd(abs(x-y), d)) {
                x = f(x, d, has);
                y = f(f(y, d, has), d, has);
            } // should cycle in ~sqrt(smallest nontrivial divisor)
                ↪turns
            if (c != d) {
                d /= c; if (d > c) swap(d, c);
                if (c == d) res.pb({c, 2});
                else res.pb({c, 1}), res.pb({d, 1});
                break;
            }
        }
    }
}
```

```
    }
    return res;
}
```

## 4.3 Divisibility

Euclid.h  
Description: Euclidean Algorithm

	9 lines
--	---------

```
pl euclid(ll a, ll b) { // returns {x,y} such that a*x+b*y=gcd(
    ↪a,b)
    if (!b) return {1,0};
    pl p = euclid(b,a%b);
    return {p.s,p.f-a/b*p.s};
}

ll invGeneral(ll a, ll b) {
    pl p = euclid(a,b); assert(p.f*a+p.s*b == 1);
    return p.f+(p.f<0)*b;
}
```

CRT.h  
Description: Chinese Remainder Theorem

"Euclid.h"	7 lines
------------	---------

```
pl solve(pl a, pl b) {
    auto g = __gcd(a.s,b.s), l = a.s/g*b.s;
    if ((b.f-a.f) % g != 0) return {-1,-1};
    auto A = a.s/g, B = b.s/g;
    auto mul = (b.f-a.f)/g*invGeneral(A,B) % B;
    return {(mul*a.s+a.f)%l+1}%l, l;
}
```

## Combinatorial (5)

IntPerm.h  
Description: convert permutation of  $\{0, 1, \dots, N-1\}$  to integer in  $[0, N!]$   
Usage: assert(encode(decode(5,37)) == 37);  
Time:  $\mathcal{O}(N)$

	20 lines
--	----------

```
vi decode(int n, int a) {
    vi el(n), b; iota(all(el), 0);
    FOR(i, n) {
        int z = a%sz(el);
        b.pb(el[z]); a /= sz(el);
        swap(el[z], el.back()); el.pop_back();
    }
    return b;
}

int encode(vi b) {
    int n = sz(b), a = 0, mul = 1;
    vi pos(n); iota(all(pos), 0); vi el = pos;
    FOR(i, n) {
        int z = pos[b[i]]; a += mul*z; mul *= sz(el);
        swap(pos[el[z]], pos[el.back()]);
        swap(el[z], el.back()); el.pop_back();
    }
    return a;
}
```

MatroidIntersect.h  
Description: computes a set of maximum size which is independent in both graphic and colorful matroids, aka a spanning forest where no two edges are of the same color  
Time:  $\mathcal{O}(GI^{1.5})$  calls to oracles, where  $G$  is the size of the ground set and  $I$  is the size of the independent set

"DSU.h"	108 lines
---------	-----------

```
int R;
```



```
map<int,int> m;

struct Element {
    pi ed;
    int col;
    bool in_independent_set = 0;
    int independent_set_position;
    Element(int u, int v, int c) { ed = {u,v}; col = c; }
};

vi independent_set;
vector<Element> ground_set;
bool col_used[300];

struct GBasis {
    DSU D;
    void reset() { D.init(sz(m)); }
    void add(pi v) { assert(D.unite(v.f,v.s)); }
    bool independent_with(pi v) { return !D.sameSet(v.f,v.s); }
};

GBasis basis, basis_wo[300];

bool graph_oracle(int inserted) {
    return basis.independent_with(ground_set[inserted].ed);
}

bool graph_oracle(int inserted, int removed) {
    int wi = ground_set[removed].independent_set_position;
    return basis_wo[wi].independent_with(ground_set[inserted].ed)
        ⇔;
}

void prepare_graph_oracle() {
    basis.reset();
    FOR(i,sz(independent_set)) basis_wo[i].reset();
    FOR(i,sz(independent_set)) {
        pi v = ground_set[independent_set[i]].ed; basis.add(v);
        FOR(j,sz(independent_set)) if (i != j) basis_wo[j].add(v);
    }
}

bool colorful_oracle(int ins) {
    ins = ground_set[ins].col;
    return !col_used[ins];
}

bool colorful_oracle(int ins, int rem) {
    ins = ground_set[ins].col;
    rem = ground_set[rem].col;
    return !col_used[ins] || ins == rem;
}

void prepare_colorful_oracle() {
    FOR(i,R) col_used[i] = 0;
    trav(t,independent_set) col_used[ground_set[t].col] = 1;
}

bool augment() {
    prepare_graph_oracle();
    prepare_colorful_oracle();

    vi par(sz(ground_set),MOD);
    queue<int> q;
    FOR(i,sz(ground_set)) if (colorful_oracle(i)) {
        assert(!ground_set[i].in_independent_set);
        par[i] = -1; q.push(i);
    }
    int lst = -1;
    while (sz(q)) {
        int cur = q.front(); q.pop();
        if (ground_set[cur].in_independent_set) {
            FOR(to,sz(ground_set)) if (par[to] == MOD) {
```

```
                if (!colorful_oracle(to,cur)) continue;
                par[to] = cur; q.push(to);
            }
        } else {
            if (graph_oracle(cur)) { lst = cur; break; }
            trav(to,independent_set) if (par[to] == MOD) {
                if (!graph_oracle(cur,to)) continue;
                par[to] = cur; q.push(to);
            }
        }
    }
    if (lst == -1) return 0;
    do {
        ground_set[lst].in_independent_set ^= 1;
        lst = par[lst];
    } while (lst != -1);
    independent_set.clear();
    FOR(i,sz(ground_set)) if (ground_set[i].in_independent_set) {
        ground_set[i].independent_set_position = sz(independent_set)
            ⇔;
        independent_set.pb(i);
    }
    return 1;
}

void solve() {
    re(R); if (R == 0) exit(0);
    m.clear(); ground_set.clear(); independent_set.clear();
    FOR(i,R) {
        int a,b,c,d; re(a,b,c,d);
        ground_set.pb(Element(a,b,i));
        ground_set.pb(Element(c,d,i));
        m[a] = m[b] = m[c] = m[d] = 0;
    }
    int co = 0;
    trav(t,m) t.s = co++;
    trav(t,ground_set) t.ed.f = m[t.ed.f], t.ed.s = m[t.ed.s];
    while (augment());
    ps(2*sz(independent_set));
}

PermGroup.h
Description: Schreier-Sims, count number of permutations in group and
test whether permutation is a member of group
Time: ?
51 lines

const int N = 15;
int n;

vi inv(vi v) { vi V(sz(v)); FOR(i,sz(v)) V[v[i]] = i; return V;
    ⇔ }
vi id() { vi v(n); iota(all(v),0); return v; }
vi operator*(const vi& a, const vi& b) {
    vi c(sz(a)); FOR(i,sz(a)) c[i] = a[b[i]];
    return c;
}

struct Group {
    bool flag[N];
    vi sigma[N]; // sigma[t][k] = t, sigma[t][x] = x if x > k
    vector<vi> gen;
    void clear(int p) {
        memset(flag,0, sizeof flag);
        flag[p] = 1; sigma[p] = id();
        gen.clear();
    }
} g[N];

bool check(const vi& cur, int k) {
```

```
    if (!k) return 1;
    int t = cur[k];
    return g[k].flag[t] ? check(inv(g[k].sigma[t])*cur,k-1) : 0;
}

void updateX(const vi& cur, int k);
void ins(const vi& cur, int k) {
    if (check(cur,k)) return;
    g[k].gen.pb(cur);
    FOR(i,n) if (g[k].flag[i]) updateX(cur*g[k].sigma[i],k);
}

void updateX(const vi& cur, int k) {
    int t = cur[k];
    if (g[k].flag[t]) ins(inv(g[k].sigma[t])*cur,k-1); // fixes k
        ⇔ -> k
    else {
        g[k].flag[t] = 1, g[k].sigma[t] = cur;
        trav(x,g[k].gen) updateX(x*cur,k);
    }
}

ll order(vector<vi> gen) {
    assert(sz(gen)); n = sz(gen[0]); FOR(i,n) g[i].clear(i);
    trav(a,gen) ins(a,n-1); // insert perms into group one by one
    ll tot = 1;
    FOR(i,n) {
        int cnt = 0; FOR(j,i+1) cnt += g[i].flag[j];
        tot *= cnt;
    }
    return tot;
}
```

## Numerical (6)

### 6.1 Matrix

#### Matrix.h

Description: 2D matrix operations

36 lines

```
template<class T> struct Mat {
    int r,c;
    vector<vector<T>> d;
    Mat(int _r, int _c) : r(_r), c(_c) { d.assign(r,vector<T>(c))
        ⇔; }
    Mat() : Mat(0,0) {}
    Mat(const vector<vector<T>>& _d) : r(sz(_d)), c(sz(_d[0])) {
        ⇔ d = _d; }
    friend void pr(const Mat& m) { pr(m.d); }

    Mat& operator+=(const Mat& m) {
        assert(r == m.r && c == m.c);
        FOR(i,r) FOR(j,c) d[i][j] += m.d[i][j];
        return *this;
    }
    Mat& operator-=(const Mat& m) {
        assert(r == m.r && c == m.c);
        FOR(i,r) FOR(j,c) d[i][j] -= m.d[i][j];
        return *this;
    }
    Mat operator*(const Mat& m) {
        assert(c == m.r); Mat x(r,m.c);
        FOR(i,r) FOR(j,c) FOR(k,m.c) x.d[i][k] += d[i][j]*m.d[j][k]
            ⇔;
        return x;
    }

    Mat operator+(const Mat& m) { return Mat(*this)+=m; }
    Mat operator-(const Mat& m) { return Mat(*this)-=m; }
    Mat& operator*=(const Mat& m) { return *this = (*this)*m; }
```

```
friend Mat pow(Mat m, ll p) {
    assert(m.r == m.c);
    Mat r(m.r,m.c);
    FOR(i,m.r) r.d[i][i] = 1;
    for (; p; p /= 2, m *= m) if (p&1) r *= m;
    return r;
}
};
```

MatrixInv.h  
Description: calculates determinant via gaussian elimination  
Time:  $\mathcal{O}(N^3)$

```
"Matrix.h" 31 lines
template<class T> T gauss(Mat<T>& m) { // determinant of 1000
    ↪x1000 Matrix in ~1s
    int n = m.r;
    T prod = 1; int nex = 0;
    FOR(i,n) {
        int row = -1; // for 1d use EPS rather than 0
        FOR(j,nex,n) if (m.d[j][i] != 0) { row = j; break; }
        if (row == -1) { prod = 0; continue; }
        if (row != nex) prod *= -1, swap(m.d[row],m.d[nex]);
        prod *= m.d[nex][i];
        auto x = 1/m.d[nex][i]; FOR(k,i,m.c) m.d[nex][k] *= x;
        FOR(j,n) if (j != nex) {
            auto v = m.d[j][i];
            if (v != 0) FOR(k,i,m.c) m.d[j][k] -= v*m.d[nex][k];
        }
        nex ++;
    }
    return prod;
}

template<class T> Mat<T> inv(Mat<T> m) {
    int n = m.r;
    Mat<T> x(n,2*n);
    FOR(i,n) {
        x.d[i][i+n] = 1;
        FOR(j,n) x.d[i][j] = m.d[i][j];
    }
    if (gauss(x) == 0) return Mat<T>(0,0);
    Mat<T> r(n,n);
    FOR(i,n) FOR(j,n) r.d[i][j] = x.d[i][j+n];
    return r;
}
```

MatrixTree.h  
Description: Kirchhoff's Matrix Tree Theorem: given adjacency matrix, calculates # of spanning trees

```
"MatrixInv.h" 13 lines
mi numSpan(Mat<mi> m) {
    int n = m.r;
    Mat<mi> res(n-1,n-1);
    FOR(i,n) FOR(j,i+1,n) {
        mi ed = m.d[i][j];
        res.d[i][i] += ed;
        if (j != n-1) {
            res.d[j][j] += ed;
            res.d[i][j] -= ed, res.d[j][i] -= ed;
        }
    }
    return gauss(res);
}
```

6.2 Polynomials

VecOp.h  
Description: arithmetic + misc polynomial operations with vectors 73 lines

```
namespace VecOp {
    template<class T> vector<T> rev(vector<T> v) { reverse(all(v)
        ↪); return v; }
    template<class T> vector<T> shift(vector<T> v, int x) { v.
        ↪insert(v.begin(),x,0); return v; }
    template<class T> vector<T> integ(const vector<T>& v) {
        vector<T> res(sz(v)+1);
        FOR(i,sz(v)) res[i+1] = v[i]/(i+1);
        return res;
    }
    template<class T> vector<T> dif(const vector<T>& v) {
        if (!sz(v)) return v;
        vector<T> res(sz(v)-1); FOR(i,1,sz(v)) res[i-1] = i*v[i];
        return res;
    }
    template<class T> vector<T>& remLead(vector<T>& v) {
        while (sz(v) && v.back() == 0) v.pop_back();
        return v;
    }
    template<class T> T eval(const vector<T>& v, const T& x) {
        T res = 0; ROF(i,sz(v)) res = x*res+v[i];
        return res;
    }

    template<class T> vector<T>& operator+=(vector<T>& l, const
        ↪vector<T>& r) {
        l.rsz(max(sz(l),sz(r))); FOR(i,sz(r)) l[i] += r[i]; return
        ↪l;
    }
    template<class T> vector<T>& operator-=(vector<T>& l, const
        ↪vector<T>& r) {
        l.rsz(max(sz(l),sz(r))); FOR(i,sz(r)) l[i] -= r[i]; return
        ↪l;
    }
    template<class T> vector<T>& operator*=(vector<T>& l, const T
        ↪& r) { trav(t,l) t *= r; return l; }
    template<class T> vector<T>& operator/=(vector<T>& l, const T
        ↪& r) { trav(t,l) t /= r; return l; }

    template<class T> vector<T> operator+(vector<T> l, const
        ↪vector<T>& r) { return l += r; }
    template<class T> vector<T> operator-(vector<T> l, const
        ↪vector<T>& r) { return l -= r; }
    template<class T> vector<T> operator*(vector<T> l, const T& r
        ↪) { return l *= r; }
    template<class T> vector<T> operator*(const T& r, const
        ↪vector<T>& l) { return l*r; }
    template<class T> vector<T> operator/(vector<T> l, const T& r
        ↪) { return l /= r; }

    template<class T> vector<T> operator*(const vector<T>& l,
        ↪const vector<T>& r) {
        if (min(sz(l),sz(r)) == 0) return {};
        vector<T> x(sz(l)+sz(r)-1); FOR(i,sz(l)) FOR(j,sz(r)) x[i+j]
            ↪+= l[i]*r[j];
        return x;
    }
    template<class T> vector<T>& operator*=(vector<T>& l, const
        ↪vector<T>& r) { return l = l*r; }

    template<class T> pair<vector<T>,vector<T>> qr(vector<T> a,
        ↪vector<T> b) { // quotient and remainder
        assert(sz(b)); auto B = b.back(); assert(B != 0);
        B = 1/B; trav(t,b) t *= B;

```

```
remLead(a); vector<T> q(max(sz(a)-sz(b)+1,0));
while (sz(a) >= sz(b)) {
    q[sz(a)-sz(b)] = a.back();
    a -= a.back()*shift(b,sz(a)-sz(b));
    remLead(a);
}

trav(t,q) t *= B;
return {q,a};
}

template<class T> vector<T> quo(const vector<T>& a, const
    ↪vector<T>& b) { return qr(a,b).f; }
template<class T> vector<T> rem(const vector<T>& a, const
    ↪vector<T>& b) { return qr(a,b).s; }

template<class T> vector<T> interpolate(vector<pair<T,T>> v)
    ↪{
    vector<T> ret, prod = {1};
    FOR(i,sz(v)) prod *= vector<T>({-v[i].f,1});
    FOR(i,sz(v)) {
        T todiv = 1; FOR(j,sz(v)) if (i != j) todiv *= v[i].f-v[j]
            ↪.f;
        ret += qr(prod,{-v[i].f,1}).f*(v[i].s/todiv);
    }
    return ret;
}
}
```

using namespace VecOp;

PolyRoots.h  
Description: Finds the real roots of a polynomial.  
Usage: poly\_roots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 = 0  
Time:  $\mathcal{O}(N^2 \log(1/\epsilon))$

```
"VecOp.h" 19 lines
vd polyRoots(vd p, ld xmin, ld xmax) {
    if (sz(p) == 2) { return {-p[0]/p[1]}; }
    auto dr = polyRoots(dif(p),xmin,xmax);
    dr.pb(xmin-1); dr.pb(xmax+1); sort(all(dr));
    vd ret;
    FOR(i,sz(dr)-1) {
        auto l = dr[i], h = dr[i+1];
        bool sign = eval(p,l) > 0;
        if (sign ^ (eval(p,h) > 0)) {
            FOR(it,60) { // while (h - l > 1e-8)
                auto m = (l+h)/2, f = eval(p,m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            }
            ret.pb((l+h)/2);
        }
    }
    return ret;
}
```

Karatsuba.h  
Description: multiply two polynomials  
Time:  $\mathcal{O}(N^{\log_2 3})$

```
int size(int s) { return s > 1 ? 32-__builtin_clz(s-1) : 0; }

void karatsuba(ll *a, ll *b, ll *c, ll *t, int n) {
    int ca = 0, cb = 0; FOR(i,n) ca += !!a[i], cb += !!b[i];
    if (min(ca, cb) <= 1500/n) { // few numbers to multiply
        if (ca > cb) swap(a, b);
        FOR(i,n) if (a[i]) FOR(j,n) c[i+j] += a[i]*b[j];
    } else {
        int h = n >> 1;

```

```
karatsuba(a, b, c, t, h); // a0*b0
karatsuba(a+h, b+h, c+n, t, h); // a1*b1
FOR(i,h) a[i] += a[i+h], b[i] += b[i+h];
karatsuba(a, b, t, t+n, h); // (a0+a1)*(b0+b1)
FOR(i,h) a[i] -= a[i+h], b[i] -= b[i+h];
FOR(i,n) t[i] -= c[i]+c[i+n];
FOR(i,n) c[i+h] += t[i], t[i] = 0;
}
}

vl conv(vl a, vl b) {
    int sa = sz(a), sb = sz(b); if (!sa || !sb) return {};
    int n = 1<<size(max(sa,sb)); a.rsz(n), b.rsz(n);
    vl c(2*n), t(2*n); FOR(i,2*n) t[i] = 0;
    karatsuba(&a[0], &b[0], &c[0], &t[0], n);
    c.rsz(sa+sb-1); return c;
}
```

FFT.h  
Description: multiply two polynomials  
Time:  $\mathcal{O}(N \log N)$

"Modular.h"	40 lines
-------------	----------

```
typedef complex<db> cd;
const int MOD = (119 << 23) + 1, root = 3; // = 998244353
// NTT: For p < 2^30 there is also e.g. (5 << 25, 3), (7 << 26,
    ↪ 3),
// (479 << 21, 3) and (483 << 21, 5). The last two are > 10^9.

constexpr int size(int s) { return s > 1 ? 32-__builtin_clz(s)
    ↪ -1 : 0; }
void genRoots(vmi& roots) { // primitive n-th roots of unity
    int n = sz(roots); mi r = pow(mi(root), (MOD-1)/n);
    roots[0] = 1; FOR(i,1,n) roots[i] = roots[i-1]*r;
}
void genRoots(vcd& roots) { // change cd to complex<double>
    ↪ instead?
    int n = sz(roots); double ang = 2*PI/n;
    FOR(i,n) roots[i] = cd(cos(ang*i), sin(ang*i)); // is there a
        ↪ way to do this more quickly?
}

template<class T> void fft(vector<T>& a, const vector<T>& roots
    ↪, bool inv = 0) {
    int n = sz(a);
    for (int i = 1, j = 0; i < n; i++) { // sort by reverse bit
        ↪ representation
        int bit = n >> 1;
        for (; j&bit; bit >>= 1) j ^= bit;
        j ^= bit; if (i < j) swap(a[i], a[j]);
    }
    for (int len = 2; len <= n; len <= 1)
        for (int i = 0; i < n; i += len)
            FOR(j,len/2) {
                int ind = n/len*j; if (inv && ind) ind = n-ind;
                auto u = a[i+j], v = a[i+j+len/2]*roots[ind];
                a[i+j] = u+v, a[i+j+len/2] = u-v;
            }
    if (inv) { T i = T(1)/T(n); trav(x,a) x *= i; }
}

template<class T> vector<T> mult(vector<T> a, vector<T> b) {
    int s = sz(a)+sz(b)-1, n = 1<<size(s);
    vector<T> roots(n); genRoots(roots);
    a.rsz(n), fft(a,roots);
    b.rsz(n), fft(b,roots);
    FOR(i,n) a[i] *= b[i];
    fft(a,roots,1); return a;
}
```

FFTmod.h  
Description: multiply two polynomials with arbitrary MOD ensures precision by splitting in half

"FFT.h"	27 lines
---------	----------

```
vl multMod(const vl& a, const vl& b) {
    if (!min(sz(a),sz(b))) return {};
    int s = sz(a)+sz(b)-1, n = 1<<size(s), cut = sqrt(MOD);
    vcd roots(n); genRoots(roots);

    vcd ax(n), bx(n);
    FOR(i,sz(a)) ax[i] = cd((int)a[i]/cut, (int)a[i]%cut); // ax(
        ↪ x)=a1(x)+i*a0(x)
    FOR(i,sz(b)) bx[i] = cd((int)b[i]/cut, (int)b[i]%cut); // bx(
        ↪ x)=b1(x)+i*b0(x)
    fft(ax,roots), fft(bx,roots);

    vcd vl(n), v0(n);
    FOR(i,n) {
        int j = (i ? (n-i) : i);
        vl[i] = (ax[i]+conj(ax[j]))*cd(0.5,0)*bx[i]; // vl = a1*b1
            ↪ +b0*cd(0,1));
        v0[i] = (ax[i]-conj(ax[j]))*cd(0,-0.5)*bx[i]; // v0 = a0*(
            ↪ b1+b0*cd(0,1));
    }
    fft(vl,roots,1), fft(v0,roots,1);

    vl ret(n);
    FOR(i,n) {
        ll V2 = (ll)round(vl[i].real()); // a1*b1
        ll V1 = (ll)round(vl[i].imag())+(ll)round(v0[i].real()); //
            ↪ a0*b1+a1*b0
        ll V0 = (ll)round(v0[i].imag()); // a0*b0
        ret[i] = ((V2%MOD*cut+V1)%MOD*cut+V0)%MOD;
    }
    ret.rsz(s); return ret;
} // ~0.8s when sz(a)=sz(b)=1<<19
```

PolyInv.h  
Description: ?  
Time: ?

"FFT.h"	11 lines
---------	----------

```
template<class T> vector<T> inv(vector<T> v, int p) { //
    ↪ compute inverse of v mod x^p, where v[0] = 1
    v.rsz(p); vector<T> a = {T(1)/v[0]};
    for (int i = 1; i < p; i *= 2) {
        if (2*i > p) v.rsz(2*i);
        auto l = vector<T>(begin(v),begin(v)+i), r = vector<T>(
            ↪ begin(v)+i,begin(v)+2*i);
        auto c = mult(a,l); c = vector<T>(begin(c)+i,end(c));
        auto b = mult(a*T(-1),mult(a,r)+c); b.rsz(i);
        a.insert(end(a),all(b));
    }
    a.rsz(p); return a;
}
```

PolyDiv.h  
Description: divide two polynomials  
Time:  $\mathcal{O}(N \log N)$

"PolyInv.h"	7 lines
-------------	---------

```
template<class T> pair<vector<T>,vector<T>> divi(const vector<T>
    ↪ &f, const vector<T>& g) { // f = q*g+r
    if (sz(f) < sz(g)) return {{},f};
    auto q = mult(inv(rev(g),sz(f)-sz(g)+1),rev(f));
    q.rsz(sz(f)-sz(g)+1); q = rev(q);
    auto r = f-mult(q,g); r.rsz(sz(g)-1);
    return {q,r};
}
```

PolySqrt.h  
Description: find sqrt of polynomial  
Time:  $\mathcal{O}(N \log N)$ ?

"PolyInv.h"	8 lines
-------------	---------

```
template<class T> vector<T> sqrt(vector<T> v, int p) { // S*S =
    ↪ v mod x^p, p is power of 2
    assert(v[0] == 1); if (p == 1) return {1};
    v.rsz(p);
    auto S = sqrt(v,p/2);
    auto ans = S+mult(v,inv(S,p));
    ans.rsz(p); ans *= T(1)/T(2);
    return ans;
}
```

6.3 Misc

LinRec.h  
Description: Berlekamp-Massey: computes linear recurrence of order n for sequence of 2n terms  
Time: ?

	35 lines
--	----------

```
using namespace vecOp;

struct LinRec {
    vmi x; // original sequence
    vmi C, rC;
    void init(const vmi& _x) {
        x = _x; int n = sz(x), m = 0;
        vmi B; B = C = {1}; // B is fail vector

        mi b = 1; // B gives 0,0,0,...,b
        FOR(i,n) {
            m ++;
            mi d = x[i]; FOR(j,1,sz(C)) d += C[j]*x[i-j];
            if (d == 0) continue; // recurrence still works
            auto _B = C; C.rsz(max(sz(C),m+sz(B)));
            mi coef = d/b; FOR(j,m,m+sz(B)) C[j] -= coef*B[j-m]; //
                ↪ recurrence that gives 0,0,0,...,d
            if (sz(_B) < m+sz(B)) { B = _B; b = d; m = 0; }
        }

        rC = C; reverse(all(rC)); // polynomial for getPo
        C.erase(begin(C)); trav(t,C) t *= -1; // x[i]=sum_{j=0}^{sz
            ↪ (C)-1}C[j]*x[i-j-1]
        }

        vmi getPo(int n) {
            if (n == 0) return {1};
            vmi x = getPo(n/2); x = rem(x*x,rC);
            if (n&1) { vmi v = {0,1}; x = rem(x*v,rC); }
            return x;
        }
        mi eval(int n) {
            vmi t = getPo(n);
            mi ans = 0; FOR(i,sz(t)) ans += t[i]*x[i];
            return ans;
        }
};
```

Integrate.h  
Description: ?

	8 lines
--	---------

```
// db f(db x) { return x*x+3*x+1; }

db quad(db (*f)(db), db a, db b) {
    const int n = 1000;
    db dif = (b-a)/2/n, tot = f(a)+f(b);
    FOR(i,1,2*n) tot += f(a+i*dif)*(i&1?4:2);
    return tot*dif/3;
}
```

IntegrateAdaptive.h

Description: ? 30 lines

```
// db f(db x) { return x*x+3*x+1; }

db simpson(db (*f)(db), db a, db b) {
    db c = (a+b) / 2;
    return (f(a) + 4*f(c) + f(b)) * (b-a) / 6;
}

db rec(db (*f)(db), db a, db b, db eps, db S) {
    db c = (a+b) / 2;
    db S1 = simpson(f, a, c);
    db S2 = simpson(f, c, b), T = S1 + S2;
    if (abs(T - S) <= 15*eps || b-a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps/2, S1) + rec(f, c, b, eps/2, S2);
}

db quad(db (*f)(db), db a, db b, db eps = 1e-8) {
    return rec(f, a, b, eps, simpson(f, a, b));
}
```

Simplex.h

Description: Simplex algorithm for linear programming, maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$

Time: ? 73 lines

```
typedef double T;
typedef vector<T> vd;
typedef vector<vd> vvd;
const T eps = 1e-8, inf = 1/.0;

#define ltj(X) if (s == -1 || mp(X[j],N[j]) < mp(X[s],N[s])) s=j

struct LPSolver {
    int m, n;
    vi N, B;
    vvd D;

    LPSolver(const vvd& A, const vd& b, const vd& c) :
        m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
        FOR(i,m) FOR(j,n) D[i][j] = A[i][j];
        FOR(i,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i]; }
            // B[i] -> basic variables, col n+1 is for constants
            // why D[i][n]=-1?
        FOR(j,n) { N[j] = j; D[m][j] = -c[j]; } // N[j] -> non-
            // basic variables, all zero
        N[n] = -1; D[m+1][n] = 1;
    }

    void print() {
        ps("D");
        trav(t,D) ps(t);
        ps();
        ps("B",B);
        ps("N",N);
        ps();
    }

    void pivot(int r, int s) { // row, column
        T *a = D[r].data(), inv = 1/a[s]; // eliminate col s from
            // consideration
        FOR(i,m+2) if (i != r && abs(D[i][s]) > eps) {
            T *b = D[i].data(), inv2 = b[s]*inv;
            FOR(j,n+2) b[j] -= a[j]*inv2;
```

```
        b[s] = a[s]*inv2;
    }
    FOR(j,n+2) if (j != s) D[r][j] *= inv;
    FOR(i,m+2) if (i != r) D[i][s] *= -inv;
    D[r][s] = inv; swap(B[r], N[s]); // swap a basic and non-
        // basic variable
    }

    bool simplex(int phase) {
        int x = m+phase-1;
        for (;;) {
            int s = -1; FOR(j,n+1) if (N[j] != -phase) ltj(D[x]); //
                // find most negative col
            if (D[x][s] >= -eps) return true; // have best solution
            int r = -1;
            FOR(i,m) {
                if (D[i][s] <= eps) continue;
                if (r == -1 || mp(D[i][n+1] / D[i][s], B[i])
                    < mp(D[r][n+1] / D[r][s], B[r])) r = i; // find
                    // smallest positive ratio
            }
            if (r == -1) return false; // unbounded
            pivot(r, s);
        }
    }

    T solve(vd &x) {
        int r = 0; FOR(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
        if (D[r][n+1] < -eps) { // x=0 is not a solution
            pivot(r, n); // -1 is artificial variable, initially set
                // to smth large but want to get to 0
            if (!simplex(2) || D[m+1][n+1] < -eps) return -inf; // no
                // solution
            // D[m+1][n+1] is max possible value of the negation of
                // artificial variable, starts negative but should get
                // to zero
            FOR(i,m) if (B[i] == -1) {
                int s = 0; FOR(j,1,n+1) ltj(D[i]);
                pivot(i,s);
            }
        }
        bool ok = simplex(1); x = vd(n);
        FOR(i,m) if (B[i] < n) x[B[i]] = D[i][n+1];
        return ok ? D[m][n+1] : inf;
    }
};
```

Graphs (7)

7.1 Fundamentals

DSU.h

Description: ? 29 lines

```
template<int SZ> struct DSU {
    int par[SZ];
    int size[SZ];
    DSU() {
        M00(i, SZ) par[i] = i, size[i] = 1;
    }
    int get(int node) {
        if(par[node] != node) par[node] = get(par[node]);
        return par[node];
    }
    bool connected(int n1, int n2) {
        return (get(n1) == get(n2));
    }
};
```

```
int sz(int node) {
    return size[get(node)];
}
void unite(int n1, int n2) {
    n1 = get(n1);
    n2 = get(n2);
    if(n1 == n2) return;
    if(rand()%2) {
        par[n1] = n2;
        size[n2] += size[n1];
    } else {
        par[n2] = n1;
        size[n1] += size[n2];
    }
}
};
```

ManhattanMST.h

Description: Compute minimum spanning tree of points where edges are manhattan distances

Time:  $\mathcal{O}(N \log N)$  60 lines

```
"MST.h"

int N;
vector<array<int,3>> cur;
vector<pair<ll,pi>> ed;
vi ind;

struct {
    map<int,pi> m;
    void upd(int a, pi b) {
        auto it = m.lb(a);
        if (it != m.end() && it->s <= b) return;
        m[a] = b; it = m.find(a);
        while (it != m.begin() && prev(it)->s >= b) m.erase(prev(it)
            // );
    }
    pi query(int y) { // for all a > y find min possible value of
        // a
        auto it = m.ub(y);
        if (it == m.end()) return {2*MOD,2*MOD};
        return it->s;
    }
} S;

void solve() {
    sort(all(ind),[](int a, int b) { return cur[a][0] > cur[b]
        // [0]; });
    S.m.clear();
    int nex = 0;
    trav(x,ind) { // cur[x][0] <= ?, cur[x][1] < ?
        while (nex < N && cur[ind[nex]][0] >= cur[x][0]) {
            int b = ind[nex++];
            S.upd(cur[b][1],{cur[b][2],b});
        }
        pi t = S.query(cur[x][1]);
        if (t.s != 2*MOD) ed.pb({(1ll)t.f-cur[x][2],{x,t.s}});
    }
}

ll mst(vpi v) {
    N = sz(v); cur.resz(N); ed.clear();
    ind.clear(); FOR(i,N) ind.pb(i);
    sort(all(ind),[&v](int a, int b) { return v[a] < v[b]; });
    FOR(i,N-1) if (v[ind[i]] == v[ind[i+1]]) ed.pb({0,{ind[i],ind
        // [i+1]}});
    FOR(i,2) { // it's probably ok to consider just two quadrants
        //
        FOR(i,N) {
```

```

    auto a = v[i];
    cur[i][2] = a.f+a.s;
}
FOR(i,N) { // first octant
    auto a = v[i];
    cur[i][0] = a.f-a.s;
    cur[i][1] = a.s;
}
solve();
FOR(i,N) { // second octant
    auto a = v[i];
    cur[i][0] = a.f;
    cur[i][1] = a.s-a.f;
}
solve();
trav(a,v) a = {a.s,-a.f}; // rotate 90 degrees, repeat
}
return kruskal(ed);
}

```

## Dijkstra.h

**Description:** Dijkstra's algorithm for shortest path

**Time:**  $\mathcal{O}(E \log V)$

31 lines

```

template<int SZ> struct dijkstra {
    vector<pair<int, ll>> adj[SZ];
    bool vis[SZ];
    ll d[SZ];

    void addEdge(int u, int v, ll l) {
        adj[u].PB(MP(v, l));
    }

    ll dist(int v) {
        return d[v];
    }

    void build(int u) {
        M00(i, SZ) vis[i] = 0;
        priority_queue<pair<ll, int>, vector<pair<ll, int>>,
            <greater<pair<ll, int>>> pq;
        M00(i, SZ) d[i] = 1e17;
        d[u] = 0;
        pq.push(MP(0, u));
        while(!pq.empty()) {
            pair<ll, int> t = pq.top(); pq.pop();
            while(!pq.empty() && vis[t.S]) t = pq.top(), pq.pop()
                <math>\hookrightarrow</math>();
            vis[t.S] = 1;

            for(auto& v: adj[t.S]) if(!vis[v.F]) {
                if(d[v.F] > d[t.S] + v.S) {
                    d[v.F] = d[t.S] + v.S;
                    pq.push(MP(d[v.F], v.F));
                }
            }
        }
    }
};

```

## DijkstraV2.h

**Description:** Dijkstra's algorithm for shortest path

**Time:**  $\mathcal{O}(V^2)$

27 lines

```

template<int SZ> struct dijkstra {
    vector<pair<int, ll>> adj[SZ];
    bool vis[SZ];
    ll d[SZ];

    void addEdge(int u, int v, ll l) {
        adj[u].PB(MP(v, l));
    }
}

```

```

}
ll dist(int v) {
    return d[v];
}

void build(int u) {
    M00(i, SZ) vis[i] = 0;
    M00(i, SZ) d[i] = 1e17;
    d[u] = 0;
    while(1) {
        pair<ll, int> t = MP(1e17, -1);
        M00(i, SZ) if(!vis[i]) t = min(t, MP(d[i], i));
        if(t.S == -1) return;
        vis[t.S] = 1;

        for(auto& v: adj[t.S]) if(!vis[v.F]) {
            if(d[v.F] > d[t.S] + v.S) d[v.F] = d[t.S] + v.S
                <math>\hookrightarrow</math>;
        }
    }
}

};

```

## 7.2 Trees

### LCAjumps.h

**Description:** calculates least common ancestor in tree with binary jumping

**Time:**  $\mathcal{O}(N \log N)$

44 lines

```

template<int SZ> struct tree {
    vector<pair<int, ll>> adj[SZ];
    const static int LGSZ = 32-__builtin_clz(SZ-1);
    pair<int, ll> ppar[SZ][LGSZ];
    int depth[SZ];
    ll distfromroot[SZ];

    void addEdge(int u, int v, int d) {
        adj[u].PB(MP(v, d));
        adj[v].PB(MP(u, d));
    }

    void dfs(int u, int dep, ll dis) {
        depth[u] = dep;
        distfromroot[u] = dis;
        for(auto& v: adj[u]) if(ppar[u][0].F != v.F) {
            ppar[v.F][0] = MP(u, v.S);
            dfs(v.F, dep + 1, dis + v.S);
        }
    }

    void build() {
        ppar[0][0] = MP(0, 0);
        M00(i, SZ) depth[i] = 0;
        dfs(0, 0, 0);
        M00(i, 1, LGSZ) M00(j, SZ) {
            ppar[j][i].F = ppar[ppar[j][i-1].F][i-1].F;
            ppar[j][i].S = ppar[j][i-1].S + ppar[ppar[j][i-1].F][i-1].S
                <math>\hookrightarrow</math>[i-1].S;
        }
    }

    int lca(int u, int v) {
        if(depth[u] < depth[v]) swap(u, v);
        M00d(i, LGSZ) if(depth[ppar[u][i].F] >= depth[v]) u =
            <math>\hookrightarrow</math>ppar[u][i].F;
        if(u == v) return u;
        M00d(i, LGSZ) {
            if(ppar[u][i].F != ppar[v][i].F) {
                u = ppar[u][i].F;
                v = ppar[v][i].F;
            }
        }
        return ppar[u][0].F;
    }
}

```

```

}
ll dist(int u, int v) {
    return distfromroot[u] + distfromroot[v] - 2*
        <math>\hookrightarrow</math>distfromroot[lca(u, v)];
}

};

```

## CentroidDecomp.h

**Description:** can support tree path queries and updates

**Time:**  $\mathcal{O}(N \log N)$

45 lines

```

template<int SZ> struct CD {
    vi adj[SZ];
    bool done[SZ];
    int sub[SZ], par[SZ];
    vl dist[SZ];
    pi cen[SZ];
    void addEdge(int a, int b) { adj[a].pb(b), adj[b].pb(a); }

    void dfs (int x) {
        sub[x] = 1;
        trav(y,adj[x]) if (!done[y] && y != par[x]) {
            par[y] = x; dfs(y);
            sub[x] += sub[y];
        }
    }

    int centroid(int x) {
        par[x] = -1; dfs(x);
        for (int sz = sub[x];;) {
            pi mx = {0,0};
            trav(y,adj[x]) if (!done[y] && y != par[x])
                ckmax(mx,{sub[y],y});
            if (mx.f*2 <= sz) return x;
            x = mx.s;
        }
    }

    void genDist(int x, int p) {
        dist[x].pb(dist[p].back()+1);
        trav(y,adj[x]) if (!done[y] && y != p) {
            cen[y] = cen[x];
            genDist(y,x);
        }
    }

    void gen(int x, bool fst = 0) {
        done[x = centroid(x)] = 1; dist[x].pb(0);
        if (fst) cen[x].f = -1;
        int co = 0;
        trav(y,adj[x]) if (!done[y]) {
            cen[y] = {x,co++};
            genDist(y,x);
        }
        trav(y,adj[x]) if (!done[y]) gen(y);
    }

    void init() { gen(1,1); }
};

```

## HLD.h

**Description:** Heavy Light Decomposition

**Time:**  $\mathcal{O}(\log^2 N)$  per path operations

50 lines

```

template<int SZ, bool VALUES_IN_EDGES> struct HLD {
    int N; vi adj[SZ];
    int par[SZ], sz[SZ], depth[SZ];
    int root[SZ], pos[SZ];
    LazySegTree<ll,SZ> tree;
    void addEdge(int a, int b) { adj[a].pb(b), adj[b].pb(a); }

    void dfs_sz(int v = 1) {

```

```

    if (par[v]) adj[v].erase(find(all(adj[v]),par[v]));
    sz[v] = 1;
    trav(u,adj[v]) {
        par[u] = v; depth[u] = depth[v]+1;
        dfs_sz(u); sz[v] += sz[u];
        if (sz[u] > sz[adj[v][0]]) swap(u, adj[v][0]);
    }
}
void dfs_hld(int v = 1) {
    static int t = 0;
    pos[v] = t++;
    trav(u,adj[v]) {
        root[u] = (u == adj[v][0] ? root[v] : u);
        dfs_hld(u);
    }
}
void init(int _N) {
    N = _N; par[1] = depth[1] = 0; root[1] = 1;
    dfs_sz(); dfs_hld();
}

template <class BinaryOperation>
void processPath(int u, int v, BinaryOperation op) {
    for (; root[u] != root[v]; v = par[root[v]]) {
        if (depth[root[u]] > depth[root[v]]) swap(u, v);
        op(pos[root[v]], pos[v]);
    }
    if (depth[u] > depth[v]) swap(u, v);
    op(pos[u]+VALUES_IN_EDGES, pos[v]);
}

void modifyPath(int u, int v, int val) { // add val to
    ↪ vertices/edges along path
    processPath(u, v, [this, &val](int l, int r) { tree.upd(l,
        ↪ r, val); });
}
void modifySubtree(int v, int val) { // add val to vertices/
    ↪ edges in subtree
    tree.upd(pos[v]+VALUES_IN_EDGES, pos[v]+sz[v]-1, val);
}
ll queryPath(int u, int v) { // query sum of path
    ll res = 0; processPath(u, v, [this, &res](int l, int r) {
        ↪ res += tree.qsum(l, r); });
    return res;
}
};

```

## 7.3 DFS Algorithms

### SCC.h

**Description:** Kosaraju's Algorithm: DFS two times to generate SCCs in topological order

**Time:**  $\mathcal{O}(N + M)$

24 lines

```

template<int SZ> struct SCC {
    int N, comp[SZ];
    vi adj[SZ], radj[SZ], todo, allComp;
    bitset<SZ> visit;
    void addEdge(int a, int b) { adj[a].pb(b), radj[b].pb(a); }

    void dfs(int v) {
        visit[v] = 1;
        trav(w,adj[v]) if (!visit[w]) dfs(w);
        todo.pb(v);
    }
    void dfs2(int v, int val) {
        comp[v] = val;
        trav(w,radj[v]) if (comp[w] == -1) dfs2(w,val);
    }
}

```

```

void init(int _N) { // fills allComp
    N = _N;
    FOR(i,N) comp[i] = -1, visit[i] = 0;
    FOR(i,N) if (!visit[i]) dfs(i);
    reverse(all(todo)); // now todo stores vertices in order of
        ↪ topological sort
    trav(i,todo) if (comp[i] == -1) dfs2(i,i), allComp.pb(i);
}
};

```

### 2SAT.h

**Description:** ?

"SCC.h"

38 lines

```

template<int SZ> struct TwoSat {
    SCC<2*SZ> S;
    bitset<SZ> ans;
    int N = 0;
    int addVar() { return N++; }

    void either(int x, int y) {
        x = max(2*x,-1-2*x), y = max(2*y,-1-2*y);
        S.addEdge(x^1,y); S.addEdge(y^1,x);
    }
    void implies(int x, int y) { either(~x,y); }
    void setVal(int x) { either(x,x); }
    void atMostOne(const vi& li) {
        if (sz(li) <= 1) return;
        int cur = ~li[0];
        FOR(i,2,sz(li)) {
            int next = addVar();
            either(cur,~li[i]);
            either(cur,next);
            either(~li[i],next);
            cur = ~next;
        }
        either(cur,~li[1]);
    }

    bool solve(int _N) {
        if (_N != -1) N = _N;
        S.init(2*N);
        for (int i = 0; i < 2*N; i += 2)
            if (S.comp[i] == S.comp[i^1]) return 0;
        reverse(all(S.allComp));
        vi tmp(2*N);
        trav(i,S.allComp) if (tmp[i] == 0)
            tmp[i] = 1, tmp[S.comp[i^1]] = -1;
        FOR(i,N) if (tmp[S.comp[2*i]] == 1) ans[i] = 1;
        return 1;
    }
}
};

```

### EulerPath.h

**Description:** Eulerian Path for both directed and undirected graphs

**Time:**  $\mathcal{O}(N + M)$

30 lines

```

template<int SZ, bool directed> struct Euler {
    int N, M = 0;
    vpi adj[SZ];
    vpi::iterator its[SZ];
    vector<bool> used;

    void addEdge(int a, int b) {
        if (directed) adj[a].pb({b,M});
        else adj[a].pb({b,M}), adj[b].pb({a,M});
        used.pb(0); M++;
    }
}

```

```

vpi solve(int _N, int src = 1) {
    N = _N;
    FOR(i,1,N+1) its[i] = begin(adj[i]);
    vector<pair<pi,int>> ret, s = {{{src,-1},-1}};
    while (sz(s)) {
        int x = s.back().f.f;
        auto& it = its[x], end = adj[x].end();
        while (it != end && used[it->s]) it++;
        if (it == end) {
            if (sz(ret) && ret.back().f.s != s.back().f.f) return
                ↪ {}; // path isn't valid
            ret.pb(s.back()), s.pop_back();
        } else { s.pb({it->f,x},it->s}); used[it->s] = 1; }
    }
    if (sz(ret) != M+1) return {};
    vpi ans; trav(t,ret) ans.pb({t.f.f,t.s});
    reverse(all(ans)); return ans;
}
};

```

### BCC.h

**Description:** computes biconnected components

**Time:**  $\mathcal{O}(N + M)$

37 lines

```

template<int SZ> struct BCC {
    int N;
    vpi adj[SZ], ed;
    void addEdge(int u, int v) {
        adj[u].pb({v,sz(ed)}), adj[v].pb({u,sz(ed)});
        ed.pb({u,v});
    }

    int disc[SZ];
    vi st; vector<vi> fin;
    int bcc(int u, int p = -1) { // return lowest disc
        static int ti = 0;
        disc[u] = ++ti; int low = disc[u];
        int child = 0;
        trav(i,adj[u]) if (i.s != p)
            if (!disc[i.f]) {
                child++; st.pb(i.s);
                int LOW = bcc(i.f,i.s); ckmin(low,LOW);
                // disc[u] < LOW -> bridge
                if (disc[u] <= LOW) {
                    // if (p != -1 || child > 1) -> u is articulation
                    ↪ point
                    vi tmp; while (st.back() != i.s) tmp.pb(st.back()),
                        ↪ st.pop_back();
                    tmp.pb(st.back()), st.pop_back();
                    fin.pb(tmp);
                }
            } else if (disc[i.f] < disc[u]) {
                ckmin(low, disc[i.f]);
                st.pb(i.s);
            }
        return low;
    }

    void init(int _N) {
        N = _N; FOR(i,N) disc[i] = 0;
        FOR(i,N) if (!disc[i]) bcc(i); // st should be empty after
            ↪ each iteration
    }
}
};

```



7.4 Flows

Dinic.h

Description: faster flow

Time:  $\mathcal{O}(N^2M)$  flow,  $\mathcal{O}(M\sqrt{N})$  bipartite matching

<pre>template&lt;int SZ&gt; struct Dinic {     typedef ll F; // flow type     struct Edge { int to, rev; F flow, cap; };      int N,s,t;     vector&lt;Edge&gt; adj[SZ];     typename vector&lt;Edge&gt;::iterator cur[SZ];     void addEdge(int u, int v, F cap) {         assert(cap &gt;= 0); // don't try smth dumb         Edge a{v, sz(adj[v]), 0, cap}, b{u, sz(adj[u]), 0, 0};         adj[u].pb(a), adj[v].pb(b);     }      int level[SZ];     bool bfs() { // level = shortest distance from source         // after computing flow, edges {u,v} such that level[u] \         //   ↳ neq -1, level[v] = -1 are part of min cut         M00(i,N) level[i] = -1, cur[i] = begin(adj[i]);         queue&lt;int&gt; q({s}); level[s] = 0;         while (sz(q)) {             int u = q.front(); q.pop();             for(Edge e: adj[u]) if (level[e.to] &lt; 0 &amp;&amp; e.flow &lt;                 ↳ e.cap)                 q.push(e.to), level[e.to] = level[u]+1;         }         return level[t] &gt;= 0;     }     F sendFlow(int v, F flow) {         if (v == t) return flow;         for (; cur[v] != end(adj[v]); cur[v]++) {             Edge&amp; e = *cur[v];             if (level[e.to] != level[v]+1    e.flow == e.cap)                 ↳ continue;             auto df = sendFlow(e.to,min(flow,e.cap-e.flow));             if (df) { // saturated at least one edge                 e.flow += df; adj[e.to][e.rev].flow -= df;                 return df;             }         }         return 0;     }     F maxFlow(int _N, int _s, int _t) {         N = _N, s = _s, t = _t; if (s == t) return -1;         F tot = 0;         while (bfs()) while (auto df = sendFlow(s,numeric_limits&lt;F&gt;             ↳ &gt;::max())) tot += df;         return tot;     } };</pre>	45 lines
--	----------

MCMF.h

Description: Min-Cost Max Flow, no negative cycles allowed

Time:  $\mathcal{O}(NM^2 \log M)$

<pre>template&lt;class T&gt; using pqg = priority_queue&lt;T,vector&lt;T&gt;,     ↳ greater&lt;T&gt;&gt;; template&lt;class T&gt; T poll(pqg&lt;T&gt;&amp; x) {     T y = x.top(); x.pop();     return y; }  template&lt;int SZ&gt; struct mcmf {     typedef ll F; typedef ll C;</pre>	53 lines
---	----------

<pre>struct Edge { int to, rev; F flow, cap; C cost; int id; }; vector&lt;Edge&gt; adj[SZ]; void addEdge(int u, int v, F cap, C cost) {     assert(cap &gt;= 0);     Edge a{v, sz(adj[v]), 0, cap, cost}, b{u, sz(adj[u]), 0, 0,         ↳ -cost};     adj[u].pb(a), adj[v].pb(b); }  int N, s, t; pi pre[SZ]; // previous vertex, edge label on path pair&lt;C,F&gt; cost[SZ]; // tot cost of path, amount of flow C totCost, curCost; F totFlow; void reweight() { // makes all edge costs non-negative     // all edges on shortest path become 0     F0R(i,N) trav(p,adj[i]) p.cost += cost[i].f-cost[p.to].f; } bool spfa() { // reweight ensures that there will be negative     ↳ weights     // only during the first time you run this     F0R(i,N) cost[i] = {INF,0}; cost[s] = {0,INF};     pqg&lt;pair&lt;C,int&gt;&gt; todo; todo.push({0,s});     while (sz(todo)) {         auto x = poll(todo); if (x.f &gt; cost[x.s].f) continue;         trav(a,adj[x.s]) if (x.f+a.cost &lt; cost[a.to].f &amp;&amp; a.flow             ↳ &lt; a.cap) {             // if costs are doubles, add some EPS to ensure that             // you do not traverse some 0-weight cycle repeatedly             pre[a.to] = {x.s,a.rev};             cost[a.to] = {x.f+a.cost,min(a.cap-a.flow,cost[x.s].s)                 ↳ };             todo.push({cost[a.to].f,a.to});         }         curCost += cost[t].f; return cost[t].s;     } } void backtrack() {     F df = cost[t].s; totFlow += df, totCost += curCost*df;     for (int x = t; x != s; x = pre[x].f) {         adj[x][pre[x].s].flow -= df;         adj[pre[x].f][adj[x][pre[x].s].rev].flow += df;     } } pair&lt;F,C&gt; calc(int _N, int _s, int _t) {     N = _N; s = _s, t = _t; totFlow = totCost = curCost = 0;     while (spfa()) reweight(), backtrack();     return {totFlow, totCost}; } };</pre>	56 lines
---	----------

GomoryHu.h

Description: Compute max flow between every pair of vertices of undirected graph

<pre>"Dinic.h" template&lt;int SZ&gt; struct GomoryHu {     int N;     vector&lt;pair&lt;pi,int&gt;&gt; ed;     void addEdge(int a, int b, int c) { ed.pb({{a,b},c}); }      vector&lt;vi&gt; cor = {}; // groups of vertices     map&lt;int,int&gt; adj[2*SZ]; // current edges of tree     int side[SZ];      int gen(vector&lt;vi&gt; cc) {         Dinic&lt;SZ&gt; D = Dinic&lt;SZ&gt;();         vi comp(N+1); F0R(i,sz(cc)) trav(t,cc[i]) comp[t] = i;         trav(t,ed) if (comp[t.f.f] != comp[t.f.s]) {             D.addEdge(comp[t.f.f],comp[t.f.s],t.s);         }     } };</pre>	26 lines
--	----------

<pre>D.addEdge(comp[t.f.s],comp[t.f.f],t.s); } int f = D.maxFlow(0,1); F0R(i,sz(cc)) trav(j,cc[i]) side[j] = D.level[i] &gt;= 0; //     ↳ min cut return f; }  void fill(vi&amp; v, int a, int b) {     trav(t,cor[a]) v.pb(t);     trav(t,adj[a]) if (t.f != b) fill(v,t.f,a); }  void addTree(int a, int b, int c) { adj[a][b] = c, adj[b][a]     ↳ = c; } void delTree(int a, int b) { adj[a].erase(b), adj[b].erase(a)     ↳ ; }  vector&lt;pair&lt;pi,int&gt;&gt; init(int _N) { // returns edges of     ↳ Gomory-Hu Tree     N = _N;     F0R(i,1,N+1) cor[0].pb(i);     queue&lt;int&gt; todo; todo.push(0);     while (sz(todo)) {         int x = todo.front(); todo.pop();         vector&lt;vi&gt; cc; trav(t,cor[x]) cc.pb({t});         trav(t,adj[x]) {             cc.pb({});             fill(cc.back(),t.f,x);         }         int f = gen(cc); // run max flow         cor.pb({}), cor.pb({});         trav(t,cor[x]) cor[sz(cor)-2+side[t]].pb(t);         F0R(i,2) if (sz(cor[sz(cor)-2+i]) &gt; 1) todo.push(sz(cor)             ↳ -2+i);         F0R(i,sz(cor)-2) if (i != x &amp;&amp; adj[i].count(x)) {             addTree(i,sz(cor)-2+side[cor[i][0]],adj[i][x]);             delTree(i,x);         } // modify tree edges         addTree(sz(cor)-2,sz(cor)-1,f);     }     vector&lt;pair&lt;pi,int&gt;&gt; ans;     F0R(i,sz(cor)) trav(j,adj[i]) if (i &lt; j.f)         ans.pb({{cor[i][0],cor[j.f][0]},j.s});     return ans; } };</pre>	26 lines
--	----------

7.5 Matching

DFSmatch.h

Description: naive bipartite matching

Time:  $\mathcal{O}(NM)$

<pre>template&lt;int SZ&gt; struct MaxMatch {     int N, flow = 0, match[SZ], rmatch[SZ];     bitset&lt;SZ&gt; vis;     vi adj[SZ];     MaxMatch() {         memset(match,0,sizeof match);         memset(rmatch,0,sizeof rmatch);     }      void connect(int a, int b, bool c = 1) {         if (c) match[a] = b, rmatch[b] = a;         else match[a] = rmatch[b] = 0;     }     bool dfs(int x) {         if (!x) return 1;     } };</pre>	26 lines
--	----------

```
    if (vis[x]) return 0;
    vis[x] = 1;
    trav(t,adj[x]) if (t != match[x] && dfs(rmatch[t]))
        return connect(x,t),1;
    return 0;
}
void tri(int x) { vis.reset(); flow += dfs(x); }
void init(int _N) {
    N = _N; FOR(i,1,N+1) if (!match[i]) tri(i);
}
};
```

Hungarian.h

Description: finds min cost to complete n jobs w/ m workers each worker is assigned to at most one job (n <= m)

Time: ?

28 lines

```
int HungarianMatch(const vector<vi>& a) { // cost array,
    ↪negative values are ok
    int n = sz(a)-1, m = sz(a[0])-1; // jobs 1..n, workers 1..m
    vi u(n+1), v(m+1), p(m+1); // p[j] -> job picked by worker j
    FOR(i,1,n+1) { // find alternating path with job i
        p[0] = i; int j0 = 0;
        vi dist(m+1, MOD), pre(m+1,-1); // dist, previous vertex on
            ↪ shortest path
        vector<bool> done(m+1, false);
        do {
            done[j0] = true;
            int i0 = p[j0], j1; int delta = MOD;
            FOR(j,1,m+1) if (!done[j]) {
                auto cur = a[i0][j]-u[i0]-v[j];
                if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
                if (dist[j] < delta) delta = dist[j], j1 = j;
            }
            FOR(j,m+1) // just dijkstra with potentials
                if (done[j]) u[p[j]] += delta, v[j] -= delta;
                else dist[j] -= delta;
            j0 = j1;
        } while (p[j0]);
        do { // update values on alternating path
            int j1 = pre[j0];
            p[j0] = p[j1];
            j0 = j1;
        } while (j0);
    }
    return -v[0]; // min cost
}
```

UnweightedMatch.h

Description: general unweighted matching

Time: ?

79 lines

```
template<int SZ> struct UnweightedMatch {
    int vis[SZ], par[SZ], orig[SZ], match[SZ], aux[SZ], t, N; //
        ↪1-based index
    vi adj[SZ];
    queue<int> Q;
    void addEdge(int u, int v) {
        adj[u].pb(v); adj[v].pb(u);
    }

    void init(int n) {
        N = n; t = 0;
        FOR(i,N+1) {
            adj[i].clear();
            match[i] = aux[i] = par[i] = 0;
        }
    }
};
```

```
void augment(int u, int v) {
    int pv = v, nv;
    do {
        pv = par[v]; nv = match[pv];
        match[v] = pv; match[pv] = v;
        v = nv;
    } while(u != pv);
}

int lca(int v, int w) {
    ++t;
    while (1) {
        if (v) {
            if (aux[v] == t) return v; aux[v] = t;
            v = orig[par[match[v]]];
        }
        swap(v, w);
    }
}

void blossom(int v, int w, int a) {
    while (orig[v] != a) {
        par[v] = w; w = match[v];
        if (vis[w] == 1) Q.push(w), vis[w] = 0;
        orig[v] = orig[w] = a;
        v = par[w];
    }
}

bool bfs(int u) {
    fill(vis+1, vis+1+N, -1); iota(orig + 1, orig + N + 1, 1);
    Q = queue<int> (); Q.push(u); vis[u] = 0;
    while (sz(Q)) {
        int v = Q.front(); Q.pop();
        trav(x,adj[v]) {
            if (vis[x] == -1) {
                par[x] = v; vis[x] = 1;
                if (!match[x]) return augment(u, x), true;
                Q.push(match[x]); vis[match[x]] = 0;
            } else if (vis[x] == 0 && orig[v] != orig[x]) {
                int a = lca(orig[v], orig[x]);
                blossom(x, v, a); blossom(v, x, a);
            }
        }
    }
    return false;
}

int match() {
    int ans = 0;
    // find random matching (not necessary, constant
        ↪improvement)
    vi V(N-1); iota(all(V), 1);
    shuffle(all(V), mt19937(0x94949));
    trav(x,V) if (!match[x])
        trav(y,adj[x]) if (!match[y]) {
            match[x] = y, match[y] = x;
            ++ans; break;
        }

    FOR(i,1,N+1) if (!match[i] && bfs(i)) ++ans;
    return ans;
};
```

7.6 Misc

MaximalCliques.h

Description: Finds all maximal cliques

Time:  $\mathcal{O}\left(3^{n/3}\right)$

19 lines

```
typedef bitset<128> B;
int N;
B adj[128];

void cliques(B P = ~B(), B X={}, B R={}) { // possibly in
    ↪clique, not in clique, in clique
    if (!P.any()) {
        if (!X.any()) {
            // do smth with maximal clique
        }
        return;
    }
    auto q = (P|X)._Find_first();
    auto cand = P&~eds[q]; // clique must contain q or non-
        ↪neighbor of q
    FOR(i,N) if (cand[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

LCT.h

Description: Link-Cut Tree, use vir for subtree size queries

Time:  $\mathcal{O}(\log N)$

96 lines

```
typedef struct snode* sn;

struct snode {
    sn p, c[2]; // parent, children
    int val; // value in node
    int sum, mn, mx; // sum of values in subtree, min and max
        ↪prefix sum
    bool flip = 0;
    // int vir = 0; stores sum of virtual children

    snode(int v) {
        p = c[0] = c[1] = NULL;
        val = v; calc();
    }

    friend int getSum(sn x) { return x?x->sum:0; }
    friend int getMn(sn x) { return x?x->mn:0; }
    friend int getMx(sn x) { return x?x->mx:0; }

    void prop() {
        if (!flip) return;
        swap(c[0],c[1]); tie(mn,mx) = mp(sum-mx,sum-mn);
        FOR(i,2) if (c[i]) c[i]->flip ^= 1;
        flip = 0;
    }
    void calc() {
        FOR(i,2) if (c[i]) c[i]->prop();
        int s0 = getSum(c[0]), s1 = getSum(c[1]); sum = s0+val+s1;
            ↪+vir
        mn = min(getMn(c[0]),s0+val+getMn(c[1]));
        mx = max(getMx(c[0]),s0+val+getMx(c[1]));
    }

    int dir() {
        if (!p) return -2;
        FOR(i,2) if (p->c[i] == this) return i;
    }
};
```

```

    return -1; // p is path-parent pointer, not in current
    ↪ splay tree
}
bool isRoot() { return dir() < 0; }

friend void setLink(sn x, sn y, int d) {
    if (y) y->p = x;
    if (d >= 0) x->c[d] = y;
}
void rot() { // assume p and p->p propagated
    assert(!isRoot()); int x = dir(); sn pa = p;
    setLink(pa->p, this, pa->dir());
    setLink(pa, c[x^1], x);
    setLink(this, pa, x^1);
    pa->calc(); calc();
}
void splay() {
    while (!isRoot() && !p->isRoot()) {
        p->p->prop(), p->prop(), prop();
        dir() == p->dir() ? p->rot() : rot();
        rot();
    }
    if (!isRoot()) p->prop(), prop(), rot();
    prop();
}

void access() { // bring this to top of tree
    for (sn v = this, pre = NULL; v; v = v->p) {
        v->splay();
        // if (pre) v->vir -= pre->sz;
        // if (v->c[1]) v->vir += v->c[1]->sz;
        v->c[1] = pre; v->calc();
        pre = v;
        // v->sz should remain the same if using vir
    }
    splay(); assert(!c[1]); // left subtree of this is now path
    ↪ to root, right subtree is empty
}
void makeRoot() { access(); flip ^= 1; }
void set(int v) { splay(); val = v; calc(); } // change value
    ↪ in node, splay suffices instead of access because it
    ↪ doesn't affect values in nodes above it

friend sn lca(sn x, sn y) {
    if (x == y) return x;
    x->access(), y->access(); if (!x->p) return NULL; // access
    ↪ at y did not affect x, so they must not be connected
    x->splay(); return x->p ? x->p : x;
}
friend bool connected(sn x, sn y) { return lca(x,y); }
friend int balanced(sn x, sn y) {
    x->makeRoot(); y->access();
    return y->sum-2*y->mn;
}

friend bool link(sn x, sn y) { // make x parent of y
    if (connected(x,y)) return 0; // don't induce cycle
    y->makeRoot(); y->p = x;
    // x->access(); x->sz += y->sz; x->vir += y->sz;
    return 1; // success!
}
friend bool cut(sn x, sn y) { // x is originally parent of y
    x->makeRoot(); y->access();
    if (y->c[0] != x || x->c[0] || x->c[1]) return 0; // splay
    ↪ tree with y should not contain anything else besides x
    x->p = y->c[0] = NULL; y->calc(); return 1; // calc is
    ↪ redundant as it will be called elsewhere anyways?
}
};

```

## DirectedMST.h

**Description:** computes minimum weight directed spanning tree, edge from  $inv[i] \rightarrow i$  for all  $i \neq r$

**Time:**  $\mathcal{O}(M \log M)$

```

"DSUrb.h"
64 lines

struct Edge { int a, b; ll w; };
struct Node {
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
        delta = 0;
    }
    Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
    if (!a || !b) return a ? b;
    a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll,vi> dmst(int n, int r, const vector<Edge>& g) {
    DSUrb dsu; dsu.init(n); // DSU with rollback if need to
    ↪ return edges
    vector<Node*> heap(n); // store edges entering each vertex in
    ↪ increasing order of weight
    trav(e,g) heap[e.b] = merge(heap[e.b], new Node(e));
    ll res = 0; vi seen(n,-1); seen[r] = r;
    vpi in(n,{-1,-1});
    vector<pair<int,vector<Edge>>> cys;
    FOR(s,n) {
        int u = s, w;
        vector<pair<int,Edge>> path;
        while (seen[u] < 0) {
            if (!heap[u]) return {-1,{};};
            seen[u] = s;
            Edge e = heap[u]->top(); path.pb({u,e});
            heap[u]->delta -= e.w, pop(heap[u]);
            res += e.w, u = dsu.get(e.a);
            if (seen[u] == s) { // compress verts in cycle
                Node* cyc = 0; cys.pb({u,{};});
                do {
                    cyc = merge(cyc, heap[w = path.back().f]);
                    cys.back().s.pb(path.back().s);
                    path.pop_back();
                } while (dsu.unite(u, w));
                u = dsu.get(u); heap[u] = cyc, seen[u] = -1;
            }
        }
        trav(t,path) in[dsu.get(t.s.b)] = {t.s.a,t.s.b}; // found
        ↪ path from root
    }
    while (sz(cys)) { // expand cys to restore sol
        auto c = cys.back(); cys.pop_back();
        pi inEdge = in[c.f];
        trav(t,c.s) dsu.rollback();
        trav(t,c.s) in[dsu.get(t.b)] = {t.a,t.b};
        in[dsu.get(inEdge.s)] = inEdge;
    }
    vi inv;
    FOR(i,n) {
        assert(i == r ? in[i].s == -1 : in[i].s == i);
        inv.pb(in[i].f);
    }
}

```

```

}
return {res,inv};
}

```

## DominatorTree.h

**Description:**  $a$  dominates  $b$  iff every path from 1 to  $b$  passes through  $a$

**Time:**  $\mathcal{O}(M \log N)$

```

46 lines

template<int SZ> struct Dominator {
    vi adj[SZ], ans[SZ]; // input edges, edges of dominator tree
    vi radj[SZ], child[SZ], sdomChild[SZ];
    int label[SZ], rlabel[SZ], sdom[SZ], dom[SZ], co;
    int root = 1;

    int par[SZ], bes[SZ];
    int get(int x) {
        // DSU with path compression
        // get vertex with smallest sdom on path to root
        if (par[x] != x) {
            int t = get(par[x]); par[x] = par[par[x]];
            if (sdom[t] < sdom[bes[x]]) bes[x] = t;
        }
        return bes[x];
    }

    void dfs(int x) { // create DFS tree
        label[x] = ++co; rlabel[co] = x;
        sdom[co] = par[co] = bes[co] = co;
        trav(y,adj[x]) {
            if (!label[y]) {
                dfs(y);
                child[label[x]].pb(label[y]);
            }
            radj[label[y]].pb(label[x]);
        }
    }
    void init() {
        dfs(root);
        ROF(i,1,co+1) {
            trav(j,radj[i]) ckmin(sdom[i],sdom[get(j)]);
            if (i > 1) sdomChild[sdom[i]].pb(i);
            trav(j,sdomChild[i]) {
                int k = get(j);
                if (sdom[j] == sdom[k]) dom[j] = sdom[j];
                else dom[j] = k;
            }
            trav(j,child[i]) par[j] = i;
        }
        FOR(i,2,co+1) {
            if (dom[i] != sdom[i]) dom[i] = dom[dom[i]];
            ans[rlabel[dom[i]]].pb(rlabel[i]);
        }
    }
};

```

## EdgeColor.h

**Description:** naive implementation of Misra & Gries edge coloring, by Vizing's Theorem a simple graph with max degree  $d$  can be edge colored with at most  $d+1$  colors

**Time:**  $\mathcal{O}(MN^2)$

```

54 lines

template<int SZ> struct EdgeColor {
    int N = 0, maxDeg = 0, adj[SZ][SZ], deg[SZ];
    EdgeColor() {
        memset(adj,0,sizeof adj);
        memset(deg,0,sizeof deg);
    }
    void addEdge(int a, int b, int c) {
        adj[a][b] = adj[b][a] = c;
    }
};

```

```
    }
    int delEdge(int a, int b) {
        int c = adj[a][b];
        adj[a][b] = adj[b][a] = 0;
        return c;
    }
    vector<bool> genCol(int x) {
        vector<bool> col(N+1); FOR(i,N) col[adj[x][i]] = 1;
        return col;
    }
    int freeCol(int u) {
        auto col = genCol(u);
        int x = 1; while (col[x]) x ++; return x;
    }
    void invert(int x, int d, int c) {
        FOR(i,N) if (adj[x][i] == d)
            delEdge(x,i), invert(i,c,d), addEdge(x,i,c);
    }
    void addEdge(int u, int v) { // follows wikipedia steps
        // check if you can add edge w/o doing any work
        assert(N); ckmx(maxDeg,max(++deg[u],++deg[v]));
        auto a = genCol(u), b = genCol(v);
        FOR(i,1,maxDeg+2) if (!a[i] && !b[i]) return addEdge(u,v,i)
            ↪;

        // 2. find maximal fan of u starting at v
        vector<bool> use(N); vi fan = {v}; use[v] = 1;
        while (1) {
            auto col = genCol(fan.back());
            if (sz(fan) > 1) col[adj[fan.back()][u]] = 0;
            int i = 0; while (i < N && (use[i] || col[adj[u][i]])) i
                ↪++;
            if (i < N) fan.pb(i), use[i] = 1;
            else break;
        }

        // 3/4. choose free cols for endpoints of fan, invert cd_u
        ↪path
        int c = freeCol(u), d = freeCol(fan.back()); invert(u,d,c);
        // 5. find i such that d is free on fan[i]
        int i = 0; while (i < sz(fan) && genCol(fan[i])[d]
            && adj[u][fan[i]] != d) i ++;
        assert (i != sz(fan));
        // 6. rotate fan from 0 to i
        FOR(j,i) addEdge(u,fan[j],delEdge(u,fan[j+1]));
        // 7. add new edge
        addEdge(u,fan[i],d);
    }
};
```

## Geometry (8)

### 8.1 Primitives

Point.h

Description: Easy Geo

44 lines

```
typedef ld T;
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }

namespace Point {
    typedef pair<T,T> P;
    typedef vector<P> vP;

    P dir(T ang) {
        auto c = exp(ang*complex<T>(0,1));
        return P(c.real(),c.imag());
    }
}
```

```
T norm(P x) { return x.f*x.f+x.s*x.s; }
T abs(P x) { return sqrt(norm(x)); }
T angle(P x) { return atan2(x.s,x.f); }
P conj(P x) { return P(x.f,-x.s); }

P operator+(const P& l, const P& r) { return P(l.f+r.f,l.s+r.
    ↪s); }
P operator-(const P& l, const P& r) { return P(l.f-r.f,l.s-r.
    ↪s); }
P operator*(const P& l, const T& r) { return P(l.f*r,l.s*r);
    ↪};
P operator*(const T& l, const P& r) { return r*l; }
P operator/(const P& l, const T& r) { return P(l.f/r,l.s/r);
    ↪};
P operator*(const P& l, const P& r) { return P(l.f*r.f-l.s*r.
    ↪s,l.s*r.f+l.f*r.s); }
P operator/(const P& l, const P& r) { return l*conj(r)/norm(r
    ↪); }

P& operator+=(P& l, const P& r) { return l = l+r; }
P& operator-=(P& l, const P& r) { return l = l-r; }
P& operator*=(P& l, const T& r) { return l = l*r; }
P& operator/=(P& l, const T& r) { return l = l/r; }
P& operator*=(P& l, const P& r) { return l = l*r; }
P& operator/=(P& l, const P& r) { return l = l/r; }

P unit(P x) { return x/abs(x); }
T dot(P a, P b) { return (conj(a)*b).f; }
T cross(P a, P b) { return (conj(a)*b).s; }
T cross(P p, P a, P b) { return cross(a-p,b-p); }
P rotate(P a, T b) { return a*P(cos(b),sin(b)); }

P reflect(P p, P a, P b) { return a+conj((p-a)/(b-a))*(b-a);
    ↪};
P foot(P p, P a, P b) { return (p+reflect(p,a,b))/(T)2; }
bool onSeg(P p, P a, P b) { return cross(a,b,p) == 0 && dot(p
    ↪-a,p-b) <= 0; }
};
```

using namespace Point;

AngleCmp.h

Description: sorts points according to atan2

5 lines

```
"Point.h"
template<class T> int half(pair<T,T> x) { return mp(x.s,x.f) >
    ↪mp((T)0,(T)0); }
bool angleCmp(P a, P b) {
    int A = half(a), B = half(b);
    return A == B ? cross(a,b) > 0 : A < B;
}
```

LineDist.h

Description: computes distance between P and line AB

1 lines

```
"Point.h"
T lineDist(P p, P a, P b) { return abs(cross(p,a,b))/abs(a-b);
    ↪};
```

SegDist.h

Description: computes distance between P and line segment AB

5 lines

```
"lineDist.h"
T segDist(P p, P a, P b) {
    if (dot(p-a,b-a) <= 0) return abs(p-a);
    if (dot(p-b,a-b) <= 0) return abs(p-b);
    return lineDist(p,a,b);
}
```

LineIntersect.h

Description: computes the intersection point(s) of lines AB, CD; returns -1,0,0 if infinitely many, 0,0,0 if none, 1,x if x is the unique point

8 lines

```
"Point.h"
P extension(P a, P b, P c, P d) {
    T x = cross(a,b,c), y = cross(a,b,d);
    return (d*x-c*y)/(x-y);
}
pair<int,P> lineIntersect(P a, P b, P c, P d) {
    if (cross(b-a,d-c) == 0) return {- (cross(a,c,d) == 0),P(0,0)
        ↪};
    return {1,extension(a,b,c,d)};
}
```

SegIntersect.h

Description: computes the intersection point(s) of line segments AB, CD

11 lines

```
"Point.h"
vP segIntersect(P a, P b, P c, P d) {
    T x = cross(a,b,c), y = cross(a,b,d);
    T X = cross(c,d,a), Y = cross(c,d,b);
    if (sgn(x)*sgn(y) < 0 && sgn(X)*sgn(Y) < 0) return {(d*x-c*y)
        ↪/(x-y)};
    set<P> s;
    if (onSeg(a,c,d)) s.insert(a);
    if (onSeg(b,c,d)) s.insert(b);
    if (onSeg(c,a,b)) s.insert(c);
    if (onSeg(d,a,b)) s.insert(d);
    return {all(s)};
}
```

HowardGeo.h

Description: geo template that Howard uses

68 lines

```
<bits/stdc++.h>
using namespace std;
#define ld long double
#define cd complex<ld>
#define all(v) v.begin(), v.end()

const ld PI = acos(-1.0);
const ld EPS = 1e-7;
```

```
bool eq(cd a, cd b) { return abs(a-b) < EPS; }
cd normalize(cd z) { return z / norm(z); }
```

```
// reflects z over the line through a and b
cd reflect(cd z, cd a, cd b) { return conj((z-a)/(b-a)) * (b-a)
    ↪+ a; }
```

```
// projects z onto the line through a and b
cd proj(cd z, cd a, cd b) { return (z + reflect(z, a, b))/(ld)
    ↪2; }
```

```
// check collinearity
bool collinear(cd a, cd b, cd c) { return abs(imag((b-a)/(c-a))
    ↪) < EPS; }
```

```
// intersection of the line through a,b with the line through c
    ↪,d
cd intersect(cd a, cd b, cd c, cd d) {
    cd num = (conj(a)*b - a*conj(b))*(c-d) - (a-b)*(conj(c)*d -
        ↪c*conj(d));
    cd den = (conj(a) - conj(b))*(c-d) - (a-b)*(conj(c) - conj(
        ↪d));
    return num / den;
}

cd circumcenter(cd a, cd b, cd c) {
```

```

    b -= a, c -= a;
    return (b*norm(c) - c*norm(b))/(b*conj(c) - c*conj(b)) + a;
}

// Convex Hull

bool cmpAngle(cd a, cd b) { return arg(a / b) < 0; }
bool cmpImag(cd a, cd b) { return imag(a) < imag(b); }
vector<cd> ConvexHull(vector<cd> pts) {
    if (pts.size() <= 3) return pts;
    sort(all(pts), cmpImag);
    cd o = pts[0];
    for (cd &p : pts) p -= o;
    sort(pts.begin() + 1, pts.end(), cmpAngle);
    for (cd &p : pts) p += o;
    vector<cd> h{ pts[0], pts[1] };
    for (int i = 2; i < pts.size(); i++) {
        cd a = h[h.size() - 2];
        cd b = h[h.size() - 1];
        cd c = pts[i];
        while (arg((a - b) / (c - b)) <= EPS) { // If angle ABC
            ↪ is concave, remove B
            h.pop_back();
            a = h[h.size() - 2];
            b = h[h.size() - 1];
        }
        h.push_back(c);
    }
    return h;
}

int main() {
    cd z = cd(3, 4); // 3 + 4i
    real(z); // 3.0
    imag(z); // 4.0
    abs(z); // 5.0
    norm(z); // 25.0
    arg(z); // angle in [-pi, pi]
    conj(z); // 3 - 4i
    polar(r, theta); // r * e^theta
}

```

## 8.2 Polygons

### Area.h

**Description:** computes area + the center of mass of a polygon with constant mass per unit area

**Time:**  $\mathcal{O}(N)$

```

"Point.h" 16 lines

T area(const vP& v) {
    T area = 0;
    FOR(i,sz(v)) {
        int j = (i+1)%sz(v); T a = cross(v[i],v[j]);
        area += a;
    }
    return std::abs(area)/2;
}

P centroid(const vP& v) {
    P cen(0,0); T area = 0; // 2*signed area
    FOR(i,sz(v)) {
        int j = (i+1)%sz(v); T a = cross(v[i],v[j]);
        cen += a*(v[i]+v[j]); area += a;
    }
    return cen/area/(T)3;
}

```

### InPoly.h

**Description:** tests whether a point is inside, on, or outside the perimeter of any polygon

**Time:**  $\mathcal{O}(N)$

```

"Point.h" 10 lines

string inPoly(const vP& p, P z) {
    int n = sz(p), ans = 0;
    FOR(i,n) {
        P x = p[i], y = p[(i+1)%n];
        if (onSeg(z,x,y)) return "on";
        if (x.s > y.s) swap(x,y);
        if (x.s <= z.s && y.s > z.s && cross(z,x,y) > 0) ans ^= 1;
    }
    return ans ? "in" : "out";
}

```

### ConvexHull.h

**Description:** Top-bottom convex hull

**Time:**  $\mathcal{O}(N \log N)$

```

"Point.h" 48 lines

struct convexHull {
    set<pair<ld,ld>> dupChecker;
    vector<pair<ld,ld>> points;
    vector<pair<ld,ld>> dn, up, hull;

    convexHull() {}
    bool cw(pd o, pd a, pd b) {
        return ((a.f-o.f)*(b.s-o.s)-(a.s-o.s)*(b.f-o.f) <= 0);
    }
    void addPoint(pair<ld,ld> p) {
        if(dupChecker.count(p)) return;
        points.pb(p);
        dupChecker.insert(p);
    }
    void addPoint(ld x, ld y) {
        addPoint(mp(x,y));
    }
    void build() {
        sort(points.begin(), points.end());
        if(sz(points) < 3) {
            for(pair<ld,ld> p: points) {
                dn.pb(p);
                hull.pb(p);
            }
            M00d(i, sz(points)) {
                up.pb(points[i]);
            }
        } else {
            for(int i = 0; i < (int)points.size(); i++) {
                while(dn.size() >= 2 && cw(dn[dn.size()-2], dn[
                    ↪ dn.size()-1], points[i])) {
                    dn.erase(dn.end()-1);
                }
                dn.push_back(points[i]);
            }
            for(int i = (int)points.size()-1; i >= 0; i--) {
                while(up.size() >= 2 && cw(up[up.size()-2], up[
                    ↪ up.size()-1], points[i])) {
                    up.erase(up.end()-1);
                }
                up.push_back(points[i]);
            }
            sort(dn.begin(), dn.end());
            sort(up.begin(), up.end());

            for(int i = 0; i < up.size()-1; i++) hull.pb(up[i])
                ↪;
            for(int i = sz(dn)-1; i > 0; i--) hull.pb(dn[i]);
        }
    }
}

```

```

    }
};

PolyDiameter.h
Description: computes longest distance between two points in P
Time: O(N) given convex hull

"ConvexHull.h" 10 lines

ld diameter(vP P) { // rotating calipers
    P = hull(P);
    int n = sz(P), ind = 1; ld ans = 0;
    FOR(i,n)
        for (int j = (i+1)%n;; ind = (ind+1)%n) {
            ckmax(ans,abs(P[i]-P[ind]));
            if (cross(P[j]-P[i],P[(ind+1)%n]-P[ind]) <= 0) break;
        }
    return ans;
}

```

## 8.3 Circles

### Circles.h

**Description:** misc operations with two circles

```

"Point.h" 46 lines

typedef pair<P,T> circ;
bool on(circ x, P y) { return abs(y-x.f) == x.s; }
bool in(circ x, P y) { return abs(y-x.f) <= x.s; }
T arcLength(circ x, P a, P b) {
    P d = (a-x.f)/(b-x.f);
    return x.s*acos(d.f);
}

P intersectPoint(circ x, circ y, int t = 0) { // assumes
    ↪ intersection points exist
    T d = abs(x.f-y.f); // distance between centers
    T theta = acos((x.s*x.s+d*d-y.s*y.s)/(2*x.s*d)); // law of
    ↪ cosines
    P tmp = (y.f-x.f)/d*x.s;
    return x.f+tmp*dir(t == 0 ? theta : -theta);
}

T intersectArea(circ x, circ y) { // not thoroughly tested
    T d = abs(x.f-y.f), a = x.s, b = y.s; if (a < b) swap(a,b);
    if (d >= a+b) return 0;
    if (d <= a-b) return PI*b*b;
    auto ca = (a*a+d*d-b*b)/(2*a*d), cb = (b*b+d*d-a*a)/(2*b*d);
    auto s = (a+b*d)/2, h = 2*sqrt(s*(s-a)*(s-b)*(s-d))/d;
    return a*a*acos(ca)+b*b*acos(cb)-d*h;
}

P tangent(P x, circ y, int t = 0) {
    y.s = abs(y.s); // abs needed because internal calls y.s < 0
    if (y.s == 0) return y.f;
    T d = abs(x-y.f);
    P a = pow(y.s/d,2)*(x-y.f)+y.f;
    P b = sqrt(d*d-y.s*y.s)/d*y.s*unit(x-y.f)*dir(PI/2);
    return t == 0 ? a+b : a-b;
}

vector<pair<P,P>> external(circ x, circ y) { // external
    ↪ tangents
    vector<pair<P,P>> v;
    if (x.s == y.s) {
        P tmp = unit(x.f-y.f)*x.s*dir(PI/2);
        v.pb(mp(x.f+tmp,y.f+tmp));
        v.pb(mp(x.f-tmp,y.f-tmp));
    } else {
        P p = (y.s*x.f-x.s*y.f)/(y.s-x.s);
        FOR(i,2) v.pb({tangent(p,x,i),tangent(p,y,i)});
    }
    return v;
}

```



```
}
vector<pair<P,P>> internal(circ x, circ y) { // internal
    ↪tangents
    x.s *= -1; return external(x,y);
}
```

Circumcenter.h

**Description:** returns {circumcenter,circumradius}

"Point.h"5 lines

```
pair<P,T> ccCenter(P a, P b, P c) {
    b -= a; c -= a;
    P res = b*c*(conj(c)-conj(b))/(b*conj(c)-conj(b)*c);
    return {a+res,abs(res)};
}
```

MinEnclosingCircle.h

**Description:** computes minimum enclosing circle

**Time:** expected  $\mathcal{O}(N)$

"Circumcenter.h"13 lines

```
pair<P, T> mec(vP ps) {
    shuffle(all(ps), mt19937(time(0)));
    P o = ps[0]; T r = 0, EPS = 1 + 1e-8;
    FOR(i,sz(ps)) if (abs(o-ps[i]) > r*EPS) {
        o = ps[i], r = 0;
        FOR(j,i) if (abs(o-ps[j]) > r*EPS) {
            o = (ps[i]+ps[j])/2, r = abs(o-ps[i]);
            FOR(k,j) if (abs(o-ps[k]) > r*EPS)
                tie(o,r) = ccCenter(ps[i],ps[j],ps[k]);
        }
    }
    return {o,r};
}
```

8.4 Misc

ClosestPair.h

**Description:** line sweep to find two closest points

**Time:**  $\mathcal{O}(N \log N)$

21 lines

```
using namespace Point;

pair<P,P> solve(vP v) {
    pair<ld,pair<P,P>> bes; bes.f = INF;
    set<P> S; int ind = 0;

    sort(all(v));
    FOR(i,sz(v)) {
        if (i && v[i] == v[i-1]) return {v[i],v[i]};
        for (; v[i].f-v[ind].f >= bes.f; ++ind)
            S.erase({v[ind].s,v[ind].f});
        for (auto it = S.sub({v[i].s-bes.f,INF});
            it != end(S) && it->f < v[i].s+bes.f; ++it) {
            P t = {it->s,it->f};
            ckmin(bes,{abs(t-v[i]),(t,v[i])});
        }
        S.insert({v[i].s,v[i].f});
    }

    return bes.s;
}
```

DelaunayFast.h

**Description:** Delaunay Triangulation, concyclic points are OK (but not all collinear)

**Time:**  $\mathcal{O}(N \log N)$

"Point.h"94 lines

```
typedef ll T;
```

```
typedef struct Quad* Q;
typedef __int128_t ll1; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX,LLONG_MAX); // not equal to any other point

struct Quad {
    bool mark; Q o, rot; P p;
    P F() { return r()->p; }
    Q r() { return rot->rot; }
    Q prev() { return rot->o->rot; }
    Q next() { return r()->prev(); }
};

// test if p is in the circumcircle
bool circ(P p, P a, P b, P c) {
    ll ar = cross(a,b,c); assert(ar); if (ar < 0) swap(a,b);
    ll1 p2 = norm(p), A = norm(a)-p2,
        B = norm(b)-p2, C = norm(c)-p2;
    return cross(p,a,b)*C+cross(p,b,c)*A+cross(p,c,a)*B > 0;
}

Q makeEdge(P orig, P dest) {
    Q q[] = {new Quad{0,0,0,orig}, new Quad{0,0,0,arb},
            new Quad{0,0,0,dest}, new Quad{0,0,0,arb}};
    FOR(i,4) q[i]->o = q[-i & 3], q[i]->rot = q[(i+1) & 3];
    return *q;
}

void splice(Q a, Q b) {
    swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}

Q connect(Q a, Q b) {
    Q q = makeEdge(a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
    return q;
}

pair<Q,Q> rec(const vector<P>& s) {
    if (sz(s) <= 3) {
        Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
        if (sz(s) == 2) return { a, a->r() };
        splice(a->r(), b);
        auto side = cross(s[0], s[1], s[2]);
        Q c = side ? connect(b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
    }

#define H(e) e->F(), e->p
#define valid(e) (cross(e->F(),H(base)) > 0)
    Q A, B, ra, rb;
    int half = sz(s) / 2;
    tie(ra, A) = rec({all(s) - half});
    tie(B, rb) = rec({sz(s) - half + all(s)});
    while ((cross(B->p,H(A)) < 0 && (A = A->next())) ||
            (cross(A->p,H(B)) > 0 && (B = B->r()->o)));
    Q base = connect(B->r(), A);
    if (A->p == ra->p) ra = base->r();
    if (B->p == rb->p) rb = base;

#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
        Q t = e->dir; \
        splice(e, e->prev()); \
        splice(e->r(), e->r()->prev()); \
        e = t; \
    }
    for (;;) {
        DEL(LC, base->r(), o); DEL(RC, base, prev());
        if (!valid(LC) && !valid(RC)) break;
    }
}
```

```
if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
    base = connect(RC, base->r());
else
    base = connect(base->r(), LC->r());
}
return {ra, rb};
}

vector<array<P,3>> triangulate(vector<P> pts) {
    sort(all(pts)); assert(unique(all(pts)) == pts.end());
    if (sz(pts) < 2) return {};

    Q e = rec(pts).f; vector<Q> q = {e};
    int qi = 0;
    while (cross(e->o->F(), e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
    q.push_back(c->r()); c = c->next(); } while (c != e); }
    ADD; pts.clear();
    while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;

    vector<array<P,3>> ret;
    FOR(i,sz(pts)/3) ret.pb({pts[3*i],pts[3*i+1],pts[3*i+2]});
    return ret;
}
```

8.5 3D

Point3D.h

**Description:** Basic 3D Geometry

45 lines

```
typedef ld T;

namespace Point3D {
    typedef array<T,3> P3;
    typedef vector<P3> vP3;

    T norm(const P3& x) {
        T sum = 0; FOR(i,sz(x)) sum += x[i]*x[i];
        return sum;
    }
    T abs(const P3& x) { return sqrt(norm(x)); }

    P3& operator+=(P3& l, const P3& r) { FOR(i,3) l[i] += r[i];
        ↪return l; }
    P3& operator-=(P3& l, const P3& r) { FOR(i,3) l[i] -= r[i];
        ↪return l; }
    P3& operator*=(P3& l, const T& r) { FOR(i,3) l[i] *= r;
        ↪return l; }
    P3& operator/=(P3& l, const T& r) { FOR(i,3) l[i] /= r;
        ↪return l; }

    P3 operator+(P3 l, const P3& r) { return l += r; }
    P3 operator-(P3 l, const P3& r) { return l -= r; }
    P3 operator*(P3 l, const T& r) { return l *= r; }
    P3 operator*(const T& r, const P3& l) { return l*r; }
    P3 operator/(P3 l, const T& r) { return l /= r; }

    T dot(const P3& a, const P3& b) {
        T sum = 0; FOR(i,3) sum += a[i]*b[i];
        return sum;
    }
    P3 cross(const P3& a, const P3& b) {
        return {a[1]*b[2]-a[2]*b[1],
                a[2]*b[0]-a[0]*b[2],
                a[0]*b[1]-a[1]*b[0]};
    }

    bool isMult(const P3& a, const P3& b) {
        auto c = cross(a,b);
    }
}
```



```
FOR(i,sz(c)) if (c[i] != 0) return 0;
return 1;
}
bool collinear(const P3& a, const P3& b, const P3& c) {
    ↪return isMult(b-a,c-a); }
bool coplanar(const P3& a, const P3& b, const P3& c, const P3
    ↪& d) {
    return isMult(cross(b-a,c-a),cross(b-a,d-a));
}
}

using namespace Point3D;
```

Hull3D.h  
**Description:** 3D Convex Hull + Polyedron Volume  
**Time:**  $\mathcal{O}(N^2)$

"Point3D.h"	48 lines
-------------	----------

```
struct ED {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
};

struct F { P3 q; int a, b, c; };

vector<F> hull3d(const vP3& A) {
    assert(sz(A) >= 4);
    vector<vector<ED>> E(sz(A), vector<ED>(sz(A), {-1, -1}));
    #define E(x,y) E[f.x][f.y]
    vector<F> FS; // faces
    auto mf = [&](int i, int j, int k, int l) { // make face
        P3 q = cross(A[j]-A[i],A[k]-A[i]);
        if (dot(q,A[l]) > dot(q,A[i])) q *= -1; // make sure q
            ↪points outward
        F f{q, i, j, k};
        E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
        FS.pb(f);
    };
    FOR(i,4) FOR(j,i+1,4) FOR(k,j+1,4) mf(i, j, k, 6-i-j-k);

    FOR(i,4,sz(A)) {
        FOR(j,sz(FS)) {
            F f = FS[j];
            if (dot(f.q,A[i]) > dot(f.q,A[f.a])) { // face is visible
                ↪, remove edges
                E(a,b).rem(f.c), E(a,c).rem(f.b), E(b,c).rem(f.a);
                swap(FS[j--], FS.back());
                FS.pop_back();
            }
        }
        FOR(j,sz(FS)) { // add faces with new point
            F f = FS[j];
            #define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i,
                ↪f.c);
            C(a, b, c); C(a, c, b); C(b, c, a);
        }
    }
    trav(it, FS) if (dot(cross(A[it.b]-A[it.a],A[it.c]-A[it.a]),
        ↪it.q) <= 0)
        swap(it.c, it.b);
    return FS;
} // computes hull where no four are coplanar

T signedPolyVolume(const vP3& p, const vector<F>& trilst) {
    T v = 0;
    trav(i,trilst) v += dot(cross(p[i.a],p[i.b]),p[i.c]);
    return v/6;
```

Strings (9)  
9.1 Lightweight  
KMP.h  
**Description:** f[i] equals the length of the longest proper suffix of the i-th prefix of s that is a prefix of s  
**Time:**  $\mathcal{O}(N)$

	15 lines
--	----------

```
vi kmp(string s) {
    int N = sz(s); vi f(N+1); f[0] = -1;
    FOR(i,1,N+1) {
        f[i] = f[i-1];
        while (f[i] != -1 && s[f[i]] != s[i-1]) f[i] = f[f[i]];
        f[i] ++;
    }
    return f;
}

vi getOc(string a, string b) { // find occurrences of a in b
    vi f = kmp(a+"@"+b), ret;
    FOR(i,sz(a),sz(b)+1) if (f[i+sz(a)+1] == sz(a)) ret.pb(i-sz(a)
        ↪);
    return ret;
}
```

Z.h  
**Description:** for each index i, computes the the maximum len such that s.substr(0,len) == s.substr(i,len)  
**Time:**  $\mathcal{O}(N)$

	19 lines
--	----------

```
vi z(string s) {
    int N = sz(s); s += '#';
    vi ans(N); ans[0] = N;
    int L = 1, R = 0;
    FOR(i,1,N) {
        if (i <= R) ans[i] = min(R-i+1,ans[i-L]);
        while (s[i+ans[i]] == s[ans[i]]) ans[i] ++;
        if (i+ans[i]-1 > R) L = i, R = i+ans[i]-1;
    }
    return ans;
}

vi getPrefix(string a, string b) { // find prefixes of a in b
    vi t = z(a+b), T(sz(b));
    FOR(i,sz(T)) T[i] = min(t[i+sz(a)],sz(a));
    return T;
}

// pr(z("abcbabcbabcaba"),getPrefix("abcb","uwetrabcerabcb"))
    ↪;
```

Manacher.h  
**Description:** Calculates length of largest palindrome centered at each character of string  
**Time:**  $\mathcal{O}(N)$

	18 lines
--	----------

```
vi manacher(string s) {
    string s1 = "@#";
    trav(c,s) s1 += c, s1 += "#";
    s1[sz(s1)-1] = '&#39;&#39;;

    vi ans(sz(s1)-1);
    int lo = 0, hi = 0;
    FOR(i,1,sz(s1)-1) {
        if (i != 1) ans[i] = min(hi-i,ans[hi-i+lo]);
```

```
        while (s1[i-ans[i]-1] == s1[i+ans[i]+1]) ans[i] ++;
        if (i+ans[i] > hi) lo = i-ans[i], hi = i+ans[i];
    }

    ans.erase(begin(ans));
    FOR(i,sz(ans)) if ((i&1) == (ans[i]&1)) ans[i] ++; // adjust
        ↪lengths
    return ans;
}
// ps(manacher("abacaba"))
```

MinRotation.h  
**Description:** minimum rotation of string  
**Time:**  $\mathcal{O}(N)$

	8 lines
--	---------

```
int minRotation(string s) {
    int a = 0, N = sz(s); s += s;
    FOR(b,N) FOR(i,N) { // a is current best rotation found up to
        ↪b-1
        if (a+i == b || s[a+i] < s[b+i]) { b += max(0, i-1); break;
            ↪ } // b to b+i-1 can't be better than a to a+i-1
        if (s[a+i] > s[b+i]) { a = b; break; } // new best found
    }
    return a;
}
```

LyndonFactorization.h  
**Description:** A string is "simple" if it is strictly smaller than any of its own nontrivial suffixes. The Lyndon factorization of the string s is a factorization  $s = w_1w_2 \dots w_k$  where all strings  $w_i$  are simple and  $w_1 \geq w_2 \geq \dots \geq w_k$   
**Time:**  $\mathcal{O}(N)$

	20 lines
--	----------

```
vector<string> duval(const string& s) {
    int n = sz(s); vector<string> factors;
    for (int i = 0; i < n; ) {
        int j = i + 1, k = i;
        for (; j < n && s[k] <= s[j]; j++) {
            if (s[k] < s[j]) k = i;
            else k ++;
        }
        for (; i <= k; i += j-k) factors.pb(s.substr(i, j-k));
    }
    return factors;
}

int minRotation(string s) { // get min index i such that cyclic
    ↪shift starting at i is min rotation
    int n = sz(s); s += s;
    auto d = duval(s); int ind = 0, ans = 0;
    while (ans+sz(d[ind]) < n) ans += sz(d[ind++]);
    while (ind && d[ind] == d[ind-1]) ans -= sz(d[ind--]);
    return ans;
}
```

RabinKarp.h  
**Description:** generates hash values of any substring in  $\mathcal{O}(1)$ , equal strings have same hash value  
**Time:**  $\mathcal{O}(N)$  build,  $\mathcal{O}(1)$  get hash value of a substring

	25 lines
--	----------

```
template<int SZ> struct rabinKarp {
    const ll mods[3] = {1000000007, 999119999, 1000992299};
    ll p[3][SZ];
    ll h[3][SZ];
    const ll base = 1000696969;
    rabinKarp() {}
    void build(string a) {
        M00(i, 3) {
            p[i][0] = 1;
            h[i][0] = (int)a[0];
```

```

        MOO(j, 1, (int)a.length()) {
            p[i][j] = (p[i][j-1] * mods[i]) % base;
            h[i][j] = (h[i][j-1] * mods[i] + (int)a[j]) %
                ↪base;
        }
    }
}
tuple<ll, ll, ll> hsh(int a, int b) {
    if(a == 0) return make_tuple(h[0][b], h[1][b], h[2][b])
    ↪;
    tuple<ll, ll, ll> ans;
    get<0>(ans) = ((h[0][b] - h[0][a-1]*p[0][b-a+1]) %
        ↪base) + base) % base;
    get<1>(ans) = ((h[1][b] - h[1][a-1]*p[1][b-a+1]) %
        ↪base) + base) % base;
    get<2>(ans) = ((h[2][b] - h[2][a-1]*p[2][b-a+1]) %
        ↪base) + base) % base;
    return ans;
}
};

```

## 9.2 Suffix Structures

### ACfixed.h

**Description:** for each prefix, stores link to max length suffix which is also a prefix

**Time:**  $\mathcal{O}(N \sum)$

36 lines

```

struct ACfixed { // fixed alphabet
    struct node {
        array<int,26> to;
        int link;
    };
    vector<node> d;
    ACfixed() { d.eb(); }

    int add(string s) { // add word
        int v = 0;
        trav(C,s) {
            int c = C-'a';
            if (!d[v].to[c]) {
                d[v].to[c] = sz(d);
                d.eb();
            }
            v = d[v].to[c];
        }
        return v;
    }

    void init() { // generate links
        d[0].link = -1;
        queue<int> q; q.push(0);
        while (sz(q)) {
            int v = q.front(); q.pop();
            FOR(c,26) {
                int u = d[v].to[c]; if (!u) continue;
                d[u].link = d[v].link == -1 ? 0 : d[d[v].link].to[c];
                q.push(u);
            }
            if (v) FOR(c,26) if (!d[v].to[c])
                d[v].to[c] = d[d[v].link].to[c];
        }
    }
};

```

### PalTree.h

**Description:** palindromic tree, computes number of occurrences of each palindrome within string

**Time:**  $\mathcal{O}(N \sum)$

25 lines

```

template<int SZ> struct PalTree {
    static const int sigma = 26;
    int s[SZ], len[SZ], link[SZ], to[SZ][sigma], oc[SZ];
    int n, last, sz;
    PalTree() { s[n++] = -1; link[0] = 1; len[1] = -1; sz = 2; }

    int getLink(int v) {
        while (s[n-len[v]-2] != s[n-1]) v = link[v];
        return v;
    }

    void addChar(int c) {
        s[n++] = c;
        last = getLink(last);
        if (!to[last][c]) {
            len[sz] = len[last]+2;
            link[sz] = to[getLink(link[last])][c];
            to[last][c] = sz++;
        }
        last = to[last][c]; oc[last] ++;
    }

    void numOc() {
        vpi v; FOR(i,2,sz) v.pb((len[i],i));
        sort(rall(v)); trav(a,v) oc[link[a.s]] += oc[a.s];
    }
};

```

### SuffixArray.h

**Description:** ?

**Time:**  $\mathcal{O}(N \log N)$

43 lines

```

template<int SZ> struct suffixArray {
    const static int LGSZ = 33-__builtin_clz(SZ-1);
    pair<pi, int> tup[SZ];
    int sortIndex[LGSZ][SZ];
    int res[SZ];
    int len;
    suffixArray(string s) {
        this->len = (int)s.length();
        MOO(i, len) tup[i] = MP(MP((int)s[i], -1), i);
        sort(tup, tup+len);
        int temp = 0;
        tup[0].F.F = 0;
        MOO(i, 1, len) {
            if(s[tup[i].S] != s[tup[i-1].S]) temp++;
            tup[i].F.F = temp;
        }
        MOO(i, len) sortIndex[0][tup[i].S] = tup[i].F.F;
        MOO(i, 1, LGSZ) {
            MOO(j, len) tup[j] = MP(MP(sortIndex[i-1][j], (j
                ↪+(1<<(i-1))<len)?sortIndex[i-1][j+(1<<(i-1))
                ↪]:-1), j));
            sort(tup, tup+len);
            int temp2 = 0;
            sortIndex[i][tup[0].S] = 0;
            MOO(j, 1, len) {
                if(tup[j-1].F != tup[j].F) temp2++;
                sortIndex[i][tup[j].S] = temp2;
            }
        }
        MOO(i, len) res[sortIndex[LGSZ-1][i]] = i;
    }

    int LCP(int x, int y) {
        if(x == y) return len - x;
        int ans = 0;
        MOOd(i, LGSZ) {
            if(x >= len || y >= len) break;
            if(sortIndex[i][x] == sortIndex[i][y]) {
                x += (1<<i);

```

```

                y += (1<<i);
                ans += (1<<i);
            }
        }
        return ans;
    }
};

```

### ReverseBW.h

**Description:** The Burrows-Wheeler Transform appends # to a string, sorts the rotations of the string in increasing order, and constructs a new string that contains the last character of each rotation. This function reverses the transform.

**Time:**  $\mathcal{O}(N \log N)$

8 lines

```

string reverseBW(string s) {
    vi nex(sz(s));
    vector<pair<char,int>> v; FOR(i,sz(s)) v.pb({s[i],i});
    sort(all(v)); FOR(i,sz(v)) nex[i] = v[i].s;
    int cur = nex[0]; string ret;
    for (; cur; cur = nex[cur]) ret += v[cur].f;
    return ret;
}

```

### SuffixAutomaton.h

**Description:** constructs minimal DFA that recognizes all suffixes of a string

**Time:**  $\mathcal{O}(N \log \sum)$

73 lines

```

struct SuffixAutomaton {
    struct state {
        int len = 0, firstPos = -1, link = -1;
        bool isClone = 0;
        map<char, int> next;
        vi invLink;
    };

    vector<state> st;
    int last = 0;
    void extend(char c) {
        int cur = sz(st); st.eb();
        st[cur].len = st[last].len+1, st[cur].firstPos = st[cur].
            ↪len-1;
        int p = last;
        while (p != -1 && !st[p].next.count(c)) {
            st[p].next[c] = cur;
            p = st[p].link;
        }
        if (p == -1) {
            st[cur].link = 0;
        } else {
            int q = st[p].next[c];
            if (st[p].len+1 == st[q].len) {
                st[cur].link = q;
            } else {
                int clone = sz(st); st.pb(st[q]);
                st[clone].len = st[p].len+1, st[clone].isClone = 1;
                while (p != -1 && st[p].next[c] == q) {
                    st[p].next[c] = clone;
                    p = st[p].link;
                }
                st[q].link = st[cur].link = clone;
            }
        }
        last = cur;
    }

    void init(string s) {
        st.eb(); trav(x,s) extend(x);
        FOR(v,1,sz(st)) st[st[v].link].invLink.pb(v);
    }
}

```

```
// APPLICATIONS
void getAllOccur(vi& oc, int v) {
    if (!st[v].isClone) oc.pb(st[v].firstPos);
    trav(u, st[v].invLink) getAllOccur(oc, u);
}
vi allOccur(string s) {
    int cur = 0;
    trav(x, s) {
        if (!st[cur].next.count(x)) return {};
        cur = st[cur].next[x];
    }
    vi oc; getAllOccur(oc, cur); trav(t, oc) t += 1-sz(s);
    sort(all(oc)); return oc;
}

vl distinct;
ll getDistinct(int x) {
    if (distinct[x]) return distinct[x];
    distinct[x] = 1;
    trav(y, st[x].next) distinct[x] += getDistinct(y.s);
    return distinct[x];
}
ll numDistinct() { // # of distinct substrings, including
    ↪empty
    distinct.rsz(sz(st));
    return getDistinct(0);
}
ll numDistinct2() { // another way to get # of distinct
    ↪substrings
    ll ans = 1;
    FOR(i, 1, sz(st)) ans += st[i].len-st[st[i].link].len;
    return ans;
}
};
```

## SuffixTree.h

**Description:** Ukkonen's algorithm for suffix tree

**Time:**  $\mathcal{O}(N \log N)$

61 lines

```
struct SuffixTree {
    string s; int node, pos;
    struct state {
        int fpos, len, link = -1;
        map<char, int> to;
        state(int fpos, int len) : fpos(fpos), len(len) {}
    };
    vector<state> st;
    int makeNode(int pos, int len) {
        st.pb(state(pos, len)); return sz(st)-1;
    }
    void goEdge() {
        while (pos > 1 && pos > st[st[node].to[s[sz(s)-pos]]].len)
            ↪{
                node = st[node].to[s[sz(s)-pos]];
                pos -= st[node].len;
            }
    }
    void extend(char c) {
        s += c; pos++; int last = 0;
        while (pos) {
            goEdge();
            char edge = s[sz(s)-pos];
            int& v = st[node].to[edge];
            char t = s[st[v].fpos+pos-1];
            if (v == 0) {
                v = makeNode(sz(s)-pos, MOD);
                st[last].link = node; last = 0;
            } else if (t == c) {

```

```
                st[last].link = node;
                return;
            } else {
                int u = makeNode(st[v].fpos, pos-1);
                st[u].to[c] = makeNode(sz(s)-1, MOD); st[u].to[t] = v;
                st[v].fpos += pos-1; st[v].len -= pos-1;
                v = u; st[last].link = u; last = u;
            }
            if (node == 0) pos--;
            else node = st[node].link;
        }
    }
    void init(string _s) {
        makeNode(0, MOD); node = pos = 0;
        trav(c, _s) extend(c);
    }
    bool isSubstr(string _x) {
        string x; int node = 0, pos = 0;
        trav(c, _x) {
            x += c; pos++;
            while (pos > 1 && pos > st[st[node].to[x[sz(x)-pos]]].len)
                ↪{
                    node = st[node].to[x[sz(x)-pos]];
                    pos -= st[node].len;
                }
            char edge = x[sz(x)-pos];
            if (pos == 1 && !st[node].to.count(edge)) return 0;
            int& v = st[node].to[edge];
            char t = s[st[v].fpos+pos-1];
            if (c != t) return 0;
        }
        return 1;
    }
};
```

## 9.3 Misc

### TandemRepeats.h

**Description:** Main-Lorentz algorithm, finds all  $(x, y)$  such that  $s.substr(x, y-1) == s.substr(x+y, y-1)$

**Time:**  $\mathcal{O}(N \log N)$

"Z.h"

54 lines

```
struct StringRepeat {
    string S;
    vector<array<int, 3>> al;
    // (t[0], t[1], t[2]) -> there is a repeating substring
    ↪starting at x
    // with length t[0]/2 for all t[1] <= x <= t[2]

    vector<array<int, 3>> solveLeft(string s, int m) {
        vector<array<int, 3>> v;

        vi v2 = getPrefix(string(s.begin()+m+1, s.end()), string(s.
            ↪begin(), s.begin()+m+1));
        string V = string(s.begin(), s.begin()+m+2); reverse(all(V))
            ↪; vi v1 = z(V); reverse(all(v1));

        FOR(i, m+1) if (v1[i]+v2[i] >= m+2-i) {
            int lo = max(1, m+2-i-v2[i]), hi = min(v1[i], m+1-i);
            lo = i-lo+1, hi = i-hi+1; swap(lo, hi);
            v.pb({2*(m+1-i), lo, hi});
        }

        return v;
    }

    void divi(int l, int r) {
        if (l == r) return;
        int m = (l+r)/2; divi(l, m); divi(m+1, r);
    }
};
```

```
string t = string(S.begin()+l, S.begin()+r+1);
m = (sz(t)-1)/2;
auto a = solveLeft(t, m);
reverse(all(t));
auto b = solveLeft(t, sz(t)-2-m);

trav(x, a) al.pb({x[0], x[1]+1, x[2]+1});
trav(x, b) {
    int ad = r-x[0]+1;
    al.pb({x[0], ad-x[2], ad-x[1]});
}
}

void init(string _S) {
    S = _S; divi(0, sz(S)-1);
}

vi genLen() { // min length of repeating substring starting
    ↪at each index
    priority_queue<pi, vpi, greater<pi>> m; m.push({MOD, MOD});
    vpi ins[sz(S)]; trav(a, al) ins[a[1]].pb({a[0], a[2]});
    vi len(sz(S));
    FOR(i, sz(S)) {
        trav(j, ins[i]) m.push(j);
        while (m.top().s < i) m.pop();
        len[i] = m.top().f;
    }
    return len;
}
};
```