




DIMENSIONS OF FORGED FLANGES ANSI B 16.5



SLIP-ON FLANGE



WELDING NECK FLANGE



BLIND FLANGE

ASA 150 CLASS

Nominal Pipe Size (MM) (INCH.)	Flange Dia O	Dia of Bolt Circle A	Dia of Bolt Holes D	No. of Holes	Thk of Flange C	Dia of Hub E	Length through Hub			Dia of Bore		Dia of R/F R	Depth of Socket F	Pipe Dia X
							S/O & S/W Y	W/N Y	L/J Y	S/O & S/W B	L/J B			
15	1/2	90.0	60.3	15.9	4	11.1	15.9	47.6	15.9	22.3	22.9	34.9	9.5	21.33
20	3/4	100.0	69.8	15.9	4	12.7	15.9	52.4	15.9	27.7	28.2	42.9	11.1	26.67
25	1	110.0	79.4	15.9	4	14.3	17.5	55.6	17.5	34.5	35.0	50.8	12.7	33.40
32	1 1/4	115.0	88.9	15.9	4	15.9	20.6	57.1	20.6	43.2	43.7	63.5	14.3	42.16
40	1 1/2	125.0	98.4	15.9	4	17.5	22.2	61.9	22.2	49.5	50.0	73.0	15.9	48.26
50	2	150.0	120.6	19.0	4	19.0	25.4	63.5	25.4	62.0	62.5	92.1	17.5	60.31
65	2 1/2	180.0	139.7	19.0	4	22.2	28.6	69.8	28.6	74.7	75.4	104.8	19.0	73.02
80	3	190.0	152.4	19.0	4	23.8	30.2	69.8	30.2	90.7	91.4	127.0	20.6	88.90
100	4	230.0	190.5	19.0	8	23.8	33.3	76.2	33.3	116.1	116.8	157.2	23.8	114.30
125	5	255.0	215.9	22.2	8	23.8	36.5	88.9	36.5	143.8	144.5	185.7	23.8	141.30
150	6	280.0	241.3	22.2	8	25.4	39.7	88.9	39.7	170.7	171.4	215.9	27.0	168.27
200	8	345.0	298.4	22.2	8	28.6	44.4	101.6	44.4	221.5	222.2	269.9	31.7	219.07
250	10	405.0	361.9	25.4	12	30.2	49.2	101.6	49.2	276.3	277.4	323.8	33.3	273.05
300	12	485.0	431.8	25.4	12	31.8	55.6	114.3	55.6	327.1	328.2	381.0	39.7	323.85
350	14	535.0	476.2	28.6	12	34.9	57.1	127.0	79.4	359.1	360.2	412.7	41.3	355.60
400	16	595.0	539.7	28.6	16	36.5	63.5	127.0	87.3	410.5	411.2	469.9	44.4	406.40
450	18	635.0	577.8	31.7	16	39.7	68.3	139.7	96.8	461.8	462.3	533.4	49.2	457.20
500	20	700.0	635.0	31.7	20	42.9	73.0	144.5	103.2	513.1	514.3	584.2	54.0	508.00
600	24	815.0	749.3	34.9	20	47.6	82.5	152.4	111.1	615.9	615.9	692.1	63.5	609.60


All Dimensions are in Millimeters ● Flanges except Lap Joint will be furnished with (1.6mm) Raised Face, which is included in Thickness(C) and Length through Hub(Y).

ASA 300 CLASS


Nominal Pipe Size (MM) (INCH.)	Flange Dia O	Dia of Bolt Circle A	Dia of Bolt Holes D	No. of Holes	Thk of Flange C	Dia of Hub E	Length through Hub			Dia of Bore		Dia of R/F R	Depth of Socket F	Pipe Dia X
							S/O & S/W Y	W/N Y	L/J Y	S/O & S/W B	L/J B			
15	1/2	95.0	66.7	15.9	4	14.3	22.2	52.4	22.2	22.3	22.9	34.9	9.5	21.33
20	3/4	115.0	82.5	19.0	4	15.9	25.4	57.1	25.4	27.7	28.2	42.9	11.1	26.67
25	1	125.0	88.9	19.0	4	17.5	27.0	61.9	27.0	34.5	35.0	50.8	12.7	33.40
32	1 1/4	135.0	98.4	19.0	4	19.0	27.0	65.1	27.0	43.2	43.7	63.5	14.3	42.16
40	1 1/2	155.0	114.3	22.2	4	20.6	30.2	68.3	30.2	49.5	50.0	73.0	15.9	48.26
50	2	165.0	127.0	19.0	8	22.2	33.3	69.8	33.3	62.0	62.5	92.1	17.5	60.31
65	2 1/2	190.0	149.2	22.2	8	25.4	38.1	76.2	38.1	74.7	75.4	104.8	19.0	73.02
80	3	210.0	168.3	22.2	8	28.6	42.9	79.4	42.9	90.7	91.4	127.0	20.6	88.90
100	4	255.0	200.0	22.2	8	31.8	47.6	85.7	47.6	116.1	116.8	157.2	23.8	114.30
125	5	280.0	234.9	22.2	8	34.9	50.8	98.4	50.8	143.8	144.5	185.7	-	141.30
150	6	320.0	269.9	22.2	12	36.5	52.4	98.4	52.4	170.7	171.4	215.9	-	168.27
200	8	380.0	330.2	25.4	12	41.3	61.9	111.1	61.9	221.5	222.2	269.9	-	219.07
250	10	445.0	387.3	28.6	16	47.6	66.7	117.5	95.2	276.3	277.4	323.8	-	273.05
300	12	520.0	450.8	31.7	16	50.8	73.0	130.2	101.6	327.1	328.2	381.0	-	323.85
350	14	585.0	514.3	31.7	20	54.0	76.2	142.9	111.1	359.1	360.2	412.7	-	355.60
400	16	650.0	571.5	34.9	20	57.2	82.5	146.0	120.6	410.5	411.2	469.9	-	406.40
450	18	710.0	628.5	34.9	24	60.3	88.9	158.7	130.2	461.8	462.3	533.4	-	457.20
500	20	775.0	685.8	34.9	24	63.5	95.2	161.9	139.7	513.1	514.3	584.2	-	508.00
600	24	915.0	812.8	41.3	24	69.8	106.4	168.3	152.4	615.9	615.9	692.1	-	609.60

All Dimensions are in Millimeters ● Flanges except Lap Joint will be furnished with (1.6mm) Raised Face, which is included in Thickness(C) and Length through Hub(Y).


DIMENSIONS OF FORGED FLANGES ANSI B 16.5



THREADED FLANGES



LAP JOINT FLANGES



SOCKET WELD FLANGES

ASA 600 CLASS

Nominal Pipe Size (MM)	Flange Dia O	Dia of Bolt Circle A	Dia of Bolt Holes D	No. of Holes	Thk of Flange C	Dia of Hub E	Length through Hub			Dia of Bore		Dia of R/F R	Depth of Socket F	Pipe Dia X
							S/O & S/W Y	W/N Y	L/J Y	S/O & S/W B	L/J B			
15	95.2	66.7	15.9	4	14.3	38.1	22.2	52.4	22.3	22.3	22.8	34.9	9.5	21.33
20	117.5	82.5	19.0	4	15.9	47.6	25.4	57.1	25.4	27.7	28.1	42.9	11.1	26.67
25	123.8	88.9	19.0	4	17.5	54.0	27.0	61.9	26.9	34.5	35.0	50.8	12.7	33.40
32	133.3	98.4	19.0	4	20.6	63.5	28.6	66.7	28.4	43.2	43.6	63.5	14.2	42.16
40	155.6	114.3	22.2	4	22.2	69.8	31.7	69.8	31.7	49.5	50.0	73.0	15.8	48.26
50	165.1	127.0	19.0	8	25.4	84.1	36.5	73.0	36.5	62.0	62.4	92.1	17.4	60.31
65	190.5	149.2	22.2	8	28.6	100.0	41.3	79.4	41.1	74.7	75.4	104.8	19.0	73.02
80	209.5	168.3	22.2	8	31.8	117.5	46.0	82.5	45.9	90.7	91.4	127.0	-	88.90
100	273.0	215.9	25.4	8	38.1	152.4	54.0	101.6	53.8	116.1	116.8	157.2	-	114.30
125	330.2	266.7	28.6	8	44.4	188.9	60.3	114.3	60.4	143.8	144.5	185.7	-	141.30
150	355.6	292.1	28.6	12	47.6	222.2	66.7	117.5	66.5	170.7	171.4	215.9	-	168.27
200	419.1	349.2	31.7	12	55.6	273.0	76.2	133.3	76.2	221.5	222.2	269.9	-	219.07
250	508.0	431.8	34.9	16	63.5	342.9	85.7	152.4	111.2	276.3	277.4	323.8	-	273.05
300	558.8	488.9	34.9	20	66.7	400.0	92.1	155.6	117.3	327.1	328.2	381.0	-	323.85
350	603.2	527.0	38.1	20	69.9	431.8	93.7	165.1	127.0	359.1	360.1	412.7	-	355.60
400	685.8	603.2	41.3	20	76.2	495.3	106.4	177.8	139.7	410.5	411.2	469.9	-	406.40
450	742.9	654.0	44.4	20	82.6	546.1	117.5	184.1	152.4	461.8	462.3	533.4	-	457.20
500	812.8	723.9	44.4	24	88.9	609.9	127.0	190.5	165.1	513.1	514.3	584.2	-	508.00
600	939.8	838.2	50.8	24	101.6	717.5	139.7	203.2	184.1	615.9	615.9	692.1	-	609.60

All Dimensions are in Millimeters • Flanges except Lap Joint will be furnished with (6.35mm) Raised Face, which is not included in Thickness(C) and Length through Hub(Y).

ASA 900 CLASS

Nominal Pipe Size (MM)	Flange Dia O	Dia of Bolt Circle A	Dia of Bolt Holes D	No. of Holes	Thk of Flange C	Dia of Hub E	Length through Hub			Dia of Bore		Dia of R/F R	Depth of Socket F	Pipe Dia X
							S/O & S/W Y	W/N Y	L/J Y	S/O & S/W B	L/J B			
15	120.6	82.5	22.2	4	22.2	38.1	31.7	60.3	31.7	22.3	22.8	34.9	9.5	21.33
20	130.2	88.9	22.2	4	25.4	44.4	34.9	69.8	35.0	27.7	28.1	42.9	11.1	26.67
25	149.2	101.6	25.4	4	28.6	52.4	41.3	73.0	41.1	34.5	35.0	50.8	12.7	33.40
32	158.7	111.1	25.4	4	28.6	63.5	41.3	73.0	41.1	43.2	43.6	63.5	14.2	42.16
40	177.8	123.8	28.6	4	31.8	69.8	44.4	82.5	44.4	49.5	50.0	73.0	15.8	48.26
50	215.9	165.1	25.4	8	38.1	104.8	57.1	101.6	57.1	62.0	62.4	92.1	17.4	60.31
65	244.5	190.5	28.6	8	41.3	123.8	63.5	104.8	63.5	74.1	75.4	104.8	19.0	73.02
80	241.3	190.5	25.4	8	38.1	127.0	53.9	101.6	53.8	90.7	91.4	127.0	-	88.90
100	292.1	234.9	31.7	8	44.4	158.7	69.8	114.3	69.8	116.0	116.8	157.2	-	114.30
125	349.2	279.4	35.0	8	50.8	190.5	79.3	127.0	79.2	143.7	144.5	185.7	-	141.30
150	381.0	317.5	31.7	12	55.6	234.9	85.8	139.7	85.8	170.6	171.4	215.9	-	168.27
200	469.9	393.7	38.1	12	63.5	298.4	101.6	162.0	114.3	221.4	222.2	269.9	-	219.07
250	546.1	469.9	38.1	16	69.8	368.3	107.9	184.1	127.0	276.3	277.3	323.8	-	273.05
300	609.6	533.4	38.1	20	79.3	419.1	117.4	200.0	142.7	327.1	328.1	381.0	-	323.85

All Dimensions are in Millimeters • Flanges except Lap Joint will be furnished with (6.35mm) Raised Face, which is included in Thickness(C) and Length through Hub(Y).

DIMENSION OF PIPE FLANGES AS PER TABLE BS - 10

Table D

Table D: For Working Steam Pressure upto 50 lbs per sq. inch

Nominal Pipe Size	O.D. of Pipe	Dia. of Flange	Dia. of Bolt Circle	No. of Bolt	Dia. of Bolt	Thickness
1/2"	21.3	95.3	66.7	4	12.7	4.8
3/4"	26.7	101.6	73.0	4	12.7	4.8
1"	33.4	114.3	82.6	4	12.7	4.8
1 1/4"	42.2	120.7	87.6	4	12.7	6.4
1 1/2"	48.3	133.4	98.4	4	12.7	6.4
2"	60.3	152.4	114.3	4	15.9	7.9
2 1/2"	73.0	165.1	127.0	4	15.9	7.9
3"	88.9	184.2	146.1	4	15.9	9.5
3 1/2"	101.6	203.2	165.1	4	15.9	9.5
4"	114.3	215.9	177.8	4	15.9	9.5
5"	141.3	254.0	209.6	8	15.9	12.7
6"	168.3	279.4	235.0	8	15.9	12.7
7"	190.5	304.8	260.4	8	15.9	12.7
8"	219.1	336.6	292.1	8	15.9	12.7
9"	244.5	368.3	323.9	8	15.9	15.9
10"	273.0	406.4	355.6	8	19.1	15.9
12"	323.9	457.2	406.4	12	19.1	15.9
14"	355.6	527.1	469.9	12	22.2	19.1
16"	406.4	577.9	520.7	12	22.2	19.1
18"	457.2	641.4	584.2	12	22.2	22.2
20"	508.0	704.9	641.4	16	22.5	25.4
24"	609.6	825.5	755.7	16	25.4	28.6

Table E

Table E : For Working Steam Pressure 50 lbs upto 100 lbs per sq. inch

Nominal Pipe Size	Dia. of Flange	Dia. of Bolt Circle	No. of Bolt	Dia. of Bolt	Thickness
1/2"	95.3	66.7	4	12.7	6.4
3/4"	101.6	73.0	4	12.7	6.4
1"	114.3	82.6	4	12.7	7.1
1 1/4"	120.7	87.6	4	12.7	7.9
1 1/2"	133.4	98.4	4	12.7	8.7
2"	152.4	114.3	4	15.9	9.5
2 1/2"	165.1	127.0	4	15.9	10.3
3"	184.2	146.1	4	15.9	11.1
3 1/2"	203.2	165.1	8	15.9	11.9
4"	215.9	177.8	8	15.9	12.7
5"	254.0	209.6	8	15.9	14.3
6"	279.4	235.0	8	19.1	17.5
7"	304.8	260.4	8	19.1	19.1
8"	336.6	292.1	8	19.1	19.1
9"	368.3	323.9	12	19.1	20.6
10"	406.4	355.6	12	19.1	22.2
12"	457.2	406.4	12	22.2	25.4
14"	527.1	469.9	12	22.2	25.4
16"	577.9	520.7	12	22.2	25.4
18"	641.4	584.2	16	22.2	28.6
20"	704.9	641.4	16	22.2	31.8
24"	825.5	755.7	16	25.4	38.1

Table F

Table F: For Working Steam Pressure above 100 lbs and upto 150 lbs per sq. inch

Nominal Pipe Size	O.D. of Pipe	Dia of Flange	Dia of Bolt Circle	No. of Bolt	Dia. of Bolt	Thickness
1/2"	21.3	95.3	66.7	4	12.7	9.5
3/4"	26.7	101.6	73.0	4	12.7	9.5
1"	33.4	120.7	87.3	4	15.9	9.5
1 1/4"	42.2	133.4	98.4	4	15.9	12.7
1 1/2"	48.3	139.7	104.8	4	15.9	12.7
2"	60.3	165.1	127.0	4	15.9	15.9
2 1/2"	73.0	184.2	146.1	8	15.9	15.9
3"	88.9	203.2	165.1	8	15.9	15.9
3 1/2"	101.6	215.9	177.8	8	15.9	19.1
4"	114.3	228.6	190.5	8	15.9	19.1
5"	141.3	279.4	235.0	8	19.1	22.2
6"	168.3	304.8	260.4	12	19.1	22.2
7"	190.3	336.6	292.1	12	19.1	22.2
8"	219.1	368.3	323.9	12	19.1	25.4
9"	244.5	406.4	355.6	12	22.2	25.4
10"	273.0	431.8	381.0	12	22.2	25.4
12"	323.0	489.0	438.2	16	22.2	28.6
14"	355.6	552.5	495.3	16	25.4	31.8
16"	406.4	609.6	552.5	20	25.4	31.8
18"	457.2	673.1	609.6	20	28.6	34.9
20"	508.0	736.6	673.1	24	28.6	38.1
24"	609.6	850.9	781.1	24	31.8	41.3

Table H

Table H : For Working Steam Pressure above 150 lbs and upto 250 lbs per sq. inch

Nominal Pipe Size	Dia of Flange	Dia. of Bolt Circle	No. of Bolt	Dia. of Bolt	Thickness
1/2"	114.3	82.6	4	15.9	12.7
3/4"	114.3	82.6	4	15.9	12.7
1"	120.78	87.3	4	15.9	14.3
1 1/4"	133.4	98.4	4	15.9	17.5
1 1/2"	139.7	104.8	4	15.9	17.5
2"	165.1	127.0	4	15.9	19.1
2 1/2"	184.2	146.1	8	15.9	19.1
3"	203.2	165.1	8	15.9	22.2
3 1/2"	215.9	177.8	8	15.9	22.2
4"	228.6	190.5	8	15.9	25.4
5"	279.4	235.0	8	19.1	28.6
6"	304.8	260.4	12	19.1	28.6
7"	336.6	292.1	12	19.1	31.8
8"	368.3	323.9	12	19.1	31.8
9"	406.4	355.6	12	22.2	34.9
10"	431.8	381.0	12	22.2	34.9
12"	489.0	438.2	16	22.2	38.1
14"	552.5	495.3	16	25.4	41.3
16"	609.6	552.5	20	25.4	44.5
18"	673.1	609.6	20	28.6	47.6
20"	736.6	673.1	24	28.6	50.8
24"	850.9	781.1	24	31.8	57.2

DIMENSION OF PIPE FLANGES AS PER DIN STANDARD
N D - 10

Nominal Pipe Size (in mm)	Flange Diameter mm	Flange thickness	Number of holes	Diameter of holes mm	P.C.D. mm
15	95	14	4	14	65
20	105	16	4	14	75
25	115	16	4	14	85
32	140	16	4	18	100
40	150	16	4	18	110
50	165	18	4	18	125
65	185	18	4	18	145
80	200	20	4	18	160
100	220	20	8	18	180
125	250	22	8	18	210
150	285	22	8	22	240
200	340	24	8	22	295
250	395	26	12	22	350
300	445	28	12	22	400
350	550	28	16	22	460
400	565	32	16	26	515
450	615	38	20	26	565
500	670	38	20	26	620
600	780	40	20	26	725

N D - 16

Nominal Pipe Size (in mm)	Flange Diameter mm	Flange thickness steel mm.	Number of holes	Diameter of holes mm	P.C.D. mm
15	95	14	4	14	65
20	105	16	4	14	75
25	115	16	4	14	85
32	140	16	4	18	100
40	150	16	4	18	110
50	165	18	4	18	125
65	185	18	4	18	145
80	200	20	8	18	160
100	220	20	8	18	180
125	250	22	8	18	210
150	285	22	8	23	240
200	340	24	12	23	295
250	405	26	12	27	355
300	460	28	12	27	410
350	520	30	16	27	470
400	580	32	16	30	525
450	640	34	20	30	585
500	715	34	20	33	650
600	840	36	20	36	770

N D - 40

Nominal Pipe Size (in mm)	Flange Diameter mm	Flange thickness steel mm.	Number of holes	Diameter of holes mm	P.C.D. mm
15	95	16	4	14	65
20	105	18	4	14	75
25	115	18	4	14	85
32	140	18	4	18	100
40	150	18	4	18	110
50	165	20	4	18	125
65	185	22	4	18	145
80	200	24	8	18	160
100	235	24	8	23	190
125	270	26	8	27	220
150	300	28	8	27	250
200	375	34	12	30	320
250	450	38	12	33	385
300	515	42	16	33	450
350	580	46	16	36	510
400	660	50	16	39	585
500	755	52	20	42	670

IS - 1538

Nominal Pipe Size (in mm) mm	Diameter of Flange mm	P.C.D. mm	Holes		Thickness mm
			Number mm	Diameter mm	
80	200	160	4	19	21
100	220	180	8	19	22
125	250	210	8	19	22.5
150	285	240	8	23	23
200	340	295	8	23	24.5
250	395	350	12	23	26
300	445	400	12	23	27.5
350	505	450	16	23	29
400	565	515	16	28	30
500	670	620	20	28	33

Important Tolerances B16.5 - 2009			
Outside Diameter	O	If O ≤ 610 mm	+1.6, -1.6
		If O > 610 mm	+3.1, -3.1
Inside Diameter	B	If NPS ≤ 10"	+0.8, -0.0
		If NPS ≥ 12"	+1.5, -0.0
Diameter of Hub	X	If NPS ≤ 12"	+2.4, -1.5
		If NPS ≥ 14"	+3.1, -3.1
Hub Dia at Weld Point	Ah	If NPS ≤ 5"	+2, -1
		If NPS ≥ 6"	+4, -1
Raised Face Dia	R	If 150#, 300#	+0.8, -0.8
		If 400#	+0.4, -0.4
Drilling	W	PCD	+0.8, -0.8
		Hole Spacing	+0.4, -0.5
Flange Thickness	Tf	If NPS ≤ 18"	+3, -0
		If NPS ≥ 20"	+5, -0
Length Through Hub	Y	If NPS ≤ 4"	+1.5, -1.5
		If 5" ≤ NPS ≤ 10"	+1.5, -3
		If NPS ≥ 12"	+3, -5
Bore	B	WNRF 150#	+1, -1
		WNRF 300#	+0, -1
		S0LJ	+1, 0
		SW	+0.25, -0.25



WELDNECK FLANGE



SLIP ON FLANGE



BLIND FLANGE

