# socket — Low-level networking interface

Source code: Lib/socket.py

This module provides access to the BSD *socket* interface. It is available on all modern Unix systems, Windows, MacOS, and probably additional platforms.

**Note:** Some behavior may be platform dependent, since calls are made to the operating system socket APIs.

The Python interface is a straightforward transliteration of the Unix system call and library interface for sockets to Python's object-oriented style: the socket() function returns a *socket object* whose methods implement the various socket system calls. Parameter types are somewhat higher-level than in the C interface: as with read() and write() operations on Python files, buffer allocation on receive operations is automatic, and buffer length is implicit on send operations.

#### See also:

Module socketserver

Classes that simplify writing network servers.

Module ssl

A TLS/SSL wrapper for socket objects.

# Socket families

Depending on the system and the build options, various socket families are supported by this module.

The address format required by a particular socket object is automatically selected based on the address family specified when the socket object was created. Socket addresses are represented as follows:

• The address of an AF\_UNIX socket bound to a file system node is represented as a string, using the file system encoding and the 'surrogateescape' error handler (see PEP 383). An address in Linux's abstract namespace is returned as a bytes-like object with an initial null byte; note that sockets in this namespace can communicate with normal file system sockets, so programs intended to run on Linux may need to deal with both types of address. A string or bytes-like object can be used for either type of address when passing it as an argument.

Changed in version 3.3: Previously, AF UNIX socket paths were assumed to use UTF-8 encoding.

Changed in version 3.5: Writable bytes-like object is now accepted.

- A pair (host, port) is used for the AF\_INET address family, where host is a string representing either a
  hostname in Internet domain notation like 'daring.cwi.nl' or an IPv4 address like '100.50.200.5', and
  port is an integer.



For socket module methods, *flowinfo* and *scope\_id* can be omitted just for backward compatibility. Note, however, omission of *scope\_id* can cause problems in manipulating scoped IPv6 addresses.

Changed in version 3.7: For multicast addresses (with scope\_id meaningful) address may not contain %scope\_id (or zone id) part. This information is superfluous and may be safely omitted (recommended).

- AF\_NETLINK sockets are represented as pairs (pid, groups).
- Linux-only support for TIPC is available using the AF\_TIPC address family. TIPC is an open, non-IP based networked protocol designed for use in clustered computer environments. Addresses are represented by a tuple, and the fields depend on the address type. The general tuple form is (addr\_type, v1, v2, v3 [, scope]), where:
  - addr\_type is one of TIPC\_ADDR\_NAMESEQ, TIPC\_ADDR\_NAME, or TIPC\_ADDR\_ID.
  - scope is one of TIPC\_ZONE\_SCOPE, TIPC\_CLUSTER\_SCOPE, and TIPC\_NODE\_SCOPE.
  - If addr\_type is TIPC\_ADDR\_NAME, then v1 is the server type, v2 is the port identifier, and v3 should be 0.

If addr\_type is TIPC\_ADDR\_NAMESEQ, then v1 is the server type, v2 is the lower port number, and v3 is the upper port number.

If addr\_type is TIPC\_ADDR\_ID, then v1 is the node, v2 is the reference, and v3 should be set to 0.

- A tuple (interface, ) is used for the AF\_CAN address family, where *interface* is a string representing a network interface name like 'can0'. The network interface name '' can be used to receive packets from all network interfaces of this family.
  - CAN\_ISOTP protocol require a tuple (interface, rx\_addr, tx\_addr) where both additional parameters are unsigned long integer that represent a CAN identifier (standard or extended).
  - CAN\_J1939 protocol require a tuple (interface, name, pgn, addr) where additional parameters are
     64-bit unsigned integer representing the ECU name, a 32-bit unsigned integer representing the
     Parameter Group Number (PGN), and an 8-bit integer representing the address.
- A string or a tuple (id, unit) is used for the SYSPROTO\_CONTROL protocol of the PF\_SYSTEM family. The string is the name of a kernel control using a dynamically-assigned ID. The tuple can be used if ID and unit number of the kernel control are known or if a registered ID is used.

New in version 3.3.

- AF\_BLUETOOTH supports the following protocols and address formats:
  - BTPROTO\_L2CAP accepts (bdaddr, psm) where bdaddr is the Bluetooth address as a string and psm is an integer.
  - BTPROTO\_RFCOMM accepts (bdaddr, channel) where bdaddr is the Bluetooth address as a string and channel is an integer.
  - BTPROTO\_HCI accepts (device\_id,) where device\_id is either an integer or a string with the Bluetooth address of the interface. (This depends on your OS; NetBSD and DragonFlyBSD expect a Bluetooth address while everything else expects an integer.)

Changed in version 3.2: NetBSD and DragonFlyBSD support added.

- BTPROTO\_SCO accepts bdaddr where bdaddr is a bytes object containing the Bluetooth address in a string format. (ex. b'12:23:34:45:56:67') This protocol is not supported under FreeBSD.
- AF\_ALG is a Linux-only socket based interface to Kernel cryptography. An algorithm socket is configured with a tuple of two to four elements (type, name [, feat [, mask]]), where:
  - type is the algorithm type as string, e.g. aead, hash, skcipher or rng.



**→** | Q

feat and mask are unsigned 32bit integers.

Availability: Linux 2.6.38, some algorithm types require more recent Kernels.

New in version 3.6.

AF\_VSOCK allows communication between virtual machines and their hosts. The sockets are represented as
a (CID, port) tuple where the context ID or CID and port are integers.

Availability: Linux >= 4.8 QEMU >= 2.8 ESX >= 4.0 ESX Workstation >= 6.5.

New in version 3.7.

- AF\_PACKET is a low-level interface directly to network devices. The packets are represented by the tuple (ifname, proto[, pkttype[, hatype[, addr]]]) where:
  - ifname String specifying the device name.
  - proto An in network-byte-order integer specifying the Ethernet protocol number.
  - o pkttype Optional integer specifying the packet type:
    - PACKET\_HOST (the default) Packet addressed to the local host.
    - PACKET\_BROADCAST Physical-layer broadcast packet.
    - PACKET\_MULTIHOST Packet sent to a physical-layer multicast address.
    - PACKET\_OTHERHOST Packet to some other host that has been caught by a device driver in promiscuous mode.
    - PACKET OUTGOING Packet originating from the local host that is looped back to a packet socket.
  - hatype Optional integer specifying the ARP hardware address type.
  - addr Optional bytes-like object specifying the hardware physical address, whose interpretation depends on the device.

Availability: Linux >= 2.2.

 AF\_QIPCRTR is a Linux-only socket based interface for communicating with services running on coprocessors in Qualcomm platforms. The address family is represented as a (node, port) tuple where the node and port are non-negative integers.

Availability: Linux >= 4.7.

New in version 3.8.

• IPPROTO\_UDPLITE is a variant of UDP which allows you to specify what portion of a packet is covered with the checksum. It adds two socket options that you can change. self.setsockopt(IPPROTO\_UDPLITE, UDPLITE\_SEND\_CSCOV, length) will change what portion of outgoing packets are covered by the checksum and self.setsockopt(IPPROTO\_UDPLITE, UDPLITE\_RECV\_CSCOV, length) will filter out packets which cover too little of their data. In both cases length should be in range(8, 2\*\*16, 8).

Such a socket should be constructed with socket(AF\_INET, SOCK\_DGRAM, IPPROTO\_UDPLITE) for IPv4 or socket(AF\_INET6, SOCK\_DGRAM, IPPROTO\_UDPLITE) for IPv6.

Availability: Linux >= 2.6.20, FreeBSD >= 10.1-RELEASE

New in version 3.9.

If you use a hostname in the *host* portion of IPv4/v6 socket address, the program may show a nondeterministic behavior, as Python uses the first address returned from the DNS resolution. The socket address will be



All errors raise exceptions. The normal exceptions for invalid argument types and out-of-memory conditions can be raised; starting from Python 3.3, errors related to socket or address semantics raise OSError or one of its subclasses (they used to raise socket.error).

Non-blocking mode is supported through setblocking(). A generalization of this based on timeouts is supported through settimeout().

# Module contents

The module socket exports the following elements.

## Exceptions

#### exception socket.error

A deprecated alias of OSError.

Changed in version 3.3: Following PEP 3151, this class was made an alias of OSError.

# exception socket. herror

A subclass of OSError, this exception is raised for address-related errors, i.e. for functions that use  $h\_errno$  in the POSIX C API, including gethostbyname\_ex() and gethostbyaddr(). The accompanying value is a pair (h\_errno, string) representing an error returned by a library call.  $h\_errno$  is a numeric value, while *string* represents the description of  $h\_errno$ , as returned by the hstrerror() C function.

Changed in version 3.3: This class was made a subclass of OSError.

# exception socket. gaierror

A subclass of OSError, this exception is raised for address-related errors by <code>getaddrinfo()</code> and <code>getnameinfo()</code>. The accompanying value is a pair (error, string) representing an error returned by a library call. <code>string</code> represents the description of <code>error</code>, as returned by the <code>gai\_strerror()</code> C function. The numeric <code>error</code> value will match one of the <code>EAI\_\*</code> constants defined in this module.

Changed in version 3.3: This class was made a subclass of OSError.

#### exception socket. timeout

A subclass of OSError, this exception is raised when a timeout occurs on a socket which has had timeouts enabled via a prior call to settimeout() (or implicitly through setdefaulttimeout()). The accompanying value is a string whose value is currently always "timed out".

Changed in version 3.3: This class was made a subclass of OSError.

#### Constants

The AF\_\* and SOCK\_\* constants are now AddressFamily and SocketKind IntEnum collections.

New in version 3.4.

```
socket.AF_UNIX
socket.AF_INET
socket.AF_INET6
```

These constants represent the address (and protocol) families, used for the first argument to socket(). If the AF\_UNIX constant is not defined then this protocol is unsupported. More constants may be available depending on the system.



socket.SOCK\_RAW
socket.SOCK\_RDM

socket. SOCK\_SEQPACKET

Q

These constants represent the socket types, used for the second argument to socket(). More constants may be available depending on the system. (Only SOCK\_STREAM and SOCK\_DGRAM appear to be generally useful.)

```
socket.SOCK_CLOEXEC
socket.SOCK_NONBLOCK
```

These two constants, if defined, can be combined with the socket types and allow you to set some flags atomically (thus avoiding possible race conditions and the need for separate calls).

**See also:** Secure File Descriptor Handling for a more thorough explanation.

Availability: Linux >= 2.6.27.

New in version 3.2.

```
SO_*
socket.SOMAXCONN
MSG_*
SOL_*
SCM_*
IPPROTO_*
IPPORT_*
INADDR_*
IP_*
IPV6_*
EAI_*
AI_*
NI_*
TCP_*
```

Many constants of these forms, documented in the Unix documentation on sockets and/or the IP protocol, are also defined in the socket module. They are generally used in arguments to the setsockopt() and getsockopt() methods of socket objects. In most cases, only those symbols that are defined in the Unix header files are defined; for a few symbols, default values are provided.

Changed in version 3.6: SO\_DOMAIN, SO\_PROTOCOL, SO\_PEERSEC, SO\_PASSSEC, TCP\_USER\_TIMEOUT, TCP\_CONGESTION were added.

Changed in version 3.6.5: On Windows, TCP\_FASTOPEN, TCP\_KEEPCNT appear if run-time Windows supports.

Changed in version 3.7: TCP\_NOTSENT\_LOWAT was added.

On Windows, TCP\_KEEPIDLE, TCP\_KEEPINTVL appear if run-time Windows supports.

```
socket.AF_CAN
socket.PF_CAN
SOL_CAN_*
CAN *
```

Many constants of these forms, documented in the Linux documentation, are also defined in the socket module.



New in version 3.3.

# socket. CAN\_BCM CAN\_BCM\_\*

CAN\_BCM, in the CAN protocol family, is the broadcast manager (BCM) protocol. Broadcast manager constants, documented in the Linux documentation, are also defined in the socket module.

Availability: Linux >= 2.6.25.

Q

**Note:** The CAN\_BCM\_CAN\_FD\_FRAME flag is only available on Linux >= 4.8.

New in version 3.4.

# socket. CAN\_RAW\_FD\_FRAMES

Enables CAN FD support in a CAN\_RAW socket. This is disabled by default. This allows your application to send both CAN and CAN FD frames; however, you must accept both CAN and CAN FD frames when reading from the socket.

This constant is documented in the Linux documentation.

Availability: Linux >= 3.6.

New in version 3.5.

# socket. CAN\_RAW\_JOIN\_FILTERS

Joins the applied CAN filters such that only CAN frames that match all given CAN filters are passed to user space.

This constant is documented in the Linux documentation.

Availability: Linux >= 4.1.

New in version 3.9.

#### socket. CAN ISOTP

CAN\_ISOTP, in the CAN protocol family, is the ISO-TP (ISO 15765-2) protocol. ISO-TP constants, documented in the Linux documentation.

Availability: Linux >= 2.6.25.

New in version 3.7.

# socket. CAN\_J1939

CAN\_J1939, in the CAN protocol family, is the SAE J1939 protocol. J1939 constants, documented in the Linux documentation.

Availability: Linux >= 5.4.

New in version 3.9.

socket. AF\_PACKET socket. PF\_PACKET

# PACKET \*

Many constants of these forms, documented in the Linux documentation, are also defined in the socket module.

```
Q
socket. AF_RDS
socket. PF_RDS
socket. SOL_RDS
RDS *
    Many constants of these forms, documented in the Linux documentation, are also defined in the socket
    module.
    Availability: Linux >= 2.6.30.
    New in version 3.3.
socket. SIO_RCVALL
socket. SIO_KEEPALIVE_VALS
socket. SIO_LOOPBACK_FAST_PATH
RCVALL_*
    Constants for Windows' WSAloctl(). The constants are used as arguments to the ioctl() method of
    socket objects.
    Changed in version 3.6: SIO_LOOPBACK_FAST_PATH was added.
TIPC_*
    TIPC related constants, matching the ones exported by the C socket API. See the TIPC documentation
    for more information.
socket.AF_ALG
{\tt socket.} \, \textbf{SOL\_ALG}
ALG_*
    Constants for Linux Kernel cryptography.
    Availability: Linux >= 2.6.38.
    New in version 3.6.
socket. AF_VSOCK
socket. IOCTL_VM_SOCKETS_GET_LOCAL_CID
VMADDR*
SO_VM*
    Constants for Linux host/guest communication.
    Availability: Linux >= 4.8.
    New in version 3.7.
socket. AF LINK
    Availability: BSD, macOS.
    New in version 3.4.
socket. has_ipv6
    This constant contains a boolean value which indicates if IPv6 is supported on this platform.
```

socket. BDADDR\_ANY socket. BDADDR LOCAL



BTPROTO\_RFCOMM.

socket.HCI\_FILTER
socket.HCI\_TIME\_STAMP
socket.HCI\_DATA\_DIR

For use with BTPROTO\_HCI. HCI\_FILTER is not available for NetBSD or DragonFlyBSD. HCI\_TIME\_STAMP and HCI\_DATA\_DIR are not available for FreeBSD, NetBSD, or DragonFlyBSD.

# socket. AF\_QIPCRTR

Constant for Qualcomm's IPC router protocol, used to communicate with service providing remote processors.

Availability: Linux >= 4.7.

#### **Functions**

# Creating sockets

The following functions all create socket objects.

Q

```
class socket. socket(family=AF_INET, type=SOCK_STREAM, proto=0, fileno=None)
```

Create a new socket using the given address family, socket type and protocol number. The address family should be AF\_INET (the default), AF\_INET6, AF\_UNIX, AF\_CAN, AF\_PACKET, or AF\_RDS. The socket type should be SOCK\_STREAM (the default), SOCK\_DGRAM, SOCK\_RAW or perhaps one of the other SOCK\_ constants. The protocol number is usually zero and may be omitted or in the case where the address family is AF\_CAN the protocol should be one of CAN\_RAW, CAN\_BCM, CAN\_ISOTP or CAN\_J1939.

If *fileno* is specified, the values for *family*, *type*, and *proto* are auto-detected from the specified file descriptor. Auto-detection can be overruled by calling the function with explicit *family*, *type*, or *proto* arguments. This only affects how Python represents e.g. the return value of <code>socket.getpeername()</code> but not the actual OS resource. Unlike <code>socket.fromfd()</code>, *fileno* will return the same socket and not a duplicate. This may help close a detached socket using <code>socket.close()</code>.

The newly created socket is non-inheritable.

Raises an auditing event socket. new with arguments self, family, type, protocol.

Changed in version 3.3: The AF\_CAN family was added. The AF\_RDS family was added.

Changed in version 3.4: The CAN BCM protocol was added.

Changed in version 3.4: The returned socket is now non-inheritable.

Changed in version 3.7: The CAN\_ISOTP protocol was added.

Changed in version 3.7: When SOCK\_NONBLOCK or SOCK\_CLOEXEC bit flags are applied to type they are cleared, and socket.type will not reflect them. They are still passed to the underlying system socket() call. Therefore,

```
sock = socket.socket(
    socket.AF_INET,
    socket.SOCK_STREAM | socket.SOCK_NONBLOCK)
```

will still create a non-blocking socket on OSes that support SOCK\_NONBLOCK, but sock.type will be set to socket.SOCK\_STREAM.



# socket. socketpair([family[, type[, proto]]])

Build a pair of connected socket objects using the given address family, socket type, and protocol number. Address family, socket type, and protocol number are as for the socket() function above. The default family is AF\_UNIX if defined on the platform; otherwise, the default is AF\_INET.

The newly created sockets are non-inheritable.

Changed in version 3.2: The returned socket objects now support the whole socket API, rather than a subset.

Changed in version 3.4: The returned sockets are now non-inheritable.

Changed in version 3.5: Windows support added.

```
socket.create_connection(address[, timeout[, source_address]])
```

Connect to a TCP service listening on the Internet address (a 2-tuple (host, port)), and return the socket object. This is a higher-level function than socket.connect(): if host is a non-numeric hostname, it will try to resolve it for both AF\_INET and AF\_INET6, and then try to connect to all possible addresses in turn until a connection succeeds. This makes it easy to write clients that are compatible to both IPv4 and IPv6.

Passing the optional *timeout* parameter will set the timeout on the socket instance before attempting to connect. If no *timeout* is supplied, the global default timeout setting returned by getdefaulttimeout() is used.

If supplied, source\_address must be a 2-tuple (host, port) for the socket to bind to as its source address before connecting. If host or port are "or 0 respectively the OS default behavior will be used.

Changed in version 3.2: source\_address was added.

```
socket. create_server(address, *, family=AF_INET, backlog=None, reuse_port=False, dualstack_ipv6=False)
```

Convenience function which creates a TCP socket bound to *address* (a 2-tuple (host, port)) and return the socket object.

family should be either AF\_INET or AF\_INET6. backlog is the queue size passed to socket.listen(); when 0 a default reasonable value is chosen. reuse\_port dictates whether to set the SO\_REUSEPORT socket option.

If dualstack\_ipv6 is true and the platform supports it the socket will be able to accept both IPv4 and IPv6 connections, else it will raise ValueError. Most POSIX platforms and Windows are supposed to support this functionality. When this functionality is enabled the address returned by socket.getpeername() when an IPv4 connection occurs will be an IPv6 address represented as an IPv4-mapped IPv6 address. If dualstack\_ipv6 is false it will explicitly disable this functionality on platforms that enable it by default (e.g. Linux). This parameter can be used in conjunction with has\_dualstack\_ipv6():

```
import socket

addr = ("", 8080) # all interfaces, port 8080
if socket.has_dualstack_ipv6():
    s = socket.create_server(addr, family=socket.AF_INET6, dualstack_ipv6=True)
else:
    s = socket.create_server(addr)
```



New in version 3.8.

# socket.has\_dualstack\_ipv6()

Return True if the platform supports creating a TCP socket which can handle both IPv4 and IPv6 connections.

New in version 3.8.

# socket. fromfd(fd, family, type, proto=0)

Duplicate the file descriptor fd (an integer as returned by a file object's fileno() method) and build a socket object from the result. Address family, socket type and protocol number are as for the socket() function above. The file descriptor should refer to a socket, but this is not checked — subsequent operations on the object may fail if the file descriptor is invalid. This function is rarely needed, but can be used to get or set socket options on a socket passed to a program as standard input or output (such as a server started by the Unix inet daemon). The socket is assumed to be in blocking mode.

The newly created socket is non-inheritable.

Changed in version 3.4: The returned socket is now non-inheritable.

# socket. fromshare(data)

Instantiate a socket from data obtained from the socket.share() method. The socket is assumed to be in blocking mode.

Availability: Windows.

New in version 3.3.

#### socket. **SocketType**

This is a Python type object that represents the socket object type. It is the same as type(socket(...)).

#### Other functions

The socket module also offers various network-related services:

# socket. close(fd)

Close a socket file descriptor. This is like os.close(), but for sockets. On some platforms (most noticeable Windows) os.close() does not work for socket file descriptors.

New in version 3.7.

# socket.getaddrinfo(host, port, family=0, type=0, proto=0, flags=0)

Translate the *host/port* argument into a sequence of 5-tuples that contain all the necessary arguments for creating a socket connected to that service. *host* is a domain name, a string representation of an IPv4/v6 address or None. *port* is a string service name such as 'http', a numeric port number or None. By passing None as the value of *host* and *port*, you can pass NULL to the underlying C API.

The *family*, *type* and *proto* arguments can be optionally specified in order to narrow the list of addresses returned. Passing zero as a value for each of these arguments selects the full range of results. The *flags* argument can be one or several of the AI\_\* constants, and will influence how results are computed and returned. For example, AI\_NUMERICHOST will disable domain name resolution and will raise an error if *host* is a domain name.



(tamily, type, proto, canonname, sockaddr)

In these tuples, family, type, proto are all integers and are meant to be passed to the socket() function. canonname will be a string representing the canonical name of the host if AI\_CANONNAME is part of the flags argument; else canonname will be empty. sockaddr is a tuple describing a socket address, whose format depends on the returned family (a (address, port) 2-tuple for AF\_INET, a (address, port, flowinfo, scope\_id) 4-tuple for AF\_INET6), and is meant to be passed to the socket.connect() method.

Raises an auditing event socket.getaddrinfo with arguments host, port, family, type, protocol.

The following example fetches address information for a hypothetical TCP connection to example.org on port 80 (results may differ on your system if IPv6 isn't enabled):

```
>>> socket.getaddrinfo("example.org", 80, proto=socket.IPPROTO_TCP)

[(<AddressFamily.AF_INET6: 10>, <SocketType.SOCK_STREAM: 1>,
6, '', ('2606:2800:220:1:248:1893:25c8:1946', 80, 0, 0)),
(<AddressFamily.AF_INET: 2>, <SocketType.SOCK_STREAM: 1>,
6, '', ('93.184.216.34', 80))]
```

Changed in version 3.2: parameters can now be passed using keyword arguments.

Changed in version 3.7: for IPv6 multicast addresses, string representing an address will not contain %scope\_id part.

# socket. getfqdn([name])

Return a fully qualified domain name for *name*. If *name* is omitted or empty, it is interpreted as the local host. To find the fully qualified name, the hostname returned by <code>gethostbyaddr()</code> is checked, followed by aliases for the host, if available. The first name which includes a period is selected. In case no fully qualified domain name is available and *name* was provided, it is returned unchanged. If *name* was empty or equal to <code>'0.0.0.0'</code>, the hostname from <code>gethostname()</code> is returned.

## socket.gethostbyname(hostname)

Translate a host name to IPv4 address format. The IPv4 address is returned as a string, such as '100.50.200.5'. If the host name is an IPv4 address itself it is returned unchanged. See gethostbyname\_ex() for a more complete interface. gethostbyname() does not support IPv6 name resolution, and getaddrinfo() should be used instead for IPv4/v6 dual stack support.

Raises an auditing event socket.gethostbyname with argument hostname.

# socket.gethostbyname ex(hostname)

Translate a host name to IPv4 address format, extended interface. Return a triple (hostname, aliaslist, ipaddrlist) where hostname is the host's primary host name, aliaslist is a (possibly empty) list of alternative host names for the same address, and ipaddrlist is a list of IPv4 addresses for the same interface on the same host (often but not always a single address). gethostbyname\_ex() does not support IPv6 name resolution, and getaddrinfo() should be used instead for IPv4/v6 dual stack support.

Raises an auditing event socket.gethostbyname with argument hostname.

# socket.gethostname()

Return a string containing the hostname of the machine where the Python interpreter is currently executing.



Note: gethostname() doesn't always return the tully qualified domain name; use get+qdn() for that.

# socket.gethostbyaddr(ip\_address)

Return a triple (hostname, aliaslist, ipaddrlist) where *hostname* is the primary host name responding to the given *ip\_address*, *aliaslist* is a (possibly empty) list of alternative host names for the same address, and *ipaddrlist* is a list of IPv4/v6 addresses for the same interface on the same host (most likely containing only a single address). To find the fully qualified domain name, use the function getfqdn(). gethostbyaddr() supports both IPv4 and IPv6.

Raises an auditing event socket.gethostbyaddr with argument ip\_address.

# socket.getnameinfo(sockaddr, flags)

Translate a socket address *sockaddr* into a 2-tuple (host, port). Depending on the settings of *flags*, the result can contain a fully-qualified domain name or numeric address representation in *host*. Similarly, *port* can contain a string port name or a numeric port number.

For IPv6 addresses, %scope\_id is appended to the host part if sockaddr contains meaningful scope\_id. Usually this happens for multicast addresses.

For more information about *flags* you can consult *getnameinfo(3)*.

Raises an auditing event socket.getnameinfo with argument sockaddr.

# socket.getprotobyname(protocolname)

Translate an Internet protocol name (for example, 'icmp') to a constant suitable for passing as the (optional) third argument to the socket() function. This is usually only needed for sockets opened in "raw" mode (SOCK\_RAW); for the normal socket modes, the correct protocol is chosen automatically if the protocol is omitted or zero.

# socket.getservbyname(servicename[, protocolname])

Translate an Internet service name and protocol name to a port number for that service. The optional protocol name, if given, should be 'tcp' or 'udp', otherwise any protocol will match.

Raises an auditing event socket.getservbyname with arguments servicename, protocolname.

# socket.getservbyport(port[, protocolname])

Translate an Internet port number and protocol name to a service name for that service. The optional protocol name, if given, should be 'tcp' or 'udp', otherwise any protocol will match.

Raises an auditing event socket.getservbyport with arguments port, protocolname.

# socket. **ntohl**(x)

Convert 32-bit positive integers from network to host byte order. On machines where the host byte order is the same as network byte order, this is a no-op; otherwise, it performs a 4-byte swap operation.

#### socket. **ntohs**(x)

Convert 16-bit positive integers from network to host byte order. On machines where the host byte order is the same as network byte order, this is a no-op; otherwise, it performs a 2-byte swap operation.

Deprecated since version 3.7: In case x does not fit in 16-bit unsigned integer, but does fit in a positive C int, it is silently truncated to 16-bit unsigned integer. This silent truncation feature is deprecated, and will raise an exception in future versions of Python.



is the same as network byte order, this is a no-op; otherwise, it performs a 4-byte swap operation.

# socket. htons(x)

Convert 16-bit positive integers from host to network byte order. On machines where the host byte order is the same as network byte order, this is a no-op; otherwise, it performs a 2-byte swap operation.

Deprecated since version 3.7: In case x does not fit in 16-bit unsigned integer, but does fit in a positive C int, it is silently truncated to 16-bit unsigned integer. This silent truncation feature is deprecated, and will raise an exception in future versions of Python.

# socket.inet\_aton(ip\_string)

Convert an IPv4 address from dotted-quad string format (for example, '123.45.67.89') to 32-bit packed binary format, as a bytes object four characters in length. This is useful when conversing with a program that uses the standard C library and needs objects of type struct in\_addr, which is the C type for the 32-bit packed binary this function returns.

inet\_aton() also accepts strings with less than three dots; see the Unix manual page inet(3) for details.

If the IPv4 address string passed to this function is invalid, OSError will be raised. Note that exactly what is valid depends on the underlying C implementation of inet\_aton().

inet\_aton() does not support IPv6, and inet\_pton() should be used instead for IPv4/v6 dual stack support.

# socket.inet\_ntoa(packed\_ip)

Convert a 32-bit packed IPv4 address (a bytes-like object four bytes in length) to its standard dotted-quad string representation (for example, '123.45.67.89'). This is useful when conversing with a program that uses the standard C library and needs objects of type struct in\_addr, which is the C type for the 32-bit packed binary data this function takes as an argument.

If the byte sequence passed to this function is not exactly 4 bytes in length, <code>OSError</code> will be raised. <code>inet\_ntoa()</code> does not support IPv6, and <code>inet\_ntop()</code> should be used instead for IPv4/v6 dual stack support.

Changed in version 3.5: Writable bytes-like object is now accepted.

# socket.inet\_pton(address\_family, ip\_string)

Convert an IP address from its family-specific string format to a packed, binary format. inet\_pton() is useful when a library or network protocol calls for an object of type struct in\_addr (similar to inet\_aton()) or struct in6\_addr.

Supported values for address\_family are currently AF\_INET and AF\_INET6. If the IP address string ip\_string is invalid, OSError will be raised. Note that exactly what is valid depends on both the value of address\_family and the underlying implementation of inet\_pton().

Availability: Unix (maybe not all platforms), Windows.

Changed in version 3.4: Windows support added

# socket.inet\_ntop(address\_family, packed\_ip)

Convert a packed IP address (a bytes-like object of some number of bytes) to its standard, family-specific string representation (for example, '7.10.0.5' or '5aef:2b::8'). inet\_ntop() is useful when a library



•

Q

Supported values for *address\_family* are currently AF\_INET and AF\_INET6. If the bytes object *packed\_ip* is not the correct length for the specified address family, ValueError will be raised. OSError is raised for errors from the call to inet\_ntop().

Availability: Unix (maybe not all platforms), Windows.

Changed in version 3.4: Windows support added

Changed in version 3.5: Writable bytes-like object is now accepted.

# socket. CMSG\_LEN(length)

Return the total length, without trailing padding, of an ancillary data item with associated data of the given *length*. This value can often be used as the buffer size for <code>recvmsg()</code> to receive a single item of ancillary data, but **RFC 3542** requires portable applications to use <code>CMSG\_SPACE()</code> and thus include space for padding, even when the item will be the last in the buffer. Raises <code>OverflowError</code> if <code>length</code> is outside the permissible range of values.

Availability: most Unix platforms, possibly others.

New in version 3.3.

# socket. CMSG\_SPACE(Length)

Return the buffer size needed for <code>recvmsg()</code> to receive an ancillary data item with associated data of the given <code>length</code>, along with any trailing padding. The buffer space needed to receive multiple items is the sum of the <code>CMSG\_SPACE()</code> values for their associated data lengths. Raises <code>OverflowError</code> if <code>length</code> is outside the permissible range of values.

Note that some systems might support ancillary data without providing this function. Also note that setting the buffer size using the results of this function may not precisely limit the amount of ancillary data that can be received, since additional data may be able to fit into the padding area.

Availability: most Unix platforms, possibly others.

New in version 3.3.

#### socket.getdefaulttimeout()

Return the default timeout in seconds (float) for new socket objects. A value of None indicates that new socket objects have no timeout. When the socket module is first imported, the default is None.

# socket. setdefaulttimeout(timeout)

Set the default timeout in seconds (float) for new socket objects. When the socket module is first imported, the default is None. See settimeout() for possible values and their respective meanings.

# socket. sethostname(name)

Set the machine's hostname to name. This will raise an OSError if you don't have enough rights.

Raises an auditing event socket.sethostname with argument name.

Availability: Unix.

New in version 3.3.

socket.if\_nameindex()



•

Q

Availability: Unix, Windows.

New in version 3.3.

Changed in version 3.8: Windows support was added.

**Note:** On Windows network interfaces have different names in different contexts (all names are examples):

- UUID: {FB605B73-AAC2-49A6-9A2F-25416AEA0573}
- name: ethernet 32770
- friendly name: vEthernet (nat)
- description: Hyper-V Virtual Ethernet Adapter

This function returns names of the second form from the list, ethernet\_32770 in this example case.

# socket.if\_nametoindex(if\_name)

Return a network interface index number corresponding to an interface name. OSError if no interface with the given name exists.

Availability: Unix, Windows.

New in version 3.3.

Changed in version 3.8: Windows support was added.

**See also:** "Interface name" is a name as documented in if\_nameindex().

# socket.if\_indextoname(if\_index)

Return a network interface name corresponding to an interface index number. OSError if no interface with the given index exists.

Availability: Unix, Windows.

New in version 3.3.

Changed in version 3.8: Windows support was added.

**See also:** "Interface name" is a name as documented in if\_nameindex().

# socket. send\_fds(sock, buffers, fds[, flags[, address]])

Send the list of file descriptors *fds* over an AF\_UNIX socket *sock*. The *fds* parameter is a sequence of file descriptors. Consult sendmsg() for the documentation of these parameters.

Availability: Unix supporting sendmsg() and SCM\_RIGHTS mechanism.

New in version 3.9.

# socket.recv\_fds(sock, bufsize, maxfds[, flags])

Receive up to *maxfds* file descriptors from an AF\_UNIX socket *sock*. Return (msg, list(fds), flags, addr). Consult recvmsg() for the documentation of these parameters.



New in version 3.9.

**Note:** Any truncated integers at the end of the list of file descriptors.

# Socket Objects

Socket objects have the following methods. Except for makefile(), these correspond to Unix system calls applicable to sockets.

Changed in version 3.2: Support for the context manager protocol was added. Exiting the context manager is equivalent to calling close().

# socket.accept()

Accept a connection. The socket must be bound to an address and listening for connections. The return value is a pair (conn, address) where *conn* is a *new* socket object usable to send and receive data on the connection, and *address* is the address bound to the socket on the other end of the connection.

The newly created socket is non-inheritable.

Q

Changed in version 3.4: The socket is now non-inheritable.

Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).

# socket.bind(address)

Bind the socket to *address*. The socket must not already be bound. (The format of *address* depends on the address family — see above.)

Raises an auditing event socket.bind with arguments self, address.

#### socket. **close**()

Mark the socket closed. The underlying system resource (e.g. a file descriptor) is also closed when all file objects from makefile() are closed. Once that happens, all future operations on the socket object will fail. The remote end will receive no more data (after queued data is flushed).

Sockets are automatically closed when they are garbage-collected, but it is recommended to close() them explicitly, or to use a with statement around them.

Changed in version 3.6: OSError is now raised if an error occurs when the underlying close() call is made.

**Note:** close() releases the resource associated with a connection but does not necessarily close the connection immediately. If you want to close the connection in a timely fashion, call shutdown()
before close().

# socket. connect(address)

Connect to a remote socket at *address*. (The format of *address* depends on the address family — see above.)

If the connection is interrupted by a signal, the method waits until the connection completes, or raise a socket.timeout on timeout, if the signal handler doesn't raise an exception and the socket is blocking or



Raises an auditing event socket.connect with arguments self, address.

Changed in version 3.5: The method now waits until the connection completes instead of raising an InterruptedError exception if the connection is interrupted by a signal, the signal handler doesn't raise an exception and the socket is blocking or has a timeout (see the **PEP 475** for the rationale).

# socket. connect\_ex(address)

Q

Like connect(address), but return an error indicator instead of raising an exception for errors returned by the C-level connect() call (other problems, such as "host not found," can still raise exceptions). The error indicator is 0 if the operation succeeded, otherwise the value of the error variable. This is useful to support, for example, asynchronous connects.

Raises an auditing event socket.connect with arguments self, address.

# socket. detach()

Put the socket object into closed state without actually closing the underlying file descriptor. The file descriptor is returned, and can be reused for other purposes.

New in version 3.2.

# socket. dup()

Duplicate the socket.

The newly created socket is non-inheritable.

Changed in version 3.4: The socket is now non-inheritable.

# socket.fileno()

Return the socket's file descriptor (a small integer), or -1 on failure. This is useful with select.select().

Under Windows the small integer returned by this method cannot be used where a file descriptor can be used (such as os.fdopen()). Unix does not have this limitation.

## socket.get\_inheritable()

Get the inheritable flag of the socket's file descriptor or socket's handle: True if the socket can be inherited in child processes, False if it cannot.

New in version 3.4.

#### socket.getpeername()

Return the remote address to which the socket is connected. This is useful to find out the port number of a remote IPv4/v6 socket, for instance. (The format of the address returned depends on the address family — see above.) On some systems this function is not supported.

#### socket.getsockname()

Return the socket's own address. This is useful to find out the port number of an IPv4/v6 socket, for instance. (The format of the address returned depends on the address family — see above.)

# socket.getsockopt(level, optname[, buflen])

Return the value of the given socket option (see the Unix man page *getsockopt(2)*). The needed symbolic constants (S0\_\* etc.) are defined in this module. If *buflen* is absent, an integer option is assumed and its integer value is returned by the function. If *buflen* is present, it specifies the maximum length of the buffer



encoded as byte strings).

Q

# socket.getblocking()

Return True if socket is in blocking mode, False if in non-blocking.

This is equivalent to checking socket.gettimeout() == 0.

New in version 3.7.

# socket.gettimeout()

Return the timeout in seconds (float) associated with socket operations, or None if no timeout is set. This reflects the last call to setblocking() or settimeout().

socket.ioctl(control, option)

Platform: Windows

The ioctl() method is a limited interface to the WSAloctl system interface. Please refer to the Win32 documentation for more information.

On other platforms, the generic fcntl.fcntl() and fcntl.ioctl() functions may be used; they accept a socket object as their first argument.

Currently only the following control codes are supported: SIO\_RCVALL, SIO\_KEEPALIVE\_VALS, and SIO LOOPBACK FAST PATH.

Changed in version 3.6: SIO\_LOOPBACK\_FAST\_PATH was added.

# socket. listen([backLog])

Enable a server to accept connections. If *backlog* is specified, it must be at least 0 (if it is lower, it is set to 0); it specifies the number of unaccepted connections that the system will allow before refusing new connections. If not specified, a default reasonable value is chosen.

Changed in version 3.5: The backlog parameter is now optional.

socket. makefile(mode='r', buffering=None, \*, encoding=None, errors=None, newLine=None)

Return a file object associated with the socket. The exact returned type depends on the arguments given to makefile(). These arguments are interpreted the same way as by the built-in open() function, except the only supported mode values are 'r' (default), 'w' and 'b'.

The socket must be in blocking mode; it can have a timeout, but the file object's internal buffer may end up in an inconsistent state if a timeout occurs.

Closing the file object returned by makefile() won't close the original socket unless all other file objects have been closed and socket.close() has been called on the socket object.

**Note:** On Windows, the file-like object created by makefile() cannot be used where a file object with a file descriptor is expected, such as the stream arguments of subprocess.Popen().

# socket.recv(bufsize[, flags])

Receive data from the socket. The return value is a bytes object representing the data received. The maximum amount of data to be received at once is specified by *bufsize*. See the Unix manual page recv(2) for the meaning of the optional argument *flags*; it defaults to zero.



Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).

# socket.recvfrom(bufsize[, flags])

Receive data from the socket. The return value is a pair (bytes, address) where bytes is a bytes object representing the data received and address is the address of the socket sending the data. See the Unix manual page recv(2) for the meaning of the optional argument flags; it defaults to zero. (The format of address depends on the address family — see above.)

Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).

Changed in version 3.7: For multicast IPv6 address, first item of address does not contain %scope\_id part anymore. In order to get full IPv6 address use getnameinfo().

# socket.recvmsg(bufsize[, ancbufsize[, flags]])

Receive normal data (up to *bufsize* bytes) and ancillary data from the socket. The *ancbufsize* argument sets the size in bytes of the internal buffer used to receive the ancillary data; it defaults to 0, meaning that no ancillary data will be received. Appropriate buffer sizes for ancillary data can be calculated using CMSG\_SPACE() or CMSG\_LEN(), and items which do not fit into the buffer might be truncated or discarded. The *flags* argument defaults to 0 and has the same meaning as for recv().

The return value is a 4-tuple: (data, ancdata, msg\_flags, address). The *data* item is a bytes object holding the non-ancillary data received. The *ancdata* item is a list of zero or more tuples (cmsg\_level, cmsg\_type, cmsg\_data) representing the ancillary data (control messages) received: cmsg\_level and cmsg\_type are integers specifying the protocol level and protocol-specific type respectively, and cmsg\_data is a bytes object holding the associated data. The msg\_flags item is the bitwise OR of various flags indicating conditions on the received message; see your system documentation for details. If the receiving socket is unconnected, *address* is the address of the sending socket, if available; otherwise, its value is unspecified.

On some systems, <code>sendmsg()</code> and <code>recvmsg()</code> can be used to pass file descriptors between processes over an <code>AF\_UNIX</code> socket. When this facility is used (it is often restricted to <code>SOCK\_STREAM</code> sockets), <code>recvmsg()</code> will return, in its ancillary data, items of the form <code>(socket.SOL\_SOCKET, socket.SCM\_RIGHTS, fds)</code>, where <code>fds</code> is a <code>bytes</code> object representing the new file descriptors as a binary array of the native <code>C int type</code>. If <code>recvmsg()</code> raises an exception after the system call returns, it will first attempt to close any file descriptors received via this mechanism.

Some systems do not indicate the truncated length of ancillary data items which have been only partially received. If an item appears to extend beyond the end of the buffer, recvmsg() will issue a RuntimeWarning, and will return the part of it which is inside the buffer provided it has not been truncated before the start of its associated data.

On systems which support the SCM\_RIGHTS mechanism, the following function will receive up to *maxfds* file descriptors, returning the message data and a list containing the descriptors (while ignoring unexpected conditions such as unrelated control messages being received). See also sendmsg().

```
misg, ancuata, Trags, addr = SOCK.recvmsg(msgren, SOCKet.Cmso_Len(maxtus * Tus.Items
for cmsg_level, cmsg_type, cmsg_data in ancdata:
    if cmsg_level == socket.SOL_SOCKET and cmsg_type == socket.SCM_RIGHTS:
        # Append data, ignoring any truncated integers at the end.
        fds.frombytes(cmsg_data[:len(cmsg_data) - (len(cmsg_data) % fds.itemsize)])
    return msg, list(fds)
```

Availability: most Unix platforms, possibly others.

```
Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).
```

```
socket.recvmsg_into(buffers[, ancbufsize[, flags]])
```

Receive normal data and ancillary data from the socket, behaving as recvmsg() would, but scatter the non-ancillary data into a series of buffers instead of returning a new bytes object. The *buffers* argument must be an iterable of objects that export writable buffers (e.g. bytearray objects); these will be filled with successive chunks of the non-ancillary data until it has all been written or there are no more buffers. The operating system may set a limit (sysconf() value SC\_IOV\_MAX) on the number of buffers that can be used. The *ancbufsize* and *flags* arguments have the same meaning as for recvmsg().

The return value is a 4-tuple: (nbytes, ancdata, msg\_flags, address), where *nbytes* is the total number of bytes of non-ancillary data written into the buffers, and *ancdata*, *msg\_flags* and *address* are the same as for recvmsg().

#### Example:

```
>>> import socket
>>> s1, s2 = socket.socketpair()
>>> b1 = bytearray(b'----')
>>> b2 = bytearray(b'0123456789')
>>> b3 = bytearray(b'------')
>>> s1.send(b'Mary had a little lamb')
22
>>> s2.recvmsg_into([b1, memoryview(b2)[2:9], b3])
(22, [], 0, None)
>>> [b1, b2, b3]
[bytearray(b'Mary'), bytearray(b'01 had a 9'), bytearray(b'little lamb---')]
```

Availability: most Unix platforms, possibly others.

New in version 3.3.

```
socket.recvfrom_into(buffer[, nbytes[, flags]])
```

Receive data from the socket, writing it into *buffer* instead of creating a new bytestring. The return value is a pair (nbytes, address) where *nbytes* is the number of bytes received and *address* is the address of the socket sending the data. See the Unix manual page recv(2) for the meaning of the optional argument *flags*; it defaults to zero. (The format of *address* depends on the address family — see above.)

```
socket.recv_into(buffer[, nbytes[, flags]])
```

Receive up to *nbytes* bytes from the socket, storing the data into a buffer rather than creating a new bytestring. If *nbytes* is not specified (or 0), receive up to the size available in the given buffer. Returns the



# socket. send(bytes[, flags])

Send data to the socket. The socket must be connected to a remote socket. The optional *flags* argument has the same meaning as for recv() above. Returns the number of bytes sent. Applications are responsible for checking that all data has been sent; if only some of the data was transmitted, the application needs to attempt delivery of the remaining data. For further information on this topic, consult the Socket Programming HOWTO.

Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).

# socket. sendall(bytes[, flags])

Send data to the socket. The socket must be connected to a remote socket. The optional *flags* argument has the same meaning as for recv() above. Unlike send(), this method continues to send data from *bytes* until either all data has been sent or an error occurs. None is returned on success. On error, an exception is raised, and there is no way to determine how much data, if any, was successfully sent.

Changed in version 3.5: The socket timeout is no more reset each time data is sent successfully. The socket timeout is now the maximum total duration to send all data.

Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).

```
socket. sendto(bytes, address)
socket. sendto(bytes, flags, address)
```

Send data to the socket. The socket should not be connected to a remote socket, since the destination socket is specified by *address*. The optional *flags* argument has the same meaning as for recv() above. Return the number of bytes sent. (The format of *address* depends on the address family — see above.)

Raises an auditing event socket.sendto with arguments self, address.

Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).

# socket.sendmsg(buffers[, ancdata[, flags[, address]]])

Send normal and ancillary data to the socket, gathering the non-ancillary data from a series of buffers and concatenating it into a single message. The *buffers* argument specifies the non-ancillary data as an iterable of bytes-like objects (e.g. bytes objects); the operating system may set a limit (sysconf() value SC\_IOV\_MAX) on the number of buffers that can be used. The *ancdata* argument specifies the ancillary data (control messages) as an iterable of zero or more tuples (cmsg\_level, cmsg\_type, cmsg\_data), where *cmsg\_level* and *cmsg\_type* are integers specifying the protocol level and protocol-specific type respectively, and *cmsg\_data* is a bytes-like object holding the associated data. Note that some systems (in particular, systems without CMSG\_SPACE()) might support sending only one control message per call. The *flags* argument defaults to 0 and has the same meaning as for send(). If *address* is supplied and not None, it sets a destination address for the message. The return value is the number of bytes of non-ancillary data sent.

The following function sends the list of file descriptors fds over an AF\_UNIX socket, on systems which support the SCM\_RIGHTS mechanism. See also recvmsg().



Availability: most Unix platforms, possibly others.

Raises an auditing event socket.sendmsg with arguments self, address.

New in version 3.3.

Changed in version 3.5: If the system call is interrupted and the signal handler does not raise an exception, the method now retries the system call instead of raising an InterruptedError exception (see PEP 475 for the rationale).

```
socket.sendmsg_afalg([msg,]*,op[,iv[,assoclen[,flags]]])
```

Specialized version of sendmsg() for AF\_ALG socket. Set mode, IV, AEAD associated data length and flags for AF\_ALG socket.

Availability: Linux >= 2.6.38.

New in version 3.6.

# socket. sendfile(file, offset=0, count=None)

Send a file until EOF is reached by using high-performance os.sendfile and return the total number of bytes which were sent. file must be a regular file object opened in binary mode. If os.sendfile is not available (e.g. Windows) or file is not a regular file send() will be used instead. offset tells from where to start reading the file. If specified, count is the total number of bytes to transmit as opposed to sending the file until EOF is reached. File position is updated on return or also in case of error in which case file.tell() can be used to figure out the number of bytes which were sent. The socket must be of SOCK\_STREAM type. Non-blocking sockets are not supported.

New in version 3.5.

# socket.set\_inheritable(inheritable)

Set the inheritable flag of the socket's file descriptor or socket's handle.

New in version 3.4.

# socket. setblocking(flag)

Set blocking or non-blocking mode of the socket: if *flag* is false, the socket is set to non-blocking, else to blocking mode.

This method is a shorthand for certain settimeout() calls:

- sock.setblocking(True) is equivalent to sock.settimeout(None)
- sock.setblocking(False) is equivalent to sock.settimeout(0.0)

Changed in version 3.7: The method no longer applies SOCK\_NONBLOCK flag on socket.type.

# socket. settimeout(value)

Set a timeout on blocking socket operations. The *value* argument can be a nonnegative floating point number expressing seconds, or None. If a non-zero value is given, subsequent socket operations will



For further information, please consult the notes on socket timeouts.

Changed in version 3.7: The method no longer toggles SOCK\_NONBLOCK flag on socket.type.

```
socket. setsockopt(level, optname, value: int)
socket. setsockopt(level, optname, value: buffer)
socket. setsockopt(level, optname, None, optlen: int)
```

Set the value of the given socket option (see the Unix manual page <code>setsockopt(2)</code>). The needed symbolic constants are defined in the <code>socket</code> module (SO\_\* etc.). The value can be an integer, <code>None</code> or a <code>bytes-like object</code> representing a buffer. In the later case it is up to the caller to ensure that the bytestring contains the proper bits (see the optional built-in module <code>struct</code> for a way to encode <code>C</code> structures as bytestrings). When <code>value</code> is set to <code>None</code>, <code>optlen</code> argument is required. It's equivalent to call <code>setsockopt()</code> <code>C</code> function with <code>optval=NULL</code> and <code>optlen=optlen</code>.

Changed in version 3.5: Writable bytes-like object is now accepted.

Changed in version 3.6: setsockopt(level, optname, None, optlen: int) form added.

# socket. **shutdown**(how)

Shut down one or both halves of the connection. If *how* is SHUT\_RD, further receives are disallowed. If *how* is SHUT\_RDWR, further sends and receives are disallowed.

```
socket. share(process id)
```

Duplicate a socket and prepare it for sharing with a target process. The target process must be provided with *process\_id*. The resulting bytes object can then be passed to the target process using some form of interprocess communication and the socket can be recreated there using <code>fromshare()</code>. Once this method has been called, it is safe to close the socket since the operating system has already duplicated it for the target process.

Availability: Windows.

New in version 3.3.

Note that there are no methods read() or write(); use recv() and send() without flags argument instead.

Socket objects also have these (read-only) attributes that correspond to the values given to the socket constructor.

socket. **family** 

The socket family.

socket. type

The socket type.

socket. **proto** 

The socket protocol.

Notes on socket timeouts



- In blocking mode, operations block until complete or the system returns an error (such as connection timed out).
- In non-blocking mode, operations fail (with an error that is unfortunately system-dependent) if they cannot
  be completed immediately: functions from the select can be used to know when and whether a socket is
  available for reading or writing.
- In *timeout mode*, operations fail if they cannot be completed within the timeout specified for the socket (they raise a timeout exception) or if the system returns an error.

**Note:** At the operating system level, sockets in *timeout mode* are internally set in non-blocking mode. Also, the blocking and timeout modes are shared between file descriptors and socket objects that refer to the same network endpoint. This implementation detail can have visible consequences if e.g. you decide to use the fileno() of a socket.

#### Timeouts and the connect method

The connect() operation is also subject to the timeout setting, and in general it is recommended to call settimeout() before calling connect() or pass a timeout parameter to create\_connection(). However, the system network stack may also return a connection timeout error of its own regardless of any Python socket timeout setting.

#### Timeouts and the accept method

If getdefaulttimeout() is not None, sockets returned by the accept() method inherit that timeout. Otherwise, the behaviour depends on settings of the listening socket:

- if the listening socket is in *blocking mode* or in *timeout mode*, the socket returned by accept() is in *blocking mode*:
- if the listening socket is in *non-blocking mode*, whether the socket returned by accept() is in blocking or non-blocking mode is operating system-dependent. If you want to ensure cross-platform behaviour, it is recommended you manually override this setting.

# Example

Here are four minimal example programs using the TCP/IP protocol: a server that echoes all data that it receives back (servicing only one client), and a client using it. Note that a server must perform the sequence socket(), bind(), listen(), accept() (possibly repeating the accept() to service more than one client), while a client only needs the sequence socket(), connect(). Also note that the server does not sendall()/recv() on the socket it is listening on but on the new socket returned by accept().

The first two examples support IPv4 only.





Q conn. Senuali (uata)

```
# Echo client program
import socket
HOST = 'daring.cwi.nl' # The remote host
PORT = 50007
                         # The same port as used by the server
with socket.socket(socket.AF_INET, socket.SOCK_STREAM) as s:
    s.connect((HOST, PORT))
   s.sendall(b'Hello, world')
   data = s.recv(1024)
print('Received', repr(data))
```

The next two examples are identical to the above two, but support both IPv4 and IPv6. The server side will listen to the first address family available (it should listen to both instead). On most of IPv6-ready systems, IPv6 will take precedence and the server may not accept IPv4 traffic. The client side will try to connect to the all addresses returned as a result of the name resolution, and sends traffic to the first one connected successfully.

```
# Echo server program
import socket
import sys
                          # Symbolic name meaning all available interfaces
HOST = None
PORT = 50007
                          # Arbitrary non-privileged port
s = None
for res in socket.getaddrinfo(HOST, PORT, socket.AF_UNSPEC,
                              socket.SOCK_STREAM, 0, socket.AI_PASSIVE):
    af, socktype, proto, canonname, sa = res
    try:
        s = socket.socket(af, socktype, proto)
    except OSError as msg:
        s = None
        continue
    try:
        s.bind(sa)
        s.listen(1)
    except OSError as msg:
        s.close()
        s = None
        continue
if s is None:
    print('could not open socket')
    sys.exit(1)
conn, addr = s.accept()
with conn:
    print('Connected by', addr)
    while True:
        data = conn.recv(1024)
        if not data: break
        conn.send(data)
```

```
# Echo client program
import socket
import sys
```

```
s = None

for res in socket getaddrinfo(HOST_PORT_socket AF_LINSPEC_socket SOCK_STREAM):
```

```
for res in socket.getaddrinfo(HOST, PORT, socket.AF UNSPEC, socket.SOCK STREAM):
    af, socktype, proto, canonname, sa = res
    try:
        s = socket.socket(af, socktype, proto)
    except OSError as msg:
        s = None
        continue
    try:
        s.connect(sa)
    except OSError as msg:
        s.close()
        s = None
        continue
    break
if s is None:
    print('could not open socket')
    sys.exit(1)
with s:
    s.sendall(b'Hello, world')
    data = s.recv(1024)
print('Received', repr(data))
```

The next example shows how to write a very simple network sniffer with raw sockets on Windows. The example requires administrator privileges to modify the interface:

```
import socket

# the public network interface
HOST = socket.gethostbyname(socket.gethostname())

# create a raw socket and bind it to the public interface
s = socket.socket(socket.AF_INET, socket.SOCK_RAW, socket.IPPROTO_IP)
s.bind((HOST, 0))

# Include IP headers
s.setsockopt(socket.IPPROTO_IP, socket.IP_HDRINCL, 1)

# receive all packages
s.ioctl(socket.SIO_RCVALL, socket.RCVALL_ON)

# receive a package
print(s.recvfrom(65565))

# disabled promiscuous mode
s.ioctl(socket.SIO_RCVALL, socket.RCVALL_OFF)
```

The next example shows how to use the socket interface to communicate to a CAN network using the raw socket protocol. To use CAN with the broadcast manager protocol instead, open a socket with:

```
socket.socket(socket.AF_CAN, socket.SOCK_DGRAM, socket.CAN_BCM)
```

After binding (CAN\_RAW) or connecting (CAN\_BCM) the socket, you can use the socket.send(), and the socket.recv() operations (and their counterparts) on the socket object as usual.

This last example might require special privileges:



import struct # CAN frame packing/unpacking (see 'struct can\_frame' in <linux/can.h>) can\_frame\_fmt = "=IB3x8s" can\_frame\_size = struct.calcsize(can\_frame\_fmt) def build\_can\_frame(can\_id, data): can\_dlc = len(data) data = data.ljust(8, b'\x00') return struct.pack(can\_frame\_fmt, can\_id, can\_dlc, data) def dissect can frame(frame): can\_id, can\_dlc, data = struct.unpack(can\_frame\_fmt, frame) return (can\_id, can\_dlc, data[:can\_dlc]) # create a raw socket and bind it to the 'vcan0' interface s = socket.socket(socket.AF\_CAN, socket.SOCK\_RAW, socket.CAN\_RAW) s.bind(('vcan0',)) while True: cf, addr = s.recvfrom(can\_frame\_size) print('Received: can\_id=%x, can\_dlc=%x, data=%s' % dissect\_can\_frame(cf)) try: s.send(cf) except OSError: print('Error sending CAN frame') try: s.send(build\_can\_frame(0x01, b'\x01\x02\x03')) except OSError: print('Error sending CAN frame')

Running an example several times with too small delay between executions, could lead to this error:

```
OSError: [Errno 98] Address already in use
```

This is because the previous execution has left the socket in a TIME\_WAIT state, and can't be immediately reused.

There is a socket flag to set, in order to prevent this, socket.SO REUSEADDR:

```
s = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
s.setsockopt(socket.SOL_SOCKET, socket.SO_REUSEADDR, 1)
s.bind((HOST, PORT))
```

the SO\_REUSEADDR flag tells the kernel to reuse a local socket in TIME\_WAIT state, without waiting for its natural timeout to expire.

**See also:** For an introduction to socket programming (in C), see the following papers:

- An Introductory 4.3BSD Interprocess Communication Tutorial, by Stuart Sechrest
- An Advanced 4.3BSD Interprocess Communication Tutorial, by Samuel J. Leffler et al,



information on the details of socket semantics. For Unix, refer to the manual pages; for Windows, see the WinSock (or Winsock 2) specification. For IPv6-ready APIs, readers may want to refer to **RFC 3493** titled Basic Socket Interface Extensions for IPv6.