Second Bus Topology

```
* -*- Mode:C++; c-file-style:"gnu"; indent-tabs-mode:nil; -*- */
* This program is free software; you can redistribute it and/or modify
* it under the terms of the GNU General Public License version 2 as
* published by the Free Software Foundation;
* This program is distributed in the hope that it will be useful,
* but WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
* GNU General Public License for more details.
* You should have received a copy of the GNU General Public License
* along with this program; if not, write to the Free Software
* Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
*/
#include "ns3/core-module.h"
#include "ns3/network-module.h"
#include "ns3/csma-module.h"
#include "ns3/internet-module.h"
#include "ns3/point-to-point-module.h"
#include "ns3/applications-module.h"
#include "ns3/ipv4-global-routing-helper.h"
#include "ns3/netanim-module.h"
#include "ns3/mobility-module.h"
// Default Network Topology
//
//
     10.1.1.0
// n0 ----- n1 n2 n3 n4
   point-to-point | | |
            =============
//
//
             LAN 10.1.2.0
using namespace ns3;
NS_LOG_COMPONENT_DEFINE ("SecondScriptExample");
main (int argc, char *argv[])
 bool verbose = true;
 uint32_t nCsma = 3;
 CommandLine cmd ( FILE );
 cmd.AddValue ("nCsma", "Number of \"extra\" CSMA nodes/devices", nCsma);
 cmd.AddValue ("verbose", "Tell echo applications to log if true", verbose);
```

```
cmd.Parse (argc,argv);
if (verbose)
  LogComponentEnable ("UdpEchoClientApplication", LOG_LEVEL_INFO);
  LogComponentEnable ("UdpEchoServerApplication", LOG_LEVEL_INFO);
nCsma = nCsma == 0 ? 1 : nCsma;
NodeContainer p2pNodes;
p2pNodes.Create (2);
NodeContainer csmaNodes;
csmaNodes.Add (p2pNodes.Get (1));
csmaNodes.Create (nCsma);
PointToPointHelper pointToPoint;
pointToPoint.SetDeviceAttribute ("DataRate", StringValue ("5Mbps"));
pointToPoint.SetChannelAttribute ("Delay", StringValue ("2ms"));
NetDeviceContainer p2pDevices;
p2pDevices = pointToPoint.Install (p2pNodes);
CsmaHelper csma;
csma.SetChannelAttribute ("DataRate", StringValue ("100Mbps"));
csma.SetChannelAttribute ("Delay", TimeValue (NanoSeconds (6560)));
NetDeviceContainer csmaDevices;
csmaDevices = csma.Install (csmaNodes);
InternetStackHelper stack;
stack.Install (p2pNodes.Get (0));
stack.Install (csmaNodes);
Ipv4AddressHelper address;
address.SetBase ("10.1.1.0", "255.255.255.0");
Ipv4InterfaceContainer p2pInterfaces;
p2pInterfaces = address.Assign (p2pDevices);
address.SetBase ("10.1.2.0", "255.255.255.0");
Ipv4InterfaceContainer csmaInterfaces;
csmaInterfaces = address.Assign (csmaDevices);
UdpEchoServerHelper echoServer (9);
ApplicationContainer serverApps = echoServer.Install (csmaNodes.Get (nCsma));
serverApps.Start (Seconds (1.0));
serverApps.Stop (Seconds (10.0));
UdpEchoClientHelper echoClient (csmaInterfaces.GetAddress (nCsma), 9);
echoClient.SetAttribute ("MaxPackets", UintegerValue (1));
```

```
echoClient.SetAttribute ("Interval", TimeValue (Seconds (1.0)));
 echoClient.SetAttribute ("PacketSize", UintegerValue (1024));
 ApplicationContainer clientApps = echoClient.Install (p2pNodes.Get (0));
 clientApps.Start (Seconds (2.0));
 clientApps.Stop (Seconds (10.0));
MobilityHelper mobility;
mobility.SetMobilityModel("ns3::ConstantPositionMobilityModel");
mobility.Install(csmaNodes);
AnimationInterface anim("second.xml");
AnimationInterface::SetConstantPosition(csmaNodes.Get(0),10,25);
AnimationInterface::SetConstantPosition(csmaNodes.Get(1),40,25);
AnimationInterface::SetConstantPosition(csmaNodes.Get(2),60,25);
AnimationInterface::SetConstantPosition(csmaNodes.Get(3),80,25);
anim.EnablePacketMetadata(true);
pointToPoint.EnablePcapAll("second");
 Ipv4GlobalRoutingHelper::PopulateRoutingTables ();
 pointToPoint.EnablePcapAll ("second");
 csma.EnablePcap ("second", csmaDevices.Get (1), true);
 Simulator::Run ();
 Simulator::Destroy ();
 return 0;
```