


Web 2.0

Lecture 5: Data Structures - Atom and AtomPub

doc. Ing. Tomáš Vitvar, Ph.D.

tomas@vitvar.com • @TomasVitvar • <http://vitvar.com>



Czech Technical University in Prague

Faculty of Information Technologies • Software and Web Engineering • <http://vitvar.com/courses/w20>




Evropský sociální fond
Praha & EU: investujeme do vaší budoucnosti

Modified: Tue Mar 21 2017, 15:56:31
Humla v0.3

Overview

- Overview of Formats and Protocols
- Atom Syndication Format
- AtomPub Protocol


Data on the Web



Data Syntax, Structure and Semantics


Semantic Web Layered Cake

syntax and formal semantics



Web Data Formats

syntax and semantics (structure)



Atom Standard


- A need for a standard syndication format
 - *machine-processable Web site content*
 - *Alternative to RSS*
 - *RSS spec does not say how to encode content, strings only ASCII-encoded, not clearly defined meaning of RSS elements, etc.*
 - *See RSS Flaws* [↗](#)
- IETF Atom Publishing Format and Protocol WG
 - *RFC 4287: Atom Syndication Format* [↗](#)
 - *RFC 5023: Atom Publishing Protocol* [↗](#)
- Adoption
 - *Google: Google Data Protocol (GData)*
 - *Microsoft: Open Data Protocol (ODP)*

Overview


- Overview of Formats and Protocols
- Atom Syndication Format
- AtomPub Protocol

Atom Syndication Format

Atom Feed Document



Atom Entry Document



- Two types of atom documents
 - *Atom Feed Document*
 - represents an atom feed, its metadata and some or all entries associated with it.
 - *Atom Entry Document*
 - represents exactly one entry, outside of context of

Atom Syndication Format

- Atom Feed Document Example

```
1  <?xml version="1.0" encoding="utf-8"?>
2  <feed xmlns="http://www.w3.org/2005/Atom">
3
4      <title>Example Feed</title>
5      <link href="http://example.org/" />
6      <updated>2003-12-13T18:30:02Z</updated>
7      <author>
8          <name>John Doe</name>
9      </author>
10     <id>urn:uuid:60a76c80-d399-11d9-b93C-0003939e0af6</id>
11
12     <entry>
13         <title>Example feed title</title>
14         <link href="http://example.org/2003/12/13/atom03" />
15         <id>urn:uuid:1225c695-cfb8-4ebb-aaaa-80da344efa6a</id>
16         <updated>2003-12-13T18:30:02Z</updated>
17         <summary>Some text</summary>
18     </entry>
19 </feed>
```


Atom Elements - Atom Feed

- Specification
 - *defined as XML information set, serialized as XML 1.0*
 - *must be well-formed, no DTD/Schema → no requirements to be valid.*
- **atom:feed** element
 - (*)*: zero or more occurrences – repeating fields
 - (?)*: zero or one occurrence – non-repeating fields
 - ()*: exactly one occurrence – non-repeating fields

```
1  atomFeed =
2      element atom:feed {
3          atomCommonAttributes,
4              (atomAuthor*
5                & atomCategory*
6                & atomContributor*
7                & atomGenerator?
8                & atomIcon?
9                & atomId
10               & atomLink*
11               & atomLogo?
12               & atomRights?
13               & atomSubtitle?
14               & atomTitle
15               & atomUpdated
16               & extensionElement*),
17          atomEntry*
18      }
```

Atom Elements - Atom Entry

- **atom:entry** element

()*: zero or more occurrences – repeating fields

(?): zero or one occurrence – non-repeating fields

(): exactly one occurrence – non-repeating fields


```
1  atomEntry =  
2      element atom:entry {  
3          atomCommonAttributes,  
4              (atomAuthor*  
5                  & atomCategory*  
6                  & atomContent?  
7                  & atomContributor*  
8                  & atomId  
9                  & atomLink*  
10                 & atomPublished?  
11                 & atomRights?  
12                 & atomSource?  
13                 & atomSummary?  
14                 & atomTitle  
15                 & atomUpdated  
16                 & extensionElement*)  
17     }
```

Pointers to other information

- URI identifier
 - *unique identification of*
 - *feed/entry id*
 - *author and contributor (person uri)*
 - *generator (uri)*
 - *category schema (uri), term (uri)**example:*

```
1 | <category scheme="http://example.org/dogs"  
2 |   term="http://example.org/dogs#basset"  
3 |   label="Basset"/>
```

Example category schema
URI: <http://example.org/dogs>



- Unambiguous identification of things using URIs

– *Helps interoperability can take advantage of wikipedia*

Atom Links

- Links to other Atom documents
 - *Atom defines simple link structure*
 - **type** defines content type
 - **rel** defines relation to this resource
 - *self, alternate, related, enclosure, via*
 - *standardized by IANA*
- Adoption by RESTful services
 - *Core for HATEOAS*
 - *Adopted in Link header, see Web Linking [🔗](#)*
 - *More details in [Lecture 4 - HATEOAS](#).*

Encoding Textual Content

- Plain text

```
1 | <title type="text">
2 |   Less: &lt;
3 | </text>
```

- *simple text, must not contain child elements*

- HTML


```
1 | <title type="html">
2 |   Less: &lt;em> &amp;lt; &lt;/em>
3 | </text>
```

- *html text, must not contain child elements*
 - *any markup must be escaped,*
 - *should be possible to display it as HTML inside*
<div> element

- XHTML

```
1 | <title type="xhtml" xmlns:x="http://www.w3.org/1999/xhtml">
2 |   <x:div>Less: <x:em> &amp;lt; </x:em></x:div>
3 | </text>
```

Aggregation



- Atom feed may include entries from another atom feed
 - these entries do not originally belong to this feed
- **source** element should contain at least:
 - required atom feed's metadata **id**, **title** and **updated**

Data and Time


- Notion of time
 - *Atom document is a snapshot of resource in some time*
 - **updated** (*feed, entry*) – *last update of the resource*
 - **published** (*entry*) – *initial creation of the first availability of the resource*
- Data format
 - *Examples:*

```
1 | <updated>2003-12-13</updated>  
2 | <updated>2003-12-13T18:30:02.25Z</updated>  
3 | <updated>2003-12-13T18:30:02.25+01:00</updated>
```

T – *time delimiter*

Z – *identifies UTC time (~GMT)*

Polling



- **updated** is the last updated time of the resource at the server
- *resource refresh interval is pre-defined by the*

Extensions

- Possible to combine various vocabularies
 - *through namespaces `xmlns` attribute, extensions of `link.rel` attribute*
- Example: GData (PicasaWeb, Docs, ...)
 - *combines vocabularies such as Geo location*

```
1  <?xml version='1.0' encoding='UTF-8'?>
2  <feed xmlns='http://www.w3.org/2005/Atom' xmlns:gml='http://www.opengis.net/gml'
3  xmlns:gphoto='http://schemas.google.com/photos/2007'
4  xmlns:georss='http://www.georss.org/georss'>
5      <id>http://picasaweb.google.com/.../albumid/5262593967320034641</id>
6      <updated>2010-02-25T20:47:53.295Z</updated>
7      <category
8          scheme='http://schemas.google.com/g/2005#kind'
9          term='http://schemas.google.com/photos/2007#album' />
10     <title type='text'>Památkově chráněný dům v Loukově</title>
11     <link rel='http://schemas.google.com/g/2005#feed' type='application/atom+xml'
12         href='http://picasaweb.google.com/.../albumid/5262593967320034641?hl=en_U'
13     <link rel='http://schemas.google.com/photos/2007#slideshow'
14         type='application/x-shockwave-flash'
15         href='https://picasaweb.google.com/s/c/bin/slideshow.swf?... ' />
16     <georss:where>
17         <gml:Point>
18             <gml:pos>50.5576865 15.0356436</gml:pos>
19         </gml:Point>
20     </georss:where>
21     <gphoto:allowPrints>true</gphoto:allowPrints>
22
```

Overview


- Overview of Formats and Protocols
- Atom Syndication Format
- AtomPub Protocol
 - *Extensions*

AtomPub Protocol


- Standard protocol for manipulation of resources
 - *Defines a service description by following constructs*
 - **service** – *a set of workspaces*
 - **workspace** – *a set of collections*
 - **collection** – *a set of resources*
 - *Defines protocol for editing, that is: creating (POST), updating (PUT), reading (GET), deleting (DELETE)*
- Relation to Atom Syndication Format
 - *Atom Feed and Atom Entry as resource representations*

AtomPub Elements

Types of Member Resources




AtomPub Service Description



- Collection properties and definition of constraints
 - **URI** – *id of the collection (Atom Feed)*
 - **categories** – *list of allowed categories in the collection*
 - **accept** – *list of Internet media types allowed in the*

Example Blogging Site Description

Conceptual structure of a blogging site



- Workspaces
 - *Main Site, Sidebar*
- Collections
 - *Blog entries, pictures, interesting links*


Example Blogging Site Description

```
1 <?xml version='1.0' encoding='UTF-8'?>
2 <service xmlns="http://www.w3.org/2007/app"
3   xmlns:atom="http://www.w3.org/2005/Atom">
4   <workspace>
5     <atom:title>Main Site</atom:title>
6     <collection href="http://example.org/blog/main">
7       <atom:title>Blog Entries</atom:title>
8       <categories
9         href="http://example.com/cats" />
10    </collection>
11    <collection href="http://example.org/blog/pic" >
12      <atom:title>Pictures</atom:title>
13      <accept>image/png</accept>
14      <accept>image/gif</accept>
15    </collection>
16  </workspace>
17  <workspace>
18    <atom:title>Sidebar</atom:title>
19    <collection href="http://example.org/blog/sidebar" >
20      <atom:title>Interesting Links</atom:title>
21      <accept>application/atom+xml;type=entry</accept>
22      <categories fixed="yes">
23        <atom:category
24          scheme="http://example.org/cats"
25          term="http://example.org/cats#joke" />
26        <atom:category
27          scheme="http://example.org/cats"
28          term="http://example.org/cats#serious" />
29      </categories>
30    </collection>
31  </workspace>
32 </service>
```

Protocol Operations


- Operations to manipulate resources
 - *Retrieving a service document (is obvious, GET)*
 - *Listing collection members (filtering and projections)*
 - *Creating a resource (entry and media)*
 - *Editing a resource (is obvious, PUT and DELETE)*
- AtomPub **does not define:**
 - *Any manipulation with*
 - *service documents, workspaces and collections*
 - *How service documents are discovered*

Creating Entry Resource



- *Server checks constraints of the collection*
- *Server may modify member representation*
 - *such as changes **id**, adds **updated** element*
- *if **Content-Location** is not equal to **Location** the request and response representation are not the same!*
- **ETag** should be used for
 - *conditional GET and PUT (see **lecture 4 - scalability**)*

Creating Media Resource



- *Server checks the constraints of the collection*
 - may return **415 Unsupported Media Type** if not accepted
- *Media Link Entry is an Entry resource that describes metadata about media resource (such as a picture)*

Listing Collection

- Must provide representation in Atom Feed
- Contains list of Atom **Entry** elements
 - *must have **link** with attribute **edit***
 - *must have **edited**, order of entries by this date*
 - *is not the same as **Last-Modified** header*
- Entries in collection are not full representations
 - *clients should retrieve them using GET on entry URI*
- To limit amount of entries
 - *links with semantics for navigation through the whole list*

```
1 | <feed xmlns="http://www.w3.org/2005/Atom">
2 |   <link rel="first" href="http://example.org/blog/main/"
```

Overview

- Overview of Formats and Protocols
- Atom Syndication Format
- AtomPub Protocol
 - *Extensions*

Extensions

- OpenSearch
 - *Specification: OpenSearch* [↗](#)
 - *Search service description and search results*
- Google Data Protocol
 - *Filtering, partial response and partial update*
 - *Entity tag attribute for **<feed>** and **<entry>** elements*
 - *HTTP methods overriding*

OpenSearch

- Open Search Specification
 - **Open Search Description Document (OSDD)**
→ *description of a search service*
 - **OpenSearch Response Document**
→ *Standard description of search results by search services*
→ *extension of syndication formats, RSS and Atom*
- Adoption
 - *Browsers such as IE, Google Chrome – search engines you can use to search various sites.*
 - *APIs such as Bing API, Google Docs, etc. – description of search results.*

OpenSearch Description Document

- Example:

```
1  <?xml version="1.0" encoding="UTF-8"?>
2  <OpenSearchDescription xmlns="http://a9.com/-/spec/opensearch/1.1/">
3    <ShortName>Web Search</ShortName>
4    <Description>Use Example.com to search the Web.</Description>
5    <Tags>example web</Tags>
6    <Contact>admin@example.com</Contact>
7    <Url type="application/atom+xml"
8        template="http://example.com/?q={searchTerms}&pw={startPage?}&format
9    <Url type="application/rss+xml"
10       template="http://example.com/?q={searchTerms}&pw={startPage?}&format
11    <Url type="text/html"
12       template="http://example.com/?q={searchTerms}&pw={startPage?}" />
13    <Image height="64" width="64" type="image/png">
14       http://example.com/websearch.png
15    </Image>
16    <Query role="example" searchTerms="cat" />
17    <Developer>Example.com Development Team</Developer>
18    <AdultContent>>false</AdultContent>
19    <Language>en-us</Language>
20    <OutputEncoding>UTF-8</OutputEncoding>
21    <InputEncoding>UTF-8</InputEncoding>
22  </OpenSearchDescription>
```

– **searchTerms** *is a free text*

OpenSearch Response Document

- Example:
 - *Result in Atom format of a search query*

```
1  <?xml version="1.0" encoding="UTF-8"?>
2  <feed xmlns="http://www.w3.org/2005/Atom"
3      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
4      <title>Example.com Search: New York history
5      <updated>2003-12-13T18:30:02Z</updated>
6      <author>
7          <name>Example.com, Inc.</name>
8      </author>
9      <id>urn:uuid:60a76c80-d399-11d9-b93C-0003939e0af6</id>
10     <opensearch:totalResults>4230000</opensearch:totalResults>
11     <opensearch:startIndex>21</opensearch:startIndex>
12     <opensearch:itemsPerPage>10</opensearch:itemsPerPage>
13     <opensearch:Query role="request" searchTerms="New York History" />
14     ...
15     <link rel="search" type="application/opensearchdescription+xml"
16         href="http://example.com/opensearchdescription.xml"/>
17     <entry>
18         <title>New York History</title>
19         ...
20     </entry>
21 </feed>
22
```

GData Protocol: Advanced Search

Query

- OpenSearch does not specify syntax for search query

- *It can be anything, free text*
- *GData Protocol further allows for filtering and projection*

- Filtering

- *Fine-grained conditions based on values of various elements*
 - *such as author, category, max-results, min and max of published and updated elements.*

- 1 `http://www.example.com/feeds/jo?q=Darcy&updated-min=2005-04-19T15:30:00Z`
- 2 `http://www.example.com/feeds?category=Fritz%7CLaurie` // URL encoded OR
- 3 `http://www.example.com/feeds?category=Fritz,CLaurie` // AND

- Partial Response (~Projection)

- *Which elements of an entry should appear in the search result*
- *A language based on XPath syntax (subset of a valid*

GData Protocol: Partial Update

- **PATCH** HTTP Method
 - *IETF specification, see PATCH Method for HTTP [↗](#)*
 - *Add, modify or delete selected elements of an entry*
- Examples
 - *To delete a description element and add a new title element*
 - **gd:fields** *uses partial response syntax*

```
1 PATCH /myFeed/1/1/
2 Content-Type: application/xml
3
4 <entry xmlns='http://www.w3.org/2005/Atom'
5       xmlns:gd='http://schemas.google.com/g/2005'
6       gd:fields='description'>
7   <title>New title</title>
8 </entry>
```

- Rules
 - *Fields not already present are added*
 - *Non-repeating fields already present are updated*
 - *Repeating fields already present are appended*

GData Protocol: Entity Tags

- Resource Versioning
 - *Conditional GET and PUT (concurrency control)*
 - See *Lecture 4 - scalability*
 - *Etagas on atom and entry elements*

- Example

```
1  GData-Version: 2.0
2  ETag: W/"C0QBRXcycSp7ImA9WxRVFuk."
3  ...
4  <?xml version='1.0' encoding='utf-8'?>
5  <feed xmlns='http://www.w3.org/2005/Atom'
6      xmlns:gd='http://schemas.google.com/g/2005'
7      gd:etag='W/"C0QBRXcycSp7ImA9WxRVFuk."'>
8      ...
9      <entry gd:etag=' "CUUEQX47eCp7ImA9WxRVEkQ." '>
10         ...
11         </entry>
12     </feed>
13
```

- *It is possible to do a conditional GET/PUT on the entry by using the ETag "CUUEQX47eCp7ImA9WxRVEkQ."*

GData Protocol: HTTP Methods

Overriding

- Firewall restrictions
 - *Some firewall configurations do not allow to send HTTP request other than GET and POST*
- HTTP methods overriding through **POST**

X-HTTP-Method-Override: PUT

X-HTTP-Method-Override: DELETE

X-HTTP-Method-Override: PATCH

- Example

```
1 POST /myfeed/1/1/
2 X-HTTP-Method-Override: PATCH
3 Content-Type: application/xml
4 ...
```