

Web 2.0

Lecture 1: Introduction to JavaScript

doc. Ing. Tomáš Vitvar, Ph.D.
tomas@vitvar.com • @TomasVitvar • http://vitvar.com



Czech Technical University in Prague
Faculty of Information Technologies • Software and Web Engineering • <http://vitvar.com/courses/w20>




Univerzita Karlova v Praze
Práva & EU (rozšíření do veřejného sektoru)

Modified: Fri Mar 17 2017, 12:53:26
Humla v0.3


Web 2.0 Application Architecture

Web Application

client-side technologies for
presentation and user
interactions



Web 2.0 Application



JavaScript

- Lightweight, interpreted, object-oriented language
- Standard
 - *All major browsers support ECMAScript 6 and 7*
- Major characteristics
 - *First-class functions*
 - *functions as first-class citizens*
 - *language supports: passing functions as arguments to other functions, returning functions as values from other functions, assigning functions to variables or storing them in data structures.*
 - *Anonymous functions*
 - *declared without any named identifier to refer to it*
 - *Closures*

Lecture 1: Introduction to JavaScript, CTU Summer Semester 2016/2017, @TomasVilvar

– 3 –

Overview

- **JavaScript Basics**
- Server-side JavaScript

Lecture 1: Introduction to JavaScript, CTU Summer Semester 2016/2017, @TomasVilvar

– 4 –

Objects and Arrays

- Objects and Arrays

```
1 // objects - key/value pairs
2 var obj = { name: "Tomas", main-city : "Innsbruck", value : 3 };
3 obj.name = "Peter"; // assign the name property another value
4 obj["main-city"] = "Prague"; // another way to access object's values; it's not an array!
5
6 // arrays
7 var a = ["Tomas", "Peter", "Alice"];
8 for (var i = 0; i < a.length; i++)
9     // do something with a[i]
10
11 // combinations of arrays and objects
12 var obj_a = [
13     { name: "Tomas", city: "Innsbruck" },
14     { name: "Peter", city: "Prague" },
15     { name: "Alice", cities: ["Prague", "Brno"] } ];
16
17 for (var i = 0; i < obj_a.length; i++)
18     // do something with obj_a[i].name, ...
```

- Functions

```
1 // assign a function to a variable
2 var minus = function(a, b) {
3     return a - b;
4 }
5
6 // call the function;
7 // now you can pass 'minus' as a parameter to another function
8 var r2 = minus(6, 4);
```

Functions

- Function Callbacks

– You can use them to handle asynchronous events occurrences

```
1 // function returns the result through a callback, not directly;
2 // this is not a non-blocking I/O, just demonstration of the callback
3 function add(a, b, callback) {
4     callback(a + b);
5 }
6
7 // assign the callback to a variable
8 var print = function(result) {
9     console.log(result);
10 };
11
12 // call the function with callback as a parameter
13 add(7, 8, print);
```

- Functions as values in object

```
1 var obj = {
2     data : [2, 3, "Tomas", "Alice", 4 ],
3
4     getIndexdOf : function(val) {
5         for (var i = 0; i < this.data.length; i++)
6             if (this.data[i] == val)
7                 return i;
8         return -1;
9     }
10 }
11
12 obj.getIndexOf(3); // will return 1
```

Closures

- Closures

– A function value that references variables from outside its body

```
1  function adder() {  
2      sum = 0;  
3      return function(x) {  
4          sum += x;  
5          return sum;  
6      }  
7  }  
8  
9  var pos = adder();  
10  
11 console.log(pos(3)); // returns 3  
12 console.log(pos(4)); // returns 7  
13 console.log(pos(5)); // returns 12
```

Overview

- JavaScript Basics
- Server-side JavaScript

Recall: Application Server


- Environment that runs an application logic
 - Client communicates with AS via an application protocol
 - Client – Browser, application protocol – HTTP
- Terminology
 - Application Server × Web Server × HTTP Server
 - AS is a modular environment; provides technology to realize enterprise systems
 - AS contains a Web server/HTTP server
 - We will deal with Web server only
- Two major models to realize communication
 - Blocking I/O (also called synchronous I/O)
 - Non-blocking I/O (also called asynchronous I/O)
- A technology we will look at

Lecture 1: Introduction to JavaScript, CTU Summer Semester 2016/2017, @TomasVitvar

– 9 –

Non-Blocking I/O Model

- Connections maintained by the OS, not the Web app
 - The Web app registers events, OS triggers events when occur



- Characteristics
 - Event examples: new connection, read, write, closed
 - The app may create working threads, but controls the number!
 - much less number of working threads as opposed to blocking I/O

Lecture 1: Introduction to JavaScript, CTU Summer Semester 2016/2017, @TomasVitvar

– 10 –

Node.js

- Node.js [↗](#)
 - Web server technology, very efficient and fast!
 - Event-driven I/O framework, based on JavaScript V8 engine
 - Any I/O is non-blocking (it is asynchronous)
 - One worker thread to process requests
 - You do not need to deal with concurrency issues
 - More threads to realize I/O
 - Open sourced, @GitHub [↗](#), many libraries [↗](#)
 - Future platform for Web 2.0 apps
- Every I/O as an event
 - reading and writing from/to files
 - reading and writing from/to sockets

```
1 // pseudo code; ask for the last edited time of a file
2 stat( 'somefile', function( result ) {
3   // use the result here
4 } );
```

HTTP Server in Node.js

- HTTP Server implementation
 - server running at 138.232.189.127, port 8080.

```
1 // http library
2 var http = require("http");
3
4 http.createServer(function(req, res) {
5   // check the value of host header
6   if (req.headers.host == "company.cz") {
7     res.writeHead(201, "Content-Type: text/plain");
8     res.end("This is the response...");
9   } else ;
10   // handle enterprise.com app logic...
11 }).listen('0.0.0.0', 8080);
```

– Test it using Telnet

```
1 telnet 138.232.189.127 8080
2 # ...lines omitted due to brevity
3 GET /orders HTTP/1.1
4 Host: company.cz
5
6 HTTP/1.1 201 OK
7 Content-Type: plain/text
8
9 This is the response...
```

Google Apps Script

- Google Apps Script
 - JavaScript cloud scripting language
 - easy ways to automate tasks across Google products and third party services
- You can
 - Automate repetitive processes and workflows
 - Link Google products with third party services
 - Create custom spreadsheet functions
 - Build rich graphical user interfaces and menus

```
1 // create spreadsheet menu
2 function onOpen() {
3   var ss = SpreadsheetApp.getActiveSpreadsheet();
4   var menuEntries = [ {name: "Say Hi", functionName: "sayHi"},
5                       {name: "Say Hello", functionName: "sayHello"} ];
6   ss.addMenu("Tutorial", menuEntries);
7 }
8
9 function sayHi() {
10  Browser.msgBox("Hi");
11 }
12
13 function sayHello() {
14  Browser.msgBox("Hello");
15 }
```

Lecture 1: Introduction to JavaScript, CTU Summer Semester 2016/2017, @TomasVitvar

– 13 –

Rhino

- Rhino
 - open-source implementation of JavaScript written entirely in Java
 - managed by the Mozilla Foundation
 - also provides another implementation of JavaScript engine written in C named SpiderMonkey
 - typically embedded into Java applications to provide scripting to end users
 - core language only and doesn't contain objects or methods for manipulating HTML documents
 - enabling development of webapps with JavaScript in containers like Jetty, Tomcat, and Google AppEngine

```
1 $ cat echo.js
2 for (i in arguments) {
3   print(arguments[i])
4 }
5 $ java org.mozilla.javascript.tools.shell.Main echo.js foo bar
6 foo
7 bar
8 $
```

Lecture 1: Introduction to JavaScript, CTU Summer Semester 2016/2017, @TomasVitvar

– 14 –