

Web 2.0

Lecture 3: REST Architecture 2

doc. Ing. Tomáš Vitvar, Ph.D.

tomas@vitvar.com • @TomasVitvar • <http://vitvar.com>



Czech Technical University in Prague

Faculty of Information Technologies • Software and Web Engineering • <http://vitvar.com/courses/w20>




Modified: Sun Feb 25 2018, 23:22:52
Humla v0.3

Overview

- **Uniform Interface**
 - *Basic operations*
 - *Handling Errors*
 - *Advanced Design Issues*
- Selected Protocols
- Selected Extensions

Uniform Interface

- Uniform interface = finite set of operations
 - Resource manipulation
 - *CRUD* – Create (*POST/PUT*), Read (*GET*), Update (*PUT/PATCH*), Delete (*DELETE*)
 - operations are not domain-specific
 - For example, **GET /orders** and not **getOrders()**
 - This reduces complexity when solving interoperability
- Integration issues examples



Safe and Unsafe Operations

- Safe operations
 - Do not change the resource state
 - Usually "read-only" or "lookup" operation
 - Clients can cache the results and refresh the cache freely
- Unsafe operations
 - May change the state of the resource
 - Transactions such as buy a ticket, post a message
 - Unsafe does not mean dangerous!
- Unsafe interactions and transaction results
 - **POST** response may include transaction results
 - you buy a ticket and submit a purchase data
 - you get transaction results
 - and you cannot bookmark this..., why?
 - Should be referable with a persistent URI

Idempotence

- Idempotent operation
 - *Invoking a method on the same resource always has the same effect*
 - Operations **GET**, **PUT**, **DELETE**
- Non-idempotent operation
 - *Invoking a method on the same resource may have different effects*
 - Operation **POST**
- Effect = a state change
 - *recall the effect definition in MDW*

Overview

- Uniform Interface
 - *Basic operations*
 - *Handling Errors*
 - *Advanced Design Issues*
- Selected Protocols
- Selected Extensions

GET

- Reading

- **GET** *retrieves a representation of a state of a resource*
 - > GET /orders HTTP/1.1
 - > Accept: application/xml
 - < HTTP/1.1 200 OK
 - < Content-Type: application/xml
 - <
 - < ...resource representation in xml...
- *It is read-only operation*
- *It is **safe***
- *It is **idempotent***
- **GET** *retrieves different states over time but the effect is always the same, cf. **resource state** hence it is idempotent.*
- *Invocation of **GET** involves content negotiation*

PUT

- Updating or Inserting

- **PUT** *updates or inserts a representation of a state of a resource*
- *Updating the resource is a **complete replacement of the resource***
 - > PUT /orders/4456 HTTP/1.1
 - > Content-Type: application/xml
 - >
 - > <order>...</order>
 - < HTTP/1.1 CODE
- *where **CODE** is:*
 - **200 OK** or **204 No Content** *for updating: A resource with id **4456** exists, the client sends an updated resource*
 - **201 Created** *for inserting: A resource **does not exist**, the client generates the id **4456** and sends a representation of it.*
- *It is **not safe** and it is **idempotent***

PATCH

- **PATCH** to partial update a resource
 - IETF specification, see *PATCH Method for HTTP* [↗](#)
 - Use in GData Protocol
 - To add, modify or delete selected elements of an Atom feed entry
 - Example to delete a description element and add a new title element
 - gd:fields** uses the partial response syntax
- ```
1 PATCH /myFeed/1/1/
2 Content-Type: application/xml
3
4 <entry xmlns='http://www.w3.org/2005/Atom'
5 xmlns:gd='http://schemas.google.com/g/2005'
6 gd:fields='description'>
7 <title>New title</title>
8 </entry>
```
- Rules
    - Fields not already present are added
    - Non-repeating fields already present are updated
    - Repeating fields already present are appended

# POST

- Inserting
    - **POST** inserts a new resource
    - A server generates a new resource ID, client only supplies a content and a resource URI where the new resource will be inserted.
- ```
> POST /orders HTTP/1.1
> Content-Type: application/xml
>
> <order>...</order>

< HTTP/1.1 201 Created
< Location: /orders/4456
```
- It is **not safe** and it is **not idempotent**
 - A client may "suggest" a resource's id using the **Slug** header
 - Defined in AtomPub protocol [↗](#)

DELETE

- Deleting
 - **DELETE** *deletes a resource with specified URI*
 - > `DELETE /orders/4456 HTTP/1.1`
 - < `HTTP/1.1 CODE`
 - *where CODE is:*
 - **200 OK**: *the response body contains an entity describing a result of the operation.*
 - **204 No Content**: *there is no response body.*
 - *It is **not safe** and it is **idempotent***
 - *Multiple invocation of **DELETE /orders/4456** has always the same effect – the resource **/orders/4456** does not exist.*

Other

- HEAD
 - *same as **GET** but only retrieves HTTP headers*
 - *It is **safe** and **idempotent***
- OPTIONS
 - *queries the resource for resource configuration*
 - *It is **safe** and **idempotent***

Overview

- Uniform Interface
 - *Basic operations*
 - *Handling Errors*
 - *Advanced Design Issues*
- Selected Protocols
- Selected Extensions

Types of Errors

- Client-side – status code **4xx**
 - **400 Bad Request**
 - *generic client-side error*
 - *invalid format, such as syntax or validation error*
 - **404 Not Found**
 - *server can't map URI to a resource*
 - **401 Unauthorized**
 - *wrong credentials (such as user/pass, or API key)*
 - *the response contains **WWW-Authenticate** indicating what kind of authentication the service accepts*
 - **405 Method Not Allowed**
 - *the resource does not support the HTTP method the client used*
 - *the response contains **Allow** header to indicate methods it supports*
 - **406 Not Acceptable**
 - *so many restrictions on acceptable content types (using **Accept-***)*
 - *server cannot serialize the resource to requested content types*

Types of Errors (Cont.)

- Server-side – status code **5xx**
 - **500 Internal Server Error**
 - *generic server-side error*
 - *usually not expressive, logs a message for system admins*
 - **503 Service Not Available**
 - *server is overloaded or is under maintenance*
 - *the response contains **Retry-After** header*

Use of Status Codes

- Service should respect semantics of status codes!
 - > GET /orders HTTP/1.1
 - > Accept: application/json
 - < HTTP/1.1 200 OK
 - < Content-Type: application/json
 - < { "error" :
 - < { "error_text" :
 - < "you do not have rights to access this resource " }
 - < }
- *Client must understand the semantics of the response.*
- *This breaks loose coupling and reusability service principles*
- *The response should be:*
 - < HTTP/1.1 401 Unauthorized
 - < ...
 - < ...optional text describing the error...

Overview

- Uniform Interface
 - *Basic operations*
 - *Handling Errors*
 - *Advanced Design Issues*
- Selected Protocols
- Selected Extensions

Respect HTTP Semantics

- Do not overload semantics of HTTP methods
 - *For example, GET is read-only method and idempotent*
 - *REST Anti-pattern:*
 - `GET /orders/?add=new_order`
 - *This is not REST!*
 - *This breaks both safe and idempotent principles*
- Consequences
 - *Result of GET can be cached by proxy servers*
 - *They can revalidate their caches freely*
 - *You can end up with new entries in your storage without you knowing!*
- The same is true for other methods

Change Order Status

- **status** property of **/orders/{order-id}** resource
 - *reflects a state of the process*
 - *No need to use a stateful service, state is communicated through the order representation*
- How do you implement a canceling an order?
 - *You can delete it using **DELETE***
 - *But you may want to cancel it in order to:*
 - *maintain a list of canceled orders*
 - *have a possibility to "roll-back" canceled orders*

DELETE to cancel

- A bad solution to cancel the order
 - *to cancel with **DELETE***
 - DELETE /orders/3454/?cancel=true**
 - *you overload the meaning of **DELETE***
 - *you violate the uniform interface principle*
- Always ask a question:
 - *Is the operation a state of the resource?*
 - *if yes, the operation should be:*
 - *modeled within the data format*
 - *or as a separated resource (sub-resource)*
- No verbs in **path** and **query** components!
 - */cancelOrder, /orders/{order-id}/?action=delete, etc.*
 - *Verbs in URIs indicate that a resource is actually an operation!*

PUT to cancel

- A RESTful solution to cancel an order

1. *first, have an order's status*
 - as part of the *Order representation format*
 - we extend "open" and "close" with "cancel"
2. *Use PUT to cancel an order*

```
1 > PUT /orders/{order-id}
2 > Content-Type: application/json
3 >
4 > { "status" : "cancel" }
5
6 < HTTP/1.1 204 No Content
```

- Clean-up all cancelled orders

- you can have a resource "all valid orders": **/orders/valid**
(~ all orders that are not canceled)
 - **GET /orders/valid** will return all non-canceled orders
 - **POST /orders/valid** will purge all cancelled orders


Overview

- Uniform Interface
- Selected Protocols
 - *Caching and Revalidation*
 - *Concurrency Control*
- Selected Extensions

Scalability

- Need for scalability
 - *Huge amount of requests on the Web every day*
 - *Huge amount of data downloaded*
- Some examples
 - *Google, Facebook: 5 billion API calls/day*
 - *Twitter: 3 billions of API calls/day (75% of all the traffic)*
 - *50 million tweets a day*
 - *eBay: 8 billion API calls/month*
 - *Bing: 3 billion API calls/month*
 - *Amazon WS: over 100 billion objects stored in S3*
- Scalability in REST
 - *Caching and revalidation*
 - *Concurrency control*

Caching



- Your service should cache:
 - *anytime there is a static resource*
 - *even there is a dynamic resource*
 - *with chances it updates often*
 - *you can force clients to always revalidate*
- three steps:
 - *client GETs the resource representation*
 - *server controls how it should cache through **Cache-Control** header*
 - *client revalidates the content via conditional GET*

Cache Headers

- **Cache-Control** response header
 - controls over local and proxy caches
 - **private** – no proxy should cache, only clients can
 - **public** – any intermediary can cache (proxies and clients)
 - **no-cache** – the response should not be cached. If it is cached, the content should always be revalidated.
 - **no-store** – can cache but should not store persistently. When a client restarts, content is lost
 - **no-transform** – no transformation of cached data; e.g. compressions
 - **max-age**, **s-maxage** a time in seconds how long the cache is valid; **s-maxage** for proxies
- **Last-Modified** and **ETag** response headers
 - Content last modified date and a content entity tag
- **If-Modified-Since** and **If-None-Match** request headers
 - Content revalidation (conditional GET)

Example Date Revalidation

- Cache control example:

```
> GET /orders HTTP/1.1
> ...

< HTTP/1.1 200 OK
< Content-Type: application/xml
< Cache-Control: private, no-store, max-age=200
< Last-Modified: Sun, 7 Nov 2011, 09:40 CET
<
< ...data...
```

 - only client can cache, must not be stored on the disk, the cache is valid for 200 seconds.
- Revalidation (conditional GET) example:
 - A client revalidates the cache after **200** seconds.

```
> GET /orders HTTP/1.1
> If-Modified-Since: Sun, 7 Nov 2011, 09:40 CET

< HTTP/1.1 304 Not Modified
< Cache-Control: private, no-store, max-age=200
< Last-Modified: Sun, 7 Nov 2011, 09:40 CET
```

Entity Tags

- Signature of the response body
 - A hash such as MD5
 - A sequence number that changes with any modification of the content
- Types of tag
 - Strong ETag: reflects the content bit by bit
 - Weak ETag: reflects the content "semantically"
 - The app defines the meaning of its weak tags
- Example content revalidation with ETag

```
< HTTP/1.1 200 OK
< Cache-Control: private, no-store, max-age=200
< Last-Modified: Sun, 7 Nov 2011, 09:40 CET
< ETag: "4354a5f6423b43a54d"

> GET /orders HTTP/1.1
> If-None-Match: "4354a5f6423b43a54d"

< HTTP/1.1 304 Not Modified
< Cache-Control: private, no-store, max-age=200
< Last-Modified: Sun, 7 Nov 2011, 09:40 CET
< ETag: "4354a5f6423b43a54d"
```

Design Suggestions

- Composed resources use weak ETags
 - For example **/orders**
 - a composed resource that contains a summary information
 - changes to an order's items will not change semantics of **/orders**
 - It is usually not possible to perform updates on these resources
- Non-composed resources use strong ETags
 - For example **/orders/{order-id}**
 - They can be updated
- Further notes
 - Server should send both **Last-Modified** and **ETag** headers
 - If client sends both **If-Modified-Since** and **If-None-Match**, **ETag** validation takes preference

Weak ETag Example

- App specific, **/orders** resource example

```
1  {
2    "orders" :
3    [
4      { "id"      : 2245,
5        "customer" : "Tomas",
6        "descr"    : "Stuff to build a house.",
7        "items"    : [...] },
8      { "id"      : 5546,
9        "customer" : "Peter",
10       "descr"    : "Things to build a pipeline.",
11       "items"    : [...] }
12    ]
13  }
```

- Weak ETag compute function example


– Any modification to an order's items is not significant for **/orders**:

```
1  var crypto = require("crypto");
2
3  function computeWeakETag(orders) {
4    var content = "";
5    for (var i = 0; i < orders.length; i++)
6      content += orders[i].id + orders[i].customer + orders[i].descr;
7    return crypto.createHash('md5').update(content).digest("hex");
8  }
```

Weak ETag Revalidation

- Updating **/orders** resource

– **POST /orders/{order-id}** inserts a new item to an order
– Any changes to orders' items will not change the Weak ETag



Overview


- Uniform Interface
- Selected Protocols
 - *Caching and Revalidation*
 - *Concurrency Control*
- Selected Extensions

Concurrency

- Two clients may update the same resource
 - 1) a client GETs a resource **GET /orders/5545**
 - 2) the client modifies the resource
 - 3) the client updates the resource via **PUT /orders/5545 HTTP/1.1**

What happens if another client updates the resource between 1) and 3) ?
- Concurrency control
 - Conditional **PUT**
 - *Update the resource only if it has not changed since a specified date or a specified ETag matches the resource content*
 - **If-Unmodified-Since** and **If-Match** headers
 - Response to conditional **PUT**:
 - **200 OK** if the **PUT** was successful
 - **412 Precondition Failed** if the resource was updated in the meantime.

Concurrency Control Protocol



- Conditional PUT and ETags
 - *Conditional PUT must always use strong entity tags or date validation*

Overview

- Uniform Interface
- Selected Protocols
- Selected Extensions

GData Protocol: Entity Tags

- Resource Versioning
 - *Conditional GET and PUT (concurrency control)*
 - *Etags on atom and entry elements*

- Example

```
1  GData-Version: 2.0
2  ETag: W/"C0QBRXcycSp7ImA9WxRVFuk."
3  ...
4  <?xml version='1.0' encoding='utf-8'?>
5  <feed xmlns='http://www.w3.org/2005/Atom'
6      xmlns:gd='http://schemas.google.com/g/2005'
7      gd:etag='W/"C0QBRXcycSp7ImA9WxRVFuk."'>
8      ...
9      <entry gd:etag='CUUEQX47eCp7ImA9WxRVEkQ.'">
10         ...
11     </entry>
12 </feed>
```

- *It is possible to do a conditional GET/PUT on the entry by using the ETag "CUUEQX47eCp7ImA9WxRVEkQ."*

GData Protocol: HTTP Methods Overriding

- Firewall restrictions
 - *Some firewall configurations do not allow to send HTTP request other than GET and POST*
- HTTP methods overriding through **POST**

X-HTTP-Method-Override: PUT
X-HTTP-Method-Override: DELETE
X-HTTP-Method-Override: PATCH

- Example

```
1  POST /myfeed/1/1/
2  X-HTTP-Method-Override: PATCH
3  Content-Type: application/xml
4  ...
```