

Web 2.0

Lecture 5: Accessing and Utilizing Services

doc. Ing. Tomáš Vitvar, Ph.D.

tomas@vitvar.com • @TomasVitvar • <http://vitvar.com>



Czech Technical University in Prague

Faculty of Information Technologies • Software and Web Engineering • <http://vitvar.com/courses/w20>



Evropský sociální fond
Praha & EU: Investujeme do vaší budoucnosti

Modified: Sun Feb 25 2018, 23:22:52
Humla v0.3

Overview

- Mashups and XHR
- Security Mechanisms
- JSON and JSONP

Mashups

- Web application hybrid/Web 2.0 application
 - *Uses APIs of two or more applications to provide new value-added functionality*
- Types
 - *Data mashup – integration/aggregation of data (read only)*
 - *Service mashup – more sophisticated workflows (read, write)*
 - *Visualization – involves UI, e.g., third-party data displayed on the Google map*
- Client-Server View
 - *client-side mashups (mainly in a browser)*
 - *JavaScript, Dynamic HTML, AJAX, JSON/JSONP*
 - *server-side mashups*
 - *server-side integration of services and data*
 - *third-party programming languages*
 - *specialized environments: Google AppsScript*
- **Web Apps developments will all be about mashups!**

XMLHttpRequest (XHR)

- Interface to utilize HTTP protocol in JavaScript
 - *standardized by Web Applications WG [↗](#) at W3C*
 - *basis for AJAX*
 - *Asynchronous JavaScript and XML*
- Typical usage
 1. *Browser loads a page that includes a script*
 2. *User clicks on a HTML element*
 - *it triggers a JavaScript function*
 3. *The function invokes a service through XHR*
 - *same origin policy, cross-origin resource sharing*
 4. *The function receives data and modifies HTML in the page*

XHR Interface – Key Methods and Properties

- Method and properties of XHR object
 - **open**, *opens the request, parameters:*
 - method** – *method to be used (e.g. GET, PUT, POST),*
 - url** – *url of the resource,*
 - asynch** – *true to make asynchronous call,*
 - user, pass** – *credentials for authentication.*
 - **onReadyStateChange** – *JavaScript function object, it is called when **readyState** changes (uninitialized, loading, loaded, interactive, completed).*
 - **send, abort** – *sends or aborts the request (for asynchronous calls)*
 - **status, statusText** – *HTTP status code and a corresponding text.*
 - **responseText, responseXML** – *response as text or as a DOM document (if possible).*
 - **onload** – *event listener to support server push.*
- See XMLHttpRequest (W3C) [🔗](#), or XMLHttpRequest (Mozilla reference) [🔗](#) for a complete reference.

How XHR works


HTML with JavaScript code

was loaded as a response to `http://prague.example.org/`

```
...  
<input type="button" value="Show Prague!" onclick="click()" />  
  
<script type="text/javascript">  
  
xhr = new XMLHttpRequest();  
  
function click() {  
  xhr.open("GET", "http://prague.example.org/api/data", true);  
  xhr.onreadystatechange = stateChanged;  
  xhr.send();  
}  
  
function stateChanged() {  
  if (xhr.readyState == 1) { // loading  
    ...  
  }  
  if (xhr.readyState == 2) { // loaded  
    ...  
  }  
  if (xhr.readyState == 3) { // interactive  
    ...  
  }  
  if (xhr.readyState == 4) { // completed  
    ...  
  }  
}  
}  
</script>
```

Browser


Resource at
`http://prague.example.org/
api/data`



Overview

- Mashups and XHR
- **Security Mechanisms**
 - *Scripting Attacks*
 - *Cross-origin Resource Sharing Protocol (CORS)*
- JSON and JSONP


Same Origin Policy



- JavaScript code can only access resources on the same domain
 - *XHR to GET, POST, PUT, UPDATE, DELETE*
 - Browsers apply **same origin policy**
- Solutions
 - *JSON and JSONP (GET only)*
 - *Cross-origin Resource Sharing Protocol (CORS)*

Why Same Origin Policy?

- Without the same origin policy, the following POST would be possible



Overview


- Mashups and XHR
- Security Mechanisms
 - *Scripting Attacks*
 - *Cross-origin Resource Sharing Protocol (CORS)*
- JSON and JSONP

Overview

- Scripting Attacks
 - *Intruders make users perform action that has side effects on their resources*
 - *Intruders inject malicious code to Web pages*
- Roles in Security Scenarios
 - *Alice, Bob*
 - *Normal users, usually Alices wants to send a message to Bob or Alice accesses a Bob's site.*
 - *Eve*
 - *A user with bad intentions, usually a passive attacker.*
 - *Mallory*
 - *An active attacker, usually sends a link to a page with malicious code.*

Recall: State management in HTTP

- Request-response interaction with cookies
 - *Session is a logical channel maintained by the server*



- Stateful Server
 - *Server remembers the session information in a server memory*
 - *Server memory is a non-persistent storage, when server restarts the memory content is lost!*


Cross-site Request Forgery (CSRF)

- Exploits a trust of a website in a user's browser
- Scenario
 1. *Mallory sends a link to Alice (in an email, in a chat, etc.)*
 - *The link points to a page that has HTML code with hrefs to Alice's private resources*
 - *For example, to perform an action on Alice's account, it is possible to use `img` like this:*

```
1 | 
```
 2. *Alice loads the page in her browser*
 - *Alice is authenticated to the bank's website, the browser sends Alice's authentication cookies with the request.*
- Issues and Prevention
 - *The bank site violates REST, i.e. overloading of GET for making actions*
 - *The bank should check HTTP `referer` header*
 - *It is a "blind" attack, Mallory does not see the result*
 - *To perform POST, current browsers today use `CORS` protocol*

Cross-site Scripting Attack (XSS)

- Exploits a trust of a user in a website



- Example Scenario
 1. An attacker injects a code to a page
 2. A users executes the code in his/her browser's session
 3. The code provides information (cookies) to the attacker
 4. The attacker uses the cookies to access the user's data

XSS Examples

- Twitter in Sep 2010

- *Injection of JavaScript code to a page using a tweet*
- *You posted following tweet to Twitter*

```
1 | There is a great event happening at  
2 | http://someurl.com/@"onmouseover="alert('test xss')"/
```

- *Twitter parses the link and wraps it with `<a>` element*

```
1 | There is a great event happening at  
2 | <a href="http://someurl.com/@"onmouseover="alert('test xss')"  
3 |     target="_blank">http://someurl.com/@"onmouseover=  
4 |     "alert('test xss')"/</a>
```

- *See details at Twitter mouseover exploit [🔗](#)*

- Other example: Google Contacts


Overview

- Mashups and XHR
- Security Mechanisms
 - *Scripting Attacks*
 - *Cross-origin Resource Sharing Protocol (CORS)*
- JSON and JSONP

Overview


- Increasing number of mashup applications
 - *client-side mashups involving multiple sites*
 - *mechanism to control an access to sites from within JavaScript*
- Allow for **cross-site HTTP requests**
 - *HTTP requests for resources from a different domain than the domain of the resource making the request.*
- W3C Recommendation
 - *see Cross-origin Resource Sharing [↗](#)*
 - *Browsers support it*
 - *see HTTP Access Control [↗](#) at Mozilla*

CORS Protocol – GET



- Read-only resource access via HTTP GET
- Headers:
 - **Origin** – identifies the origin of the request
 - **Access-Control-Allow-Origin** – defines who can access the resource
 - either the full domain name or the wildcard (*) is allowed.

CORS Protocol – other methods and "preflight"



- Preflight request queries the resource using **OPTIONS** method
 - requests other than GET (except POST w/o payload) or with custom headers
 - A browser should run preflight automatically for any XHR request meeting preflight conditions
 - The browser caches responses according to **Access-Control-Max-Age**

Overview

- Mashups and XHR
- Security Mechanisms
- JSON and JSONP

Recall: JSON

- JSON = JavaScript Object Notation
 - *Serialization format for data representation*
 - *Very easy to use in JavaScript*
 - *no need to use a parser explicitly*
 - *Also great support in many programming environments*
- Key constructs
 - ***object** is a collection of comma-separated key/value pairs:*
`{"name" : "tomas", "age" : 18, "student" : false, "car" : null}`
 - ***array** is an order list of values:*
`["prague", "innsbruck", 45]`
 - *can be nested: objects as values in an **array**:*
`[{ "name" : "tomas", "age" : 18 },
 { "name" : "peter", "age" : 19 }]`
 - *and the other way around: array as values in an **object**:*
`{ "cities" : ["prague", "innsbruck"],
 "states" : ["CZ", "AT"] }`
 - *A complete grammar see JavaScript Object Notation [🔗](#)*

JSON in JavaScript

- Native data format

```
1 // data needs to be assigned
2 var data = { "people" : ["tomas", "peter", "alice", "jana"] };
3
4 // go through the list of people
5 for (i = 0; i < data.people.length; i++) {
6     man = data.people[i];
7     // ... do something with this man
8 }
```

- Responses of service calls in JSON

- *Many support JSON, how can we load that data?*

- Example Request-Response

```
1 GET http://pipes.yahoo.com/pipes/pipe.run?_id=638c670c40c97b62&_render=json
2
3 {"count":1,"value":
4   {"title":"Web 2.0 announcements",
5     "description":"Pipes Output",
6     "link":"http://pipes.yahoo.com/pipes/pipe.info...",
7     "pubDate":"Mon, 07 Mar 2011 18:27:20 +0000",
8     "generator":"..."
9   },
10  ...
11 }
```

JSONP

- Service that supports JSONP
 - *allows to specify a query string parameter for a wrapper function to load the data in JavaScript code*
 - *otherwise the data cannot be used in JavaScript*
 - *they're loaded into the memory but assigned to nothing*
- Example
 - *if a resource at http://someurl.org/json_data returns*

```
{ "people" : ["tomas", "peter", "alice", "jana"] }
```

then the resource at
http://someurl.org/json_data?_callback=loadData *returns*

```
loadData({ "people" : ["tomas", "peter", "alice", "jana"] });
```
- A kind of workaround for the same origin policy
 - *only **GET**, nothing else works obviously*
 - *no XHR, need to load the data through the dynamic **<script>** element*

JSONP in JavaScript

- JSONP example
 - *loads JSON data using JSONP by dynamically inserting `<script>` into the current document. This will download JSON data and triggers the script.*

```
1  var TWITTER_URL = "http://api.twitter.com/1/statuses/user_timeline.json?" +
2      "&screen_name=web2e&count=100&callback=loadData";
3
4  // this needs to be loaded in window.onload
5  // after all document has finished loading...
6  function insertData() {
7      var se = document.createElement('script');
8      se.setAttribute("type", "text/javascript");
9      se.setAttribute("src", TWITTER_URL);
10     document.getElementsByTagName("head")[0].appendChild(se);
11     // And data will be loaded when loadDta callback fires...
12 }
13
14 // loads the data when they arrive
15 function loadData(data) {
16     // we need to know the the structure of JSON data that is returned
17     // and code it here accordingly
18     for (i = 0; i < data.length; i++) {
19         data[i].created_at // contains date the tweet was created
20         data[i].text // contains the tweet
21     }
22 }
```


JSON Vulnerability

- What it is
 - JSON array data accessible via GET (normal access is via XHR)
 - Attacker may load the data in a **script**, redefine **Array** object, and assign the data to a variable.
 - Attacker's page with a script that you access:
 - your browser uses your cookies to load the resource

```
1 <script type="text/javascript">
2 var yourData;
3 Array = function() {
4     yourData = this;
5 }
6 </script>
7
8 <script src="yourdomain.cz/yoursecretdata.json" type="text/javascript"></script>
```

- Prevention
 - Using prefix in the data – the prefix makes the JSON data invalid; the client must strip the prefix before parsing the data as JSON
 - 1 | ["a": "account", 433, 5543]
 - Use only POST for sensitive data