Patient De-Identification Manual

Download PDF

August, 2021

Use and Limitation

This Manual is intended to be used as a reference guide for the acquisition of images using at a GE 1.5T MRI system. Perspectum Ltd. shall not be held liable for improper installation, operation, or maintenance of the system in circumstances where procedures and specifications set out in this Manual have not been followed correctly. It is essential therefore, that you follow the specifications, procedures, and recommendations outlined in this Manual.

Disclaimer

Table Of Contents

This page is intentionally left blank.

1. De-Identification Introduction

This document describes the correct procedure to de-identify patient identifiable information(PII) on GE MRI scanners on the console and offline.

1. De-Identification Introduction

2. Compatibility

The procedures described in this document are compatible with MRI-scanners support by LiverMultiscan as described in System Requirements – MRA001.

3. De-Identification - On Console

Follow the steps described below to edit patient identifiable information.

1. Close the patient in all task and processes
2. Select the patient that is to be corrected from the Local DB section
3. At Data Apps Tab, click **Edit Patient**.
4. Correct the patient information to the appropriate identifiers as described in the Patient Registration section for the project as shown in


Figure 1. Patient de-identification on GE systems.

4. De-Identification - Offline Mac

We recommend the use of open-source programs such as *Horos* or *OsiriX* to de-identify data.

1. Select the DICOM dataset you want to de-identify into Horos or OsiriX after loading into Document Data Base.
2. Click **Anonymize** as shown in Figure 2 (page 4) left
3. Correct the patient information to the appropriate identifiers as described in the Patient Registration section for the project as shwon in Figure 2 (page 4) right.
4. If needed to customise additional DICOM tags, click the **plus sign** on the **Select a DICOM tag...** option.


Figure 2. Select anonymize to correct the patient information (left) and modify additional DICOM tags if needed (right).

5. Ensure all the following DICOM tags are selected before exporting the dataset.

5. De-Identification - Offline Windows

We recommend the use of open source program such as DicomCleaner™ to de-identify data.

Follow the steps described below, to edit patient information.

1. **Import** the dataset to de-identify as shown in Figure 3 (page 5)

Figure 3. DicomCleaner de-identification for Windows system. Import data to de-identify

2. Check **Replace box**

   In Patient's Name, Patient's ID and Accession Number fields, fill in the naming convention as described in the Patient Registration section of Image Acquisition Manuals

   Check **Remove all unreplaced identities**, and **Remove patient characteristics** boxes

   Press **Clean** button as shown in Figure 4 (page 6)

Figure 4. Fill in information according to the agreed naming convention

3. Create a folder with the patient information as described in the Patient Registration section in your local hard drive, select the proper patient dataset to export, press **Export** button, select the folder created in your local hard drive.

   Press **Choose** and data will be exported for the correct folder as shown in Figure 5 (page 6)

Figure 5. Export to a specific folder with de-identified data

6. Approvals

Head of Imaging Solutions	Head of Imaging Applications
Dr. Alex Smith	Andrea Borghetto

6. Approvals

This page is intentionally left blank.