

Запрос для BATC

```
-- 1.    ps_aors

INSERT INTO `00450672_ps_aors` (id)
--
SELECT 1002101 UNION ALL
--
SELECT 1002102 UNION ALL
SELECT 1002103 UNION ALL
SELECT 1002104 UNION ALL
SELECT 1002105 UNION ALL
SELECT 1002106 UNION ALL
SELECT 1002107;

-- 2.    __ps_auths 10-

INSERT INTO `00450672_ps_auths` (id, username, password)
--
SELECT id,
        CAST(id AS CHAR) AS username,
--      ,      - CHAR
        CONCAT(
            CHAR(FLOOR(65 + RAND()*26)),
--    A-Z
            CHAR(FLOOR(97 + RAND()*26)),
--    a-z
            CHAR(FLOOR(48 + RAND()*10)),
--    0-9
            CHAR(FLOOR(65 + RAND()*26)),
--    A-Z
            CHAR(FLOOR(97 + RAND()*26)),
--    a-z
            CHAR(FLOOR(48 + RAND()*10)),
--    0-9
            CHAR(FLOOR(65 + RAND()*26)),
--    A-Z
            CHAR(FLOOR(97 + RAND()*26)),
--    a-z
            CHAR(FLOOR(65 + RAND()*26)),
--    A-Z
            CHAR(FLOOR(97 + RAND()*26))
--    a-z
        ) AS password
FROM `00450672_ps_aors`
--
WHERE id BETWEEN 1002101 AND 1002107;
--      ,      OR

-- 3.    ps_endpoints
```

```

INSERT INTO `00450672_ps_endpoints` (id, transport, aors, auth, callerid)
--
SELECT id,
       'transport-in' AS transport,
--       in () out ()
       CAST(id AS CHAR) AS aors,
       CAST(id AS CHAR) AS auth,
       CAST(id AS CHAR) AS callerid
FROM `00450672_ps_aors`
--
WHERE id BETWEEN 1002101 AND 1002107;
--       ,           OR

-- 4.   cid   ps_endpoints

UPDATE `00450672_ps_endpoints`
--
SET cid = CASE
--
  WHEN id IN (1002101, 1002102, 1002103, 1002104) THEN 3790086
  WHEN id IN (1002105, 1002106) THEN 3790056
  WHEN id IN (1002107) THEN 3790043
  ELSE cid
--       id
END
WHERE id IN (1002101, 1002102, 1002103, 1002104, 1002105, 1002106,
1002107);  --       ( id)

-- 5.   -

UPDATE `00450672_ps_auths`
--
SET `password` = CASE
--       -   PBX,   id,
  WHEN id = 1002101 THEN 'Em18cFvmG6'
  WHEN id = 1002102 THEN 'bbVhh4jWP7'
  WHEN id = 1002103 THEN 'WpdQN2MSqW'
  WHEN id = 1002104 THEN 'St8ii1qEhA'
  WHEN id = 1002105 THEN '4nFa10HKzk'
  WHEN id = 1002106 THEN 's2XgpHwiY2'
  WHEN id = 1002107 THEN 'FABETy9A4J'
  ELSE `password`
--       id
END
WHERE id IN (1002101, 1002102, 1002103, 1002104, 1002105, 1002106,

```

```
1002107);  --      ( id)
```

```
--      ,
```