

Dynamic Scientific Retrieval with Temporal-Citation Integration and Adaptive Update Strategies

Author Name

May 2, 2026

Abstract

Scientific retrieval is inherently dynamic: the collection grows continuously, the usefulness of documents changes over time, and citation signals evolve after publication. This paper studies three connected questions in LongEval-Sci: which retrieval foundation is most reliable, how temporal and citation evidence should enter ranking, and how a system should update under continuous collection growth. We build a unified evaluation framework spanning sparse retrieval, dense retrieval, RM3 expansion, reranking, reciprocal rank fusion, temporal overlays, citation-aware overlays, router-based integration, and additive score integration. Our current results show that strong full-text sparse retrieval provides the best single-system foundation, while lexical-dense fusion offers the most robust candidate pool under collection growth. Based on this finding, we argue that temporal and citation signals should be integrated in a controlled manner rather than applied uniformly to all queries. We further frame long-term scientific retrieval as a dynamic information retrieval problem requiring multiple update mechanisms, including but not limited to periodic reindexing.

1 Introduction

Scientific corpora grow continuously as new papers, revisions, and citation links appear over time. In this setting, retrieval quality depends not only on lexical or semantic relevance, but also on document freshness, temporal intent, and the evolving citation structure of the literature. A document that is highly relevant at one time point may become less useful later, while a previously marginal paper may become central as citations accumulate or a topic shifts.

LongEval-Sci provides a suitable benchmark for studying retrieval robustness under collection evolution. Unlike purely static evaluation settings, it allows us to examine how ranking behavior changes as the corpus expands and as temporal context becomes increasingly important. In this scenario, comparing systems only by a single static nDCG score is insufficient. A more complete analysis should examine at least three aspects: the retrieval foundation, the integration of temporal and citation signals, and the mechanisms used to keep the system updated over time.

This paper follows that logic. We first compare a broad family of retrieval systems, from official baselines to stronger customized full-text and fusion variants, in order to identify a reliable base retrieval foundation. We then investigate how temporal and citation signals should be incorporated into ranking, contrasting direct overlay methods with router-based and additive integration

strategies. Finally, we extend the discussion from effectiveness to long-term maintenance by studying collection growth and outlining an adaptive update framework that goes beyond periodic full reindexing.

Our contributions are as follows:

- We construct a unified LongEval-Sci retrieval framework covering sparse retrieval, dense retrieval, RM3 expansion, reranking, reciprocal rank fusion, temporal overlays, and citation-aware overlays.
- We define and evaluate three integration paradigms for temporal and citation evidence: direct overlay, router-based selection, and additive score integration.
- We analyze robustness under collection growth through whole-train evaluation, monthly cumulative evaluation, and daily cumulative drift analysis.
- We propose an adaptive update perspective for dynamic scientific retrieval that includes reindexing as well as lighter update mechanisms such as reranking refresh, fusion refresh, query-side updates, and citation feature refresh.

2 Task, Data, and Evaluation

We study LongEval-Sci 2026 Task 1 using the **snapshot-1** training collection. Our primary supervision source is the DCTR qrels, while the raw qrels are treated as a complementary signal for additional inspection and future ablation. We report standard retrieval metrics including nDCG@10, nDCG@1000, MAP, Recall@100, and Recall@1000.

To better capture collection evolution, we conduct evaluation at three levels. First, *whole-train evaluation* measures overall system quality on the entire training snapshot and establishes our main ranking comparisons. Second, *monthly cumulative evaluation* simulates corpus growth through progressively larger subsets, specifically March, March+April, and March+April+May. Third, *daily cumulative drift analysis* provides a finer-grained view of retrieval stability as documents are added continuously over time.

These monthly and daily splits are internal simulation protocols designed to approximate collection growth. They do not redefine the official task, but instead allow us to observe when a retrieval method is strong only in a static setting and when it remains robust under dynamic expansion.

3 System Overview

Figure 1 will present the overall system architecture. The pipeline is organized into four layers.

The **first-stage retrieval layer** includes the official BM25 title+abstract run, the official dense title+abstract run, a custom BM25 full-text retriever, and RM3-based query expansion variants. These systems produce the initial candidate sets and define the retrieval foundation.

The **second-stage ranking layer** contains reranking and reciprocal rank fusion (RRF). Reranking is used to sharpen top-rank quality for selected pipelines, while RRF is used to merge complementary lexical and dense evidence into a broader and more robust candidate pool.

The **temporal-citation layer** augments the base rankers with temporal metadata features, citation-derived features, router-based control, and additive score integration. This layer is responsible for deciding whether and how non-relevance evidence should affect the final ranking.

The **update layer** models long-term system maintenance. It includes reindex monitoring as well as non-reindex update strategies that may preserve quality when the collection grows but full rebuilding is costly or unnecessary.

This section intentionally gives a high-level view of the system. Detailed modeling choices for temporal and citation integration are described later in Section 5.

4 Retrieval Baselines

We evaluate sixteen systems and organize them into several coherent families rather than treating them as disconnected trial runs. This structure is important because the central question is not merely which single configuration wins, but how retrieval quality changes as we move from official anchor systems to progressively stronger foundations and then to temporal-citation integration.

The **base model family** includes the following systems:

- `official_pyterrier`
- `official_pyterrier_dense`
- `custom_lexical_fulltext`
- `custom_title_abstract_rm3`
- `custom_title_abstract_rerank`

These systems establish the performance range for sparse, dense, expanded, and reranked retrieval.

The **fusion family** consists of RRF variants that combine lexical and dense candidate generation. These runs test whether heterogeneous evidence improves robustness and deep recall beyond what a single retriever can achieve.

The **temporal family** extends base systems with temporal overlays, and the **citation-aware family** further adds citation-derived features on top of temporalized retrieval. Together, these families allow a systematic comparison from official baselines to stronger customized models and finally to controlled integration of temporal and citation evidence.

5 Temporal and Citation Integration

This section presents the core methodological contribution of the paper. Our aim is not simply to add more features to ranking, but to understand how temporal and citation signals can be introduced without destabilizing relevance ranking. We therefore study three integration patterns: direct overlay, router-based integration, and additive score integration.

5.1 Direct Temporal Overlay

Our temporal reranker starts from a base retrieval score and augments it with time-sensitive evidence. The feature pool includes recency, update score, foundation score, lexical novelty, and query temporal intent. The intuition is that some scientific queries prefer recent or evolving work, while others are better served by stable foundational documents.

The direct temporal overlay applies this signal after base retrieval. This provides a simple and transparent way to test whether temporal evidence improves ranking quality, but it also risks over-applying freshness incentives to queries that do not actually require them.

5.2 Citation-Aware Overlay

We then extend the temporal overlay with citation features, including total inbound citations, recent inbound citations, non-self citations, citation velocity, foundational signal, emerging signal, and outbound citations. All citation features are computed *as of the evaluation cutoff* in order to avoid temporal leakage.

Citation evidence is potentially useful for distinguishing established papers from recently emerging work, but it is also noisy: highly cited documents are not always the most relevant for the current query. This makes citation integration a ranking problem rather than a simple metadata bonus.

5.3 Router-Based Integration

Router-based integration treats temporal and citation signals as query-dependent evidence channels. Instead of applying every overlay to every query, a router uses query features to choose among several ranking routes: base relevance only, temporal overlay, citation overlay, or temporal+citation overlay.

The goal is to avoid indiscriminate boosting. Some queries are primarily relevance-driven, some have strong temporal intent, and some may benefit from citation-aware preference for foundational or emerging work. Router-based integration therefore acts as a hard selection mechanism over evidence pathways.

Table X will report the performance of router-based integration compared with direct temporal and citation overlays.

5.4 Additive Score Integration

Additive integration instead combines multiple signals softly:

$$\text{final_score} = \alpha \cdot \text{relevance_score} + \beta \cdot \text{temporal_score} + \gamma \cdot \text{citation_score}.$$

The weights may be fixed globally or adapted per query. Conceptually, this differs from router-based integration in two ways: router-based integration decides *which* evidence channel to use, while additive integration decides *how much* each signal should contribute.

Table X will compare additive integration with router-based integration and direct overlay methods. If additive integration proves more stable, it would suggest that temporal and citation evidence are most useful as calibrated auxiliary signals rather than as route-level decisions.

6 Main Retrieval Results

Table 2 summarizes the current whole-train results. Among the evaluated single systems, `custom_lexical_fulltext` achieves the strongest nDCG@10 and MAP, indicating that strong full-text sparse retrieval is currently the most reliable retrieval foundation. In contrast, `rrf_bm25_ft_dense_ta` does not produce the highest top-rank effectiveness, but it achieves the best deep recall, which makes it a strong candidate-pool strategy.

Table 1: Whole-train main results.

Method	Family	nDCG@10	MAP	Recall@1000
<code>custom_lexical_fulltext</code>	base	0.3302	0.2853	0.9245
<code>custom_title_abstract_rerank</code>	base	0.3222	0.2777	0.8581
<code>rrf_bm25_ft_dense_ta</code>	fusion	0.3175	0.2749	0.9667
<code>official_pyterrier</code>	base	0.2922	0.2573	0.8581

These results support two initial conclusions. First, full-text BM25 is the strongest current single-system anchor. Second, RRF is especially attractive when recall matters, suggesting that lexical-dense fusion is better understood as a robust candidate-generation strategy than as a guaranteed top-rank winner.

7 Collection Growth Results

We next examine system behavior under simulated collection growth. Figure 2 will plot monthly nDCG@10 curves, and the key values are summarized directly in the text for clarity. For `rrf_bm25_ft_dense_ta_dctr`, nDCG@10 improves from 0.2732 in March to 0.2849 in March+April and 0.2930 in March+April+May. For `custom_lexical_fulltext_dctr`, the corresponding values are 0.2314, 0.2259, and 0.2495. For `official_pyterrier_dctr`, the values are 0.1767, 0.2047, and 0.2377.

The main finding is that RRF behaves most robustly under collection growth. Although full-text BM25 is the strongest static baseline, fusion appears more stable as the corpus expands month by

month. This shows why growth-aware evaluation is necessary: whole-train ranking alone does not reveal which systems remain reliable when the collection keeps changing.

8 Temporal/Citation Integration Results

This section is reserved for the formal comparison among direct overlays, router-based integration, and additive integration. The final interpretation will depend on the completed experiments. If router-based integration performs best, we will emphasize query-specific signal selection. If additive integration performs best, we will emphasize the stability of soft evidence composition. If neither approach consistently improves over the anchors, we will conclude that temporal and citation signals require stronger calibration, while still treating the negative result of direct overlays as informative.

Table 2: Temporal and citation integration results (placeholders to be filled after experiments complete).

Method	Integration	nDCG@10	MAP	Recall@1000	Notes
temporal-only overlay	direct	[]	[]	[]	
citation-aware overlay	direct	[]	[]	[]	
router integration	hard routing	[]	[]	[]	
additive integration	soft scoring	[]	[]	[]	
base full-text BM25	no temporal/citation	0.3302	0.2853	0.9245	anchor
RRF fulltext+dense	fusion	0.3175	0.2749	0.9667	anchor

8.1 Per-Intent Analysis

An additional analysis will break results down by query intent, including foundational, current, evolving, and survey-oriented queries. This view is especially useful for understanding whether temporal, citation, router-based, or additive integration helps only for specific information needs rather than uniformly across all queries.

9 Adaptive Update System

The final technical component of the paper concerns long-term maintenance. If scientific retrieval is dynamic, then evaluation should not end at ranking quality alone; it should also consider how the system is updated as the corpus grows.

9.1 Reindex Monitoring

Our current reindex monitoring design includes document staleness rate, index coverage gap, new-document velocity, temporal gap, trigger levels, and shadow-index promotion logic. Existing drift statistics already motivate this component. In one observed setting, the collection reaches 869,902 documents, the mean temporal gap is 410 days, and the final staleness rate is 91.84%. Over the

same period, daily nDCG@10 drops from 0.3572 to 0.3312, MAP drops from 0.3173 to 0.2879, and Recall@1000 remains stable at 0.9292.

This pattern is important because it suggests that deep recall may remain largely intact while top-rank quality declines. In other words, the problem is not always that the system fails to retrieve relevant material at all, but that the highest-ranked documents become less well calibrated over time.

9.2 Update Systems Beyond Reindex

This observation motivates update strategies beyond full reindexing. One option is **delta indexing** or two-index retrieval, in which an older main index is combined with a new-document delta index and the outputs are fused at ranking time. A second option is **reranker refresh**, where the base index remains unchanged but top-ranked candidates are rescored using updated temporal or citation models. A third option is **fusion refresh**, where existing run outputs are recombined using revised fusion settings. Additional lightweight strategies include **query-side updates**, such as query expansion refresh, temporal-intent refinement, router-policy adaptation, and score recalibration, as well as **citation feature refresh**, in which citation caches are updated periodically without rebuilding the entire retrieval index.

The core implication is straightforward: since deep recall remains stable while top-rank quality declines, update strategies should not be limited to full reindexing. In many cases, lighter reranking, fusion, query-side, or citation-refresh updates may be sufficient.

10 Discussion

Our current results support four main takeaways. First, full-text sparse retrieval is a strong foundation for LongEval-Sci. Second, lexical-dense fusion is especially useful under collection growth because it provides a more resilient candidate pool. Third, temporal and citation signals should not be injected indiscriminately; they require controlled integration, which motivates router-based and additive approaches. Fourth, dynamic scientific retrieval should be framed as a system-maintenance problem as well as a ranking problem, combining reindexing with lighter update strategies.

Taken together, these findings suggest a coherent story for dynamic scientific retrieval. A strong retrieval foundation should come first, temporal and citation evidence should be added carefully rather than globally, and update policies should be tailored to the specific type of degradation observed in the system.

11 Conclusion

We present a dynamic scientific retrieval framework for LongEval-Sci that connects three questions: the choice of retrieval foundation, the integration of temporal and citation signals, and the maintenance of retrieval systems under collection evolution. Our current results indicate that full-text BM25 is the strongest single-system anchor and that lexical-dense RRF is a strong strategy for

robust candidate generation. Ongoing router-based and additive experiments are designed to determine how temporal and citation evidence can be incorporated reliably into ranking. More broadly, our adaptive update perspective links retrieval effectiveness to long-term system maintenance and argues that dynamic scientific retrieval should be supported by multiple update mechanisms rather than periodic reindexing alone.

Planned Figures and Tables

For clarity, the current paper plan includes the following core visual elements:

- Figure 1: overall system architecture.
- Table 1: model families.
- Table 2: whole-train main results.
- Figure 2: monthly nDCG@10 curves.
- Table 3: temporal/citation integration results, including router/additive placeholders.
- Figure 3: daily drift curve showing documents versus nDCG@10 and MAP.
- Figure 4: adaptive update framework beyond reindex.

This structure keeps the paper centered on a stable narrative: the first half establishes the retrieval foundation, the middle examines how temporal and citation signals should enter ranking, and the final part addresses how a dynamic scientific retrieval system should be maintained over time.