FEAther: A Self-Learning Multi-Agent System for Lightweight Load-Bearing Part Design with Finite Element Analysis

Rifqi Wibisono
Nanjing Xiaozhuang University, Nanjing, China
Student ID L25020014

***Abstract*—Large language models (LLMs) can now write computer-aided design (CAD) programs that build three-dimensional parts, but are taught and judged by resemblance to a reference. A part can look right and still fail under load. In our finite element analysis (FEA), narrowing one bend of a bracket from 9 mm to 2 mm raises its peak stress by 53% while the shape barely changes, and in a recent study the best AI agents passed none of 50 engineering briefs on their first attempt. Existing systems check designs with physics without learning from the results, or learn only to tune fixed templates; none learns to choose a part's layout from physics. This proposal presents FEAther, a self-learning multi-agent system for lightweight load-bearing part design. A parser agent turns a request into a specification, a designer agent writes the CAD program, and a checker simulates the part with FEA and reports where it fails and by how much. The designer revises until the part passes, lightens it while it still passes, and learns from the checker's scores by reinforcement learning. We ask whether learning from physics beats learning from shape similarity, whether run-time feedback helps beyond learning, and how much material passing designs use. A pilot validated the checker within 10% of textbook calculations on ten parts and generated 40 specifications, each proven solvable; two off-the-shelf open models solved none and resubmitted their failed program in about 80% of revisions. The study will establish whether LLM-designed parts can be verified by physics rather than judged by appearance.**

***Index Terms*—code generation, computer-aided design, finite element analysis, large language models, multi-agent systems, reinforcement learning, self-repair, test oracles**

I. Introduction

A parametric CAD model can be written as a program. In CadQuery [1], a Python library on the OpenCASCADE geometry kernel, a bracket is a script that sketches profiles, extrudes them, and cuts holes; running it yields a solid that can be meshed, simulated, and printed. Because such programs are text, LLMs can learn to write them, and recent models translate text, images, or point clouds into CadQuery [2]–[4].

These models are trained and evaluated on geometric resemblance: a reward or metric compares the generated shape with a reference shape, for example by Chamfer distance. For a load-bearing part, resemblance is the wrong oracle. Two brackets that look alike can differ widely in peak stress (Fig. 1), because stress concentrates at small features such as the inside radius of a bend or the edge of a hole [5], [6]. Regenwetter et al. showed that similarity metrics miss engineering performance [7]. When designs are checked by physics, current systems fail: in Son et al.'s 50 FEA-checked engineering briefs, no frontier agent's first design passed every requirement [8], and CADEngBench reports that matching a reference FEA response "remains difficult" [9].




Fig. 1. Peak von Mises stress in two L-brackets that differ only in the inside radius of the bend, computed by the checker (Section IV) under the same 15 N load at 70 mm from the wall, with the same 6 × 24 mm section and bolts. Tightening the bend from 9 mm to 2 mm raises the peak from 8.7 to 13.4 MPa, 34% over the 10 MPa limit, and saves only 0.7 g. Gray: zones next to the rigid bolts and the load patch, where stress is not read.

From a software-engineering view, a CAD program is code whose test oracle is physics. Code-generation research offers two lessons that should transfer: execution feedback can train a model through reinforcement learning, and feedback at run time (self-repair) helps less than expected once its extra attempts are paid for [10]. Neither has been tested with a physics oracle.

The closest work, COSMO-Agent [11], trains Qwen3-8B with the GRPO algorithm and the CalculiX solver in the loop, but only to choose parameter values for 25 fixed CadQuery templates. In engineering terms this is *sizing*; it caps cost rather than minimizing mass, and it used 16 H200 GPUs. No work we found trains a model to make *configuration* choices (the layout: where material goes, whether there is a rib or a cutout), written as a CAD program, against FEA-checked requirements. Our last arXiv search, on 1 November 2026, found RL-trained CAD generators that still reward only shape resemblance. This proposal contributes:

- an FEA test oracle for generated CAD programs, with sandboxed execution and a staged reward, validated against hand calculations;
- a specification generator in which every specification is

TABLE I
RESEARCH QUESTIONS, VARIABLES, AND ANALYSIS

Question	Independent variable	Dependent variable	Analysis
RQ1: Does GRPO with an FEA-graded reward fully pass more held-out specs than SFT alone and than a shape-similarity reward?	training: SFT only; GRPO with a shape reward, an FEA reward, or both	full pass rate; share of requirements met; invalid rate	McNemar's test; bootstrap 95% intervals
RQ2: Does run-time FEA feedback improve designs beyond training, and is the gain from the feedback or from more attempts?	designer: SFT, GRPO, GRPO with revise and lighten prompts; attempts: one-shot, best-of-k, loop; $k \in \{1, 3, 5, 10\}$	specs passed within k; mass of the lightest pass; tokens per solved spec	McNemar's test at each k
RQ3: How much material do passing designs use, and what does the reward's mass term change?	reward with or without the mass term	mass relative to sizing-only and topology-optimized references; pass rate	Wilcoxon signed-rank test

proven solvable, and a sizing-only baseline that separates configuration from sizing;
- a recipe that trains one designer to design, revise, and lighten on a single 16 GB GPU;
- an evaluation that separates the effect of feedback from the effect of more attempts.

II. Related Work

LLMs that write CAD programs. CAD-Recode reconstructs CadQuery programs from point clouds, trained on one million procedurally generated programs [2]. CAD-Coder generates CadQuery from text, fine-tuned on about 110,000 text–code–shape triplets and then trained with GRPO on a geometric reward [3]; cadrille applies reinforcement learning to multi-modal reconstruction [4]. All of their rewards measure resemblance to a target shape.

Physics in the loop. Son et al. give frontier agents FEA reports at run time and let them iterate; their agents are called self-improving because they iterate on feedback, but no model is trained [8]. CADEngBench benchmarks parametric design against simulation without training [9]. COSMO-Agent trains on simulation results but sizes fixed templates [11]. FEAther differs from all three by training the model that chooses the configuration, and by rewarding low mass as well as passing.

Self-repair in code generation. Self-Debug [12] teaches models to fix their code from execution results. Olausson et al. found that, at an equal budget, self-repair often gains little over drawing more independent samples, because models rarely act well on feedback [10]. RQ2 tests this claim with a physics oracle, before and after the repair skill is trained.

III. Research Questions and Hypotheses

Table I lists the questions, their variables, and the planned analysis. The hypotheses are: **H1:** the FEA-graded reward raises the full pass rate over both SFT alone and the shape reward, because only it scores what a spec requires. **H2:** for untrained and SFT-only designers, best-of-k sampling matches or beats the loop at equal k, as in our pilot; after training on revise and lighten prompts, the loop beats best-of-k. **H3:** without the mass term, passing designs are no lighter than the sizing-only reference; with it, they are lighter, because the designer can move material instead of only scaling it.




Fig. 2. One pass through FEAther on generated spec l_bracket-0000: an excerpt of the spec's reference program, the checker's part and mesh, and its actual report. Only the designer (blue outline) is trained. At run time the report returns to the designer, which revises while the part fails and lightens it while it passes, as here. In training, the checker's reward updates the designer by GRPO (dashed).

IV. Approach

Specifications. Fig. 2 follows one specification (spec) through the system. Each spec is a structured record and an English prompt that states every number in it: a load (force, point, direction, and patch radius), bolt holes (axis and diameter), an envelope the part must stay inside, the material (PLA, Young's modulus 2300 MPa), and limits on peak stress, deflection, and mass. A generator samples specs for each part family (first L-brackets and wall hooks, about five by the end, with one or two families held out of training). It sizes a reference program from that family's template by hand calculation and keeps the spec only if the checker passes the reference. Each kept spec is therefore proven solvable. The reference then sets two limits. The deflection limit is 1.3 to 2 times the reference's deflection. The mass budget is 80% of the reference's mass, because a budget at the reference would stop rewarding any design lighter than what sizing alone achieves.

Checker. Programs from the model are untrusted. Each one runs in its own process with no network (its own user and

(a) Prompt of a generated spec. I need a wall bracket that holds a load out from the wall, printed in PLA. Stay within the box x 0 to 60, y -15 to 15, z -1 to 76 mm. Requirements: peak stress under 10 MPa, deflection under 3.8 mm, and mass ideally below 9.3 g. Mount it on the wall at x = 0 with 2 M5 bolts; their 5.5 mm holes run along x at (y, z) = (0, 10) and (y, z) = (0, 43) mm. A 10 N load presses straight down on it at the point (42, 0, 76) mm, spread over a patch of radius 4 mm.

(b) Checker report on reference part L1, built to fail.

```
FAIL at stage 'structure' (reward 0.70 of 1.00)
- Largest deflection 3.90 mm (no limit set).
- Peak stress 13.40 MPa at (6.6, 0.9, 61.4) mm;
  limit 10.00 MPa, over the limit by 34%.
- Mass 24.38 g (not scored until the structure passes).
```

Fig. 3. What the designer sees: (a) a spec's prompt, with every number in the spec; (b) the report it revises from. The peak lies on the inside of L1's 2 mm bend radius, where curved-beam theory puts it.

network namespaces) and with limits on memory, CPU time, and file size; it must leave its part in a variable named `result`. The checker then grades in stages, and credit stops at the first that fails: the program runs (0.1); it makes exactly one valid solid (0.1); every bolt hole is open where the spec puts it, a surface lies at the load point, and the part stays in the envelope (0.2); the structure (0.4, the mean over requirements of $\min(1, \text{limit}/\text{value})$ for peak stress and deflection); and the mass ($0.2\,\min(1, \text{budget}/\text{mass})$, counted only once the structure passes). Gmsh [13] meshes the part with quadratic tetrahedra, refined on curved faces, and CalculiX [14] solves a linear static case: bolt bores held rigid, the load spread over a patch. Both of these raise stress artificially near the bores and the patch, so peak von Mises stress is read outside a zone one bolt diameter beyond each bore and twice the patch radius around the load. The report states which stage failed, the peak stress, where it is, and by how much it misses its limit (Fig. 3).

Agents and loop. The designer writes a program; while it fails, the designer receives its own program and the report and revises; once it passes, it is asked for a lighter version that still passes, and the lightest passing design is kept.

Training. The designer is Qwen3-8B [15], with Qwen3-1.7B for pilots. Supervised fine-tuning (SFT) on public text-to-CadQuery data [2], [3] teaches the language. Group Relative Policy Optimization (GRPO) [16] then samples a group of $G = 8$ programs for each prompt, scores them with the checker $(R_1, \ldots, R_G)$ and gives each program the advantage

$$A_i = \frac{R_i - \text{mean}(R_1, \ldots, R_G)}{\text{std}(R_1, \ldots, R_G)}. \tag{1}$$

The update makes the tokens of programs with $A_i > 0$ more likely and the rest less likely. A prompt whose eight programs all score the same therefore teaches nothing, which is why the reward is graded rather than pass/fail. Training mixes three prompt kinds, the same ones the loop uses: design; revise, with one of the model's own failed programs and its report; and lighten, with a passing program. QLoRA [17] freezes the base model in 4-bit precision and trains small adapter matrices, which brings the 8B model within a 16 GB laptop GPU (about 11 GB, estimated). FEA rewards run on 20 CPU workers at 2–8 s each, so generating designs on the GPU is the bottleneck.

TABLE II
CHECKER FEA AGAINST HAND CALCULATIONS (PEAK STRESS)

Family	Parts	Hand calculation at worst point	FEA / hand
L-bracket	4	curved beam (Winkler), bend	1.031–1.099
Wall hook	3	curved beam (Winkler), curve	0.975–1.047
Hanger strap	3	hole in a strip (Heywood)	0.995–1.010

TABLE III
UNTRAINED BASELINE: SPECS (OF 40) WHOSE BEST OF EIGHT ATTEMPTS GOT PAST EACH STAGE

	Qwen3-1.7B		Qwen3-8B	
Stage passed	samples	loop	samples	loop
program runs	8	1	34	18
one valid solid	5	1	12	4
holes, envelope	0	0	0	0
all requirements	0	0	0	0

V. PRELIMINARY RESULTS

Checker validation. A cantilever beam gave a tip deflection of 1.736 mm against 1.739–1.753 mm from beam theory without and with shear deflection. Ten hand-written reference parts in three families put their worst point where a reliable formula applies (Table II): curved-beam theory for the bends of L-brackets and hooks, and Heywood's formula for a hole in a strip [5], [6]. On all ten, the checker's FEA peak lies within 10% of the hand calculation and within 4.4 mm of the predicted point or its mirror image, and refining the mesh moves each value by under 4%. The checker fails the three parts built to exceed the 10 MPa limit and passes the other seven, in 2–8 s per part. Separate tests confirm that a crashing program, an endless loop, a program grabbing 8 GB, an attempt to reach the network, a part in two pieces, a missing bolt hole, and a hole 0.7 mm too large each fail at the right stage.

Specification generation. The generator produced 40 specs, 20 L-brackets and 20 hooks; every reference passed on its first FEA run, with peaks of 7.6–9.1 MPa against the 10 MPa limit.

Untrained baseline. We served Qwen3-1.7B (16-bit) and Qwen3-8B (8-bit floating point) with vLLM [18], thinking mode off, and gave each eight checker runs per spec, either as eight independent samples or in the loop (Table III). Neither model passed a spec. Most programs misuse the CadQuery interface; those that make a solid cross into the wall, because CadQuery centers boxes on the origin. In the loop, about 80% of revisions (225 of 280 for 1.7B, 221 of 280 for 8B) repeat the program they were asked to fix, so independent samples reach running code on more specs than the loop does (34 against 18 for the 8B). This agrees with Olausson et al. [10] and is the baseline that trained revision must beat. GRPO would already have a signal on 34 of 40 specs, where the 8B's samples score differently, but only between the credits for running, for one solid, and for the interfaces; no design reached the structural checks. SFT therefore comes first.

VI. Evaluation Plan

Test material. Held-out specs, including whole held-out families, and Son et al.'s briefs if they are released [8].

Baselines. The untrained model; the SFT-only model; SFT plus GRPO with a shape-similarity reward, as in CAD-Coder [3]; and a sizing-only search that tunes the reference template's parameters without an LLM. The last isolates what choosing the configuration adds over sizing, the difference from COSMO-Agent.

Measures. The full pass rate (share of specs meeting every requirement); the share of requirements met; the invalid rate (programs that crash or make no single solid); mass relative to the references; the pass rate within k attempts; and tokens and seconds per solved spec.

Statistics. Every condition attempts the same specs, so pass/fail outcomes are paired and compared with McNemar's test, which counts only the specs on which two conditions disagree. Rates carry bootstrap 95% intervals, and mass ratios use the Wilcoxon signed-rank test, which does not assume normally distributed differences. As an extension, a subset of before-and-after designs will be 3D-printed and broken to compare measured failure loads with FEA.

VII. Threats to Validity

Construct. The oracle is a simplified model: linear static, rigid bolts, no contact, and an isotropic material, while printed PLA is weaker across its layers. Validation against hand calculations and the planned physical tests bound this. *Internal.* A trained model may exploit the oracle, for example with geometry that meshes oddly; the staged checks, the stress-reading zones, mesh-refinement spot checks, and a log of every exploit found, with earlier checkpoints re-scored after each fix, address this. *External.* The specs come from our own generator; held-out families test whether the model generalizes beyond it, and the first results cover only PLA and up to five families. *Conclusion validity.* The 40-spec pilot is small; the final evaluation uses hundreds of held-out specs and repeated seeds.

VIII. Risks, Plan, and Availability

Risks and fallbacks. If SFT still leaves no designs reaching the structural checks, training starts from easier specs (limits well above the reference's stress) and from revise prompts built by breaking reference programs. If GRPO on the 8B model does not fit in 16 GB, the 1.7B model is trained fully and a rented GPU runs the 8B experiments. If a newer paper trains a CAD generator on FEA results, the contribution rests on the mass objective, RQ2, and the physical tests.

Plan. Months 1–2: SFT, then GRPO pilots on the 1.7B and 8B models. Months 3–4: five families and RQ1–RQ3. Month 5: physical tests. Month 6: a demonstration and the thesis.

Availability. Code, the 40 specs, and all baseline results are in a Git repository, where each result in Section V re-runs with one command; it will be public with the thesis and is available to reviewers on request.

IX. Conclusion

FEAther asks whether an LLM can learn to design load-bearing parts from physics rather than from appearance. The pilot has built what this needs: a validated checker, 40 solvable specifications, and a baseline that untrained models fail entirely. The proposal succeeds if learning from FEA beats learning from shape (H1), trained revision beats independent attempts (H2), and passing designs are lighter than sizing alone makes them (H3); a negative H2 would still extend Olausson et al.'s finding [10] from code to physics-checked design. A simulation used as the test oracle for generated programs may also serve other engineering artifacts written as code.

References

[1] CadQuery contributors, "CadQuery: A Python parametric CAD scripting framework based on OCCT," https://github.com/CadQuery/cadquery, 2026, version 2.8.

[2] D. Rukhovich, E. Dupont, D. Mallis, K. Cherenkova, A. Kacem, and D. Aouada, "CAD-Recode: Reverse engineering CAD code from point clouds," arXiv:2412.14042, 2024.

[3] Y. Guan, X. Wang, X. Xing, J. Zhang, D. Xu, and Q. Yu, "CAD-Coder: Text-to-CAD generation with chain-of-thought and geometric reward," in *Advances in Neural Information Processing Systems 38 (NeurIPS)*, 2025, pp. 59 765–59 789.

[4] M. Kolodiazhnyi, D. Tarasov, D. Zhemchuzhnikov, A. Nikulin, I. Zisman, A. Vorontsova, A. Konushin, V. Kurenkov *et al.*, "cadrille: Multi-modal CAD reconstruction with reinforcement learning," in *International Conference on Learning Representations (ICLR)*, 2026.

[5] R. G. Budynas and J. K. Nisbett, *Shigley's Mechanical Engineering Design*, 11th ed. McGraw-Hill, 2020.

[6] W. D. Pilkey and D. F. Pilkey, *Peterson's Stress Concentration Factors*, 3rd ed. Wiley, 2008.

[7] L. Regenwetter, A. Srivastava, D. Gutfreund, and F. Ahmed, "Beyond statistical similarity: Rethinking metrics for deep generative models in engineering design," *Computer-Aided Design*, vol. 165, p. 103609, 2023.

[8] G. Son, J. Park, S. Park, S. Ahn, and Y. Yu, "Self-improving CAD generation agents with finite element analysis as feedback," arXiv:2605.17448, 2026.

[9] H. Singh, A. Dubey, and J. A. A. Herrera, "CADEngBench: It looks like CAD, but does it work? evaluating parametric design, assembly reasoning, and physics simulation," arXiv:2608.09296, 2026.

[10] T. X. Olausson, J. P. Inala, C. Wang, J. Gao, and A. Solar-Lezama, "Is self-repair a silver bullet for code generation?" in *International Conference on Learning Representations (ICLR)*, 2024.

[11] L. Deng, S. Deng, Y. Chen, Y. Dai, Z. Zhong, L. Li, X. Sun, Y. Shi *et al.*, "COSMO-Agent: Tool-augmented agent for closed-loop optimization, simulation, and modeling orchestration," arXiv:2604.05547, 2026.

[12] X. Chen, M. Lin, N. Schärli, and D. Zhou, "Teaching large language models to self-debug," in *International Conference on Learning Representations (ICLR)*, 2024.

[13] C. Geuzaine and J.-F. Remacle, "Gmsh: A 3-D finite element mesh generator with built-in pre- and post-processing facilities," *International Journal for Numerical Methods in Engineering*, vol. 79, no. 11, pp. 1309–1331, 2009.

[14] G. Dhondt, *The Finite Element Method for Three-Dimensional Thermomechanical Applications*. Wiley, 2004.

[15] A. Yang *et al.*, "Qwen3 technical report," arXiv:2505.09388, 2025.

[16] Z. Shao, P. Wang, Q. Zhu, R. Xu, J. Song, X. Bi, H. Zhang, M. Zhang *et al.*, "DeepSeekMath: Pushing the limits of mathematical reasoning in open language models," arXiv:2402.03300, 2024.

[17] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient finetuning of quantized LLMs," in *Advances in Neural Information Processing Systems 36 (NeurIPS)*, 2023.

[18] W. Kwon, Z. Li, S. Zhuang, Y. Sheng, L. Zheng, C. H. Yu, J. E. Gonzalez, H. Zhang, and I. Stoica, "Efficient memory management for large language model serving with PagedAttention," in *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP)*, 2023, pp. 611–626.