

MV Spares suitable for 8BK88+ Panel Type 3AH0 12kV 26.3kA 800A to 1600A

SIEMENS

Electrical Components commonly used in 3AH0 12kV

Description of products	Remarks Resistance at 20 Degree C	Snaps of Products
Closing / Tripping Coil: Rating - 24V to 250V DC (3AY1510)	OHM (as per requirement)	Closing / Tripping Coil
Spring Charging: Motor - 220V (3AY1611-0F)	220V DC	
Motor - 110V DC / V AC (3AY1611-0E)	110V DC	For Gear Box - drive mechanism Motor
2ND SHUNT REL 24V to 220V DCS.NO.	3AX1101	
2ND SHUNT REL 100-110V AC 50Hz	3AX1101	WINDS SERVERS
2ND SHUNT REL 230V AC 50Hz	3AX1101	Transmission to the state of th
		MAGARINES AND

Description of Additional Trip Coil CT Operated, Undervoltage Coil	Remarks	Snaps of Products
CT OPERAT. RELEASE 0.5A	3AX1102	
Under Voltage Coil 24V to 220V DC	3AX1103	
U/V REL 100V to 230V AC 50HZ	3AX1103	
		WINDSHEAD SECTION OF THE PARTY
Limit (Snap) switch	Minimum Order Qty of 5 Nos.	NCCC OF CONTROL STATE OF CONTROL
Auxiliary switch 6NO+6NC (3SV92 74)	Installation At Switch Off	THE COLUMN TWO IS NOT
Auxiliary switch 12NO+12NC (3SV92 74)	Block	
Test / Service Position switch (4NO+4NC)	Installation at Drive Box	

Description of Antipumping Contactor	Remarks	Snaps of Products
Anti-pumping contactor, 2NO+2NC - 24V to 220V DC		
	Installation near Switch Off Block	100
Rectifier		3 (*) AAX 1055 - 15* - ab (*) 1 44) ESTANS (*) 2
Male Pin for 64 Assembly		
Female Pin for 64 Assembly	A 1 3 3	
64 Plug Pin Assembly		
24 / 32 Plug Pin Assembly		The state of the s

VCB Pole Spares 3AH0 12kV 26.3 kA 800 / 1250 / 1600 AMP for one VCB

Sr. No.	Spare Requirements	Product Descriptions	Rating	Images
1	Mandatory	Vacuum Interrupter VS 12025 GB	800 to 1600 Amp	
2	Mandatory	Housing with Nut plate	800 to 1250 Amp	
3	Mandatory	Housing with Nut plate	1600 Amp	
4	Recommended	Switch Off Spring (RED)	800 to 1250 Amp	
_		Upper Contact Arms	800 Amp	
5	Mandatory	Upper Contact Arms	1250 Amp	
6	Mandaton	Lower Contact Arms	800 Amp	
6	Mandatory	Lower Contact Arms	1250 Amp	
7	Mandatory	Upper Contact Arms	1600 Amp	
8	Mandatory	Lower Contact Arms	1600 Amp	
9	Mandatory	Tube Support	800 to 1600 Amp	
10	Mandatory	Current Link	800 to 1250 Amp	
11	Mandatory	Current Link	1600 Amp	
12	Mandatory	Insulating Stud	800 to 1600 Amp	
13	Mandatory	Switching Bar Assembly	800 to 1600 Amp	
14	Recommended	Lever 25 KA	800 to 1600 Amp	
15	Recommended	Bracket 25 KA	800 to 1600 Amp	
16	Mandatory	Pole Cover	800 to 1600 Amp	

VCB Mechanism Spares For 3AHO 12kV 26.3 kA

Sr. No.	Spare Requirements	Product Descriptions	Rating	lmages
1	Mandatory	Gear Box	All	
2	Mandatory	Switch Off Block	All	
3	Mandatory	Shock Absorber D3	All	
4	Mandatory	Switch ON Spring (Red) NoANGLE FEZN 3AH5	All	
5	Mandatory	Tie Rod (3AH5)	All	
6	Mandatory	Operation Counter	All	349976
7	Mandatory	Mechanical Interlock	All	

Sr. No.	Spare Requirements	Product Descriptions	Rating	Images
8	Recommended	Complete Switching shaft with bearing + Bearing	All	
9	Mandatory	Spring charging handle	All	
10	Mandatory	Damping Plate Assembly	All	
11	Mandatory	Drive Box 600mm	All	
12	Recommended	Securing Elements 1 Packet	All	
13	Recommended	Double bit key	All	
14	Recommended	Rack in – Rack out handle	All	

Sr. No.	Spare Requirements	Product Descriptions	Rating	lmages
1	Mandatory	Upper Bushing Assembly L1, L2, L3 Upper Bushing Assembly L1, L2, L3 New design Dia 27	1250 Amp	1/YPh e
		Upper Bushing Assembly L1, L2, L3	1600 Amp	
2	Mandatory	Lower Bushing For 12 kV	1250 Amp	
3	Mandatory	Lower Bushing For 12 kV (HTCT)	1250 Amp	
4	Mandatory	Upper Bushing Assembly 30 DIA AL (L1, L2, L3 PHASE) Upper Bushing Assembly 40 DIA AL (L1, L2, L3 PHASE)	800 to 1250 Amp	

Sr. No.	Spare Requirements	Product Descriptions	Rating	lmages
5	Mandatory	CT Bushing Assembly CT Bushing -1, 2, 3 Assembly	1250 to 1600 Amp	VAR NO. A B CU.WT EPOXY WT. 0-01 95.0 485.0 2.17 3.426 0-02 170.0 560.0 2.62 3.800 0-03 245.0 635.0 3.07 4.150 0-04 300.0 690.0 3.40 4.40
6	Mandatory	Insulator Dia 61 X 130 mm Length	800 to 1600 Amp	
7	Mandatory	Space Heater	800 to 1600 Amp	E Commence of the commence of
8	Mandatory	Thermostate	800 to 1600 Amp	
9	Optional	HYGROSTAT 8MR2170-4E (Optional) Hygrotherm	800 to 1600 Amp	
10	Mandatory	Local Remote Switch (Kaycee / Switron) Lockable / Non Lockable option	800 to 1600 Amp	105AL
11	Mandatory	Breaker Control Switch (Kaycee / Switron) Lockable / Non Lockable option	800 to 1600 Amp	
12	Recommend	Shroud	Upto 1600 Amp	

SPARES FOR CONTACT

Connector	Aux. Switch	Aux. Voltage
X	Υ	Z
24 / 32 / 64 PIN	6 NO + 6 NC / 12 NO + 12 NC	24 / 30 / 48 / 60 / 110 / 220V DC

Electrical & Maitainance Kit 1-B




VCB Pole Kit 3AH0 800/1250 A Figure: 2-CA



VCB Pole Kit 3AHO 1600A Figure: 2-CB



VCB Mechanism Kit 3AH0 Figure: 3C



VCB Rack in Mechanism Kit Figure: 5C



