

MQTT – Current Sensor – Module

Summary:

Module for the ESP32 S3 based modular controller board.
Module is designed to run 3 x 4–20mA Sensors, and read them
at a resolution of 15 bit.

Table of Contents


Page 2: Controller
Page 3: Headers
Page 4: SensorRecievers
Page 5: AnalogDigitalConverter
Page 6: SensorPowerConversion

Non BOM Items


—


Additional BOM Items


—




Sheet: /		
File: MQTT–Module–CurrentSensors.kicad_sch		
Title: MQTT – Current Sensor – Module		
Size: A4	Date: 2026–07–07	Rev: 1.0
KiCad E.D.A. 9.0.6	Id: 1/6	










Summary:
 – ADS1115 configured to use base address (0x48).

Sheet: /AnalogDigitalConverter/
 File: adc.kicad_sch

Title: Analog Digital Converter

Size: A4	Date: 2026-07-07	Rev: 1.0
KiCad E.D.A. 9.0.6		Id: 5/6



Summary:

- Texas Instruments generated Boost Converter, 12V to -25V
- Used a shielded inductor for minimal interference.

Sheet: /SensorPowerConversion/

File: sensorpowerconversion.kicad_sch

Title: Sensor Power Conversion

Size: A4

Date: 2026-07-07

Rev: 1.0

KiCad E.D.A. 9.0.6

Id: 6/6