



Presentation The Port Authority of NY & NJ Multifunctional snow removal vehicles

Øveraasen RS 400 runway sweepers Mercedes Benz / Øveraasen 2043 AS 4x4 trucks Øveraasen EP 9 snow plows

























General

Total length : 41 ft 8 in

Height : 10 ft 8 in

Width : 20 ft 3 in

Width transport : 9 ft 2 in

Brush diameter : 3 ft 10 in

Brush length : 20 ft 6 in

Brush material : Steel or poly

Brush speed : 0 - 720 rpm

Capasity data

Working width : 18 ft

Clearing capacity : 3 848 098 ft²

Working speed : 16 - 40 mph

Fan capacity : 1 412 587 ft³

Blowing speed : 336 mph

Engine

Engine : MTU 6R1100 EU Stage IV (Tier 4)

Power rating : 320 kW at 1700 rpm

Torque : 2100 Nm at 1300 rpm

Volumes

Fuel tank : 264 US gal

AdBlue tanks : 10 US gal

Hydraulic oil tank : 39 US gal

Electrical system


Voltage : 24 Volt

Batteries : 2x12V 170 Ah

Controllers : Danfoss Plus1



RS 400 Performance Line Drawing









OVERASENSNOWREMOVAL SYSTEMS

















RS 400 Performance Line (package)















Rear hood tilted











High capacity blowing fan

Panel and joystick in drivers cabin















EP 9 plough

- Working width : 22 ft 4 in

: 28 ft 3 in - Max width

- Number of elements : 9 pcs

- Blade width : 3 ft

- Blade height : 3 ft 11 in

- Working angle : 35°

- Weight incl. hitch : 4 475 lb

- Retract height, element: app. 5 in

- Lifting device : DuoLift parallellogram

- Parking system : Foldable wings








Drawings, EP 9 snow plow









Mercedes Benz / Øveraasen 2043 AS 4x4 truck



- Model

- Engine power

- Total weight

- Steering

- Fuel tank

- Batteries

- Emission standard

: 2043 AS 4x4

: 316 kW (430 hp)

: app. 48 500 lb

: LHD

: xxx l

: 180 Ah

: EURO 6







RS 400 Performance Line main advantages

沙兰

- Aerodynamic design for high working speeds
- Strong, heavy design without any vibrations or bouncing
- No sensible micro switches
- Automatic brush adjustment according to speed and wear
- · Effective clearing width up to 18 ft
- Working speed with total stability 40 mph
- New generation variable capacity fan up to 1 412 587 ft³/h in air tunnel at 336 mph
- Air nozzles and tunnel in front of the rear wheels
- Large size brush diameter 3 ft 10 in
- Large size support wheels
- Hydraulic fittings in non-corrosive material
- · All Din A4 stainless steel bolts and nuts
- Easy access for service and maintenance
- Latest generation EURO MOT 4 engine (Tier 4)
- MTU engine 6R1000 P=260 kW / 6R1100 P=320 kW



RS 400 Performance Line main advantages

- •Large diesel tank for 40 50 hours of operation
- Latest standard of hydraulic components
- Unique broom suspension system with mechanical float
- Special corrosion treatment and choice of materials
- Maximum brush speed v=103 mph
- Adjustable fifth wheel coupling as standard
- Strong rear bumper
- Lower investment and considerably reduced operational costs
- •(100 hours minimum per set of cassettes!)
- Extremely low life cycle cost
- Modern control panel
- Easy operation
- Joystick in armrest (Plough, brush, fan)
- •Good access to brush core to change cassettes (20 minutes)
- Variation of different options (heater, battery charger, arctic packages etc.)
- Unique Performance-Line package



RS 400 "Performance Line Package"



This package is an option and contains the following equipment at an interesting price:

- Aerodynamic main frame cover
- Orange side marking lights (engine hood and frame cover)
- ·Safety upper light bar rear
- Central lubrication system
- PC-based service tool with programs
- •220 Volt engine heater
- •220 Volt battery charger
- •220 Volt hydraulic tank heater
- •Summer/winter switch for heater and charger
- •24 Volt NATO emergency start socket
- QR code for easy access to service package
- Personal airport logo on frame cover
- Considerably savings compared to buying each option separately!







Presentation The Port Authority of NY & NJ Multifunctional snow removal vehicles

Øveraasen RS 400 runway sweepers

Mercedes Benz / Øveraasen 2043 AS 4x4 trucks

Øveraasen EP 9 snow plows





















General

Total length : 41 ft 8 in

Height : 10 ft 8 in Width : 20 ft 3 in

Width transport : 9 ft 2 in

Brush diameter : 3 ft 10 in

Brush length : 20 ft 6 in

Brush material : Steel or poly

Brush speed : 0 - 720 rpm

Capasity data

Working width : 18 ft

Clearing capacity : 3 848 098 ft²

Working speed : 16 - 40 mph

Fan capacity : 1 412 587 ft³

Blowing speed : 336 mph

Engine

Engine : MTU 6R1100 EU Stage IV (Tier 4)

Power rating : 320 kW at 1700 rpm

Torque : 2100 Nm at 1300 rpm

Volumes

Fuel tank : 264 US gal

AdBlue tanks : 10 US gal

Hydraulic oil tank : 39 US gal

Electrical system


Voltage : 24 Volt

Batteries : 2x12V 170 Ah

Controllers : Danfoss Plus1



RS 400 Performance Line Drawing






















RS 400 Performance Line (package)













Rear hood tilted













High capacity blowing fan

Panel and joystick in drivers cabin















EP 9 plough

- Working width : 22 ft 4 in

- Max width : 28 ft 3 in

- Number of elements : 9 pcs

- Blade width : 3 ft

- Blade height : 3 ft 11 in

- Working angle : 35°

- Weight incl. hitch : 4 475 lb

- Retract height, element: app. 5 in

- Lifting device : DuoLift parallellogram

Parking system : Foldable wings










Drawings, EP 9 snow plow















- Model

- Engine power

- Total weight

- Steering

- Fuel tank

- Batteries

- Emission standard

: 2043 AS 4x4

: 316 kW (430 hp)

: app. 48 500 lb

: LHD

: xxx

: 180 Ah

: EURO 6









RS 400 Performance Line main advantages

- Aerodynamic design for high working speeds
- Strong, heavy design without any vibrations or bouncing
- No sensible micro switches
- Automatic brush adjustment according to speed and wear
- Effective clearing width up to 18 ft
- Working speed with total stability 40 mph
- New generation variable capacity fan up to 1 412 587 ft³/h in air tunnel at 336 mph
- Air nozzles and tunnel in front of the rear wheels
- Large size brush diameter 3 ft 10 in
- Large size support wheels
- Hydraulic fittings in non-corrosive material
- All Din A4 stainless steel bolts and nuts
- Easy access for service and maintenance
- Latest generation EURO MOT 4 engine (Tier 4)
- MTU engine 6R1000 P=260 kW / 6R1100 P=320 kW



RS 400 Performance Line main advantages

- Large diesel tank for 40 50 hours of operation
- Latest standard of hydraulic components
- Unique broom suspension system with mechanical float
- Special corrosion treatment and choice of materials
- Maximum brush speed v=103 mph
- Adjustable fifth wheel coupling as standard
- Strong rear bumper
- Lower investment and considerably reduced operational costs
- •(100 hours minimum per set of cassettes!)
- Extremely low life cycle cost
- Modern control panel
- Easy operation
- Joystick in armrest (Plough, brush, fan)
- Good access to brush core to change cassettes (20 minutes)
- Variation of different options (heater, battery charger, arctic packages etc.)
- Unique Performance-Line package









RS 400 "Performance Line Package"



This package is an option and contains the following equipment at an interesting price:

- Aerodynamic main frame cover
- Orange side marking lights (engine hood and frame cover)
- Safety upper light bar rear
- Central lubrication system
- PC-based service tool with programs
- •220 Volt engine heater
- 220 Volt battery charger
- •220 Volt hydraulic tank heater
- Summer/winter switch for heater and charger
- 24 Volt NATO emergency start socket
- •QR code for easy access to service package
- Personal airport logo on frame cover
- Considerably savings compared to buying each option separately!

