Principles and Applications of Microcontrollers

Yan-Fu Kuo
Dept. of Bio-industrial Mechatronics Engineering
National Taiwan University

Today:

- Pulse width modulation (PWM)



Outline

- Pulse width modulation (PWM)
  - What is PWM?
  - AVR PWM pinout
  - Fast PWM
  - Phase correct PWM
  - Square wave
  - Duty cycle and frequency
- Getting started



Pulse Width Modulation

- An approach of approximating analog signal in the form of pulses (binary signal)



Analog Signal

Width Modulated Pulses

Advantages and Application

- Advantage:
  - Providing control on output power of a binary output device without changing hardware
  - Digital signal is resistant to noise
  - Less heat dissipated versus using resistors for intermediate voltage values
- Application:
  - Electric stove heater
  - Lamp dimmers
  - Voltage regulation – convert 12 volts to 5 volts by having a 41.7% duty cycle
  - Sound production

PWM Pinout


(PCINT14/RESET) PC6 1
(PCINT16/RXD) PD0 2
(PCINT17/TXD) PD1 3
(PCINT18/INT0) PD2 4
(PCINT19/OC2B/INT1) PD3 5
(PCINT20/XCK/T0) PD4 6
VCC 7
GND 8
(PCINT6/XTAL1/TOSC1) PB6 9
(PCINT7/XTAL2/TOSC2) PB7 10
(PCINT21/OC0B/T1) PD5 11
(PCINT22/OC0A/AIN0) PD6 12
(PCINT23/AIN1) PD7 13
(PCINT0/CLKO/ICP1) PB0 14
28 PC5 (ADC5/SCL/PCINT13)
27 PC4 (ADC4/SDA/PCINT12)
26 PC3 (ADC3/PCINT11)
25 PC2 (ADC2/PCINT10)
24 PC1 (ADC1/PCINT9)
23 PC0 (ADC0/PCINT8)
22 GND
21 AREF
20 AVCC
19 PB5 (SCK/PCINT5)
18 PB4 (MISO/PCINT4)
17 PB3 (MOSI/OC2A/PCINT3)
16 PB2 (SS/OC1B/PCINT2)
15 PB1 (OC1A/PCINT1)

Factors to Consider

1. Frequency
2. Duty cycle $= \frac{Pulse\ Width}{Period}$



Outline (Cont'd)

- Pulse width modulation (PWM)
  - What is PWM?
  - AVR PWM pinout
  - Fast PWM
  - Phase correct PWM
  - Square wave
  - Duty cycle and frequency
- Getting started



Fast PWM

- Timers are used to generate PWM signals
- OCR0A determines the duty cycle



TCNT0: 0 → 0xFF



PWM Mode Control: TCCR0A/B



- Re

WGM02	WGM01	WGM00	Comment
0	0	0	Normal
0	0	1	Phase Correct PWM, top 0xFF
0	1	0	CTC (Clear Timer on Compare Match)
0	1	1	Fast PWM, top 0xFF
1	0	0	Reserved
1	0	1	Phase Correct PWM, top OCR0A
1	1	0	Reserved
1	1	1	Fast PWM, top OCR0A

Fast PWM Frequency

f_{CLK}





$f_{CLK} \div p$

$f_{PWM} = f_{CLK} \div p \div 256$





Review: Timer Prescaler Control (TCCR0A/B)



CS02	CS01	CS00	Comment
0	0	0	No clock source (Timer/Counter stopped)
0	0	1	clk (No Prescaling)
0	1	0	clk / 8
0	1	1	clk / 64
1	0	0	clk / 256
1	0	1	clk / 1024
1	1	0	External clock source on T0 pin. Clock on falling edge
1	1	1	External clock source on T0 pin. Clock on rising edge

Fast PWM Duty Cycle (OC0A)

- Non-inverted vs. inverted







Non-inverted mode

$$Duty\ cycle = \frac{OCR0A + 1}{256} \times 100$$

Inverted mode

$$Duty\ cycle = \frac{255 - OCR0A}{256} \times 100$$

OC0A Invert Control: TCCR0A/B



Compare Output Mode

	COM0A1	COM0A0	Comment
Fast PWM	0	0	PWM off
	0	1	WGM02 = 0: PWM off WGM02 = 1: Toggle OC0A on compare match
	1	0	PWM, non-inverted
	1	1	PWM, inverted

	COM0A1	COM0A0	Comment
Phase Correct PWM	0	0	PWM off
	0	1	WGM02 = 0: PWM off WGM02 = 1: Toggle OC0A on compare match
	1	0	PWM, non-inverted
	1	1	PWM, inverted

Fast PWM Duty Cycle (OC0B)

- Non-inverted vs. inverted







Non-inverted mode

$$Duty\ cycle = \frac{OCR0B + 1}{256} \times 100$$

Inverted mode

$$Duty\ cycle = \frac{255 - OCR0B}{256} \times 100$$

OC0B Invert Control: TCCR0A/B



Compare Output Mode

	COM0A1	COM0A0	Comment
Fast PWM	0	0	PWM off
	0	1	WGM02 = 0: PWM off WGM02 = 1: Toggle OC0B on compare match
	1	0	PWM, non-inverted
	1	1	PWM, inverted
	COM0A1	**COM0A0**	**Comment**
Phase Correct PWM	0	0	PWM off
	0	1	WGM02 = 0: PWM off WGM02 = 1: Toggle OC0B on compare match
	1	0	PWM, non-inverted
	1	1	PWM, inverted

Example: Fast PWM

- Suppose the MCU runs at 1Mhz
- Generate PWM waves using Timer0 (non-inverted)
- Output a wave of 80% duty cycle at PD6 (OC0A)
- Output a wave of 20% duty cycle at PD5 (OC0B)
- Prescaler factor $p = 1024$





Flowchart (Fast PWM)

- What value do we set to the controller registers?

$$f_{PWM} = 10^6 \div 1024 \div 256 \approx 3.8 \text{ Hz}$$

$$\frac{OCR0A + 1}{256} \times 100 = 80 \implies OCR0A = 203$$

$$\frac{OCR0B + 1}{256} \times 100 = 20 \implies OCR0B = 50$$





Fast PWM at 3.8 Hz

```
#include <avr/io.h>

int main(void)
{
    CLKPR=(1<<CLKPCE);
    CLKPR=0b00000011;              // set clk to 1Mhz
 ① DDRD=0xFF;                      // PORTD as output
 ② OCR0A=203;                      // 80% duty cycle
    OCR0B=50;                      // 20% duty cycle
 ③ TCCR0A=0b10100011;              // fast PWM, non-inverted
 ④ TCCR0B=0b00000101;              // timer prescaler
}
```

Outline (Cont'd)

- Pulse width modulation (PWM)
  - What is PWM?
  - AVR PWM pinout
  - Fast PWM
  - Phase correct PWM
  - Square wave
  - Duty cycle and frequency
- Getting started



Phase Correct PWM

- Timers are used to generate PWM signals



TCNT0: 0 → 0xFF → 0

Phase Correct PWM Frequency and Duty Cycle

- $f_{PWM} = f_{CLK} \div p \div 510$ (p: scalar factor of the timer)
- Non-inverted vs. inverted



Non-inverted mode

$$\frac{Duty}{cycle} = \frac{OCR0A + 1}{255} \times 100$$

Inverted mode

$$\frac{Duty}{cycle} = \frac{255 - OCR0A}{255} \times 100$$

Example: Phase Correct PWM

- Suppose the MCU runs at 1Mhz
- Generate PWM waves using Timer0 (non-inverted)
- Output a wave of 80% duty cycle at PD6 (OC0A)
- Output a wave of 20% duty cycle at PD5 (OC0B)
- Prescaler factor $p = 1024$





Flowchart (Phase Correct PWM)

- What value do we set the controller registers?

$$f_{PWM} = 10^6 \div 1024 \div 510 \approx 1.9 \text{ Hz}$$

$$\frac{OCR0A + 1}{255} \times 100 = 80 \implies OCR0A = 203$$

$$\frac{OCR0B + 1}{255} \times 100 = 20 \implies OCR0B = 50$$





Phase Correct PWM at 1.9Hz

```
#include <avr/io.h>

int main(void)
{
    CLKPR=(1<<CLKPCE);
    CLKPR=0b00000011;              // set clk to 1Mhz
 ① DDRD=0xFF;                      // PORTD as output
 ② OCR0A=203;                      // 80% duty cycle
    OCR0B=50;                      // 20% duty cycle
 ③ TCCR0A=0b10100001;              // phase correct PWM
 ④ TCCR0B=0b00000101;              // timer prescaler
}
```

Outline (Cont'd)

- Pulse width modulation (PWM)
  - What is PWM?
  - AVR PWM pinout
  - Fast PWM
  - Phase correct PWM
  - Square wave
  - Duty cycle and frequency
- Getting started



Square Wave with Frequency Control

- Generate square waves with various frequencies

$$f_{PWM} = \frac{f_{CLK}}{(OCR0A + 1) \times p}$$



Note: duty cycle cannot be controlled in this mode!

Square Wave Frequency Control: Mode Setup



WGM02	WGM01	WGM00	Comment
0	0	0	Normal
0	0	1	Phase Correct PWM, top 0xFF
0	1	0	CTC (Clear Timer on Compare Match)
0	1	1	Fast PWM, top 0xFF
1	0	0	Reserved
1	0	1	Phase Correct PWM, top OCR0A
1	1	0	Reserved
1	1	1	Fast PWM, top OCR0A

Square Wave Frequency Control: Toggle Setup



Compare Output Mode

Fast PWM

COM0A1	COM0A0	Comment
0	0	PWM off
0	1	WGM02 = 0: PWM off WGM02 = 1: Toggle OC0A on compare match
1	0	PWM, non-inverted
1	1	PWM, inverted

Phase Correct PWM

COM0A1	COM0A0	Comment
0	0	PWM off
0	1	WGM02 = 0: PWM off WGM02 = 1: Toggle OC0A on compare match
1	0	PWM, non-inverted
1	1	PWM, inverted

Example: Varying LED Flash Frequency

- Suppose the MCU runs at 1Mhz
- Generate square waves continuously using PWM
- Vary the OCR0A from 30 to 250 with an increment of 55
- Output the wave at PD6 (OC0A)
- Prescaler factor $p = 1024$





Flowchart (LED Flash)

$$f_{PWM} = \frac{10^6}{(30+1)\times 1024} \approx 31.5 \text{ Hz}$$

$$f_{PWM} = \frac{10^6}{(250+1)\times 1024} \approx 3.9 \text{ Hz}$$

- What value do we set the controller registers?





Varying LED Flash Frequency

```
#define F_CPU 1000000UL
#include <avr/io.h>
#include <util/delay.h>

int main(void)
{
    CLKPR=(1<<CLKPCE);
    CLKPR=0b00000011;                  // set clk to 1Mhz
 ① DDRD=0xFF;                          // PORTD as output
 ② TCCR0A=0b01000011;                  // TOP OCR0A, toggle at TOP
 ③ TCCR0B=0b00001101;                  // timer prescaler
    while (1){
        for (int i=30; i<=250; i=i+55){
 ④          OCR0A=i;
            _delay_ms(2000);
        }
    }
}
```

Outline (Cont'd)

- Pulse width modulation (PWM)
  - What is PWM?
  - AVR PWM pinout
  - Fast PWM
  - Phase correct PWM
  - Square wave
  - Duty cycle and frequency control
- Getting started



PWM Modes of Timer/Counter1



Mode	WGM 13	WGM 12	WGM 11	WGM 10	Timer/counter mode	TOP	Update of OCR1x at	TOV1 flag set on
0	0	0	0	0	Normal	0xFFFF	Immediate	MAX
1	0	0	0	1	PWM, Phase Correct, 8-bit	0x00FF	TOP	BOTTOM
2	0	0	1	0	PWM, Phase Correct, 9-bit	0x01FF	TOP	BOTTOM
3	0	0	1	1	PWM, Phase Correct, 10-bit	0x03FF	TOP	BOTTOM
4	0	1	0	0	CTC	OCR1A	Immediate	MAX
5	0	1	0	1	Fast PWM, 8-bit	0x00FF	BOTTOM	TOP
6	0	1	1	0	Fast PWM, 9-bit	0x01FF	BOTTOM	TOP
7	0	1	1	1	Fast PWM, 10-bit	0x03FF	BOTTOM	TOP
8	1	0	0	0	PWM, Phase and Frequency Correct	ICR1	BOTTOM	BOTTOM
9	1	0	0	1	PWM, Phase and Frequency Correct	OCR1A	BOTTOM	BOTTOM
10	1	0	1	0	PWM, Phase Correct	ICR1	TOP	BOTTOM
11	1	0	1	1	PWM, Phase Correct	OCR1A	TOP	BOTTOM
12	1	1	0	0	CTC	ICR1	Immediate	MAX
13	1	1	0	1	(Reserved)	–	–	–
14	1	1	1	0	Fast PWM	ICR1	BOTTOM	TOP
15	1	1	1	1	Fast PWM	OCR1A	BOTTOM	TOP

Example: 46Hz with 8% Duty Cycle

- Suppose the MCU runs at 1MHz
- Generate a wave as the figure (46Hz and 8% duty cycle)
- Use PWM of Timer1
- Prescaler factor $p = 1$





Example: 46Hz with 8% Duty Cycle (Cont'd)

- Strategy:
  1. Mode 14 fast PWM
  2. Set frequency using **ICR1**

$$f = \frac{10^6}{\textbf{ICR1}} = 46$$

$$\Rightarrow \textbf{ICR1} = 21701$$

  3. Set duty cycle using **OCR1A**

$$DC = \frac{1.7}{20+1.7} = \frac{\textbf{OCR1A}}{\textbf{ICR1}}$$

$$\Rightarrow \textbf{OCR1A} = 1700$$



OC1A Toggle Mode: TCCR0A



Compare Output Mode

	COM0A1	COM0A0	Comment
Fast PWM	1	0	Clear OC1A on compare match, Set OC1A at BOTTOM
	1	1	Set OC1A on compare match, Clear OC1A at BOTTOM

	COM0A1	COM0A0	Comment
Phase Correct PWM	1	0	Clear OC1A on compare match, Set OC1A at BOTTOM
	1	1	Set OC1A on compare match, Clear OC1A at BOTTOM

Note: the setup for OC1B is the same

46Hz with 8% Duty Cycle

	1	0	0	0	0	0	1	0
TCCR1A	COM1A1	COM1A0	COM1B1	COM1B0	-	-	WGM11	WGM10
	0	0	0	1	1	1	0	1
TCCR1B	ICNC1	ICES1	-	WGM13	WGM12	CS12	CS11	CS10

```
#include <avr/io.h>

int main(void)
{
    CLKPR=(1<<CLKPCE);
    CLKPR=0b00000011;              // set clk to 1Mhz
    DDRB=0xFF;                     // PORTB as output
    ICR1=21701;
    OCR1A=1700;
    TCCR1A=0b10000010;
    TCCR1B=0b00011001;
}
```

Outline (Cont'd)

- Pulse width modulation (PWM)
  - What is PWM?
  - AVR PWM pinout
  - PWM modes
- Getting started



Reference

- ATmega328P data sheet
- AVR 8-bit instruction set
- AVR131: Using the AVR's High-speed PWM
- M. A. Mazidi, S. Naimi, and S. Naimi, *The AVR Microcontroller and Embedded Systems: Using Assembly and C*, Prentice Hall, 2010