The gcodepreview PythonSCAD library*

Author: William F. Adams
willadams at aol dot com

2025/11/30

Abstract

The gcodepreview library allows using PythonSCAD (Python in OpenSCAD) to move a tool in lines and arcs and output DXF and G-code files so as to work as a CAD/CAM program for CNC.

Contents

*This file (`gcodepreview`) has version number v0.93, last revised 2025/11/30.

Contents

1 readme.md





```
# gcodepreview

OpenPythonSCAD library for moving a tool in lines and arcs so as to model how a part would be cut or extruded using G-Code, so as to allow use as a compleat CAD/CAM solution for subtractive or additive 3-axis CNC (4th-axis support may come in a future version) by writing out G-code in addition to 3D modeling (in certain cases toolpaths which would not normally be feasible in typical tools), and to write out DXF files which may be imported into a traditional CAM program to create toolpaths.

![OpenSCAD gcodepreview Unit Tests](https://raw.githubusercontent.com/WillAdams/gcodepreview/main/gcodepreviewtemplate.png?raw=true)

Uses Python in OpenSCAD: https://pythonscad.org/[^pythonscad]

[^pythonscad]: Previously this was http://www.guenther-sohler.net/openscad/

A BlockSCAD file for the initial version of the
main modules is available at:

https://www.blockscad3d.com/community/projects/1244473

The project is discussed at:

https://willadams.gitbook.io/design-into-3d/programming

Since it is now programmed using Literate Programming (initially a .dtx, now a .tex file) there is a PDF: https://github.com/WillAdams/gcodepreview/blob/main/gcodepreview.pdf which includes all of the source code with commentary.

The files for this library are:

 - gcodepreview.py (gcpy) --- the Python class/functions and variables
 - gcodepreview.scad (gcpscad) --- OpenSCAD modules and parameters

And there several sample/template files which may be used as the starting point for a given project:

 - gcodepreviewtemplate.txt (gcptmpl) --- .txt file collecting all commands with brief comments which may be used as a quick reference or copy-pasting from
 - gcodepreviewtemplate.py (gcptmplpy) --- .py example file
 - gcodepreviewtemplate.scad (gcptmplscad) --- .scad example file
 - gcpdxf.py (gcpdxfpy) --- .py example file which only makes dxf file(s) and which will run in "normal" Python in addition to PythonSCAD
 - gcpgc.py (gcpgc) --- .py example which loads a G-code file and generates a 3D preview showing how the G-code will cut

Note that additional templates are in: https://github.com/WillAdams/gcodepreview/tree/main/templates

If using from PythonSCAD, place the files in C:\Users\\\~\Documents
```

```
\OpenSCAD\libraries or, load them from Github using the command:

    nimport("https://raw.githubusercontent.com/WillAdams/gcodepreview/refs/heads/main/gcodepreview.py")

If using gcodepreview.scad call as:

    use <gcodepreview.py>
    include <gcodepreview.scad>

Note that it is necessary to use the first file (this allows loading the Python commands and then include the last file (which allows using OpenSCAD variables to selectively implement the Python commands via their being wrapped in OpenSCAD modules) and define variables which match the project and then use commands such as:

    opengcodefile(Gcode_filename);
    opendxffile(DXF_filename);

    gcp = gcodepreview("cut", true, true);

    setupstock(219, 150, 8.35, "Top", "Center");

    movetosafeZ();

    toolchange(102, 17000);

    cutline(219/2, 150/2, -8.35);

    stockandtoolpaths();

    closegcodefile();
    closedxffile();

which makes a G-code file:

![OpenSCAD template G-code file](https://raw.githubusercontent.com/WillAdams/gcodepreview/main/gcodepreview_template.png?raw=true)

but one which could only be sent to a machine so as to cut only the softest and most yielding of materials since it makes a single full-depth pass, and which has a matching DXF which may be imported into a CAM tool --- but which it is not directly possible to assign a toolpath in readily available CAM tools (since it varies in depth from beginning-to-end which is not included in the DXF since few tools make use of that information).

Importing this DXF and actually cutting it is discussed at:

https://forum.makerforums.info/t/rewriting-gcodepreview-with-python/88617/14

Alternately, gcodepreview.py may be placed in a Python library location and used directly from Python to generate DXFs as shown in gcpdxf.py (generating a 3D preview requires OpenPythonSCAD and generating G-code without a preview is not supported).

In the current version, tool numbers may match those of tooling sold by Carbide 3D (ob. discl., I work for them) and other vendors, or, a vendor-neutral system may be worked up and used as desired.

Comments are included in the G-code to match those expected by CutViewer, allowing a direct preview without the need to maintain a tool library (for such tooling as that program supports).

Supporting OpenSCAD usage makes possible such examples as: openscad_gcodepreview_cutjoinery.tres.scad which is made from an OpenSCAD Graph Editor file:

![OpenSCAD Graph Editor Cut Joinery File](https://raw.githubusercontent.com/WillAdams/gcodepreview/main/OSGE_cutjoinery.png?raw=true)

| Version       | Notes         |
```

```
rdme | ------------- | ------------ |
rdme | 0.1           | Version  supports setting up stock, origin, rapid positioning, making cuts, and writing out matching G-code, and creating a DXF with polylines. |
rdme |               |  - separate dxf files are written out for each tool where tool is ball/square/V and small/large (10/31/23) |
rdme |               |  - re-writing as a Literate Program using the LaTeX package docmfp (begun 4/12/24) |
rdme |               |  - support for additional tooling shapes such as dovetail and keyhole tools |
rdme | 0.2           | Adds support for arcs, specialty toolpaths such as Keyhole which may be used for dovetail as well as keyhole cutters |
rdme | 0.3           | Support for curves along the 3rd dimension, roundover tooling |
rdme | 0.4           | Rewrite using literati documentclass, suppression of SVG code, dxfrectangle |
rdme | 0.5           | More shapes, consolidate rectangles, arcs, and circles in gcodepreview.scad |
rdme | 0.6           | Notes on modules, change file for setupstock |
rdme | 0.61          | Validate all code so that it runs without errors from sample (NEW: Note that this version is archived as gcodepreview-openscad_0_6.tex and the matching PDF is available as well|
rdme | 0.7           | Re-write completely in Python |
rdme | 0.8           | Re-re-write completely in Python and OpenSCAD, iteratively testing |
rdme | 0.801         | Add support for bowl bits with flat bottom |
rdme | 0.802         | Add support for tapered ball-nose and  V tools with flat bottom |
rdme | 0.803         | Implement initial color support and joinery modules (dovetail and full blind box joint modules) |
rdme | 0.9           | Re-write to use Python lists for 3D shapes for toolpaths and rapids. |
rdme | 0.91          | Finish converting to native OpenPythonSCAD trigonometric functions. |
rdme | 0.92          | Remove multiple DXFs and unimplemented features, add hooks for 3D printing. |
rdme | 0.93          | Initial support for 3D printing. |
rdme
rdme Possible future improvements:
rdme
rdme  - support for 4th-axis
rdme  - support for post-processors
rdme  - support for two-sided machining (import an STL or other file to
```

```
      use for stock, or possibly preserve the state after one cut and
       then rotate the cut stock/part)
 - support for additional tooling shapes (lollipop cutters)
 - create a single line font for use where text is wanted
 - Support for METAPOST and Bézier curves (latter required for
      fonts if not to be limited to lines and arcs) and surfaces

Note for G-code generation that it is up to the user to implement
     Depth per Pass so as to not take a single full-depth pass as
     noted above. Working from a DXF of course allows one to off-load
      such considerations to a specialized CAM tool.

To-do:

 - implement skin()
 - determine why one quadrant of arc command doesn't work in
      OpenSCAD
 - clock-wise arcs
 - add toolpath for cutting countersinks using ball-nose tool from
      inside working out
 - verify OpenSCAD wrapper and add any missing commands for Python
 - verify support for shaft on tooling
 - create additional template and sample files
 - fully implement/verify describing/saving/loading tools using
      CutViewer comments

Deprecated features:

 - exporting SVGs --- coordinate system differences between
      OpenSCAD/DXFs and SVGs would require managing the inversion of
      the coordinate system (using METAPOST, which shares the same
      orientation and which can write out SVGs may be used for future
       versions)
 - using linear/rotate_extrude --- 2D geometry is rotated to match
      the arc of the movement, which is appropriate to a 5-axis
      machine, but not workable for a 3-axis. Adding an option to
      support the use of such commands for horizontal movement is
      within the realm of possibility.
 - multiple DXF files
 - RapCAD support
```

2 Usage and Templates

The gcodepreview library allows the modeling of 2D geometry and 3D shapes using Python or by calling Python from within Open(Python)SCAD, enabling the creation of 2D DXFs, G-code (which cuts a 2D or 3D part), or 3D models as a preview of how the file will cut. These abilities may be accessed in "plain" Python (to make DXFs), or Python or OpenSCAD in PythonSCAD (to make DXFs, and/or G-code with 3D modeling) for a preview. Providing them in a programmatic context allows making parts or design elements of parts (*e.g.*, joinery) which would be tedious or difficult (or verging on impossible) to draw by hand in a traditional CAD or vector drawing application. A further consideration is that this is "Design for Manufacture" taken to its ultimate extreme, and that a part so designed is inherently manufacturable (so long as the dimensions and radii allows for reasonable tool (and toolpath) geometries).

The various commands are shown all together in templates so as to provide examples of usage, and to ensure that the various files are used/included as necessary, all variables are set up with the correct names (note that the sparse template in `readme.md` eschews variables), and that if enabled, files are opened before being written to, and that each is closed at the end in the correct order. Note that while the template files seem overly verbose, they specifically incorporate variables for each tool shape, possibly in two different sizes, and a feed rate parameter or ratio for each, which may be used (by setting a tool #) or ignored (by leaving the variable for a given tool at zero (0)).

It should be that the readme at the project page which serves as an overview, and this section (which serves as a collection of templates and a tutorial) are all the documentation which most users will need (and arguably is still too much). The balance of the document after this section shows all the code and implementation details, and will where appropriate show examples of usage which will be collected in a plain text template file which is concatenated to provide a usable example of each command with (brief) commentary (potentially serving as a how-to guide as well as documenting the code in a minimalistic fashion) as well as Indices (which serve as a front-end for reference).



Some comments on the templates:

- minimal — each is intended as a framework for a minimal working example (MWE) — it should be possible to comment out unused/unneeded portions and so arrive at code which tests any aspect of this project and which may be used as a starting point for a new part/project
- compleat — a quite wide variety of tools are listed (and probably more will be added in the future), but pre-defining them and having these "hooks" seems the easiest mechanism to handle the requirements of subtractive machining.
- shortcuts — as the various examples show, while in real life it is necessary to make many passes with a tool, an expedient efficiency is to forgo the `loop` operation and just use a `hull()` operation and avoid the requirement of implementing Depth per Pass (but note that this will lose the previewing of scalloped tool marks in places where they might appear otherwise)

One fundamental aspect of this tool is the question of *Layers of Abstraction* (as put forward by Dr. Donald Knuth as the crux of computer science) and *Problem Decomposition* (Prof. John Ousterhout's answer to that question). To a great degree, the basic implementation of this tool will use G-code as a reference implementation, simultaneously using the abstraction from the mechanical task of machining which it affords as a decomposed version of that task, and creating what is in essence, both a front-end, and a tool, and an API for working with G-code programmatically. This then requires an architecture which allows 3D modeling (OpenSCAD), and writing out files (Python).

Further features will be added to the templates as they are created, and the main image updated to reflect the capabilities of the system.

2.1 gcpdxf.py

The most basic usage, with the fewest dependencies is to use "plain" Python to create `dxf` files. Note that this example includes an optional command `nimport(<URL>)` which if enabled/uncommented (and the following line commented out), will allow one to use OpenPythonSCAD to import the library from Github, sidestepping the need to download and install the library into an installation of OpenPythonSCAD locally. Usage in "normal" Python will require manually installing the `gcodepreview.py` file where Python can find it. A further consideration is where the file will be placed if the full path is not enumerated, the Desktop is the default destination for Microsoft Windows.

```
from openscad import *
        # nimport("https://raw.githubusercontent.com/WillAdams/gcodepreview/refs/heads/main/gcodepreview.py")
from gcodepreview import *

gcp = gcodepreview("no_preview", # "cut" or "print"
                   False, # generategcode
                   True   # generatedxf
                   )

# [Stock] */
stockXwidth = 100
# [Stock] */
stockYheight = 50

# [Export] */
Base_filename = "gcpdxf"


# [CAM] */
large_square_tool_num = 102
# [CAM] */
small_square_tool_num = 0
# [CAM] */
large_ball_tool_num = 0
# [CAM] */
small_ball_tool_num = 0
# [CAM] */
large_V_tool_num = 0
# [CAM] */
small_V_tool_num = 0
# [CAM] */
DT_tool_num = 374
# [CAM] */
KH_tool_num = 0
# [CAM] */
Roundover_tool_num = 0
# [CAM] */
MISC_tool_num = 0

# [Design] */
inset = 3
# [Design] */
radius = 6
# [Design] */
cornerstyle = "Fillet"  # "Chamfer", "Flipped Fillet"

gcp.opendxffile(Base_filename)

gcp.dxfrectangle(large_square_tool_num, 0, 0, stockXwidth, stockYheight)

gcp.setdxfcolor("Red")

gcp.dxfarc(large_square_tool_num, inset, inset, radius,  0, 90)
gcp.dxfarc(large_square_tool_num, stockXwidth - inset, inset, radius, 90, 180)
gcp.dxfarc(large_square_tool_num, stockXwidth - inset, stockYheight - inset, radius, 180, 270)
gcp.dxfarc(large_square_tool_num, inset, stockYheight - inset, radius, 270, 360)

gcp.dxfline(large_square_tool_num, inset, inset + radius, inset, stockYheight - (inset + radius))
gcp.dxfline(large_square_tool_num, inset + radius, inset, stockXwidth - (inset + radius), inset)
gcp.dxfline(large_square_tool_num, stockXwidth - inset, inset + radius, stockXwidth - inset, stockYheight - (inset + radius))
gcp.dxfline(large_square_tool_num, inset + radius, stockYheight-inset, stockXwidth - (inset + radius), stockYheight - inset)

gcp.setdxfcolor("Blue")

gcp.dxfrectangle(large_square_tool_num, radius +inset, radius, stockXwidth/2 - (radius * 4), stockYheight - (radius * 2), cornerstyle, radius)
gcp.dxfrectangle(large_square_tool_num, stockXwidth/2 + (radius * 2) + inset, radius, stockXwidth/2 - (radius * 4), stockYheight -
```

```
              (radius * 2), cornerstyle, radius)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("Black")
gcpdxfpy
gcpdxfpy gcp.beginpolyline(large_square_tool_num)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.75+radius*1.5,
             stockYheight/4-radius/2)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.75+radius,
             stockYheight/4-radius/2)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.75+radius,
             stockYheight*0.75+radius/2)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.75+radius*1.5,
             stockYheight*0.75+radius/2)
gcpdxfpy gcp.closepolyline(large_square_tool_num)
gcpdxfpy
gcpdxfpy gcp.dxfarc(large_square_tool_num, stockXwidth*0.75+radius*1.5,
             stockYheight*0.75, radius/2,  0, 90)
gcpdxfpy
gcpdxfpy gcp.beginpolyline(large_square_tool_num)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.75+radius*2,
             stockYheight*0.75)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.75+radius*2,
             stockYheight/4)
gcpdxfpy gcp.closepolyline(large_square_tool_num)
gcpdxfpy
gcpdxfpy gcp.dxfarc(large_square_tool_num, stockXwidth*0.75+radius*1.5,
             stockYheight/4, radius/2,  270, 360)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("White")
gcpdxfpy
gcpdxfpy gcp.beginpolyline(large_square_tool_num)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.25-radius*1.5,
             stockYheight/4-radius/2)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.25-radius,
             stockYheight/4-radius/2)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.25-radius,
             stockYheight*0.75+radius/2)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.25-radius*1.5,
             stockYheight*0.75+radius/2)
gcpdxfpy gcp.closepolyline(large_square_tool_num)
gcpdxfpy
gcpdxfpy gcp.dxfarc(large_square_tool_num, stockXwidth*0.25-radius*1.5,
             stockYheight*0.75, radius/2,  90, 180)
gcpdxfpy
gcpdxfpy gcp.beginpolyline(large_square_tool_num)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.25-radius*2,
             stockYheight*0.75)
gcpdxfpy gcp.addvertex(large_square_tool_num, stockXwidth*0.25-radius*2,
             stockYheight/4)
gcpdxfpy gcp.closepolyline(large_square_tool_num)
gcpdxfpy
gcpdxfpy gcp.dxfarc(large_square_tool_num, stockXwidth*0.25-radius*1.5,
             stockYheight/4, radius/2,  180, 270)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("Yellow")
gcpdxfpy gcp.dxfcircle(large_square_tool_num, stockXwidth/4+1+radius/2,
             stockYheight/4, radius/2)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("Green")
gcpdxfpy gcp.dxfcircle(large_square_tool_num, stockXwidth*0.75-(1+radius/2),
              stockYheight*0.75, radius/2)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("Cyan")
gcpdxfpy gcp.dxfcircle(large_square_tool_num, stockXwidth/4+1+radius/2,
             stockYheight*0.75, radius/2)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("Magenta")
gcpdxfpy gcp.dxfcircle(large_square_tool_num, stockXwidth*0.75-(1+radius/2),
              stockYheight/4, radius/2)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("Dark␣Gray")
gcpdxfpy
gcpdxfpy gcp.dxfcircle(large_square_tool_num, stockXwidth/2, stockYheight/2,
              radius * 2)
gcpdxfpy
gcpdxfpy gcp.setdxfcolor("Light␣Gray")
gcpdxfpy
gcpdxfpy gcp.dxfKH(374, stockXwidth/2, stockYheight/5*3, 0, -7, 270,
```

```
            11.5875)
gcpdxfpy
gcpdxfpy gcp.closedxffile()
```

which creates a `.dxf` file which may be imported into any CAD program:



with the appearance (once converted into a `.svg` and then re-saved as a `.pdf` and edited so as to show the white elements):



and which may be imported into pretty much any CAD or CAM application, e.g., Carbide Create:



As shown/implied by the above code, the following commands/shapes are implemented:

- `dxfrectangle` (specify lower-left corner location and width (X)/height(Y))
  - `dxfrectangleround` (specified as "Fillet" and radius for the round option)
  - `dxfrectanglechamfer` (specified as "Chamfer" and radius for the round option)
  - `dxfrectangleflippedfillet` (specified as "Flipped Fillet" and radius for the option)
- `dxfcircle` (specifying their center and radius)
- `dxfline` (specifying begin/end points)
- `dxfarc` (specifying arc center, radius, and beginning/ending angles)
- `dxfKH` (specifying origin, depth, angle, distance)

2.2 gcpcutdxf.py

A notable limitation of the above is that there is no interactivity — the `.dxf` file is generated, then must be opened and the result of the run checked (if there is a DXF viewer/editor which will live-reload the file based on it being updated that would be obviated). Reworking the commands for a simplified version of the above design so as to show a 3D model in OpenPythonSCAD is a straight-forward task:

```
from openscad import *
# nimport("https://raw.githubusercontent.com/WillAdams/gcodepreview/refs/heads/main/gcodepreview.py")
from gcodepreview import *

fa = 2
fs = 0.125

gcp = gcodepreview("cut", # "print" or "no_preview"
                   False, # generategcode
                   True   # generatedxf
                   )

# [Stock] */
stockXwidth = 100
# [Stock] */
stockYheight = 50
# [Stock] */
stockZthickness = 3.175
# [Stock] */
zeroheight = "Top"  # [Top, Bottom]
# [Stock] */
stockzero = "Lower-Left"  # [Lower-Left, Center-Left, Top-Left, Center]
# [Stock] */
retractheight = 3.175

# [Export] */
```

```
Base_filename = "gcpdxf"


# [CAM] */
large_square_tool_num = 112
# [CAM] */
small_square_tool_num = 0
# [CAM] */
large_ball_tool_num = 111
# [CAM] */
small_ball_tool_num = 0
# [CAM] */
large_V_tool_num = 0
# [CAM] */
small_V_tool_num = 0
# [CAM] */
DT_tool_num = 374
# [CAM] */
KH_tool_num = 0
# [CAM] */
Roundover_tool_num = 0
# [CAM] */
MISC_tool_num = 0

# [Design] */
inset = 3
# [Design] */
radius = 6
# [Design] */
cornerstyle = "Fillet"  # "Chamfer", "Flipped Fillet"

gcp.opendxffile(Base_filename)

gcp.setupstock(stockXwidth, stockYheight, stockZthickness, zeroheight, stockzero, retractheight)

gcp.toolchange(large_square_tool_num)

gcp.setdxfcolor("Red")

gcp.cutrectangledxf(large_square_tool_num, 0, 0, 0, stockXwidth, stockYheight, stockZthickness)

gcp.toolchange(large_ball_tool_num)

gcp.setdxfcolor("Gray")

gcp.rapid(inset + radius, inset, 0, "laser")

gcp.cutlinedxf(inset + radius, inset, -stockZthickness/2)
gcp.cutquarterCCNEdxf(inset, inset + radius, -stockZthickness/2, radius)

gcp.cutlinedxf(inset, stockYheight - (inset + radius), -stockZthickness/2)

gcp.cutquarterCCSEdxf(inset + radius, stockYheight - inset, -stockZthickness/2, radius)

gcp.cutlinedxf(stockXwidth - (inset + radius), stockYheight - inset, -stockZthickness/2)

gcp.cutquarterCCSWdxf(stockXwidth - inset, stockYheight - (inset + radius), -stockZthickness/2, radius)

gcp.cutlinedxf(stockXwidth - (inset), (inset + radius), -stockZthickness/2)

gcp.cutquarterCCNWdxf(stockXwidth - (inset + radius), inset, -stockZthickness/2, radius)

gcp.cutlinedxf((inset + radius), inset, -stockZthickness/2)

gcp.setdxfcolor("Blue")

gcp.rapid(radius + inset + radius, radius, 0, "laser")

gcp.cutrectangleround dxf(large_square_tool_num, radius +inset,
```

```
                  radius, 0, stockXwidth/2 - (radius * 4), stockYheight - (radius
                  * 2), -stockZthickness/4, radius)
gcpcutdxfpy
gcpcutdxfpy gcp.rapid(stockXwidth/2 + (radius * 2) + inset + radius, radius, 0,
                   "laser")
gcpcutdxfpy
gcpcutdxfpy gcp.cutrectangleround dxf(large_square_tool_num, stockXwidth/2 + (
                  radius * 2) + inset, radius, 0, stockXwidth/2 - (radius * 4),
                  stockYheight - (radius * 2), -stockZthickness/4, radius)
gcpcutdxfpy
gcpcutdxfpy gcp.setdxfcolor("Red")
gcpcutdxfpy
gcpcutdxfpy gcp.rapid(stockXwidth/2 + radius, stockYheight/2, 0, "laser")
gcpcutdxfpy
gcpcutdxfpy gcp.toolchange(large_square_tool_num)
gcpcutdxfpy
gcpcutdxfpy gcp.cutcircleCC(stockXwidth/2, stockYheight/2, 0, -stockZthickness,
                   radius)
gcpcutdxfpy
gcpcutdxfpy gcp.cutcircleCC(stockXwidth/2, stockYheight/2, -stockZthickness, -
                  stockZthickness, radius*1.5)
gcpcutdxfpy
gcpcutdxfpy gcp.closedxffile()
gcpcutdxfpy
gcpcutdxfpy gcp.stockandtoolpaths()
```

which creates the design:



and which allows an interactive usage in working up a design such as for lasercutting, and which incorporates an option to the `rapid(x,y,z)` command which simulates turning a laser off, repositioning, then powering up the laser to resume cutting at the new position.

2.3 gcodepreviewtemplate.py

Note that since the v0.7 re-write, it is possible to directly use the underlying Python code. Using Python to generate 3D previews of how DXFs or G-code will cut requires the use of PythonSCAD.

```
gcptmplpy #!/usr/bin/env python
gcptmplpy
gcptmplpy import sys
gcptmplpy
gcptmplpy try:
gcptmplpy     if 'gcodepreview' in sys.modules:
gcptmplpy         del sys.modules['gcodepreview']
gcptmplpy except AttributeError:
gcptmplpy     pass
gcptmplpy
gcptmplpy from gcodepreview import *
gcptmplpy
gcptmplpy fa = 2
gcptmplpy fs = 0.125
gcptmplpy
gcptmplpy # [Export] */
gcptmplpy Base_filename = "aexport"
```

```
gcptmplpy # [Export] */
gcptmplpy generatedxf = True
gcptmplpy # [Export] */
gcptmplpy generategcode = True
gcptmplpy
gcptmplpy # [Stock] */
gcptmplpy stockXwidth = 220
gcptmplpy # [Stock] */
gcptmplpy stockYheight = 150
gcptmplpy # [Stock] */
gcptmplpy stockZthickness = 8.35
gcptmplpy # [Stock] */
gcptmplpy zeroheight = "Top"  # [Top, Bottom]
gcptmplpy # [Stock] */
gcptmplpy stockzero = "Center"  # [Lower-Left, Center-Left, Top-Left, Center]
gcptmplpy # [Stock] */
gcptmplpy retractheight = 9
gcptmplpy
gcptmplpy # [CAM] */
gcptmplpy toolradius = 1.5875
gcptmplpy # [CAM] */
gcptmplpy large_square_tool_num = 201  # [0:0, 112:112, 102:102, 201:201]
gcptmplpy # [CAM] */
gcptmplpy small_square_tool_num = 102  # [0:0, 122:122, 112:112, 102:102]
gcptmplpy # [CAM] */
gcptmplpy large_ball_tool_num = 202  # [0:0, 111:111, 101:101, 202:202]
gcptmplpy # [CAM] */
gcptmplpy small_ball_tool_num = 101  # [0:0, 121:121, 111:111, 101:101]
gcptmplpy # [CAM] */
gcptmplpy large_V_tool_num = 301  # [0:0, 301:301, 690:690]
gcptmplpy # [CAM] */
gcptmplpy small_V_tool_num = 390  # [0:0, 390:390, 301:301]
gcptmplpy # [CAM] */
gcptmplpy DT_tool_num = 814  # [0:0, 814:814, 808079:808079]
gcptmplpy # [CAM] */
gcptmplpy KH_tool_num = 374  # [0:0, 374:374, 375:375, 376:376, 378:378]
gcptmplpy # [CAM] */
gcptmplpy Roundover_tool_num = 56142  # [56142:56142, 56125:56125, 1570:1570]
gcptmplpy # [CAM] */
gcptmplpy MISC_tool_num = 0  # [501:501, 502:502, 45982:45982]
gcptmplpy #501 https://shop.carbide3d.com/collections/cutters/products/501-
        engraving-bit
gcptmplpy #502 https://shop.carbide3d.com/collections/cutters/products/502-
        engraving-bit
gcptmplpy #204 tapered ball nose 0.0625", 0.2500", 1.50", 3.6ř
gcptmplpy #304 tapered ball nose 0.1250", 0.2500", 1.50", 2.4ř
gcptmplpy #648 threadmill_shaft(2.4, 0.75, 18)
gcptmplpy #45982 Carbide Tipped Bowl & Tray 1/4 Radius x 3/4 Dia x 5/8 x 1/4
        Inch Shank
gcptmplpy #13921 https://www.amazon.com/Yonico-Groove-Bottom-Router-Degree/dp
        /B0CPJTMPP
gcptmplpy
gcptmplpy # [Feeds and Speeds] */
gcptmplpy plunge = 100
gcptmplpy # [Feeds and Speeds] */
gcptmplpy feed = 400
gcptmplpy # [Feeds and Speeds] */
gcptmplpy speed = 16000
gcptmplpy # [Feeds and Speeds] */
gcptmplpy small_square_ratio = 0.75  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy large_ball_ratio = 1.0  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy small_ball_ratio = 0.75  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy large_V_ratio = 0.875  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy small_V_ratio = 0.625  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy DT_ratio = 0.75  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy KH_ratio = 0.75  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy RO_ratio = 0.5  # [0.25:2]
gcptmplpy # [Feeds and Speeds] */
gcptmplpy MISC_ratio = 0.5  # [0.25:2]
gcptmplpy
gcptmplpy # Note that the various ratios are simply declared as a possible
```

```
    hook
# which might be useful and how are handled is left as an exercise
# for the reader and that they are not applied below.
# One naive option might be to multiply by the feed rate
# and divide by speeds.

gcp = gcodepreview("cut", # "print" or "no_preview"
                    generategcode,
                    generatedxf,
                    )

gcp.opengcodefile(Base_filename)
gcp.opendxffile(Base_filename)

gcp.setupstock(stockXwidth, stockYheight, stockZthickness,
    zeroheight, stockzero, retractheight)

gcp.movetosafeZ()

gcp.toolchange(102, 10000 * small_square_ratio)

gcp.rapidZ(0)

gcp.cutlinedxfgc(stockXwidth/2, stockYheight/2, -stockZthickness)

gcp.rapidZ(retractheight)
gcp.toolchange(201, 10000)
gcp.rapidXY(0, stockYheight/16)
gcp.rapidZ(0)
gcp.cutlinedxfgc(stockXwidth/16*7, stockYheight/2, -stockZthickness
    )

gcp.rapidZ(retractheight)
gcp.toolchange(202, 10000)
gcp.rapidXY(0, stockYheight/8)
gcp.rapidZ(0)
gcp.cutlinedxfgc(stockXwidth/16*6, stockYheight/2, -stockZthickness
    )

gcp.rapidZ(retractheight)
gcp.toolchange(101, 10000)
gcp.rapidXY(0, stockYheight/16*3)
gcp.rapidZ(0)
gcp.cutlinedxfgc(stockXwidth/16*5, stockYheight/2, -stockZthickness
    )

gcp.setzpos(retractheight)
gcp.toolchange(390, 10000)
gcp.rapidXY(0, stockYheight/16*4)
gcp.rapidZ(0)
gcp.cutlinedxfgc(stockXwidth/16*4, stockYheight/2, -stockZthickness
    )
gcp.rapidZ(retractheight)

gcp.toolchange(301, 10000)
gcp.rapidXY(0, stockYheight/16*6)
gcp.rapidZ(0)
gcp.cutlinedxfgc(stockXwidth/16*2, stockYheight/2, -stockZthickness
    )

rapids = gcp.rapid(gcp.xpos(), gcp.ypos(), retractheight)
gcp.toolchange(102, 10000)

gcp.rapid(-stockXwidth/4+stockYheight/16, +stockYheight/4, 0)

#gcp.cutarcCC(0, 90, gcp.xpos()-stockYheight/16, gcp.ypos(),
    stockYheight/16, -stockZthickness/4)
#gcp.cutarcCC(90, 180, gcp.xpos(), gcp.ypos()-stockYheight/16,
    stockYheight/16, -stockZthickness/4)
#gcp.cutarcCC(180, 270, gcp.xpos()+stockYheight/16, gcp.ypos(),
    stockYheight/16, -stockZthickness/4)
#gcp.cutarcCC(270, 360, gcp.xpos(), gcp.ypos()+stockYheight/16,
    stockYheight/16, -stockZthickness/4)
gcp.cutquarterCCNEdxf(gcp.xpos() - stockYheight/8, gcp.ypos() +
    stockYheight/8, -stockZthickness/4, stockYheight/8)
gcp.cutquarterCCNWdxf(gcp.xpos() - stockYheight/8, gcp.ypos() -
    stockYheight/8, -stockZthickness/2, stockYheight/8)
gcp.cutquarterCCSWdxf(gcp.xpos() + stockYheight/8, gcp.ypos() -
```

```
               stockYheight/8, -stockZthickness * 0.75, stockYheight/8)
gcptmplpy gcp.cutquarterCCSEdxf(gcp.xpos() + stockYheight/8, gcp.ypos() + stockYheight/8, -stockZthickness, stockYheight/8)
gcptmplpy
gcptmplpy gcp.movetosafeZ()
gcptmplpy gcp.rapidXY(stockXwidth/4-stockYheight/16, -stockYheight/4)
gcptmplpy gcp.rapidZ(0)
gcptmplpy
gcptmplpy
gcptmplpy #gcp.cutarcCW(180, 90, gcp.xpos()+stockYheight/16, gcp.ypos(), stockYheight/16, -stockZthickness/4)
gcptmplpy #gcp.cutarcCW(90, 0, gcp.xpos(), gcp.ypos()-stockYheight/16, stockYheight/16, -stockZthickness/4)
gcptmplpy #gcp.cutarcCW(360, 270, gcp.xpos()-stockYheight/16, gcp.ypos(), stockYheight/16, -stockZthickness/4)
gcptmplpy #gcp.cutarcCW(270, 180, gcp.xpos(), gcp.ypos()+stockYheight/16, stockYheight/16, -stockZthickness/4)
gcptmplpy
gcptmplpy #gcp.movetosafeZ()
gcptmplpy #gcp.toolchange(201, 10000)
gcptmplpy #gcp.rapidXY(stockXwidth/2, -stockYheight/2)
gcptmplpy #gcp.rapidZ(0)
gcptmplpy
gcptmplpy #gcp.cutlinedxfgc(gcp.xpos(), gcp.ypos(), -stockZthickness)
gcptmplpy #test = gcp.cutlinedxfgc(gcp.xpos(), gcp.ypos(), -stockZthickness)
gcptmplpy
gcptmplpy #gcp.movetosafeZ()
gcptmplpy #gcp.rapidXY(stockXwidth/2-6.34, -stockYheight/2)
gcptmplpy #gcp.rapidZ(0)
gcptmplpy
gcptmplpy #gcp.cutarcCW(180, 90, stockXwidth/2, -stockYheight/2, 6.34, -stockZthickness)
gcptmplpy
gcptmplpy
gcptmplpy gcp.movetosafeZ()
gcptmplpy gcp.toolchange(814, 10000)
gcptmplpy gcp.rapidXY(0, -(stockYheight/2+12.7))
gcptmplpy gcp.rapidZ(0)
gcptmplpy
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), gcp.ypos(), -stockZthickness)
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), -12.7, -stockZthickness)
gcptmplpy
gcptmplpy gcp.rapidXY(0, -(stockYheight/2+12.7))
gcptmplpy gcp.movetosafeZ()
gcptmplpy gcp.toolchange(374, 10000)
gcptmplpy gcp.rapidXY(stockXwidth/4-stockXwidth/16, -(stockYheight/4+stockYheight/16))
gcptmplpy gcp.rapidZ(0)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.toolchange(374, 10000)
gcptmplpy gcp.rapidXY(-stockXwidth/4-stockXwidth/16, -(stockYheight/4+stockYheight/16))
gcptmplpy gcp.rapidZ(0)
gcptmplpy
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2)
gcptmplpy gcp.cutlinedxfgc(gcp.xpos()+stockYheight/9, gcp.ypos(), gcp.zpos())
gcptmplpy
gcptmplpy gcp.cutline(gcp.xpos()-stockYheight/9, gcp.ypos(), gcp.zpos())
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), 0)
gcptmplpy
gcptmplpy #key = gcp.cutkeyholegcdxf(KH_tool_num, 0, stockZthickness*0.75, "E", stockYheight/9)
gcptmplpy #key = gcp.cutKHgcdxf(374, 0, stockZthickness*0.75, 90, stockYheight/9)
gcptmplpy #toolpaths = toolpaths.union(key)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.rapidXY(-stockXwidth/4+stockXwidth/16, -(stockYheight/4+stockYheight/16))
gcptmplpy gcp.rapidZ(0)
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2)
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), gcp.ypos()+stockYheight/9, gcp.zpos())
gcptmplpy
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos()-stockYheight/9, gcp.zpos())
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), 0)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
```

```
gcptmplpy gcp.rapidXY(-stockXwidth/4+stockXwidth/16, -(stockYheight/4-stockYheight/8))
gcptmplpy gcp.rapidZ(0)
gcptmplpy
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2)
gcptmplpy gcp.cutlinedxfgc(gcp.xpos()-stockYheight/9, gcp.ypos(), gcp.zpos())
gcptmplpy
gcptmplpy gcp.cutline(gcp.xpos()+stockYheight/9, gcp.ypos(), gcp.zpos())
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), 0)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.rapidXY(-stockXwidth/4-stockXwidth/16, -(stockYheight/4-stockYheight/8))
gcptmplpy gcp.rapidZ(0)
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2)
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), gcp.ypos()-stockYheight/9, gcp.zpos())
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos()+stockYheight/9, gcp.zpos())
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), 0)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.toolchange(56142, 10000)
gcptmplpy gcp.rapidXY(-stockXwidth/2, -(stockYheight/2+0.508/2))
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -1.531)
gcptmplpy gcp.cutlinedxfgc(stockXwidth/2+0.508/2, -(stockYheight/2+0.508/2), -1.531)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -1.531)
gcptmplpy gcp.cutlinedxfgc(stockXwidth/2+0.508/2, (stockYheight/2+0.508/2), -1.531)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.toolchange(45982, 10000)
gcptmplpy gcp.rapidXY(stockXwidth/8, 0)
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -(stockZthickness*7/8))
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), -stockYheight/2, -(stockZthickness*7/8))
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.toolchange(204, 10000)
gcptmplpy gcp.rapidXY(stockXwidth*0.3125, 0)
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -(stockZthickness*7/8))
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), -stockYheight/2, -(stockZthickness*7/8))
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.toolchange(502, 10000)
gcptmplpy gcp.rapidXY(stockXwidth*0.375, 0)
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -4.24)
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), -stockYheight/2, -4.24)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy gcp.toolchange(13921, 10000)
gcptmplpy gcp.rapidXY(-stockXwidth*0.375, 0)
gcptmplpy gcp.cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2)
gcptmplpy gcp.cutlinedxfgc(gcp.xpos(), -stockYheight/2, -stockZthickness/2)
gcptmplpy
gcptmplpy gcp.rapidZ(retractheight)
gcptmplpy
gcptmplpy gcp.stockandtoolpaths()
gcptmplpy
gcptmplpy gcp.closegcodefile()
gcptmplpy gcp.closedxffile()
```

Which generates a 3D model which previews in PythonSCAD as:



2.4 gcodepreviewtemplate.scad

Since the project began in OpenSCAD, having an implementation in that language has always been a goal. This is quite straight-forward since the Python code when imported into OpenSCAD may be accessed by quite simple modules which are for the most part, a series of decorators/ descriptors which wrap up the Python definitions as OpenSCAD modules. Moreover, such an implementation will facilitate usage by tools intended for this application such as OpenSCAD Graph Editor: https://github.com/derkork/openscad-graph-editor.

```
gcptmplscad //!OpenSCAD
gcptmplscad
gcptmplscad use <gcodepreview.py>
gcptmplscad include <gcodepreview.scad>
gcptmplscad
gcptmplscad $fn = $preview ? 32 : 256;
gcptmplscad fn = $preview ? 32 : 256;
gcptmplscad
gcptmplscad /* [Stock] */
gcptmplscad stockXwidth = 220;
gcptmplscad /* [Stock] */
gcptmplscad stockYheight = 150;
gcptmplscad /* [Stock] */
gcptmplscad stockZthickness = 8.35;
gcptmplscad /* [Stock] */
gcptmplscad zeroheight = "Top"; // [Top, Bottom]
gcptmplscad /* [Stock] */
gcptmplscad stockzero = "Center"; // [Lower-Left, Center-Left, Top-Left, Center
                ]
gcptmplscad /* [Stock] */
gcptmplscad retractheight = 9;
gcptmplscad
gcptmplscad /* [Export] */
gcptmplscad Base_filename = "export";
gcptmplscad /* [Export] */
gcptmplscad generatedxf = true;
gcptmplscad /* [Export] */
gcptmplscad generategcode = true;
gcptmplscad
gcptmplscad /* [CAM] */
gcptmplscad toolradius = 1.5875;
gcptmplscad /* [CAM] */
gcptmplscad large_square_tool_num = 0; // [0:0, 112:112, 102:102, 201:201]
gcptmplscad /* [CAM] */
gcptmplscad small_square_tool_num = 102; // [0:0, 122:122, 112:112, 102:102]
gcptmplscad /* [CAM] */
gcptmplscad large_ball_tool_num = 0; // [0:0, 111:111, 101:101, 202:202]
gcptmplscad /* [CAM] */
gcptmplscad small_ball_tool_num = 0; // [0:0, 121:121, 111:111, 101:101]
gcptmplscad /* [CAM] */
gcptmplscad large_V_tool_num = 0; // [0:0, 301:301, 690:690]
gcptmplscad /* [CAM] */
gcptmplscad small_V_tool_num = 0; // [0:0, 390:390, 301:301]
gcptmplscad /* [CAM] */
```

```
DT_tool_num = 0; // [0:0, 814:814, 808079:808079]
/* [CAM] */
KH_tool_num = 0; // [0:0, 374:374, 375:375, 376:376, 378:378]
/* [CAM] */
Roundover_tool_num = 0; // [56142:56142, 56125:56125, 1570:1570]
/* [CAM] */
MISC_tool_num = 0; // [648:648, 45982:45982]
//648 threadmill_shaft(2.4, 0.75, 18)
//45982 Carbide Tipped Bowl & Tray 1/4 Radius x 3/4 Dia x 5/8 x 1/4 Inch Shank

/* [Feeds and Speeds] */
plunge = 100;
/* [Feeds and Speeds] */
feed = 400;
/* [Feeds and Speeds] */
speed = 16000;
/* [Feeds and Speeds] */
small_square_ratio = 0.75; // [0.25:2]
/* [Feeds and Speeds] */
large_ball_ratio = 1.0; // [0.25:2]
/* [Feeds and Speeds] */
small_ball_ratio = 0.75; // [0.25:2]
/* [Feeds and Speeds] */
large_V_ratio = 0.875; // [0.25:2]
/* [Feeds and Speeds] */
small_V_ratio = 0.625; // [0.25:2]
/* [Feeds and Speeds] */
DT_ratio = 0.75; // [0.25:2]
/* [Feeds and Speeds] */
KH_ratio = 0.75; // [0.25:2]
/* [Feeds and Speeds] */
RO_ratio = 0.5; // [0.25:2]
/* [Feeds and Speeds] */
MISC_ratio = 0.5; // [0.25:2]

thegeneratedxf = generatedxf == true ? 1 : 0;
thegenerategcode = generategcode == true ? 1 : 0;

gcp = gcodepreview("cut", // or "print" (no preview not suited to OpenSCAD)
                    thegenerategcode,
                    thegeneratedxf,
                    );

opengcodefile(Base_filename);
opendxffile(Base_filename);

setupstock(stockXwidth, stockYheight, stockZthickness, zeroheight, stockzero);

//echo(gcp);
//gcpversion();

//c = myfunc(4);
//echo(c);

//echo(getvv());

cutline(stockXwidth/2, stockYheight/2, -stockZthickness);

rapidZ(retractheight);
toolchange(201, 10000);
rapidXY(0, stockYheight/16);
rapidZ(0);
cutlinedxfgc(stockXwidth/16*7, stockYheight/2, -stockZthickness);


rapidZ(retractheight);
toolchange(202, 10000);
rapidXY(0, stockYheight/8);
rapidZ(0);
cutlinedxfgc(stockXwidth/16*6, stockYheight/2, -stockZthickness);

rapidZ(retractheight);
toolchange(101, 10000);
rapidXY(0, stockYheight/16*3);
rapidZ(0);
```

```
gcptmplscad cutlinedxfgc(stockXwidth/16*5, stockYheight/2, -stockZthickness);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad toolchange(390, 10000);
gcptmplscad rapidXY(0, stockYheight/16*4);
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad cutlinedxfgc(stockXwidth/16*4, stockYheight/2, -stockZthickness);
gcptmplscad rapidZ(retractheight);
gcptmplscad
gcptmplscad toolchange(301, 10000);
gcptmplscad rapidXY(0, stockYheight/16*6);
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad cutlinedxfgc(stockXwidth/16*2, stockYheight/2, -stockZthickness);
gcptmplscad
gcptmplscad
gcptmplscad movetosafeZ();
gcptmplscad rapid(gcp.xpos(), gcp.ypos(), retractheight);
gcptmplscad toolchange(102, 10000);
gcptmplscad
gcptmplscad //rapidXY(stockXwidth/4+stockYheight/8+stockYheight/16, +
                stockYheight/8);
gcptmplscad rapidXY(-stockXwidth/4+stockXwidth/16, (stockYheight/4));//+
                stockYheight/16
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad //cutarcCW(360, 270, gcp.xpos()-stockYheight/16, gcp.ypos(),
                stockYheight/16, -stockZthickness);
gcptmplscad //gcp.cutarcCW(270, 180, gcp.xpos(), gcp.ypos()+stockYheight/16,
                stockYheight/16))
gcptmplscad //cutarcCC(0, 90, gcp.xpos()-stockYheight/16, gcp.ypos(),
                stockYheight/16, -stockZthickness/4);
gcptmplscad //cutarcCC(90, 180, gcp.xpos(), gcp.ypos()-stockYheight/16,
                stockYheight/16, -stockZthickness/4);
gcptmplscad //cutarcCC(180, 270, gcp.xpos()+stockYheight/16, gcp.ypos(),
                stockYheight/16, -stockZthickness/4);
gcptmplscad //cutarcCC(270, 360, gcp.xpos(), gcp.ypos()+stockYheight/16,
                stockYheight/16, -stockZthickness/4);
gcptmplscad
gcptmplscad movetosafeZ();
gcptmplscad //rapidXY(stockXwidth/4+stockYheight/8-stockYheight/16, -
                stockYheight/8);
gcptmplscad rapidXY(stockXwidth/4-stockYheight/16, -(stockYheight/4));
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad //cutarcCW(180, 90, gcp.xpos()+stockYheight/16, gcp.ypos(),
                stockYheight/16, -stockZthickness/4);
gcptmplscad //cutarcCW(90, 0, gcp.xpos(), gcp.ypos()-stockYheight/16,
                stockYheight/16, -stockZthickness/4);
gcptmplscad //cutarcCW(360, 270, gcp.xpos()-stockYheight/16, gcp.ypos(),
                stockYheight/16, -stockZthickness/4);
gcptmplscad //cutarcCW(270, 180, gcp.xpos(), gcp.ypos()+stockYheight/16,
                stockYheight/16, -stockZthickness/4);
gcptmplscad
gcptmplscad movetosafeZ();
gcptmplscad
gcptmplscad rapidXY(-stockXwidth/4 + stockYheight/8, (stockYheight/4));
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad cutquarterCCNEdxf(xpos() - stockYheight/8, ypos() + stockYheight/8,
                 -stockZthickness/4, stockYheight/8);
gcptmplscad cutquarterCCNWdxf(xpos() - stockYheight/8, ypos() - stockYheight/8,
                 -stockZthickness/2, stockYheight/8);
gcptmplscad cutquarterCCSWdxf(xpos() + stockYheight/8, ypos() - stockYheight/8,
                 -stockZthickness * 0.75, stockYheight/8);
gcptmplscad //cutquarterCCSEdxf(xpos() + stockYheight/8, ypos() + stockYheight
                /8, -stockZthickness, stockYheight/8);
gcptmplscad
gcptmplscad movetosafeZ();
gcptmplscad toolchange(201, 10000);
gcptmplscad rapidXY(stockXwidth /2 -6.34, - stockYheight /2);
gcptmplscad rapidZ(0);
gcptmplscad //cutarcCW(180, 90, stockXwidth /2, -stockYheight/2, 6.34, -
                stockZthickness);
gcptmplscad
gcptmplscad movetosafeZ();
gcptmplscad rapidXY(stockXwidth/2, -stockYheight/2);
```

```
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad //gcp.cutlinedxfgc(gcp.xpos(), gcp.ypos(), -stockZthickness);
gcptmplscad
gcptmplscad movetosafeZ();
gcptmplscad toolchange(814, 10000);
gcptmplscad rapidXY(0, -(stockYheight/2+12.7));
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad cutlinedxfgc(xpos(), ypos(), -stockZthickness);
gcptmplscad cutlinedxfgc(xpos(), -12.7, -stockZthickness);
gcptmplscad rapidXY(0, -(stockYheight/2+12.7));
gcptmplscad
gcptmplscad //rapidXY(stockXwidth/2-6.34, -stockYheight/2);
gcptmplscad //rapidZ(0);
gcptmplscad
gcptmplscad //movetosafeZ();
gcptmplscad //toolchange(374, 10000);
gcptmplscad //rapidXY(-(stockXwidth/4 - stockXwidth /16), -(stockYheight/4 + stockYheight/16))
gcptmplscad
gcptmplscad //cutline(xpos(), ypos(), (stockZthickness/2) * -1);
gcptmplscad //cutlinedxfgc(xpos() + stockYheight /9, ypos(), zpos());
gcptmplscad //cutline(xpos() - stockYheight /9, ypos(), zpos());
gcptmplscad //cutline(xpos(), ypos(), 0);
gcptmplscad
gcptmplscad movetosafeZ();
gcptmplscad
gcptmplscad toolchange(374, 10000);
gcptmplscad rapidXY(-stockXwidth/4-stockXwidth/16, -(stockYheight/4+stockYheight/16))
gcptmplscad //rapidXY(-(stockXwidth/4 - stockXwidth /16), -(stockYheight/4 + stockYheight/16))
gcptmplscad rapidZ(0);
gcptmplscad
gcptmplscad cutline(xpos(), ypos(), (stockZthickness/2) * -1);
gcptmplscad cutlinedxfgc(xpos() + stockYheight /9, ypos(), zpos());
gcptmplscad cutline(xpos() - stockYheight /9, ypos(), zpos());
gcptmplscad cutline(xpos(), ypos(), 0);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad rapidXY(-stockXwidth/4+stockXwidth/16, -(stockYheight/4+stockYheight/16));
gcptmplscad rapidZ(0);
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2);
gcptmplscad cutlinedxfgc(gcp.xpos(), gcp.ypos()+stockYheight/9, gcp.zpos());
gcptmplscad cutline(gcp.xpos(), gcp.ypos()-stockYheight/9, gcp.zpos());
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), 0);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad rapidXY(-stockXwidth/4+stockXwidth/16, -(stockYheight/4-stockYheight/8));
gcptmplscad rapidZ(0);
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2);
gcptmplscad cutlinedxfgc(gcp.xpos()-stockYheight/9, gcp.ypos(), gcp.zpos());
gcptmplscad cutline(gcp.xpos()+stockYheight/9, gcp.ypos(), gcp.zpos());
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), 0);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad rapidXY(-stockXwidth/4-stockXwidth/16, -(stockYheight/4-stockYheight/8));
gcptmplscad rapidZ(0);
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2);
gcptmplscad cutlinedxfgc(gcp.xpos(), gcp.ypos()-stockYheight/9, gcp.zpos());
gcptmplscad cutline(gcp.xpos(), gcp.ypos()+stockYheight/9, gcp.zpos());
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), 0);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad toolchange(45982, 10000);
gcptmplscad rapidXY(stockXwidth/8, 0);
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), -(stockZthickness*7/8));
gcptmplscad cutlinedxfgc(gcp.xpos(), -stockYheight/2, -(stockZthickness*7/8));
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad toolchange(204, 10000);
gcptmplscad rapidXY(stockXwidth*0.3125, 0);
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), -(stockZthickness*7/8));
gcptmplscad cutlinedxfgc(gcp.xpos(), -stockYheight/2, -(stockZthickness*7/8));
```

```
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad toolchange(502, 10000);
gcptmplscad rapidXY(stockXwidth*0.375, 0);
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), -4.24);
gcptmplscad cutlinedxfgc(gcp.xpos(), -stockYheight/2, -4.24);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad toolchange(13921, 10000);
gcptmplscad rapidXY(-stockXwidth*0.375, 0);
gcptmplscad cutline(gcp.xpos(), gcp.ypos(), -stockZthickness/2);
gcptmplscad cutlinedxfgc(gcp.xpos(), -stockYheight/2, -stockZthickness/2);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad gcp.toolchange(56142, 10000);
gcptmplscad gcp.rapidXY(-stockXwidth/2, -(stockYheight/2+0.508/2));
gcptmplscad cutlineZgcfeed(-1.531, plunge);
gcptmplscad //cutline(gcp.xpos(), gcp.ypos(), -1.531);
gcptmplscad cutlinedxfgc(stockXwidth/2+0.508/2, -(stockYheight/2+0.508/2),
                -1.531);
gcptmplscad
gcptmplscad rapidZ(retractheight);
gcptmplscad //#gcp.toolchange(56125, 10000)
gcptmplscad cutlineZgcfeed(-1.531, plunge);
gcptmplscad //toolpaths.append(gcp.cutline(gcp.xpos(), gcp.ypos(), -1.531))
gcptmplscad cutlinedxfgc(stockXwidth/2+0.508/2, (stockYheight/2+0.508/2),
                -1.531);
gcptmplscad
gcptmplscad stockandtoolpaths();
gcptmplscad //stockwotoolpaths();
gcptmplscad //outputtoolpaths();
gcptmplscad
gcptmplscad //makecube(3, 2, 1);
gcptmplscad
gcptmplscad //instantiatecube();
gcptmplscad
gcptmplscad closegcodefile();
gcptmplscad closedxffile();
```

Which generates a 3D model which previews in OpenSCAD as:



2.5 gpcthreedp.py

Setting up 3D printing will require accommodating the requirements of both the printer *and* filament being used. The most straight-forward and expedient way to arrive at this is to leverage a traditional 3D printer slicer which has settings appropriate to the machine and filament being used which are tuned to the sort of part being made/printing being done, export the G-code, and use that as a template for setting up 3D printing.

Towards that end, a G-code file for a very basic 3D printer was output for printing PLA from an Ordbot Quantum

```
#gcpthreedp.py --- Template for 3D printing
#                  Initial version.
#!/usr/bin/env python

import sys

try:
    if 'gcodepreview' in sys.modules:
        del sys.modules['gcodepreview']
except AttributeError:
    pass

from gcodepreview import *

fa = 2
fs = 0.125

# [Export] */
Base_filename = "aexport"
# [Export] */
generatedxf = False
# [Export] */
generategcode = True
# [3D Printing] */
nozzlediameter = 0.4
filamentdiameter = 1.75
extrusionwidth = 0.6
layerheight = 0.2
temperature =200

gcp = gcodepreview("print", # "cut" or "no_preview"
                   generategcode,
                   generatedxf,
                   )

gcp.opengcodefile(Base_filename)

gcp.initializeforprinting(nozzlediameter,
                          filamentdiameter,
                          extrusionwidth,
                          layerheight)

gcp.setandwaitforextrudertemperature(temperature)
gcp.liftandprimenozzle()

gcp.moveatfeedrate(0,0,layerheight,20000)
gcp.extrude(10, 20, layerheight)

gcp.stockandtoolpaths("toolpaths")

gcp.closegcodefile()
```

2.6 gcodepreviewtemplate.txt

Throughout this document, examples of commands will be shown and then collected in `gcodepreviewtemplate.txt` for easy copy-pasting (insert old computer joke about how many original Cobol programs have been written).

```
#gcptemplate.txt --- this file will collect example usages of each
#                    command with a brief commentary.
```

3 gcodepreview

This library for OpenPythonSCAD works by using Python code to persistently store and access variables which denote the machine position and describe the characteristics of tools, and to write out files while both modeling the motion of a 3-axis CNC machine (note that at least a 4^{th} additional axis may be worked up as a future option and supporting the work-around of two-sided (flip) machining by using an imported file as the Stock or preserving state and affording a second operation seems promising) and if desired, writing out DXF and/or G-code files (as opposed to the normal technique of rendering to a 3D model and writing out an STL or STEP or other model format and using a traditional CAM application). There are multiple modes for this, doing so may require loading up to two files:

- A Python file: gcodepreview.py (`gcpy`) — this has variables in the traditional sense which are used for tracking machine position and so forth. Note that where it is placed/loaded from will depend on whether it is imported into a Python file:
  `import gcodepreview_standalone as gcp`
  or used in an OpenSCAD file:
  `use <gcodepreview.py>`
  with an additional OpenSCAD module which allows accessing it and that there is an option for loading directly from the Github repository implemented in PythonSCAD
- An OpenSCAD file: gcodepreview.scad (`gcpscad`) — which `use`s the Python file and which is `include`d allowing it to access OpenSCAD variables for branching

Note that this architecture requires that many OpenSCAD modules are essentially "Dispatchers" (another term is "Descriptors") which pass information from one aspect of the environment to another, but in some instances it is expedient, or even will be necessary to re-write Python definitions in OpenSCAD rather than calling the matching Python function directly.

In earlier versions there were several possible ways to work with the 3D models of the cuts, either directly displaying the returned 3D model when explicitly called for after storing it in a variable or calling it up as a calculation (Python command `ouput(<foo>)` or OpenSCAD returning a model, or calling an appropriate OpenSCAD command), however as-of v0.9 the tool movements are modeled as lists of `hull()` operations which must be processed as such and are `difference`d from the stock. The templates set up these options as noted, and ensure that `True == true`.

PYTHON CODING CONSIDERATIONS: Python style may be checked using a tool such as: https://www.codewof.co.nz/style/python3/. Not all conventions will necessarily be adhered to — limiting line length in particular conflicts with the flexibility of Literate Programming. Note that `numpydoc`-style docstrings are added where appropriate to help define the functionality of each defined module in Python. https://numpydoc.readthedocs.io/en/latest/.

3.1 Cutviewer

This problem space, showing the result of cutting stock using tooling in 3D has a number of tools addressing it, Camotics (formerly OpenSCAM) is an opensource option. Many tools simply create a wireframe preview such as https://ncviewer.com/. Cutviewer is a notable commercial program which has a unique approach centered on G-code where specially formatted comments fill in the dimensions needed for showing the 3D preview.

3.1.1 Stock size and placement

Setting the dimensions of the stock, and placing it in 3D space relative to the origin must be done very early in the G-code file.

The CutViewer comments are in the form:

```
(STOCK/BLOCK, Length, Width, Height, Origin X, Origin Y, Origin Z)
```



3.1.2 Tool Shapes

Cutviewer is unable to show tools which undercut, but other tool shapes are represented in a straight-forward and flexible fashion.

Most tooling has quite standard shapes as described by their profile as defined in the `toolmovement` command which simply defines/declares their shape and `hull()`s them together:



- Square (#201 and 102) — able to cut a flat bottom, perpendicular side and right angle, their simple and easily understood geometry makes them a standard choice
- Ballnose (#202 and 101) — rounded, they are the standard choice for concave and organic shapes
- V tooling (#301, 302, 311 and 312) — pointed at the tip, they are available in a variety of angles and diameters and may be used for decorative V carving, or for chamfering or cutting specific angles

Note that the module for creating movement of the tool will need to handle all of the different tool shapes, generating a list of `hull()` or `rotate_extrude` commands which describe the 3D region which tool movement describes.

3.1.2.1 Tool/Mill (Square, radiused, ball-nose, and tapered-ball)

The CutViewer values include:

```
TOOL/MILL, Diameter, Corner radius, Height, Taper Angle
```



Note that it is possible to use these definitions for a wide variety of tooling, e.g., a Carbide 3D #301 V tool being represented as:

```
(TOOL/MILL,0.10, 0.05, 6.35, 45.00)
```

3.1.2.2 Corner Rounding, (roundover)

One notable tool option which cannot be supported using the Tool/Mill description is corner rounding/roundover tooling:

```
TOOL/CRMILL, Diameter1, Diameter2, Radius, Height, Length
```



3.1.2.3 V shaped tooling (and variations) Cutviewer has multiple V shaped tooling definitions:

- ;TOOL/CHAMFER, Diameter, Point Angle, Height
- ;TOOL/CHAMFER, Diameter, Point Angle, Height, Chamfer Length (note that this is the definition of a flat-bottomed V tool)
- ;TOOL/DRILL, Diameter, Point Angle, Height
- ;TOOL/CDRILL, D1, A1, L, D2, A2, H

Since such tooling may be represented (albeit with a slight compromise which arguably is a nod to the real world) using the Tool/Mill definition from above, it seems unlikely that such tooling definitions will be supported.

3.2 Module Naming Convention

> *The beginning of wisdom is to call things by their right names.*
> — CONFUCIUS

Naming modules requires that the conventions of G-code, the various file types which are written to, and the actions which the system takes are all taken into due consideration so as to arrive at a consistent scheme.

Number will be abbreviated as `num` rather than `no`, and the short form will be used internally for variable names, while the compleat word will be used in commands.

In some instances, `the` will be used as a prefix.

Tool #s where used will be the first argument where possible — this makes it obvious if they are not used — the negative consideration, that it then doesn't allow for a usage where a DEFAULT tool is used is not an issue since the command `currenttoolnumber()` may be used to access that number, and is arguably the preferred mechanism. An exception is when there are multiple tool #s as when opening a file — collecting them all at the end is a more straight-forward approach.

In natural languages such as English, there is an order to various parts of speech such as adjectives — since various prefixes and suffixes will be used for module names, having a consistent ordering/usage will help in consistency and make expression clearer. The ordering should be: sequence (if necessary), action, function, parameter, filetype, and where possible a hierarchy of large/general to small/specific should be maintained.

- Both prefix and suffix
  - `dxf` (action (write out to DXF file), filetype)
- Prefixes
  - `generate` (Boolean) — used to identify which types of actions will be done (note that in the interest of brevity the check for this will be deferred until the last possible moment, see below)
  - `write` (action) — used to write to files, will include a check for the matching `generate` command, which being true will cause the write to the file to actually transpire
  - `cut` (action — create tool movement removing volume from 3D object)
  - `extrude` (action) — 3D printing equivalent to cut
  - `rapid` (action) — create tool movement of 3D object so as to show any collision or rubbing
  - `open` (action (file))
  - `close` (action (file))
  - `set` (action/function) — note that the matching `get` is implicit in functions which return variables, e.g., `xpos()`
  - `current`
- Nouns (geometry/shapes)
  - `arc`
  - `line`
  - `rectangle`
  - `circle`
- Suffixes
  - `feed` (parameter)
  - `gcode/gc` (filetype)
  - `pos` — position
  - `tool`
  - `loop`

- `CC/CW`
- `number/num` — note that `num` is used internally for variable names, while `number` will be used for module/function names, making it straight-forward to ensure that functions and variables have different names for purposes of scope

Further note that commands which are implicitly for the generation of G-code, such as `toolchange()` will omit `gc` for the sake of conciseness.

In theory, this means that the basic `cut...` and associated commands exist (or potentially exist) in the following forms and have matching versions which may be used when programming in Python or OpenSCAD:

	line			arc		
	cut	dxf	gcode	cut	dxf	gcode
cut	cutline		cutlinegc	cutarc		cutarcgc
dxf	cutlinedxf	dxfline		cutarcdxf	dxfarc	
gcode	cutlinegc		linegc	cutarcgc		arcgc
	cutlinedxfgc			cutarcdxfgc		

Note that certain commands (`dxflinegc`, `dxfarcgc`, `linegc`, `arcgc`) are either redundant or unlikely to be needed, and will most likely not be implemented (it seems contradictory that one would write out a move command to a G-code file without making that cut in the 3D preview). Note that there may be additional versions as required for the convenience of notation or cutting, in particular, a set of `cutarc`<quadrant><direction>`gc` commands was warranted during the initial development of `arc`-related commands.

`generategcode` `generatedxf` `generatecut`

The gcode and dxf columns and the matter of having specific commands which encompass those file types is tied up in having the internal variables `generategcode`, `generatedxf` and implementations, and a strong argument could be made that this should simply be handled by `if...then` structures using those variables. The addition of a `generatecut` variable adds the necessary symmetry. Note that an early option to output a separate file for each tool used has since been deprecated and will eventually be removed. In its place there is a mechanism where each colour is offset by the stock dimensions multiplied by the colour number, so that they are arrayed on a diagonal — when opened each such set of objects may then be easily selected and moved to the appropriate layer, then aligned against the stock.

A further consideration is that when processing G-code it is typical for a given command to be minimal and only include the axis of motion for the end-position, so for each of the above which is likely to appear in a `.nc/.gcode` file, it will be necessary to have a matching command for the combinatorial possibilities, hence:

cutlineXYZ	cutlineXYZwithfeed
cutlineXY	cutlineXYwithfeed
cutlineXZ	cutlineXZwithfeed
cutlineYZ	cutlineYZwithfeed
cutlineX	cutlineXwithfeed
cutlineY	cutlineYwithfeed
cutlineZ	cutlineZwithfeed

Principles for naming modules (and variables):

- minimize use of underscores (for convenience sake, underscores are not used for index entries)
- identify which aspect of the project structure is being worked with (`cut`(ting), `dxf`, `gcode`, `tool`, etc.) note the `gcodepreview` class which will normally be imported as `gcp` so that module `<foo>` will be called as `gcp.<foo>` from Python and by the same `<foo>` in OpenSCAD

The following commands for various shapes either have been implemented (`monospace`) or have not yet been implemented, but likely will need to be (regular type):

- rectangle

  `cutrectangle`

  `cutrectangleround`

Another consideration is that all commands which write files will check to see if a given filetype is enabled or no, since that check is deferred to the last as noted above for the sake of conciseness.

There are multiple modes for programming PythonSCAD:

- Python — in gcodepreview this allows writing out `dxf` files and using mutable variables (this is done in current versions of this project)
- OpenSCAD — see: https://openscad.org/documentation.html

- Programming in Python, calling Python from OpenSCAD using dispatchers/descriptors (this is done in current versions of this project)
- Programming in OpenSCAD with variables and calling Python — this requires 3 files and was originally used in the project as written up at: https://github.com/WillAdams/gcodepreview/blob/main/gcodepreview-openscad_0_6.pdf (for further details see below, notably various commented out lines in the source `.tex` file)
- Programming in OpenSCAD and calling Python where all variables as variables are held in Python classes (this is the technique used up through v0.8)
- Programming in Python and calling OpenSCAD — https://old.reddit.com/r/OpenPythonSCAD/comments/1heczmi/finally_using_scad_modules/

For reference, structurally, when developing OpenSCAD commands which make use of Python variables this was rendered as:

```
The user-facing module is \DescribeRoutine{FOOBAR}

\lstset{firstnumber=\thegcpscad}
\begin{writecode}{a}{gcodepreview.scad}{scad}
module FOOBAR(...) {
    oFOOBAR(...);
}

\end{writecode}
\addtocounter{gcpscad}{4}

which calls the internal OpenSCAD Module \DescribeSubroutine{FOOBAR}{oFOOBAR}

\begin{writecode}{a}{pygcodepreview.scad}{scad}
module oFOOBAR(...) {
    pFOOBAR(...);
 }

\end{writecode}
\addtocounter{pyscad}{4}

which in turn calls the internal Python definitioon \DescribeSubroutine{FOOBAR}{pFOOBAR}

\lstset{firstnumber=\thegcpy}
\begin{writecode}{a}{gcodepreview.py}{python}
def pFOOBAR (...)
    ...

\end{writecode}
\addtocounter{gcpy}{3}
```

Further note that this style of definition might not have been necessary for some later modules since they are in turn calling internal modules which already use this structure.

Lastly note that this style of programming was abandoned in favour of object-oriented dot notation for versions after v0.6 (see below) and that this technique was extended to class nested within another class.

3.2.1 Parameters and Default Values

Ideally, there would be *no* hard-coded values — every value used for calculation will be parameterized, and subject to control/modification. Fortunately, Python affords a feature which specifically addresses this, optional arguments with default values:
https://stackoverflow.com/questions/9539921/how-do-i-define-a-function-with-optional-argumen

In short, rather than hard-code numbers, for example in loops, they will be assigned as default values, and thus afford the user/programmer the option of changing them when the module is called.

3.3 Implementation files and gcodepreview class

Each file will begin with a comment indicating the file type and further notes/comments on usage where appropriate:

```
gcpy #!/usr/bin/env python
gcpy #icon "C:\Program Files\PythonSCAD\bin\openscad.exe" --trust-python
gcpy #Currently tested with https://www.pythonscad.org/downloads/PythonSCAD_nolibfive-2025.06.04-x86-64-Installer.exe and Python 3.11
gcpy #gcodepreview (gcpversion)0.93, for use with PythonSCAD,
gcpy #if using from PythonSCAD using OpenSCAD code, see gcodepreview.scad
```

```

import sys

# add math functions (sqrt)
import math

# getting openscad functions into namespace
#https://github.com/gsohler/openscad/issues/39
try:
    from openscad import *
except ModuleNotFoundError as e:
    print("OpenSCAD module not loaded.")

def pygcpversion():
    thegcpversion = 0.93
    return thegcpversion
```

The OpenSCAD file must `use` the Python file (note that some test/example code is commented out):

```
//!OpenSCAD

//gcodepreview version 0.8
//
//used via include <gcodepreview.scad>;
//

use <gcodepreview.py>

module gcpversion(){
echo(pygcpversion());
}

//function myfunc(var) = gcp.myfunc(var);
//
//function getvv() = gcp.getvv();
//
//module makecube(xdim, ydim, zdim){
//gcp.makecube(xdim, ydim, zdim);
//}
//
//module placecube(){
//gcp.placecube();
//}
//
//module instantiatecube(){
//gcp.instantiatecube();
//}
//
```

If all functions are to be handled within Python, then they will need to be gathered into a class which contains them and which is initialized so as to define shared variables and initial program state, and then there will need to be objects/commands for each aspect of the program, each of which will utilise needed variables and will contain appropriate functionality. Note that they will be divided between mandatory and optional functions/variables/objects:

- Mandatory
  - gcodepreview (init)
    - generatecut, generatedxf, generategcode
  - stocksetup:
    - stockXwidth, stockYheight, stockZthickness, zeroheight, stockzero, retractheight
  - gcpfiles:
    - basefilename
  - largesquaretool:
    - large_square_tool_num, toolradius, plunge, feed, speed
  - currenttoolnum
    - endmilltype
    - diameter
    - flute
    - shaftdiameter
    - shaftheight

    * shaftlength
    * toolnumber
    * cutcolor
    * rapidcolor
    * shaftcolor

- Optional
  - smallsquaretool:
    * small_square_tool_num, small_square_ratio
  - largeballtool:
    * large_ball_tool_num, large_ball_ratio
  - largeVtool:
    * large_V_tool_num, large_V_ratio
  - smallballtool:
    * small_ball_tool_num, small_ball_ratio
  - smallVtool:
    * small_V_tool_num, small_V_ratio
  - DTtool:
    * DT_tool_num, DT_ratio
  - KHtool:
    * KH_tool_num, KH_ratio
  - Roundovertool:
    * Roundover_tool_num, RO_ratio
  - misctool:
    * MISC_tool_num, MISC_ratio

`gcodepreview` `init` The class which is defined is `gcodepreview` which begins with the `init` method which allows passing in and defining the variables which will be used by the other methods in this class. Part of this includes handling various definitions for Boolean values.

```
#gcptemplate.txt --- this file will collect example usages of each
                     command with a brief commentary.
```

3.3.1 init

Initialization of the `gcodepreview` object requires handling a number of different cases, two of which are exclusive to each other. It must also take into account the possibility of being called from OpenSCAD

```
class gcodepreview:

    def __init__(self,
                 cutorprint = "cut", #"cut", "print", "no_preview"
                 generategcode = False,
                 generatedxf = False,
                 gcpfa = 2,
                 gcpfs = 0.125,
                 steps = 10
                 ):
        """
        Initialize gcodepreview object.

        Parameters
        ----------
        cutorprint    : string
                        Enables creation of 3D model for cutting or printing.
        generategcode : boolean
                        Enables writing out G-code.
        generatedxf   : boolean
                        Enables writing out DXF file(s).

        Returns
        -------
        object
            The initialized gcodepreview object.
        """
        if cutorprint == "print":
```

```
            self.generatecut = False
            self.generateprint = True
            self.gcodefilext = ".gcode"
        elif cutorprint == "cut":
            self.generatecut = True
            self.generateprint = False
            self.gcodefilext = ".nc"
        else: # no_preview
            self.generatecut = False
            self.generateprint = False
        if generategcode == True:
            self.generategcode = True
        elif generategcode == 1:
            self.generategcode = True
        elif generategcode == 0:
            self.generategcode = False
        else:
            self.generategcode = generategcode
        if generatedxf == True:
            self.generatedxf = True
        elif generatedxf == 1:
            self.generatedxf = True
        elif generatedxf == 0:
            self.generatedxf = False
        else:
            self.generatedxf = generatedxf
# unless multiple dxfs are enabled, the check for them is of course False
        self.generatedxfs = False
# set up 3D previewing parameters
        fa = gcpfa
        fs = gcpfs
        self.steps = steps
# initialize the machine state
        self.mc = "Initialized"
        self.mpx = float(0)
        self.mpy = float(0)
        self.mpz = float(0)
        self.tpz = float(0)
# initialize the toolpath state
        self.retractheight = 5
# initialize the DEFAULT tool
        self.currenttoolnum = 102
        self.endmilltype = "square"
        self.diameter = 3.175
        self.flute = 12.7
        self.shaftdiameter = 3.175
        self.shaftheight = 12.7
        self.shaftlength = 19.5
        self.toolnumber = "100036"
        self.cutcolor = "green"
        self.rapidcolor = "orange"
        self.shaftcolor = "red"
# the command definesquaretool(3.175, 12.7, 20) is used in the toolchange command
        self.tooloutline = polygon( points=[[0,0],[3.175,0],[3.175,12.7],[0,12.7]] )
        self.toolprofile = polygon( points=[[0,0],[1.5875,0],[1.5875,12.7],[0,12.7]] )
        self.shaftoutline = polygon( points=[[0,12.7],[3.175,12.7],[3.175,25.4],[0,25.4]] )
        self.shaftprofile = polygon( points=[[0,12.7],[1.5875,12.7],[1.5875,25.4],[0,25.4]] )
        self.currenttoolshape = cylinder(h = self.flute, r = self.shaftdiameter/2)
        sh = cylinder(h = self.flute, r = self.shaftdiameter/2)
        self.currenttoolshaft = sh.translate([0,0,self.flute])
# debug mode requires a variable to track if it is on or off
        self.debugenable = False
# the variables for holding 3D models must be initialized as empty lists so as to ensure that only append or extend commands are used with them
        self.rapids = []
        self.toolpaths = []
        print("gcodepreview␣class␣initialized")

#     def myfunc(self, var):
#         self.vv = var * var
```

```
#         return self.vv
#
#     def getvv(self):
#         return self.vv
#
#     def checkint(self):
#         return self.mc
#
#     def makecube(self, xdim, ydim, zdim):
#         self.c=cube([xdim, ydim, zdim])
#
#     def placecube(self):
#         show(self.c)
#
#     def instantiatecube(self):
#         return self.c
```

3.3.2 Position and Variables

In modeling the machine motion and G-code it will be necessary to have the machine track several variables for machine position, the current tool and its parameters, and the current depth in the current toolpath. This will be done using paired functions (which will set and return the matching variable) and a matching variable.

The first such variables are for XYZ position:

mpx
- mpx

mpy
- mpy

mpz
- mpz

tpzinc

Similarly, for some toolpaths it will be necessary to track the depth along the Z-axis as the toolpath is cut out, or the increment which a cut advances — this is done using an internal variable, tpzinc.

It will further be necessary to have a variable for the current tool:

currenttoolnum
- currenttoolnum

Note that the currenttoolnum variable should always be accessed and used for any specification of a tool, being read in whenever a tool is to be made use of, or a parameter or aspect of the tool needs to be used in a calculation.

toolmovement

In early versions, the implicit union of the 3D model of the tool was available and used where appropriate, but in v0.9, this was changed to using lists for concatenating the hulled shapes of tool movements, so the module, toolmovement which given begin/end position returns the appropriate shape(s) as a list.

currenttool

The 3D model of the tool is stored in currenttool.

xpos
ypos
zpos

It will be necessary to have Python functions (xpos, ypos, and zpos) which return the current values of the machine position in Cartesian coordinates:

```
    def xpos(self):
        return self.mpx

    def ypos(self):
        return self.mpy

    def zpos(self):
        return self.mpz
```

Wrapping these in OpenSCAD functions allows use of this positional information from OpenSCAD:

```
function xpos() = gcp.xpos();

function ypos() = gcp.ypos();

function zpos() = gcp.zpos();
```

setxpos
setypos
setzpos

and in turn, functions which set the positions: setxpos, setypos, and setzpos.

```
    def setxpos(self, newxpos):
        self.mpx = newxpos

    def setypos(self, newypos):
        self.mpy = newypos

    def setzpos(self, newzpos):
        self.mpz = newzpos
```

Using the `set...` routines will afford a single point of control if specific actions are found to be contingent on changes to these positions.

3.3.3 Initial Modules

Initializing the machine state requires zeroing out the three machine position variables:

- mpx
- mpy
- mpz

Rather than a specific command for this, the code will be in-lined where appropriate (note that if machine initialization becomes sufficiently complex to warrant it, then a suitable command will need to be coded). Note that the variables are declared in the `__init__` of the class.

toolmovement endmilltype diameter flute ra

The `toolmovement` class requires that the tool be defined in terms of `endmilltype`, `diameter`, `flute` (length), `ra` (radius or angle depending on context), and `tip`, and there is a mechanism which defines an internal tool number as described below. Currently though, the interface calls the `toolchange` routine passing in a manufacturer tool number as an expedient/default/initial option.

tip toolmovement rapids toolpaths

There are two variables to record `toolmovement`, `rapids` and `toolpaths`. Initialized as empty lists, toolmovements will be `extend`ed to the lists, then for output, the lists will be expanded and subtracted from the stock separately so that rapids are colour-coded so that if there is an interaction with the stock at rapid speed it will be obvious. A similar method should be implemented for the shafts of tooling.

gcodepreview setupstock

3.3.3.1 setupstock

The first such setup subroutine is `gcodepreview setupstock` which is appropriately enough, to set up the stock, and perform other initializations — initially, the only thing done in Python was to set the value of the persistent (Python) variables (see `initializemachinestate()` above), but the rewritten standalone version handles all necessary actions.

gcp.setupstock

Since part of a class, it will be called as `gcp.setupstock`. It requires that the user set parameters for stock dimensions and so forth, and will create comments in the G-code (if generating that file is enabled) which incorporate the stock dimensions and its position relative to the zero as set relative to the stock.

```
    def setupstock(self, stockXwidth,
                   stockYheight,
                   stockZthickness,
                   zeroheight,
                   stockzero,
                   retractheight):
        """
        Set up blank/stock for material and position/zero.

        Parameters
        ----------
        stockXwidth :   float
                        X extent/dimension
        stockYheight :  float
                        Y extent/dimension
        stockZthickness : boolean
                        Z extent/dimension
        zeroheight :    string
                        Top or Bottom, determines if Z extent will
                            be positive or negative
        stockzero :     string
                        Lower-Left, Center-Left, Top-Left, Center,
                            determines XY position of stock
        retractheight : float
                        Distance which tool retracts above surface
                            of stock.

        Returns
        -------
        none
        """
        self.stockXwidth = stockXwidth
        self.stockYheight = stockYheight
        self.stockZthickness = stockZthickness
        self.zeroheight = zeroheight
        self.stockzero = stockzero
        self.retractheight = retractheight
        self.stock = cube([stockXwidth, stockYheight,
            stockZthickness])
```

`zeroheight` `stockzero` A series of `if` statements parse the `zeroheight` (Z-axis) and `stockzero` (X- and Y-axes) parameters so as to place the stock in place and suitable G-code comments are added for CutViewer.

```
        if self.zeroheight == "Top":
            if self.stockzero == "Lower-Left":
                self.stock = self.stock.translate([0, 0, -self.stockZthickness])
                if self.generategcode == True:
                    self.writegc("(stockMin:0.00mm, 0.00mm, -", str(self.stockZthickness), "mm)")
                    self.writegc("(stockMax:", str(self.stockXwidth), "mm, ", str(stockYheight), "mm, 0.00mm)")
                    self.writegc("(STOCK/BLOCK, ", str(self.stockXwidth), ", ", str(self.stockYheight), ", ", str(self.stockZthickness), ", 0.00, 0.00, ", str(self.stockZthickness), ")")
            if self.stockzero == "Center-Left":
                self.stock = self.stock.translate([0, -stockYheight / 2, -stockZthickness])
                if self.generategcode == True:
                    self.writegc("(stockMin:0.00mm, -", str(self.stockYheight/2), "mm, -", str(self.stockZthickness), "mm)")
                    self.writegc("(stockMax:", str(self.stockXwidth), "mm, ", str(self.stockYheight/2), "mm, 0.00mm)")
                    self.writegc("(STOCK/BLOCK, ", str(self.stockXwidth), ", ", str(self.stockYheight), ", ", str(self.stockZthickness), ", 0.00, ", str(self.stockYheight/2), ", ", str(self.stockZthickness), ")");
            if self.stockzero == "Top-Left":
                self.stock = self.stock.translate([0, -self.stockYheight, -self.stockZthickness])
                if self.generategcode == True:
                    self.writegc("(stockMin:0.00mm, -", str(self.stockYheight), "mm, -", str(self.stockZthickness), "mm)")
                    self.writegc("(stockMax:", str(self.stockXwidth), "mm, 0.00mm, 0.00mm)")
                    self.writegc("(STOCK/BLOCK, ", str(self.stockXwidth), ", ", str(self.stockYheight), ", ", str(self.stockZthickness), ", 0.00, ", str(self.stockYheight), ", ", str(self.stockZthickness), ")")
            if self.stockzero == "Center":
                self.stock = self.stock.translate([-self.stockXwidth / 2, -self.stockYheight / 2, -self.stockZthickness])
                if self.generategcode == True:
                    self.writegc("(stockMin: -", str(self.stockXwidth/2), ", -", str(self.stockYheight/2), "mm, -", str(self.stockZthickness), "mm)")
                    self.writegc("(stockMax:", str(self.stockXwidth/2), "mm, ", str(self.stockYheight/2), "mm, 0.00mm)")
                    self.writegc("(STOCK/BLOCK, ", str(self.stockXwidth), ", ", str(self.stockYheight), ", ", str(self.stockZthickness), ", ", str(self.stockXwidth/2), ", ", str(self.stockYheight/2), ", ", str(self.stockZthickness), ")")
        if self.zeroheight == "Bottom":
            if self.stockzero == "Lower-Left":
                 self.stock = self.stock.translate([0, 0, 0])
                 if self.generategcode == True:
                     self.writegc("(stockMin:0.00mm, 0.00mm, 0.00mm)")
                     self.writegc("(stockMax:", str(self.stockXwidth), "mm, ", str(self.stockYheight), "mm, ", str(self.stockZthickness), "mm)")
                     self.writegc("(STOCK/BLOCK, ", str(self.stockXwidth), ", ", str(self.stockYheight), ", ", str(self.stockZthickness), ", 0.00, 0.00, 0.00)")
            if self.stockzero == "Center-Left":
```

```
                self.stock = self.stock.translate([0, -self.stockYheight / 2, 0])
                if self.generategcode == True:
                    self.writegc("(stockMin:0.00mm,␣-", str(self.stockYheight/2), "mm,␣0.00mm)")
                    self.writegc("(stockMax:", str(self.stockXwidth), "mm,␣", str(self.stockYheight/2), "mm,␣-", str(self.stockZthickness), "mm)")
                    self.writegc("(STOCK/BLOCK,␣", str(self.stockXwidth), ",␣", str(self.stockYheight), ",␣", str(self.stockZthickness), ",␣0.00,␣", str(self.stockYheight/2), ",␣0.00mm)");
            if self.stockzero == "Top-Left":
                self.stock = self.stock.translate([0, -self.stockYheight, 0])
                if self.generategcode == True:
                    self.writegc("(stockMin:0.00mm,␣-", str(self.stockYheight), "mm,␣0.00mm)")
                    self.writegc("(stockMax:", str(self.stockXwidth), "mm,␣0.00mm,␣", str(self.stockZthickness), "mm)")
                    self.writegc("(STOCK/BLOCK,␣", str(self.stockXwidth), ",␣", str(self.stockYheight), ",␣", str(self.stockZthickness), ",␣0.00,␣", str(self.stockYheight), ",␣0.00)")
            if self.stockzero == "Center":
                self.stock = self.stock.translate([-self.stockXwidth / 2, -self.stockYheight / 2, 0])
                if self.generategcode == True:
                    self.writegc("(stockMin:␣-", str(self.stockXwidth/2), ",␣-", str(self.stockYheight/2), "mm,␣0.00mm)")
                    self.writegc("(stockMax:", str(self.stockXwidth/2), "mm,␣", str(self.stockYheight/2), "mm,␣", str(self.stockZthickness), "mm)")
                    self.writegc("(STOCK/BLOCK,␣", str(self.stockXwidth), ",␣", str(self.stockYheight), ",␣", str(self.stockZthickness), ",␣", str(self.stockXwidth/2), ",␣", str(self.stockYheight/2), ",␣0.00)")
        if self.generategcode == True:
            self.writegc("G90");
            self.writegc("G21");
```

Note that while the #102 is declared as a default tool, while it was originally necessary to call a tool change after invoking `setupstock`, in the 2024.09.03 version of PythonSCAD this requirement went away when an update which interfered with persistently setting a variable directly was fixed. The setupstock command is required if working with a 3D project, creating the block of stock which the following toolpath commands will cut away. Note that since Python in OpenPythonSCAD defers output of the 3D model, it is possible to define it once, then set up all the specifics for each possible positioning of the stock in terms of origin.

The OpenSCAD version is simply a descriptor:

```
module setupstock(stockXwidth, stockYheight, stockZthickness, zeroheight, stockzero, retractheight) {
    gcp.setupstock(stockXwidth, stockYheight, stockZthickness, zeroheight, stockzero, retractheight);
}
```

3.3.3.2 setupcuttingarea

If processing G-code, the parameters passed in are necessarily different, and there is of course, no need to write out G-code.

```
    def setupcuttingarea(self, sizeX, sizeY, sizeZ, extentleft, extentfb, extentd):
#        self.initializemachinestate()
        c=cube([sizeX,sizeY,sizeZ])
        c = c.translate([extentleft,extentfb,extentd])
        self.stock = c
        self.toolpaths = []
        return c
```

3.3.3.3 debug

Rather than endlessly add and then comment out `print()` commands, it is easier to have a variable for this, and a command which wraps the command which checks for that:

```
    def debug(self, *args: any, sep: str = "␣", end: str = "\n", **print_kwargs) -> None:
        """
        Print debug output if enabled.

        Accepts the same arguments as built-in print (except file is supported via print_kwargs).
        """
        if not self.debugenable:
            return
        # Build the message and print under a lock to avoid interleaving in multithreaded apps
        self.prefix = "DEBUG:␣"
        msg = self.prefix + sep.join(map(str, args))
        with self._lock:
            print(msg, end=end, **print_kwargs)
```

Note that it will be necessary to manually use commands such as:

```
self.debugenable = True

testvariable = 1

self.outputdebugnote("Current␣value␣of␣testvariable␣is:␣", testvariable)
```

3.3.4 Adjustments and Additions

For certain projects and toolpaths it will be helpful to shift the stock, and to add additional pieces to the project.

Shifting the stock is simple:

```
    def shiftstock(self, shiftX, shiftY, shiftZ):
         self.stock = self.stock.translate([shiftX, shiftY, shiftZ])
```

```
module shiftstock(shiftX, shiftY, shiftZ) {
    gcp.shiftstock(shiftX, shiftY, shiftZ);
}
```

adding stock is similar, but adds the requirement that it include options for shifting the stock:

```
    def addtostock(self, stockXwidth, stockYheight, stockZthickness,
                         shiftX = 0,
                         shiftY = 0,
                         shiftZ = 0):
         addedpart = cube([stockXwidth, stockYheight, stockZthickness])
         addedpart = addedpart.translate([shiftX, shiftY, shiftZ])
         self.stock = self.stock.union(addedpart)
```

the OpenSCAD module is a descriptor as expected:

```
module addtostock(stockXwidth, stockYheight, stockZthickness, shiftX, shiftY, shiftZ) {
    gcp.addtostock(stockXwidth, stockYheight, stockZthickness, shiftX, shiftY, shiftZ);
}
```

3.4 Tools and Shapes and Changes

Originally, it was necessary to return a shape so that modules which use a `<variable>.union` command would function as expected even when the 3D model created is stored in a variable.

rapids
toolpaths
toolmovement

Due to stack limits in OpenSCAD for the CSG tree, instead, the shapes will be stored in two variables (`rapids`, `toolpaths`) as lists processed/created using a command `toolmovement` which will subsume all tool related functionality. As other routines need access to information about the current tool, appropriate routines will allow its variables and the specifics of the current tool to be queried.

It will be necessary to describe the tool in four different fashions:

- variables — a full set of variables is required to allow defining a shape and to determine the appropriate fashion in which to treat each tool at need

  tooltype = "mill"

  diameter = first

  cornerradius = second

  height = third

  taperangle

  length

- profile — the profile is a definition of the tool from the centerline to the outer edge which is used when necessary to `rotate_extrude()` the design
- outline — the outline is the entire definition of the tool shape which is used when `rotate_extrude`ing an arc (which will also require a 3D version of the rotated tool profile at each end)
- shape — originally the program used the tool shape and `hull()`ed it from beginning to end of a movement — having the shape pre-made allows it to be `union()`ed at need.

The base/entry functionality has the instance being defined in terms of a basic set of variables (one of which is overloaded to serve multiple purposes, depending on the type of endmill).

Note that it will also be necessary to write out a tool description compatible with the program CutViewer as a G-code comment so that it may be used as a 3D previewer for the G-code for tool changes in G-code. Several forms are available as described below.

3.4.1 Numbering for Tools

Currently, the numbering scheme used is that of the various manufacturers of the tools, or descriptive short-hand numbers created for tools which lack such a designation (with a disclosure that the author is a Carbide 3D employee).

Creating any numbering scheme is like most things in life, a trade-off, balancing length and expressiveness/compleatness against simplicity and usability. The software application Carbide Create (as released by an employer of the main author) has a limit of six digits, which seems a reasonable length from a complexity/simplicity standpoint, but also potentially reasonably expressible.

It will be desirable to track the following characteristics and measurements, apportioned over the digits as follows:

$$\overbrace{\text{endmill type}}^{1}\overbrace{\text{radius/angle}}^{2-3}\overbrace{\text{cutting diameter(and tip radius for tapered ball nose)}}^{4-5}\overbrace{\text{cutting flute length}}^{6}$$

- 1st digit: endmill type:
  - 0 - manufacturer number
  - 1 - square (incl. “O”-flute)
  - 2 - ball
  - 3 - V
  - 4 - bowl
  - 5 - tapered ball
  - 6 - roundover
  - 7 - thread-cutting
  - 8 - dovetail
  - 9 - other (e.g., user-defined, or unsupported tools, keyhole, lollipop, &c.)
- 2nd and 3rd digits shape radius (ball/roundover) or angle (V), 2nd and 3rd digit together 10–99 indicate measurement in tenth of a millimeter. 2nd digit:
  - 0 - Imperial (00 indicates n/a or square)
  - any other value for both the 2nd and 3rd digits together indicate a metric measurement or an angle in degrees
- 3rd digit (if 2nd is 0 indicating Imperial)
  - 1 - 1/32$^{\text{nd}}$
  - 2 - 1/16
  - 3 - 1/8
  - 4 - 1/4
  - 5 - 5/16

  - 6 - 3/8
  - 7 - 1/2
  - 8 - 3/4
  - 9 - >1″ or other
- 4th and 5th digits cutting diameter as 2nd and 3rd above except 4th digit indicates tip radius for tapered ball nose and such tooling is only represented in Imperial measure:
- 4th digit (tapered ball nose)
  - 1 - 0.01 in (this is the 0.254mm of the #501 and 502)
  - 2 - 0.015625 in (1/64th)
  - 3 - 0.0295
  - 4 - 0.03125 in (1/32nd)
  - 5 - 0.0335
  - 6 - 0.0354
  - 7 - 0.0625 in (1/16th)
  - 8 - 0.125 in (1/8th)
  - 9 - 0.25 in (1/4)
- 6th digit cutting flute length:
  - 0 - other
  - 1 - calculate based on V angle
  - 2 - 1/16
  - 3 - 1/8
  - 4 - 1/4
  - 5 - 5/16
  - 6 - 1/2
  - 7 - 3/4
  - 8 - "long reach" or greater than 3/4″
  - 9 - calculate based on radius
- or 6th digit tip diameter for roundover tooling (added to cutting diameter to arrive at actual cutting diameter — note that these values are the same as for the tip radius of the #501 and 502)
  - 1 - 0.01 in
  - 2 - 0.015625 in (1/64th)
  - 3 - 0.0295
  - 4 - 0.03125 in (1/32nd)
  - 5 - 0.0335
  - 6 - 0.0354
  - 7 - 0.0625 in (1/16th)
  - 8 - 0.125 in (1/8th)
  - 9 - 0.25 in (1/4)

Using this technique to create tool numbers for Carbide 3D tooling we arrive at:

- Square

  #122 == 100012

  #112 == 100024

  #102 == 100036 (also #274 and #326 (Amana 46200-K))

  #201 == 100047 (also #251 and #322 (Amana 46202-K))

  #205 == 100048

  #251 == 100047 (also #201 and #322 (Amana 46202-K))

  #274 == 100036 (also #102 and #326 (Amana 46200-K))

  #278 == 100047

  #282 == 100204

  #322 == 100047 (also #201 and #251)

  #324 == 100048 (Amana 46170-K)

  #326 == 100036 (also #102 and #274)

- Ball

  #121 == 201012

  #111 == 202024

  #101 == 203036

  #202 == 204047

  #325 == 204048 (Amana 46376-K)

- V

  #301 == 390074

  #302 == 360071

  #327 == 360098 (Amana RC-1148)

- Tapered Ball Nose

  #501 == 530131

  #502 == 540131

(note that some dimensions were rounded off/approximated)
Extending that to the non-Carbide 3D tooling thus implemented:

- V

  #390

- Dovetail

  814 == 814071

  45828 == 808071

- Keyhole Tool

  374 == 906043

  375 == 906053

  376 == 907040

  378 == 907050

- Roundover Tool

  56142 == 602032

  56125 == 603042

  1568 == 603032

  1570

  1572 == 604042

  1574

- Threadmill

  648

- Bowl bit

  45981

  45982

  1370

  1372

Tools which do not have calculated numbers filled in are not supported by the system as currently defined in an unambiguous fashion (instead filling in the manufacturer's tool number padded with zeros is hard-coded). Notable limitations:

- No way to indicate flute geometry beyond O-flute (which distinction will probably be removed)
- Lack of precision for metric tooling/limited support for Imperial sizes, notably, the dimensions used are scaled for smaller tooling and are not suited to typically larger scale tooling such as bowl bits
- No way to indicate several fairly common shapes including keyhole, lollipop, and flat-bottomed V/chamfer tools (except of course for using 9#####)

A further consideration is that it is not possible to represent tools unambiguously, so that given a tool definition it is possible to derive the manufacturer's tool number, *e.g.*, given a hypothetical command/instruction:

```
self.currenttoolshape = self.toolshapes("square", 6.35, 19.05)
```

it could be viewed as representing any of three different tools (Carbide 3D #201 (upcut), #251 (downcut), and #322 (Amana 46202-K downcut)), it is worth noting that #205E is differentiated due to its longer flute length as-is #324 (Amana 46170-K compression), though the fact of its compression cutting geometry is not recorded. Affording some sort of hinting to the user may be warranted, or a mechanism to allow specifying a given manufacturer tool # as part of setting up a job.

A more likely scheme is that manufacturer tool numbers will continue to be used to identify tooling, the generated number will be used internally, then the saved manufacturer number will be exported to the G-code file, or used when generating a DXF filename for a given set of tool movements.

```
    def currenttoolnumber(self):
        return(self.currenttoolnum)
```

toolchange

The `toolchange` command will need to set several variables.

Mandatory variables include:

- endmilltype
  - O-flute
  - square
  - ball
  - V
  - keyhole
  - dovetail
  - roundover
  - tapered ball
- diameter
- flute

and depending on the tool geometry, several additional variables will be necessary (usually derived from `self.ra`):

- radius
- angle

an optional setting of a `toolnumber` may be useful in the future.

tool number
toolchange

3.4.1.1 toolchange

This command accepts a `tool number` and assigns its characteristics as parameters. It then applies the appropriate commands for a `toolchange`. Note that it is expected that this code will be updated as needed when new tooling is introduced as additional modules which require specific tooling are added.

Note that the comments written out in G-code correspond to those used by the G-code previewing tool CutViewer (which is unfortunately, no longer readily available). Similarly, the G-code previewing functionality in this library expects that such comments will be in place so as to model the stock.

A further concern is that early versions often passed the tool into a module using a parameter. That ceased to be necessary in the 2024.09.03 version of PythonSCAD, and all modules should read the tool # from `currenttoolnumber()`.

Note that there are many varieties of tooling and not all will be directly supported, and that at need, additional tool shape support may be added under `misc`.

The original implementation created the model for the tool at the current position, and a duplicate at the end position, wrapping the twain for each end of a given movement in a `hull()` command and then applying a `union`. This approach will not work within Python, so it will be necessary to instead assign and select the tool as part of the `toolmovement` command.

settoolparameters
toolchange

There are two separate commands for handling a tool being changed, the first sets the parameters which describe the tool and may be used to effect the change of a tool either in a G-code file or when making a 3D file, `settoolparameters` and a second version which processes a toolchange when presented with a tool number, `toolchange` (it may be that the latter will be set up to call the former).

3.4.1.1.1 settoolparameters

Not currently used, this command is intended for a state where tools are defined in a vendor-neutral fashion.

```
    def settoolparameters(self, tooltype, first, second, third,
        fourth, length = 0):
        if tooltype == "mill":
            diameter = first
            cornerradius = second
```

```
            height = third
            taperangle = fourth
            if cornerradius == 0:
#M6T122 (TOOL/MILL,0.80, 0.00, 1.59, 0.00)
#M6T112 (TOOL/MILL,1.59, 0.00, 6.35, 0.00)
#M6T102 (TOOL/MILL,3.17, 0.00, 12.70, 0.00)
#M6T201 (TOOL/MILL,6.35, 0.00, 19.05, 0.00)
#M6T205 (TOOL/MILL,6.35, 0.00, 25.40, 0.00)
#M6T251 (TOOL/MILL,6.35, 0.00, 19.05, 0.00)
#M6T322 (TOOL/MILL,6.35, 0.00, 19.05, 0.00)
#M6T324 (TOOL/MILL,6.35, 0.00, 22.22, 0.00)
#M6T326 (TOOL/MILL,3.17, 0.00, 12.70, 0.00)
#M6T602 (TOOL/MILL,25.40, 0.00, 9.91, 0.00)
#M6T603 (TOOL/MILL,25.40, 0.00, 9.91, 0.00)
#M6T274 (TOOL/MILL,3.17, 0.00, 12.70, 0.00)
#M6T278 (TOOL/MILL,6.35, 0.00, 19.05, 0.00)
#M6T282 (TOOL/MILL,2.00, 0.00, 6.35, 0.00)
                self.endmilltype = "square"
                self.diameter = diameter
                self.flute = height
                self.shaftdiameter = diameter
                self.shaftheight = height
                self.shaftlength = height
#
            elif cornerradius > 0 and taperangle == 0:
#M6T121 (TOOL/MILL,0.80, 0.40, 1.59, 0.00)
#M6T111 (TOOL/MILL,1.59, 0.79, 6.35, 0.00)
#M6T101 (TOOL/MILL,3.17, 1.59, 12.70, 0.00)
#M6T202 (TOOL/MILL,6.35, 3.17, 19.05, 0.00)
#M6T325 (TOOL/MILL,6.35, 3.17, 25.40, 0.00)
                self.endmilltype = "ball"
                self.diameter = diameter
                self.flute = height
                self.shaftdiameter = diameter
                self.shaftheight = height
                self.shaftlength = height
#
            elif taperangle > 0:
#M6T301 (TOOL/MILL,0.10, 0.05, 6.35, 45.00)
#M6T302 (TOOL/MILL,0.10, 0.05, 6.35, 30.00)
#M6T327 (TOOL/MILL,0.10, 0.05, 23.39, 30.00)
                self.endmilltype = "V"
                self.diameter = Tan(taperangle / 2) * height
                self.flute = height
                self.angle = taperangle
                self.shaftdiameter = Tan(taperangle / 2) * height
                self.shaftheight = height
                self.shaftlength = height
#
        elif tooltype == "chamfer":
            tipdiameter = first
            radius = second
            height = third
            taperangle = fourth
```

toolchange

3.4.1.1.2 toolchange

The Python definition for `toolchange` requires the tool number (used to write out the G-code comment description for CutViewer and also expects the speed for the current tool since this is passed into the G-code tool change command as part of the spindle on command. A simple `if-then` structure, the variables necessary for defining the toolshape are (re)defined each time the command is called so that they may be used by the command

toolmovement

`toolmovement` for actually modeling the shapes and the path and the resultant material removal.

```
    def toolchange(self, tool_number, speed = 10000):
        self.currenttoolnum = tool_number

        if (self.generategcode == True):
            self.writegc("(Toolpath)")
            self.writegc("M05")
```

3.4.1.1.3 Square (including O-flute)

The simplest sort of tool, they are defined as a cylinder.

```
        if (tool_number == 102) or (tool_number == 100036): # 102/326 == 100036
            self.writegc("(TOOL/MILL, 3.175, 0.00, 0.00, 0.00)")
```

```
            self.endmilltype = "square"
            self.diameter = 3.175
            self.flute = 12.7
            self.shaftdiameter = 3.175
            self.shaftheight = 12.7
            self.shaftlength = 19.5
```

The outline definitions for linear/rotate extrude are the same for this tool as in the default tool definition in `__init__`, but the commands `definesquaretool` and `defineshaft` are used:

```
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = 10003
        elif (tool_number == 201) or (tool_number == 100047): # 201/251/322 (Amana 46202-K) == 100047
            self.writegc("(TOOL/MILL,␣6.35,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "square"
            self.diameter = 6.35
            self.flute = 19.05
            self.shaftdiameter = 6.35
            self.shaftheight = 19.05
            self.shaftlength = 20.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "100047"
        elif (tool_number == 112) or (tool_number == 100024): #112 == 100024
            self.writegc("(TOOL/MILL,␣1.5875,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "square"
            self.diameter = 1.5875
            self.flute = 6.35
            self.shaftdiameter = 3.175
            self.shaftheight = 6.35
            self.shaftlength = 12.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength, (self.shaftdiameter - self.diameter)/2)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "100024"
        elif (tool_number == 122) or (tool_number == 100012): #122 == 100012
            self.writegc("(TOOL/MILL,␣0.79375,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "square"
            self.diameter = 0.79375
            self.flute = 1.5875
            self.shaftdiameter = 3.175
            self.shaftheight = 1.5875
            self.shaftlength = 12.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength, (self.shaftdiameter - self.diameter)/2)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "100012"
        elif (tool_number == 324): #324 (Amana 46170-K) == 100048
            self.writegc("(TOOL/MILL,␣6.35,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "square"
            self.diameter = 6.35
            self.flute = 22.225
            self.shaftdiameter = 6.35
            self.shaftheight = 22.225
            self.shaftlength = 20.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "100048"
        elif (tool_number == 205) or (tool_number == 100048): #205 == 100048
            self.writegc("(TOOL/MILL,␣6.35,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "square"
            self.diameter = 6.35
            self.flute = 25.4
```

```
            self.shaftdiameter = 6.35
            self.shaftheight = 25.4
            self.shaftlength = 20.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            defineKeyholetool(self.diameter, self.flute, self.shaftdiameter, self.shaftheight, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "100048"
#
```

The former distinction betwixt Square and O-flute tooling has been removed from the current version.

```
        elif (tool_number == 282) or (tool_number == 100204): #282 == 000204
            self.writegc("(TOOL/MILL,␣2.0,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "O-flute"
            self.diameter = 2.0
            self.flute = 6.35
            self.shaftdiameter = 6.35
            self.shaftheight = 6.35
            self.shaftlength = 12.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength, (self.shaftdiameter - self.diameter)/2)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "100204"
        elif (tool_number == 274) or (tool_number == 100036): #274 == 000036
            self.writegc("(TOOL/MILL,␣3.175,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "O-flute"
            self.diameter = 3.175
            self.flute = 12.7
            self.shaftdiameter = 3.175
            self.shaftheight = 12.7
            self.shaftlength = 20.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "100036"
        elif (tool_number == 278) or (tool_number == 100047): #278 == 000047
            self.writegc("(TOOL/MILL,␣6.35,␣0.00,␣0.00,␣0.00)")
            self.endmilltype = "O-flute"
            self.diameter = 6.35
            self.flute = 19.05
            self.shaftdiameter = 3.175
            self.shaftheight = 19.05
            self.shaftlength = 20.0
            self.definesquaretool(self.diameter, self.shaftheight, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "100047"
#
```

3.4.1.1.4 Ball-nose (including tapered-ball) The `elifs` continue with ball-nose and tapered-ball tooling which are defined as one would expect by spheres and cylinders. Note that the Cutviewer definition of a the measurement point of a tool being at the center is not yet set up — potentially it opens up greatly simplified toolpath calculations and may be implemented in a future version.

```
        elif (tool_number == 202) or (tool_number == 204047): #202 == 204047
            self.writegc("(TOOL/MILL,␣6.35,␣3.175,␣0.00,␣0.00)")
            self.endmilltype = "ball"
            self.diameter = 6.35
            self.flute = 19.05
            self.shaftdiameter = 6.35
            self.shaftheight = 19.05
            self.shaftlength = 20.0
```

```
            self.defineballnosetool(self.diameter, self.flute, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "204047"
        elif (tool_number == 101) or (tool_number == 203036): #101 == 203036
            self.writegc("(TOOL/MILL, 3.175, 1.5875, 0.00, 0.00)")
            self.endmilltype = "ball"
            self.diameter = 3.175
            self.flute = 12.7
            self.shaftdiameter = 3.175
            self.shaftheight = 12.7
            self.shaftlength = 20.0
            self.defineballnosetool(self.diameter, self.flute, self.shaftlength)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "203036"
        elif (tool_number == 111) or (tool_number == 202024): #111 == 202024
            self.writegc("(TOOL/MILL, 1.5875, 0.79375, 0.00, 0.00)")
            self.endmilltype = "ball"
            self.diameter = 1.5875
            self.flute = 6.35
            self.shaftdiameter = 3.175
            self.shaftheight = 6.35
            self.shaftlength = 20.0
            self.defineballnosetool(self.diameter, self.flute, self.shaftlength, (self.shaftdiameter - self.diameter)/2)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "202024"
        elif (tool_number == 121) or (tool_number == 201012): #121 == 201012
            self.writegc("(TOOL/MILL, 3.175, 0.79375, 0.00, 0.00)")
            self.endmilltype = "ball"
            self.diameter = 0.79375
            self.flute = 1.5875
            self.shaftdiameter = 3.175
            self.shaftheight = 1.5875
            self.shaftlength = 20.0
            self.defineballnosetool(self.diameter, self.flute, self.shaftlength, (self.shaftdiameter - self.diameter)/2)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "201012"
        elif (tool_number == 325) or (tool_number == 204048): #325 (Amana 46376-K) == 204048
            self.writegc("(TOOL/MILL, 6.35, 3.175, 0.00, 0.00)")
            self.endmilltype = "ball"
            self.diameter = 6.35
            self.flute = 25.4
            self.shaftdiameter = 6.35
            self.shaftheight = 25.4
            self.shaftlength = 20.0
            self.defineballnosetool(self.diameter, self.flute, self.shaftlength, (self.shaftdiameter - self.diameter)/2)
            self.defineshaft(self.diameter, self.shaftdiameter, self.flute, 0, self.shaftlength)
            self.toolnumber = "204048"
#
```

3.4.1.1.5 V Note that one V tool is described as an Engraver in Carbide Create. While CutViewer has specialty Tool/chamfer and Tool/drill parameters, it is possible to describe a V tool as a Tool/mill (using a very small tip radius).

```
        elif (tool_number == 301) or (tool_number == 390074): #301 == 390074
            self.writegc("(TOOL/MILL, 0.10, 0.05, 6.35, 45.00)")
            self.endmilltype = "V"
            self.diameter = 12.7
```

```
            self.flute = 6.35
            self.angle = 90
            self.shaftdiameter = 6.35
            self.shaftheight = 6.35
            self.shaftlength = 20.0
            self.defineVtool(self.diameter, self.flute, self.shaftlength, self.shaftdiameter)
            self.toolnumber = "390074"
        elif (tool_number == 302) or (tool_number == 360071): #302 == 360071
            self.writegc("(TOOL/MILL, 0.10, 0.05, 6.35, 30.00)")
            self.endmilltype = "V"
            self.diameter = 12.7
            self.flute = 11.067
            self.angle = 60
            self.shaftdiameter = 6.35
            self.shaftheight = 11.067
            self.shaftlength = 20.0
            self.defineVtool(self.diameter, self.flute, self.shaftlength, self.shaftdiameter)
            self.toolnumber = "360071"
        elif (tool_number == 390) or (tool_number == 390032): #390 == 390032
            self.writegc("(TOOL/MILL, 0.03, 0.00, 1.5875, 45.00)")
            self.endmilltype = "V"
            self.diameter = 3.175
            self.flute = 1.5875
            self.angle = 90
            self.shaftdiameter = 3.175
            self.shaftheight = 1.5875
            self.shaftlength = 20.0
            self.defineVtool(self.diameter, self.flute, self.shaftlength, self.shaftdiameter)
            self.toolnumber = "390032"
        elif (tool_number == 327) or (tool_number == 360098): #327 (Amana RC-1148) == 360098
            self.writegc("(TOOL/MILL, 0.03, 0.00, 13.4874, 30.00)")
            self.endmilltype = "V"
            self.diameter = 25.4
            self.flute = 22.134
            self.angle = 60
            self.shaftdiameter = 6.35
            self.shaftheight = 22.134
            self.shaftlength = 20.0
            self.defineVtool(self.diameter, self.flute, self.shaftlength, self.shaftdiameter)
            self.toolnumber = "360098"
        elif (tool_number == 323) or (tool_number == 330041): #323 == 330041 30 degree V Amana, 45771-K
            self.writegc("(TOOL/MILL, 0.10, 0.05, 11.18, 15.00)")
            self.endmilltype = "V"
            self.diameter = 6.35
            self.flute = 11.849
            self.angle = 30
            self.shaftdiameter = 6.35
            self.shaftheight = 11.849
            self.shaftlength = 20.0
            self.defineVtool(self.diameter, self.flute, self.shaftlength, self.shaftdiameter)
            self.toolnumber = "330041"
#
```

3.4.1.1.6 Keyhole

Keyhole tooling will primarily be used with a dedicated toolpath.

```
        elif (tool_number == 374) or (tool_number == 906043): #374 == 906043
            self.writegc("(TOOL/MILL, 9.53, 0.00, 3.17, 0.00)")
            self.endmilltype = "keyhole"
            self.diameter = 9.525
            self.flute = 3.175
            self.radius = 6.35
            self.shaftdiameter = 6.35
            self.shaftheight = 3.175
            self.shaftlength = 20.0
            self.defineKeyholetool(self.diameter, self.flute, self.shaftdiameter, self.shaftheight, self.shaftdiameter, self.shaftlength)
```

```
            self.toolnumber = "906043"
        elif (tool_number == 375) or (tool_number == 906053): #375 == 906053
            self.writegc("(TOOL/MILL,␣9.53,␣0.00,␣3.17,␣0.00)")
            self.endmilltype = "keyhole"
            self.diameter = 9.525
            self.flute = 3.175
            self.radius = 8
            self.shaftdiameter = 6.35
            self.shaftheight = 3.175
            self.shaftlength = 20.0
            self.defineKeyholetool(self.diameter, self.flute, self.shaftdiameter, self.shaftheight, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "906053"
        elif (tool_number == 376) or (tool_number == 907040): #376 == 907040
            self.writegc("(TOOL/MILL,␣12.7,␣0.00,␣4.77,␣0.00)")
            self.endmilltype = "keyhole"
            self.diameter = 12.7
            self.flute = 4.7625
            self.radius = 6.35
            self.shaftdiameter = 6.35
            self.shaftheight = 4.7625
            self.shaftlength = 20.0
            self.defineKeyholetool(self.diameter, self.flute, self.shaftdiameter, self.shaftheight, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "907040"
        elif (tool_number == 378) or (tool_number == 907050): #378 == 907050
            self.writegc("(TOOL/MILL,␣12.7,␣0.00,␣4.77,␣0.00)")
            self.endmilltype = "keyhole"
            self.diameter = 12.7
            self.flute = 4.7625
            self.radius = 8
            self.shaftdiameter = 6.35
            self.shaftheight = 4.7625
            self.shaftlength = 20.0
            self.defineKeyholetool(self.diameter, self.flute, self.shaftdiameter, self.shaftheight, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "907050"
#
```

3.4.1.1.7 Bowl

This geometry is also useful for square endmills with a radius.

```
        elif (tool_number == 45981): #45981 == 445981
#Amana Carbide Tipped Bowl & Tray 1/8 Radius x 1/2 Dia x 1/2 x 1/4 Inch Shank
            self.writegc("(TOOL/MILL,0.03,␣0.00,␣10.00,␣30.00)")
            self.writegc("(TOOL/MILL,␣15.875,␣6.35,␣19.05,␣0.00)")
            self.endmilltype = "bowl"
            self.diameter = 12.7
            self.flute = 12.7
            self.radius = 3.175
            self.shaftdiameter = 6.35
            self.shaftheight = 12.7
            self.shaftlength = 20.0
            self.definebowltool(self.diameter, self.flute, self.radius, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "445981"
        elif (tool_number == 45982):#0.507/2, 4.509
            self.writegc("(TOOL/MILL,␣15.875,␣6.35,␣19.05,␣0.00)")
            self.endmilltype = "bowl"
            self.diameter = 19.05
            self.flute = 15.875
            self.radius = 6.35
            self.shaftdiameter = 6.35
            self.shaftheight = 15.875
            self.shaftlength = 20.0
            self.definebowltool(self.diameter, self.flute, self.radius, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "445982"
        elif (tool_number == 1370): #1370 == 401370
#Whiteside Bowl & Tray Bit 1/4"SH, 1/8"R, 7/16"CD (5/16" cutting flute length)
```

```
            self.writegc("(TOOL/MILL,␣11.1125,␣8,␣3.175,␣0.00)")
            self.endmilltype = "bowl"
            self.diameter = 11.1125
            self.flute = 8
            self.radius = 3.175
            self.shaftdiameter = 6.35
            self.shaftheight = 8
            self.shaftlength = 20.0
            self.definebowltool(self.diameter, self.flute, self.radius, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "401370"
        elif (tool_number == 1372): #1372/45982 == 401372
#Whiteside Bowl & Tray Bit 1/4"SH, 1/4"R, 3/4"CD (5/8" cutting flute length)
#Amana Carbide Tipped Bowl & Tray 1/4 Radius x 3/4 Dia x 5/8 x 1/4 Inch Shank
            self.writegc("(TOOL/MILL,␣19.5,␣15.875,␣6.35,␣0.00)")
            self.endmilltype = "bowl"
            self.diameter = 19.5
            self.flute = 15.875
            self.radius = 6.35
            self.shaftdiameter = 6.35
            self.shaftheight = 15.875
            self.shaftlength = 20.0
            self.definebowltool(self.diameter, self.flute, self.radius, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "401372"
#
```

3.4.1.1.8 Tapered ball nose One vendor which provides such tooling is Precise Bits: https://www.precisebits.com/products/carbidebits/taperedcarve250b2f.asp&filter=7, but unfortunately, their tool numbering is ambiguous, the version of each major number (204 and 304) for their 1/4″ shank tooling which is sufficiently popular to also be offered in a ZRN coating could be used. Similarly, the #501 and #502 PCB engravers from Carbide 3D are supported.

Outlines and profiles for these tools are stored in SVG files:

```
501_outline.svg
501_profile.svg
501_shaft_outline.svg
501_shaft_profile.svg
502_outline.svg
502_profile.svg
502_shaft_outline.svg
502_shaft_profile.svg
```

which are then imported into the appropriate variables when a tool is loaded.

```
        elif (tool_number == 501) or (tool_number == 530131): #501 == 530131
            self.writegc("(TOOL/MILL,0.03,␣0.00,␣10.00,␣30.00)")
#             self.currenttoolshape = self.toolshapes("tapered ball", 3.175, 5.561, 30, 0.254)
            self.tooloutline = osimport("501_outline.svg")
            self.toolprofile = osimport("501_profile.svg")
            self.endmilltype = "tapered␣ball"
            self.diameter = 3.175
            self.flute = 5.561
            self.angle = 30
            self.tip = 0.254
            self.shaftdiameter = 3.175
            self.shaftheight = 5.561
            self.shaftlength = 10.0
            self.toolnumber = "530131"
        elif (tool_number == 502) or (tool_number == 540131): #502 == 540131
            self.writegc("(TOOL/MILL,0.03,␣0.00,␣10.00,␣20.00)")
#             self.currenttoolshape = self.toolshapes("tapered ball", 3.175, 4.117, 40, 0.254)
            self.endmilltype = "tapered␣ball"
            self.diameter = 3.175
            self.flute = 4.117
            self.angle = 40
            self.tip = 0.254
            self.shaftdiameter = 3.175
            self.shaftheight = 4.117
            self.shaftlength = 10.0
            self.toolnumber = "540131"
```

```
#         elif (tool_number == 204):#
#             self.writegc("()")
#             self.currenttoolshape = self.tapered_ball(1.5875, 6.35, 38.1, 3.6)
#         elif (tool_number == 304):#
#             self.writegc("()")
#             self.currenttoolshape = self.tapered_ball(3.175, 6.35, 38.1, 2.4)
#
```

3.4.1.1.9 Roundover (cove tooling)

Note that the parameters will need to incorporate the tip diameter into the overall diameter.

```
        elif (tool_number == 56125) or (tool_number == 603042):#0.508/2, 1.531 56125 == 603042
            self.writegc("(TOOL/CRMILL,␣0.508,␣6.35,␣3.175,␣7.9375,␣3.175)")
            self.endmilltype = "roundover"
            self.tipdiameter = 0.508
            self.diameter = 6.35 - self.tipdiameter
            self.flute = 8 - self.tipdiameter
            self.radius = 3.175 - self.tipdiameter/2
            self.shaftdiameter = 6.35
            self.shaftheight = 8
            self.shaftlength = 10.0
            self.defineRoundovertool(self.diameter, self.tipdiameter, self.flute, self.radius, self.shaftdiameter, self.shaftlength)
            self.toolnumber = "603042"
        elif (tool_number == 56142) or (tool_number == 602032):#0.508/2, 2.921 56142 == 602032
            self.writegc("(TOOL/CRMILL,␣0.508,␣3.571875,␣1.5875,␣5.55625,␣1.5875)")
            self.endmilltype = "roundover"
            self.tip = 0.508
            self.diameter = 3.175 - self.tip
            self.flute = 4.7625 - self.tip
            self.radius = 1.5875 - self.tip/2
            self.shaftdiameter = 3.175
            self.shaftheight = 4.7625
            self.shaftlength = 10.0
            self.toolnumber = "602032"
#         elif (tool_number == 312):#1.524/2, 3.175
#             self.writegc("(TOOL/CRMILL, Diameter1, Diameter2, Radius, Height, Length)")
#         elif (tool_number == 1568):#0.507/2, 4.509 1568 == 603032
##FIX             self.writegc("(TOOL/CRMILL, 0.17018, 9.525, 4.7625, 12.7, 4.7625)")
##             self.currenttoolshape = self.toolshapes("roundover", 3.175, 6.35, 3.175, 0.396875)
#             self.endmilltype = "roundover"
#             self.diameter = 3.175
#             self.flute = 6.35
#             self.radius = 3.175
#             self.tip = 0.396875
#             self.toolnumber = "603032"
##https://www.amanatool.com/45982-carbide-tipped-bowl-tray-1-4-radius-x-3-4-dia-x-5-8-x-1-4-inch-shank.html
#         elif (tool_number == 1570):#0.507/2, 4.509 1570 == 600002 ?!?
#             self.writegc("(TOOL/CRMILL, 0.17018, 9.525, 4.7625, 12.7, 4.7625)")
##             self.currenttoolshape = self.toolshapes("roundover", 4.7625, 9.525, 4.7625, 0.396875)
#             self.endmilltype = "roundover"
#             self.diameter = 4.7625
#             self.flute = 9.525
#             self.radius = 4.7625
#             self.tip = 0.396875
#             self.toolnumber = "600002"
#         elif (tool_number == 1572): #1572 = 604042
##FIX             self.writegc("(TOOL/CRMILL, 0.17018, 9.525, 4.7625, 12.7, 4.7625)")
##             self.currenttoolshape = self.toolshapes("roundover", 6.35, 12.7, 6.35, 0.396875)
#             self.endmilltype = "roundover"
```

```
#             self.diameter = 6.35
#             self.flute = 12.7
#             self.radius = 6.35
#             self.tip = 0.396875
#             self.toolnumber = "604042"
#         elif (tool_number == 1574): #1574 == 600062
##FIX             self.writegc("(TOOL/CRMILL, 0.17018, 9.525, 4.7625, 12.7, 4.7625)")
##             self.currenttoolshape = self.toolshapes("roundover", 9.525, 19.5, 9.515, 0.396875)
#             self.endmilltype = "roundover"
#             self.diameter = 9.525
#             self.flute = 19.5
#             self.radius = 9.515
#             self.tip = 0.396875
#             self.toolnumber = "600062"
#
```

3.4.1.1.10 Dovetails

Unfortunately, tools which support undercuts such as dovetails are not supported by many CAM tools including Carbide Create and CutViewer (CAMotics will work for such tooling, at least dovetails which may be defined as "stub" endmills with a bottom diameter greater than upper diameter).

```
        elif (tool_number == 814) or (tool_number == 814071): #814 == 814071
#Item 18J1607, 1/2" 14ř Dovetail Bit, 8mm shank
            self.writegc("(TOOL/MILL,␣12.7,␣6.367,␣12.7,␣0.00)")
        #     dt_bottomdiameter, dt_topdiameter, dt_height, dt_angle)
        #     https://www.leevalley.com/en-us/shop/tools/power-tool-accessories/router-bits/30172-dovetail-bits?item=18J1607
#             self.currenttoolshape = self.toolshapes("dovetail", 12.7, 12.7, 14)
            self.endmilltype = "dovetail"
            self.diameter = 12.7
            self.flute = 12.7
            self.angle = 14
            self.toolnumber = "814071"
        elif (tool_number == 808079) or (tool_number == 808071): #45828 == 808071
            self.writegc("(TOOL/MILL,␣12.7,␣6.816,␣20.95,␣0.00)")
        #     http://www.amanatool.com/45828-carbide-tipped-dovetail-8-deg-x-1-2-dia-x-825-x-1-4-inch-shank.html
#             self.currenttoolshape = self.toolshapes("dovetail", 12.7, 20.955, 8)
            self.endmilltype = "dovetail"
            self.diameter = 12.7
            self.flute = 20.955
            self.angle = 8
            self.toolnumber = "808071"
#
```

Each tool must be modeled in 3D using OpenSCAD commands, but it will also be necessary to have a consistent structure for managing the various shapes and aspects of shapes.

While tool shapes were initially handled as geometric shapes stored in Python variables, processing them as such after the fashion of OpenSCAD required the use of `union()` commands and assigning a small initial object (usually a primitive placed at the origin) so that the union could take place. This has the result of creating a nested union structure in the CSG tree which can quickly become so deeply nested that it exceeds the limits set in PythonSCAD.

As was discussed in the PythonSCAD Google Group (https://groups.google.com/g/pythonscad/c/rtiYa38W8tY), if a list is used instead, then the contents of the list are added all at once at a single level when processed.

An example file which shows this concept:

```
from openscad import *
fn=200

box = cube([40,40,40])

features = []

features.append(cube([36,36,40]) + [2,2,2])
features.append(cylinder(d=20,h=5) + [20,20,-1])
features.append(cylinder(d=3,h=10) ^ [[5,35],[5,35], -1])
```

```
part = difference(box, features)

show(part)
```

As per usual, the OpenSCAD command is simply a dispatcher:

```
module toolchange(tool_number, speed){
    gcp.toolchange(tool_number, speed);
}
```

For example:

```
toolchange(small_square_tool_num, speed);
```

(the assumption is that all speed rates in a file will be the same, so as to account for the most frequent use case of a trim router with speed controlled by a dial setting and feed rates/ratios being calculated to provide the correct chipload at that setting.)

3.4.1.1.11 closing G-code With the tools delineated, the module is closed out and the toolchange information written into the G-code as well as the command to start the spindle at the specified speed.

One possible feature for the G-code for tool changes would be to have the various ratios available and then to apply the appropriate one. Directly applying them in the file generated by the user is sufficiently straight-forward that this expedient option seems a needless complexity unless a compelling reason comes up.

```
        self.writegc("M6T", str(tool_number))
#         if (self.endmilltype == "square"):
#             speed = speed *
        self.writegc("M03S", str(speed))
```

3.4.2 Laser support

Two possible options for supporting a laser present themselves: color-coded DXFs or direct G-code support. An example file for the latter:
https://lasergrbl.com/test-file-and-samples/depth-of-focus-test/

```
M3 S0
S0
G0X0Y16
S1000
G1X100F1200
S0
M5 S0
M3 S0
S0
G0X0Y12
S1000
G1X100F1000
S0
M5 S0
M3 S0
S0
G0X0Y8
S1000
G1X100F800
S0
M5 S0
M3 S0
S0
G0X0Y4
S1000
G1X100F600
S0
M5 S0
M3 S0
S0
G0X0Y0
S1000
G1X100F400
S0
M5 S0
```

3.5 Shapes and tool movement

cut...
rapid...

With all the scaffolding in place, it is possible to model the tool and `hull()` between copies of the 3D model of the tool, or a cross-section of it for both `cut...` and `rapid...` operations.

Alternately, describing tools in terms of outline will allow using `linear/rotate_extrude` to be used which requires a description of the tools as profiles/outlines, but which matches the `G0/G1` and `G2/G3` G-code commands.

The majority of commands will be more general, focusing on tooling which is generally supported by this library, moving in lines and arcs so as to describe shapes which lend themselves to representation with those tools and which match up with both toolpaths and supported geometry in Carbide Create, and the usage requirements of the typical user.

This structure has the notable advantage that if a tool shape is represented as a list and always handled thus, then representing complex shapes which need to be represented in discrete elements/parts becomes a natural thing to do and the program architecture is simpler since all possible shapes may be handled by the same code/logic with no need to identify different shapes and handle them differently.

Note that it will be preferable to use `extend` if the variable to be added contains a list rather than `append` since the former will flatten out the list and add the individual elements, so that a list remains a list of elements rather than becoming a list of lists and elements, except that there will be at least two elements to each tool model list:

- cutting *tool* shape (note that this may be either a single model, or a list of discrete slices of the tool shape)
- *shaft*

and when a cut is made by hulling each element from the cut begin position to its end position, this will be done using different colors so that the shaft rubbing may be identified on the 3D surface of the preview of the cut.

3.5.1 Tooling for Undercutting Toolpaths

There are several notable candidates for undercutting tooling.

- Keyhole tools — intended to cut slots for retaining hardware used for picture hanging, they may be used to create slots for other purposes Note that it will be necessary to model these thrice, once for the actual keyhole cutting, second for the fluted portion of the shaft, and then the shaft should be modeled for collision https://assetssc.leevalley.com/en-gb/shop/tools/power-tool-accessories/router-bits/30113-keyhole-router-bits
- Dovetail cutters — used for the joinery of the same name, they cut a large area at the bottom which slants up to a narrower region at a defined angle
- Lollipop cutters — normally used for 3D work, as their name suggests they are essentially a (cutting) ball on a narrow stick (the tool shaft), they are mentioned here only for compleatness' sake and are not (at this time) implemented
- Threadmill — used for cutting threads, normally a single form geometry is used on a CNC.

3.5.2 Generalized commands and cuts

The first consideration is a naming convention which will allow a generalized set of associated commands to be defined. The initial version will only create OpenSCAD commands for 3D modeling and write out matching DXF files. At a later time this will be extended with G-code support.

There are three different movements in G-code which will need to be handled. Rapid commands will be used for G0 movements and will not appear in DXFs but will appear in G-code files, while straight line cut (G1) and arc (G2/G3) commands may appear in both G-code and DXF files, depending on the specific command invoked.

3.5.3 Movement and color

toolmovement
shaftmovement

The first command which must be defined is `toolmovement` which is used as the core of the other commands, affording a 3D model of the tool moving in a straight line. A matching `shaftmovement` command will allow modeling collision of the shaft with the stock should it occur. This differentiation raises the matter of color representation. Using a different color for the shape of the endmill when cutting and for rapid movements will similarly allow identifying instances of the tool crashing through stock at rapid speed.

```
gcpy     def setcolor(self,
gcpy                   cutcolor = "green",
gcpy                   rapidcolor = "orange",
gcpy                   shaftcolor = "red"):
gcpy         self.cutcolor = cutcolor
gcpy         self.rapidcolor = rapidcolor
gcpy         self.shaftcolor = shaftcolor
```

The possible colors are those of Web colors (https://en.wikipedia.org/wiki/Web_colors), while DXF has its own set of colors based on numbers (see table) and applying a Venn diagram and removing problematic extremes we arrive at the third column above as black and white are potentially inconsistent/confusing since at least one CAD program toggles them based on light/dark mode being applied to its interface.

Table 1: Colors in OpenSCAD and DXF

Web Colors (OpenSCAD)	**DXF**	**Both**
Black	"Black" (0)	
Red	"Red" (1)	Red
Yellow	"Yellow" (2)	Yellow
Green	"Green" (3)	Green
	"Cyan" (4)	
Blue	"Blue" (5)	Blue
	"Magenta" (6)	
White	"White" (7)	
Gray	"Dark Gray" (8)	(Dark) Gray
	"Light Gray" (9)	
Silver		
Maroon		
Olive		
Lime		
Aqua		
Teal		
Navy		
Fuchsia		
Purple		

(note that the names are not case-sensitive)

Most tools are easily implemented with concise 3D descriptions which may be connected with a simple `hull` operation. Note that extending the normal case to a pair of such operations, one for the shaft, the other for the cutting shape will markedly simplify the code, and will make it possible to color-code the shaft which may afford indication of instances of it rubbing against the stock.

Note that the variables `self.rapids` and `self.toolpaths` are used to hold the list of accumulated 3D models of the rapid motions and cuts as elements in lists so that they may be `difference`d from the stock.

3.5.3.1 toolmovement The `toolmovement` command incorporates the color variables to indicate cutting and differentiate rapid movements and the tool shaft.

Diagramming this is quite straight-forward — there is simply a movement made from the current position to the end. If we start at the origin, `X0`, `Y0`, `Z0`, then it is simply a straight-line movement (rapid)/cut (possibly a partial cut in the instance of a keyhole or roundover tool), and no variables change value.

The code for diagramming this is quite straight-forward. A BlockSCAD implementation is available at: https://www.blockscad3d.com/community/projects/1894400, and the OpenSCAD version is only a little more complex (adding code to ensure positioning):



```
    def toolmovement(self, bx, by, bz, ex, ey, ez, step = 0):
        tslist = []
        if step > 0:
            steps = step
        else:
            steps = self.steps
#
```

endmill square

3.5.3.1.1 Square (including O-flute)

The `endmill square` is a simple cylinder:

```
        if self.endmilltype == "square":
            ts = cylinder(r1=(self.diameter / 2), r2=(self.diameter / 2), h=self.flute, center = False)
            tslist.append(hull(ts.translate([bx, by, bz]), ts.translate([ex, ey, ez])))
            return tslist
#
#        if self.endmilltype == "O-flute":
#            ts = cylinder(r1=(self.diameter / 2), r2=(self.diameter / 2), h=self.flute, center = False)
#            tslist.append(hull(ts.translate([bx, by, bz]), ts.translate([ex, ey, ez])))
#            return tslist
#
```

ballnose

3.5.3.1.2 Ball nose (including tapered ball nose)

The `ballnose` is modeled as a hemisphere joined with a cylinder:

```
        if self.endmilltype == "ball":
            b = sphere(r=(self.diameter / 2))
            s = cylinder(r1=(self.diameter / 2), r2=(self.diameter / 2), h=self.flute, center=False)
            bs = union(b, s)
            bs = bs.translate([0, 0, (self.diameter / 2)])
            tslist.append(hull(bs.translate([bx, by, bz]), bs.translate([ex, ey, ez])))
            return tslist
#
```

3.5.3.1.3 bowl

The bowl tool is modeled as a series of cylinders stacked on top of each other and `hull()`ed together:

```
        if self.endmilltype == "bowl":
            inner = cylinder(r1 = self.diameter/2 - self.radius, r2 = self.diameter/2 - self.radius, h = self.flute)
            outer = cylinder(r1 = self.diameter/2, r2 = self.diameter/2, h = self.flute - self.radius)
            outer = outer.translate([0,0, self.radius])
            slices = hull(outer, inner)
#     slices = cylinder(r1 = 0.0001, r2 = 0.0001, h = 0.0001, center=False)
            for i in range(1, 90 - self.steps, self.steps):
                slice = cylinder(r1 = self.diameter / 2 - self.radius + self.radius * Sin(i), r2 = self.diameter / 2 - self.radius + self.radius * Sin(i+self.steps), h = self.radius/90, center=False)
                slices = hull(slices, slice.translate([0, 0, self.radius - self.radius * Cos(i+self.steps)]))
            tslist.append(hull(slices.translate([bx, by, bz]), slices.translate([ex, ey, ez])))
            return tslist
#
```

endmill v

3.5.3.1.4 V

The `endmill v` is modeled as a cylinder with a zero width base and a second cylinder for the shaft (note that Python's `math` defaults to radians, hence the need to convert from degrees if using it, but fortunately, trigonometric commands have been added to OpenPythonSCAD (`Sin`, `Cos`, `Tan`, `Atan`)):

```
        if self.endmilltype == "V":
```

```
            v = cylinder(r1=0, r2=(self.diameter / 2), h=((self.diameter / 2) / Tan((self.angle / 2))), center=False)
#            s = cylinder(r1=(self.diameter / 2), r2=(self.diameter / 2), h=self.flute, center=False)
#            sh = s.translate([0, 0, ((self.diameter / 2) / Tan((self.angle / 2)))])
            tslist.append(hull(v.translate([bx, by, bz]), v.translate([ex, ey, ez])))
            return tslist
```

3.5.3.1.5 Keyhole Keyhole toolpaths (see: subsection 3.8.1.1.3 are intended for use with tooling which projects beyond the narrower shaft and so will cut usefully underneath the visible surface. Also described as "undercut" tooling, but see below.



Keyhole Router Bits

#	A	B	C	D
374	3/8″	1/8″	1/4″	3/8″
375	9.525mm	3.175mm	8mm	9.525mm
376	1/2″	3/16″	1/4″	1/2″
378	12.7mm	4.7625mm	8mm	12.7mm



```
        if self.endmilltype == "keyhole":
            kh = cylinder(r1=(self.diameter / 2), r2=(self.diameter / 2), h=self.flute, center=False)
            sh = (cylinder(r1=(self.radius / 2), r2=(self.radius / 2), h=self.flute*2, center=False))
            tslist.append(hull(kh.translate([bx, by, bz]), kh.translate([ex, ey, ez])))
            tslist.append(hull(sh.translate([bx, by, bz]), sh.translate([ex, ey, ez])))
            return tslist
```

3.5.3.1.6 Tapered ball nose The tapered ball nose tool is modeled as a sphere at the tip and a pair of cylinders, where one (a cone) describes the taper, while the other represents the shaft.

```
        if self.endmilltype == "tapered␣ball":
            b = sphere(r=(self.tip / 2))
            s = cylinder(r1=(self.tip / 2), r2=(self.diameter / 2), h=self.flute, center=False)
            bshape = union(b, s)
            tslist.append(hull(bshape.translate([bx, by, bz]), bshape.translate([ex, ey, ez])))
            return tslist
```

dovetail

3.5.3.1.7 Dovetails The `dovetail` is modeled as a cylinder with the differing bottom and top diameters determining the angle (though `dt_angle` is still required as a parameter)

```
        if self.endmilltype == "dovetail":
            dt = cylinder(r1=(self.diameter / 2), r2=(self.diameter / 2) - self.flute * Tan(self.angle), h= self.flute, center=False)
            tslist.append(hull(dt.translate([bx, by, bz]), dt.translate([ex, ey, ez])))
            return tslist
        if self.endmilltype == "other":
            tslist = []
#    def dovetail(self, dt_bottomdiameter, dt_topdiameter, dt_height, dt_angle):
```

```
#         return cylinder(r1=(dt_bottomdiameter / 2), r2=(dt_topdiameter / 2), h= dt_height, center=False)
```

3.5.3.2 Concave toolshapes

While normal tooling may be represented with a one (or more) hull operation(s) betwixt two 3D toolshapes (or six in the instance of keyhole tools), concave tooling such as roundover/radius tooling require multiple sections or even slices of the tool shape to be modeled separately which are then hulled together. Something of this can be seen in the manual work-around for previewing them: https://community.carbide3d.com/t/using-unsupported-tooling-in-carbide-create-roundover-cove-radius-bits/43723.

Because it is necessary to divide the tooling into vertical slices and call the hull operation for each slice the tool definitions have to be called separately in the cut... modules, or integrated at the lowest level.

3.5.3.2.1 Roundover tooling

It is not possible to represent all tools using tool changes as coded above which require using a hull operation between 3D representations of the tools at the beginning and end points. Tooling which cannot be so represented will be implemented separately

roundover below, see paragraph 3.5.3.2 — roundover tooling will need to generate a list of slices of the tool shape hulled together.

```
        if self.endmilltype == "roundover":
            shaft = cylinder(self.steps, self.tip/2, self.tip/2)
            toolpath = hull(shaft.translate([bx, by, bz]), shaft.translate([ex, ey, ez]))
            shaft = cylinder(self.flute, self.diameter/2 + self.tip/2, self.diameter/2 + self.tip/2)
            toolpath = toolpath.union(hull(shaft.translate([bx, by, bz + self.radius]), shaft.translate([ex, ey, ez + self.radius])))
            tslist = [toolpath]
            slice = cylinder(0.0001, 0.0001, 0.0001)
            slices = slice
            for i in range(1, 90 - self.steps, self.steps):
                dx = self.radius*Cos(i)
                dxx = self.radius*Cos(i + self.steps)
                dzz = self.radius*Sin(i)
                dz = self.radius*Sin(i + self.steps)
                dh = dz - dzz
                slice = cylinder(r1 = self.tip/2+self.radius-dx, r2 = self.tip/2+self.radius-dxx, h = dh)
                slices = slices.union(hull(slice.translate([bx, by, bz+dz]), slice.translate([ex, ey, ez+dz])))
                tslist.append(slices)
            return tslist
```

Note that this routine does *not* alter the machine position variables since it may be called multiple times for a given toolpath, *e.g.*, for arcs. This command will then be called in the definitions for rapid and cutline which only differ in which variable the 3D model list is unioned with.

shaftmovement A similar routine will be used to handle the shaftmovement.

shaftmovement 3.5.3.3 shaftmovement

The shaftmovement command uses variables defined as part of the tool definition to determine the Z-axis position of the cylinder used to represent the shaft and its diameter and height:

```
    def shaftmovement(self, bx, by, bz, ex, ey, ez):
        tslist = []
        ts = cylinder(r1=(self.shaftdiameter / 2), r2=(self.shaftdiameter / 2), h=self.shaftlength, center = False)
        ts = ts.translate([0, 0, self.shaftheight])
        tslist.append(hull(ts.translate([bx, by, bz]), ts.translate([ex, ey, ez])))
        return tslist
```

3.5.3.4 tool outlines

Defining the tools as outlines which may be scaled to different sizes and rotate_extruded requires a series of modules which must define:

- self.tooloutline — the entire outline of the tool used for rotate_extrude when cutting an arc (or a line if linear_extrude is used)
- self.toolprofile — the profile of one half of the tool suited to creating a 3D model using rotate_extrude
- self.shaftoutline

- self.shaftprofile
- self.currenttoolshape
- self.currenttoolshaft

Note that when defining tooling it is expedient to use a mix of the 2D and 3D systems.

The various `self.<toolparameters>` are defined in `toolchange` and may be used at need.

An expedient option would seem to be slicing the 3D model and hulling slices from the begin/end positions, but that may result in distortions for certain tool geometries (*e.g.,* keyhole tooling).

There are several possible options for handling outlines and models — a hybrid approach governed by `if` branches will allow optimization of the resultant CSG commands.

- simple shape and straight move — 3D models of the tool at the begin and end points of the move are `hull`ed
- complex shape and straight move — 3D models of the tool at the begin and end points of the move are connected by a `linear_extrude`
- any shape and arc move — 3D models of the tool at the begin and end points of the move are connected by a `rotate_extrude`

Similarly for the tool profiles and outlines and 3D shapes:

- `polygon` — defining the shape in terms of point positions (note the PythonSCAD has an option for rounding which may be used for some shapes)
- 2D — defining the shape using rectangles or polygons and circles and Boolean operations
- SVG — drawing up the outlines and profiles in a vector drawing tool so that they may be imported as SVG files allows any shape to be imported. Filenames would be mapped to the tool numbering scheme.

3.5.3.4.1 defineshaft A separate command for defining the shaft is expedient, and allows handling the case of the cutting diameter and the shaft diameter being different, and by including both diameters as arguments, allows the transition, if not abrupt, to be modeled. The parameters:

- toolingdiameter
- shaftdiameter
- flute
- transition
- shaft

are obvious except for `shaft` — rather than the O.A.L., this is the expected length of the tool as measured from the specified `flute` and `transition` lengths to the bottom of the collet. In the absence of a specified length, the flute length (assuming no transition) should be a workable approximation.

Frequently, tools will have different diameters for cutting end and shaft — when the former is smaller, the angle typically seems to be 60 degrees — since this should *not* be used for modeling, the expedient solution is to use an easily drawn angle which is obtuse enough to be obvious, so 45 degrees will be used.

```
    def defineshaft(self, toolingdiameter, shaftdiameter, flute,
        transition, shaft):
        if shaftdiameter == 0:
            self.shaftoutline = polygon(points=[[0, flute], [
                diameter, flute], [diameter, shaft],[0, shaft]])
            self.shaftprofile = polygon(points=[[0, flute], [
                diameter/2 ,flute], [diameter/2, shaft], [0, shaft
                ]])
            sh = cylinder(h = shaft, r = diameter/2)
            self.currenttoolshaft = sh.translate([0,0,flute])
        if shaftdiameter > 0:
            self.shaftoutline = polygon(points=[
                [shaftdiameter / 2 - toolingdiameter / 2, flute],
                [0, flute + transition],
                [0, flute + transition + shaft],
                [shaftdiameter, flute + transition + shaft],
                [shaftdiameter, flute + transition],
                [shaftdiameter / 2 + toolingdiameter / 2, flute],
                ] )
            self.shaftprofile = polygon( points= [
                [0, flute],
```

```
                    [0, flute + transition + shaft],
                    [shaftdiameter/2, flute + transition + shaft],
                    [shaftdiameter/2, flute + transition],
                    [toolingdiameter/2, flute]
                    ] )
                self.currenttoolshaft = rotate_extrude(self.shaftprofile)
```

3.5.3.4.2 Square (including O-flute) The simplest sort of tooling, which is easily defined using a polygon and cylinder.

```
    def definesquaretool(self, diameter, flute, shaft, offset = 0):
        self.tooloutline = polygon( points=[[0 + offset,0],[diameter + offset,0],[diameter + offset,flute],[0 + offset,flute]] )
        self.toolprofile = polygon( points=[[0,0],[diameter/2,0],[diameter/2,flute],[0,flute]] )
        self.currenttoolshape = cylinder(h = flute, r = diameter/2)
        sh = cylinder(h = flute, r = diameter/2)
```

3.5.3.4.3 Ball-nose (including tapered-ball) Defined using 2D and 3D primitives which are unioned together, this allows the shape of the tool to be influenced by the variables fa/fs/fn.

```
    def defineballnosetool(self, diameter, flute, shaft, offset = 0):
        s = square([diameter,flute - diameter/2])
        sh = s.translate([0 + offset, diameter/2])
        c = circle(d=diameter)
        b = c.translate([diameter/2 + offset, diameter/2])
        self.tooloutline = union(sh, b)
#
        s = square([diameter/2,flute - diameter/2])
        sh = s.translate([0, diameter/2])
        c = circle(d=diameter)
        b = c.translate([0, diameter/2])
        bn = union(sh, b)
#        bns = bn.translate([0, diameter/2])
        thein = square([diameter/2,flute])
#        theins = thein.translate([diameter/2, 0])
        self.toolprofile = intersection(thein, bn)
#
        self.shaftprofile = polygon( points=[[0,flute],[diameter/2,flute],[diameter/2,shaft],[0,shaft]] )
#
#        b = self.toolprofile
#        bn = b.translate([-diameter/2, 0])
        self.currenttoolshape = rotate_extrude(self.toolprofile)
#
        self.currenttoolshaft = sh.translate([0,0,flute])
```

3.5.3.4.4 V tool outline V shaped tooling often has the V cutting flutes attached to a cylindrical shaft.

```
    def defineVtool(self, diameter, flute, shaft, shaftdiameter = 0):
        self.tooloutline = polygon([[diameter/2, 0], [diameter, flute], [0, flute]])
#

        self.toolprofile = polygon([[0, 0], [diameter/2, flute], [0, flute]])

#
        if shaftdiameter == 0:
            shaftdiameter = diameter
        self.shaftprofile = polygon([[0, flute], [shaftdiameter/2, flute], [shaftdiameter/2, flute + shaft], [0, flute + shaft]])

#
        self.currenttoolshape = rotate_extrude(self.toolprofile)
#
```

```
        self.currenttoolshaft = rotate_extrude(self.shaftprofile)
```

3.5.3.4.5 Keyhole outline

Keyhole outlines will require two cutting surfaces, since it is usual for the shaft to have cutting flutes for clearing the narrow region as part of their functionality.

```
    def defineKeyholetool(self, diameter, flute, narrowdiameter, narrowflute, shaftdiameter, shaftlength):

        self.tooloutline = polygon([[0, 0], [diameter, 0], [diameter, flute], [diameter/2 + narrowdiameter/2, flute], [diameter/2 + narrowdiameter/2, flute + narrowflute], [diameter/2 - narrowdiameter/2, flute + narrowflute], [diameter/2 - narrowdiameter/2, flute], [0, flute]])
#

        self.toolprofile = polygon([[0, 0], [diameter/2, 0], [diameter/2, flute], [narrowdiameter/2, flute], [narrowdiameter/2, flute + narrowflute], [0, flute + narrowflute]])
#
        self.shaftprofile = polygon([[0, flute + narrowflute], [narrowdiameter/2, flute + narrowflute], [shaftdiameter/2, flute + narrowflute + shaftlength], [0, flute + narrowflute + shaftlength]])

#
        self.currenttoolshape = rotate_extrude(self.toolprofile)
#
        self.currenttoolshaft = rotate_extrude(self.shaftprofile)
```

3.5.3.4.6 Bowl outline

Bowl tooling is done using `polygon()` with the third value added so as to cause the rounding of the radius.

```
    def definebowltool(self, diameter, flute, radius, shaftdiameter, shaftlength):
#        self.tooloutline =
#
        self.toolprofile = polygon([[0,0], [diameter/2, 0, radius], [diameter/2, radius], [diameter/2, flute], [0, flute]])
#
        self.shaftprofile = polygon([[0,flute], [shaftdiameter/2, flute], [shaftdiameter/2, flute + shaftlength], [0, flute + shaftlength]])
#
        self.currenttoolshape = rotate_extrude(self.toolprofile)
#
        self.currenttoolshaft = rotate_extrude(self.shaftprofile)
```

3.5.3.4.7 Tapered ball nose

Creating outlines for Tapered ball nose tooling will require that the arc and tangent for the angle and rounding be calculated out if programmed, or instead, they may be drawn.

3.5.3.4.8 Roundover (cove tooling)

The `polygon()` command does not afford an option for coves, so it will be necessary to over-draw the geometry, then remove the cove if programming, or, to simply draw the outline.

```
    def defineRoundovertool(self, diameter, tipdiameter, flute, radius, shaftdiameter, shaftlength):
#            self.tip = 0.508
#            self.diameter = 6.35 - self.tip
#            self.flute = 8 - self.tip
#            self.radius = 3.175 - self.tip/2
#            self.shaftdiameter = 6.35
#            self.shaftheight = 8
#            self.shaftlength = 10.0
#        print(diameter)
#        print(tipdiameter)
#        print(flute)
#        print(radius)
#        print(shaftdiameter)
#        print(shaftlength)
#        self.tooloutline =
```

```
#
        self.toolprofile = polygon([[0,0], [tipdiameter/2, 0], [diameter/2, flute], [0, flute]])
#
        self.shaftprofile = polygon([[0,flute], [shaftdiameter/2, flute], [shaftdiameter/2, flute + shaftlength], [0, flute + shaftlength]])
#
        self.currenttoolshape = rotate_extrude(self.toolprofile)
#
        self.currenttoolshaft = rotate_extrude(self.shaftprofile)
```

rapid **3.5.3.5 rapid and cut (lines)** A matching pair of commands is made for these, and `rapid` is used as the basis for a series of commands which match typical usages of `G0`.

Note the addition of a Laser mode which simulates the tool having been turned off before making a rapid movement — likely further changes will be required.

```
    def rapid(self, ex, ey, ez, laser = 0):
#        print(self.rapidcolor)
        if self.generateprint == True:
            laser = 1
        if laser == 0:
            tm = self.toolmovement(self.xpos(), self.ypos(), self.zpos(), ex, ey, ez)
            tm = color(tm, self.shaftcolor)
            ts = self.shaftmovement(self.xpos(), self.ypos(), self.zpos(), ex, ey, ez)
            ts = color(ts, self.rapidcolor)
            self.toolpaths.extend([tm, ts])
        self.setxpos(ex)
        self.setypos(ey)
        self.setzpos(ez)

    def cutline(self, ex, ey, ez):
#        print(self.cutcolor)
#        print(ex, ey, ez)
        tm = self.toolmovement(self.xpos(), self.ypos(), self.zpos(), ex, ey, ez)
        tm = color(tm, self.cutcolor)
        ts = self.shaftmovement(self.xpos(), self.ypos(), self.zpos(), ex, ey, ez)
        ts = color(ts, self.rapidcolor)
        self.setxpos(ex)
        self.setypos(ey)
        self.setzpos(ez)
        if self.generatecut == True:
            self.toolpaths.extend([tm, ts])
```

It is then possible to add specific `rapid...` commands to match typical usages of G-code. The first command needs to be a move to/from the safe Z height. In G-code this would be:

```
(Move to safe Z to avoid workholding)
G53G0Z-5.000
```

but in the 3D model, since we do not know how tall the Z-axis is, we simply move to safe height and use that as a starting point:

```
    def movetosafeZ(self):
        rapid = self.rapid(self.xpos(), self.ypos(), self.retractheight)
#        if self.generatepaths == True:
#            rapid = self.rapid(self.xpos(), self.ypos(), self.retractheight)
#            self.rapids = self.rapids.union(rapid)
#        else:
#  if (generategcode == true) {
#  //    writecomment("PREPOSITION FOR RAPID PLUNGE");Z25.650
#  //G1Z24.663F381.0, "F", str(plunge)
#        if self.generatepaths == False:
#            return rapid
#        else:
#            return cube([0.001, 0.001, 0.001])
        return rapid

    def rapidXYZ(self, ex, ey, ez):
        rapid = self.rapid(ex, ey, ez)
```

```
#        if self.generatepaths == False:
        return rapid

    def rapidXY(self, ex, ey):
        rapid = self.rapid(ex, ey, self.zpos())
#        if self.generatepaths == True:
#            self.rapids = self.rapids.union(rapid)
#        else:
#        if self.generatepaths == False:
        return rapid

    def rapidXZ(self, ex, ez):
        rapid = self.rapid(ex, self.ypos(), ez)
#        if self.generatepaths == False:
        return rapid

    def rapidYZ(self, ey, ez):
        rapid = self.rapid(self.xpos(), ey, ez)
#        if self.generatepaths == False:
        return rapid

    def rapidX(self, ex):
        rapid = self.rapid(ex, self.ypos(), self.zpos())
#        if self.generatepaths == False:
        return rapid

    def rapidY(self, ey):
        rapid = self.rapid(self.xpos(), ey, self.zpos())
#        if self.generatepaths == False:
        return rapid

    def rapidZ(self, ez):
        rapid = [self.rapid(self.xpos(), self.ypos(), ez)]
#        if self.generatepaths == True:
#            self.rapids = self.rapids.union(rapid)
#        else:
#        if self.generatepaths == False:
        return rapid
```

Note that rather than re-create the matching OpenSCAD commands as descriptors, due to the issue of redirection and return values and the possibility for errors it is more expedient to simply re-create the matching command (at least for the rapids):

```
module movetosafeZ(){
    gcp.rapid(gcp.xpos(), gcp.ypos(), retractheight);
}

module rapid(ex, ey, ez) {
    gcp.rapid(ex, ey, ez);
}

module rapidXY(ex, ey) {
    gcp.rapid(ex, ey, gcp.zpos());
}

module rapidXZ(ex, ez) {
    gcp.rapid(ex, gcp.zpos(), ez);
}

module rapidZ(ez) {
    gcp.rapid(gcp.xpos(), gcp.ypos(), ez);
}
```

Similarly, there is a series of `cutline...` commands as predicted above.

`cut...` `cutline` The Python commands `cut...` add the `currenttool` to the `toolpath` `hull`ed together at the current position and the end position of the move. For `cutline`, this is a straight-forward connection of the current (beginning) and ending coordinates:

```
    def moveatfeedrate(self, ex, ey, ez, f):
        self.writegc("G01 X", str(ex), " Y", str(ey), " Z", str(ez)
            , " F", str(f))
        self.feedrate = f
        return self.cutline(ex, ey, ez)

    def cutlinedxf(self, ex, ey, ez):
        self.dxfline(self.currenttoolnumber(), self.xpos(), self.
            ypos(), ex, ey)
```

```
        self.cutline(ex, ey, ez)

    def cutlinedxfgc(self, ex, ey, ez):
        self.dxfline(self.currenttoolnumber(), self.xpos(), self.ypos(), ex, ey)
        self.writegc("G01 X", str(ex), " Y", str(ey), " Z", str(ez))
        self.cutline(ex, ey, ez)

    def cutvertexdxf(self, ex, ey, ez):
        self.addvertex(self.currenttoolnumber(), ex, ey)
        self.writegc("G01 X", str(ex), " Y", str(ey), " Z", str(ez))
        self.cutline(ex, ey, ez)

    def cutlineXYZwithfeed(self, ex, ey, ez, feed):
        return self.cutline(ex, ey, ez)

    def cutlineXYZ(self, ex, ey, ez):
        return self.cutline(ex, ey, ez)

    def cutlineXYwithfeed(self, ex, ey, feed):
        return self.cutline(ex, ey, self.zpos())

    def cutlineXY(self, ex, ey):
        return self.cutline(ex, ey, self.zpos())

    def cutlineXZwithfeed(self, ex, ez, feed):
        return self.cutline(ex, self.ypos(), ez)

    def cutlineXZ(self, ex, ez):
        return self.cutline(ex, self.ypos(), ez)

    def cutlineXwithfeed(self, ex, feed):
        return self.cutline(ex, self.ypos(), self.zpos())

    def cutlineX(self, ex):
        return self.cutline(ex, self.ypos(), self.zpos())

    def cutlineYZ(self, ey, ez):
        return self.cutline(self.xpos(), ey, ez)

    def cutlineYwithfeed(self, ey, feed):
        return self.cutline(self.xpos(), ey, self.zpos())

    def cutlineY(self, ey):
        return self.cutline(self.xpos(), ey, self.zpos())

    def cutlineZgcfeed(self, ez, feed):
        self.writegc("G01 Z", str(ez), "F", str(feed))
        return self.cutline(self.xpos(), self.ypos(), ez)

    def cutlineZwithfeed(self, ez, feed):
        return self.cutline(self.xpos(), self.ypos(), ez)

    def cutlineZ(self, ez):
        return self.cutline(self.xpos(), self.ypos(), ez)
```

The matching OpenSCAD command is a descriptor:

```
module cutline(ex, ey, ez){
    gcp.cutline(ex, ey, ez);
}

module cutlinedxfgc(ex, ey, ez){
    gcp.cutlinedxfgc(ex, ey, ez);
}

module cutlineZgcfeed(ez, feed){
    gcp.cutlineZgcfeed(ez, feed);
}
```

3.5.3.6 Arcs A further consideration here is that G-code and DXF support arcs in addition to the lines already implemented. Implementing arcs wants at least the following options for quadrant and direction:

- cutarcCW — cut a partial arc described in a clock-wise direction
- cutarcCC — counter-clock-wise
- cutarcNWCW — cut the upper-left quadrant of a circle moving clockwise
- cutarcNWCC — upper-left quadrant counter-clockwise
- cutarcNECW
- cutarcNECC
- cutarcSECW
- cutarcSECC
- cutarcNECW
- cutarcNECC
- cutcircleCC — while it won't matter for generating a DXF, when G-code is implemented direction of cut will be a consideration for that
- cutcircleCW
- cutcircleCCdxf
- cutcircleCWdxf

It will be necessary to have two separate representations of arcs — the G-code and DXF may be easily and directly supported with a single command, but representing the matching tool movement in OpenSCAD may be done in two different fashions. Originally, a series of short line movements which approximate the arc cutting in each direction and at changing Z-heights so as to allow for threading and similar operations was implemented, but instead representing the tool as an outline and using `rotate_extrude` to model the movement of the tool's outline representation through the arc movement.

- G-code — G2 (clockwise) and G3 (counter-clockwise) arcs may be specified, and since the endpoint is the positional requirement, it is most likely best to use the offset to the center (I and J), rather than the radius parameter (K) `G2/3 ...`
- DXF — `dxfarc(xcenter, ycenter, radius, anglebegin, endangle, tn)`
- approximation of arc using lines (OpenSCAD) in both clock-wise and counter-clock-wise directions

Cutting the quadrant arcs greatly simplifies the calculation and interface for the modules. A full set of 8 will be necessary, then circles will have a pair of modules (one for each cut direction) made for them.

Parameters which will need to be passed in are:

- `ex` — note that the matching origins (`bx`, `by`, `bz`) as well as the (current) toolnumber are accessed using the appropriate commands for machine position
- `ey`
- `ez` — allowing a different Z position will make possible threading and similar helical toolpaths
- `xcenter` — the center position will be specified as an absolute position which will require calculating the offset when it is used for G-code's `IJ`, for which `xctr/yctr` are suggested
- `ycenter`
- `radius` — while this could be calculated, passing it in as a parameter is both convenient and (potentially) could be used as a check on the other parameters
- `tpzreldim` — the relative depth (or increase in height) of the current cutting motion

There are two possibilities for arc movement:

- stepping through the arc and approximating with straight line movements
- using `rotate_extrude` to move an outline of the tool through the specified arc — this has the added complexity of being limited to the range of the arc, requiring that the round profile of the tool be instantiated in 3D at each end

cutarcCW
cutarcCC

Stepping through the arc manually is done by iterating through a loop: cutarcCW (clockwise) or cutarcCC (counterclockwise) to handle the drawing and processing of the cutline() toolpaths as short line segments which additionally affords a single point of control for adding additional features such as allowing the depth to vary as one cuts along an arc (the line version is used rather than shape so as to capture the changing machine positions with each step through the loop). Note that the definition matches the DXF definition of defining the center position with a matching radius, but it will be necessary to move the tool to the actual origin, and to calculate the end position when writing out a G2/G3 arc.

This brings to the fore the fact that at its heart, this program is simply graphing math in 3D using tools (as presaged by the book series *Make:Geometry/Trigonometry/Calculus*). This is clear in a depiction of the algorithm for the cutarcCC/CW commands, where the x value is the cos of the radius and the y value the sin:



The code for which makes this obvious:

```
/* [Machine Position] */
mpx = 0;
/* [Machine Position] */
mpy = 0;
/* [Machine Position] */
mpz = 0;

/* [Command Arguments] */
ex = 50;
/* [Command Arguments] */
ey = 25;
/* [Command Arguments] */
ez = -10;

/* [Tooling] */
currenttoolnum = 102;

machine_extents();

radius = 50;
$fa = 2;
$fs = 0.125;

plot_arc(radius, 0, 0, 0, radius, 0, 0, 0, radius, 0, 90, 5);

module plot_arc(bx, by, bz, ex, ey, ez, acx, acy, radius, barc, earc, inc){
for (i = [barc : inc : earc-inc]) {
  union(){
    hull()
    {
      translate([acx + cos(i)*radius,
                 acy + sin(i)*radius,
                 0]){
        sphere(r=0.5);
      }
      translate([acx + cos(i+inc)*radius,
                 acy + sin(i+inc)*radius,
                 0]){
```

```
        sphere(r=0.5);
      }
    }
      translate([acx + cos(i)*radius,
                 acy + sin(i)*radius,
                 0]){
      sphere(r=2);
    }
      translate([acx + cos(i+inc)*radius,
                 acy + sin(i+inc)*radius,
                 0]){
      sphere(r=2);
    }
  }
}
}

module machine_extents(){
translate([-200, -200, 20]){
  cube([0.001, 0.001, 0.001], center=true);
}
translate([200, 200, 20]){
  cube([0.001, 0.001, 0.001], center=true);
}
}
```

Note that it is necessary to move to the beginning cutting position before calling, and that it is necessary to pass in the relative change in Z position/depth. (Previous iterations calculated the increment of change outside the loop, but it is more workable to do so inside.)

```
    def cutarcCC(self, barc, earc, xcenter, ycenter, radius, tpzreldim, stepsizearc=1):
        tpzinc = tpzreldim / (earc - barc)
        i = barc
        while i < earc:
            self.cutline(xcenter + radius * Cos(i), ycenter + radius * Sin(i), self.zpos()+tpzinc)
            i += stepsizearc
#        self.setxpos(xcenter + radius * Cos(earc))
#        self.setypos(ycenter + radius * Sin(earc))

    def cutarcCW(self, barc, earc, xcenter, ycenter, radius, tpzreldim, stepsizearc=1):
#        print(str(self.zpos()))
#        print(str(ez))
#        print(str(barc - earc))
#        tpzinc = ez - self.zpos() / (barc - earc)
#        print(str(tzinc))
#        global toolpath
#        print("Entering n toolpath")
        tpzinc = tpzreldim / (barc - earc)
#        cts = self.currenttoolshape
#        toolpath = cts
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
#        toolpath = []
        i = barc
        while i > earc:
            self.cutline(xcenter + radius * Cos(i), ycenter + radius * Sin(i), self.zpos()+tpzinc)
#            self.setxpos(xcenter + radius * Cos(i))
#            self.setypos(ycenter + radius * Sin(i))
#            print(str(self.xpos()), str(self.ypos(), str(self.zpos())))
#            self.setzpos(self.zpos()+tpzinc)
            i += abs(stepsizearc) * -1
#        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, barc, earc)
#        if self.generatepaths == True:
#            print("Unioning n toolpath")
#            self.toolpaths = self.toolpaths.union(toolpath)
#        else:
        self.setxpos(xcenter + radius * Cos(earc))
        self.setypos(ycenter + radius * Sin(earc))
#        self.toolpaths.extend(toolpath)
#        if self.generatepaths == False:
#        return toolpath
#        else:
```

```
#            return cube([0.01, 0.01, 0.01])
```

Alternately, the command for using `rotate_extrude` is quite straight-forward:

```
    def extrudearcCC(self, barc, earc, xcenter, ycenter, radius, tpzreldim, stepsizearc=1):
#        tm = self.toolmovement(self.xpos(), self.ypos(), self.zpos(), ex, ey, ez)
        tm = union(self.toolshape.translate(self.xpos(), self.ypos(), self.zpos()))
#                    self.toolshape.translate(),
#                    tooloutline.translate([r-3.175,0,0]).rotate_extrude(angle=ang2-ang1).rotz(ang1) + G3_center

        tm = color(tm, self.cutcolor)
        ts = self.shaftmovement(self.xpos(), self.ypos(), self.zpos(), ex, ey, ez)
        ts = color(ts, self.rapidcolor)
        self.setxpos(ex)
        self.setypos(ey)
        self.setzpos(ez)
        self.toolpaths.extend([tm, ts])
```

Note that it will be necessary to add versions which write out a matching DXF element:

```
    def cutarcCWdxf(self, barc, earc, xcenter, ycenter, radius, tpzreldim, stepsizearc=1):
        self.cutarcCW(barc, earc, xcenter, ycenter, radius, tpzreldim, stepsizearc=1)
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, earc, barc)
#        if self.generatepaths == False:
#        return toolpath
#        else:
#            return cube([0.01, 0.01, 0.01])

    def cutarcCCdxf(self, barc, earc, xcenter, ycenter, radius, tpzreldim, stepsizearc=1):
        self.cutarcCC(barc, earc, xcenter, ycenter, radius, tpzreldim, stepsizearc=1)
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, barc, earc)
```

Matching OpenSCAD modules are easily made:

```
module cutarcCC(barc, earc, xcenter, ycenter, radius, tpzreldim){
    gcp.cutarcCC(barc, earc, xcenter, ycenter, radius, tpzreldim);
}

module cutarcCW(barc, earc, xcenter, ycenter, radius, tpzreldim){
    gcp.cutarcCW(barc, earc, xcenter, ycenter, radius, tpzreldim);
}
```

An alternate interface which matches how G2/G3 arcs are programmed in G-code is a useful option:

```
    def cutquarterCCNE(self, ex, ey, ez, radius):
        if self.zpos() == ez:
            tpzinc = 0
        else:
            tpzinc = (ez - self.zpos()) / 90
#        print("tpzinc ", tpzinc)
        i = 1
        while i < 91:
            self.cutline(ex + radius * Cos(i), ey - radius + radius * Sin(i), self.zpos()+tpzinc)
            i += 1

    def cutquarterCCNW(self, ex, ey, ez, radius):
        if self.zpos() == ez:
            tpzinc = 0
        else:
            tpzinc = (ez - self.zpos()) / 90
#            tpzinc = (self.zpos() + ez) / 90
        self.debug("tpzinc␣", tpzinc)
        i = 91
```

```
        while i < 181:
            self.cutline(ex + radius + radius * Cos(i), ey + radius * Sin(i), self.zpos()+tpzinc)
            i += 1

    def cutquarterCCSW(self, ex, ey, ez, radius):
        if self.zpos() == ez:
            tpzinc = 0
        else:
            tpzinc = (ez - self.zpos()) / 90
#            tpzinc = (self.zpos() + ez) / 90
#        print("tpzinc ", tpzinc)
        i = 181
        while i < 271:
            self.cutline(ex + radius * Cos(i), ey + radius + radius * Sin(i), self.zpos()+tpzinc)
            i += 1

    def cutquarterCCSE(self, ex, ey, ez, radius):
        if self.zpos() == ez:
            tpzinc = 0
        else:
            tpzinc = (ez - self.zpos()) / 90
#            tpzinc = (self.zpos() + ez) / 90
#        print("tpzinc ", tpzinc)
        i = 271
        while i < 361:
            self.cutline(ex - radius + radius * Cos(i), ey + radius * Sin(i), self.zpos()+tpzinc)
            i += 1

    def cutquarterCCNEdxf(self, ex, ey, ez, radius):
        self.cutquarterCCNE(ex, ey, ez, radius)
        self.dxfarc(self.currenttoolnumber(), ex, ey - radius, radius,  0, 90)

    def cutquarterCCNWdxf(self, ex, ey, ez, radius):
        self.cutquarterCCNW(ex, ey, ez, radius)
        self.dxfarc(self.currenttoolnumber(), ex + radius, ey, radius, 90, 180)

    def cutquarterCCSWdxf(self, ex, ey, ez, radius):
        self.cutquarterCCSW(ex, ey, ez, radius)
        self.dxfarc(self.currenttoolnumber(), ex, ey + radius, radius, 180, 270)

    def cutquarterCCSEdxf(self, ex, ey, ez, radius):
        self.cutquarterCCSE(ex, ey, ez, radius)
        self.dxfarc(self.currenttoolnumber(), ex - radius, ey, radius, 270, 360)
```

```
module cutquarterCCNE(ex, ey, ez, radius){
     gcp.cutquarterCCNE(ex, ey, ez, radius);
}

module cutquarterCCNW(ex, ey, ez, radius){
     gcp.cutquarterCCNW(ex, ey, ez, radius);
}

module cutquarterCCSW(ex, ey, ez, radius){
    gcp.cutquarterCCSW(ex, ey, ez, radius);
}

module cutquarterCCSE(self, ex, ey, ez, radius){
    gcp.cutquarterCCSE(ex, ey, ez, radius);
}

module cutquarterCCNEdxf(ex, ey, ez, radius){
     gcp.cutquarterCCNEdxf(ex, ey, ez, radius);
}

module cutquarterCCNWdxf(ex, ey, ez, radius){
     gcp.cutquarterCCNWdxf(ex, ey, ez, radius);
}

module cutquarterCCSWdxf(ex, ey, ez, radius){
    gcp.cutquarterCCSWdxf(ex, ey, ez, radius);
```

```
gcpscad }
gcpscad
gcpscad module cutquarterCCSEdxf(self, ex, ey, ez, radius){
gcpscad     gcp.cutquarterCCSEdxf(ex, ey, ez, radius);
gcpscad }
```

3.5.4 tooldiameter

It will also be necessary to be able to provide the diameter of the current tool. Arguably, this would be much easier using an object-oriented programming style/dot notation.

One aspect of tool parameters which will need to be supported is shapes which create different profiles based on how deeply the tool is cutting into the surface of the material at a given point. To accommodate this, it will be necessary to either track the thickness of uncut material at any given point, or, to specify the depth of cut as a parameter.

tool diameter The public-facing OpenSCAD code, `tool diameter` simply calls the matching OpenSCAD module which wraps the Python code:

```
gcpscad function tool_diameter(td_tool, td_depth) = otool_diameter(td_tool,
        td_depth);
```

tool diameter the Python code, `tool diameter` returns appropriate values based on the specified tool number and depth:

```
gcpy     def tool_diameter(self, ptd_tool, ptd_depth):
gcpy # Square 122, 112, 102, 201
gcpy         if ptd_tool == 122:
gcpy             return 0.79375
gcpy         if ptd_tool == 112:
gcpy             return 1.5875
gcpy         if ptd_tool == 102:
gcpy             return 3.175
gcpy         if ptd_tool == 201:
gcpy             return 6.35
gcpy # Ball 121, 111, 101, 202
gcpy         if ptd_tool == 122:
gcpy             if ptd_depth > 0.396875:
gcpy                 return 0.79375
gcpy             else:
gcpy                 return ptd_tool
gcpy         if ptd_tool == 112:
gcpy             if ptd_depth > 0.79375:
gcpy                 return 1.5875
gcpy             else:
gcpy                 return ptd_tool
gcpy         if ptd_tool == 101:
gcpy             if ptd_depth > 1.5875:
gcpy                 return 3.175
gcpy             else:
gcpy                 return ptd_tool
gcpy         if ptd_tool == 202:
gcpy             if ptd_depth > 3.175:
gcpy                 return 6.35
gcpy             else:
gcpy                 return ptd_tool
gcpy # V 301, 302, 390
gcpy         if ptd_tool == 301:
gcpy             return ptd_tool
gcpy         if ptd_tool == 302:
gcpy             return ptd_tool
gcpy         if ptd_tool == 390:
gcpy             return ptd_tool
gcpy # Keyhole
gcpy         if ptd_tool == 374:
gcpy             if ptd_depth < 3.175:
gcpy                 return 9.525
gcpy             else:
gcpy                 return 6.35
gcpy         if ptd_tool == 375:
gcpy             if ptd_depth < 3.175:
gcpy                 return 9.525
gcpy             else:
gcpy                 return 8
gcpy         if ptd_tool == 376:
gcpy             if ptd_depth < 4.7625:
gcpy                 return 12.7
gcpy             else:
```

```
                return 6.35
        if ptd_tool == 378:
            if ptd_depth < 4.7625:
                return 12.7
            else:
                return 8
# Dovetail
        if ptd_tool == 814:
            if ptd_depth > 12.7:
                return 6.35
            else:
                return ptd_tool
        if ptd_tool == 808079:
            if ptd_depth > 20.95:
                return 6.816
            else:
                return ptd_tool
# Bowl Bit
#https://www.amanatool.com/45982-carbide-tipped-bowl-tray-1-4-radius-x-3-4-dia-x-5-8-x-1-4-inch-shank.html
        if ptd_tool == 45982:
            if ptd_depth > 6.35:
                return 15.875
            else:
                return ptd_tool
# Tapered Ball Nose
        if ptd_tool == 204:
            if ptd_depth > 6.35:
                return ptd_tool
        if ptd_tool == 304:
            if ptd_depth > 6.35:
                return ptd_tool
            else:
                return ptd_tool
```

`tool radius`

Since it is often necessary to utilise the radius of the tool, an additional command, `tool radius` to return this value is worthwhile:

```
    def tool_radius(self, ptd_tool, ptd_depth):
        tr = self.tool_diameter(ptd_tool, ptd_depth)/2
        return tr
```

(Note that where values are not fully calculated values currently the passed in tool number (`ptd tool`)is returned which will need to be replaced with code which calculates the appropriate values.)

3.5.5 Feeds and Speeds

`feed` `plunge` `speed`

There are several possibilities for handling feeds and speeds. Currently, base values for `feed`, `plunge`, and `speed` are used, which may then be adjusted using various `<tooldescriptor>_ratio` values, as an acknowledgement of the likelihood of a trim router being used as a spindle, the assumption is that the `speed` will remain unchanged.

The tools which need to be calculated thus are those in addition to the `large_square` tool:

- `small_square_ratio`
- `small_ball_ratio`
- `large_ball_ratio`
- `small_V_ratio`
- `large_V_ratio`
- `KH_ratio`
- `DT_ratio`

3.5.6 3D Printing

Support for 3D printing requires that there be G-code commands for non-mill/router aspects such as:

- fan(s) on/off
- extruder(s)
- Heater(s)

- temperature(s)
- accelerometers
- load cells
- Filament Sensor(s)
- Filament Cutter(s)
- Display Status
  - Message
  - Build Percentage
  - (Clear) Message
- any additional commands such as "Clean Nozzle"

Moreover, it will be necessary for all values to be adjusted for specific firmware, printer and filament type combinations. Probably the best beginning will be to create a simple file using a tested set of settings in a compatible slicer as a template and to adjust based on the values from such a file.

3.5.6.1 Sample 3D printing file

```
M106 S0
M106 P2 S0
;TYPE:Custom
;;===== date: 20240520 =====================
;printer_model:Elegoo Centauri Carbon
;initial_filament:PLA
;curr_bed_type:Textured PEI Plate
M400 ; wait for buffer to clear
M220 S100 ;Set the feed speed to 100%
M221 S100 ;Set the flow rate to 100%
M104 S140
M140 S60
G90
G28 ;home
M729 ;Clean Nozzle
M190 S60


;=============turn on fans to prevent PLA jamming=================


    M106 P3 S255
    ;Prevent PLA from jamming


;enable_pressure_advance:false
;This value is called if pressure advance is enabled

M204 S5000 ;Call exterior wall print acceleration


G1 X128.5 Y-1.2 F20000
G1 Z0.3 F900
M73 P1 R0
M109 S210
M83
G92 E0 ;Reset Extruder
G1 F6000
G1 X-1.2 E10.156 ;Draw the first line
G1 Y98.8 E7.934
M73 P7 R0
G1 X-0.5 Y100 E0.1
M73 P11 R0
G1 Y-0.3 E7.934
G1 X78.5 E6.284
M73 P15 R0
G1 F1680
M73 P18 R0
G1 X98.5 E2
G1 F8400
M73 P21 R0
G1 X118.5 E2
G1 F1680
G1 X138.5 E2
```

```
G1 F8400
M73 P24 R0
G1 X158.5 E2
G1 F8400
M73 P25 R0
G1 X178.5 E2
;End PA test.


G3 I-1 J0 Z0.6 F1200.0 ;Move to side a little
M73 P27 R0
G1 F20000
G92 E0 ;Reset Extruder
;LAYER_COUNT:1
;LAYER:0
G90
G21
M83 ; use relative distances for extrusion
; filament start gcode
M106 P3 S200


;LAYER_CHANGE
;Z:0.2
;HEIGHT:0.2
;BEFORE_LAYER_CHANGE
;0.2
G92 E0

G1 E-.8 F1800
;LAYER:1

;_SET_FAN_SPEED_CHANGING_LAYER
SET_VELOCITY_LIMIT ACCEL=500
EXCLUDE_OBJECT_START NAME=Disc_id_0_copy_0
G1 X135.645 Y128.74 F30000
M73 P31 R0
G1 Z.6
G1 Z.2
G1 E.8 F1800
;TYPE:Outer wall
;WIDTH:0.499999
G1 F3000
G3 X128.198 Y121.357 I-7.146 J-.24 E1.19765
M73 P34 R0
G3 X130.232 Y121.573 I.058 J9.145 E.07407
G3 X135.591 Y127.663 I-1.733 J6.927 E.31169
M73 P35 R0
G1 X135.643 Y128.7 E.03754
G1 E-.728 F1800
;WIPE_START
G1 F30000
G1 X135.585 Y129.458 E-.0456
G1 X135.504 Y129.891 E-.0264
;WIPE_END
G1 X132.262 Y122.981 Z.6
M73 P36 R0
G1 X132.077 Y122.586 Z.6
G1 Z.2
M73 P37 R0
G1 E.8 F1800
;TYPE:Bottom surface
;WIDTH:0.505817
G1 F6300
G1 X133.335 Y123.844 E.06511
G3 X134.64 Y125.803 I-4.602 J4.479 E.08662
G1 X131.189 Y122.353 E.17854
M73 P38 R0
G1 X130.445 Y122.073 E.02909
G1 X130.192 Y122.01 E.00954
G1 X134.995 Y126.813 E.24849
M73 P39 R0
G3 X135.149 Y127.621 I-3.921 J1.166 E.03018
G1 X129.378 Y121.851 E.29858
M73 P40 R0
G2 X128.676 Y121.803 I-.554 J2.949 E.02582
G1 X135.204 Y128.331 E.33779
M73 P41 R0
```

```
G3 X135.19 Y128.972 I-3.173 J.251 E.02348
G1 X128.027 Y121.809 E.37065
M73 P42 R0
G2 X127.438 Y121.874 I.029 J2.945 E.02172
M73 P43 R0
G1 X135.124 Y129.56 E.39772
M73 P44 R0
G3 X135.017 Y130.108 I-2.76 J-.255 E.02045
G1 X126.89 Y121.981 E.42051
M73 P45 R0
G1 X126.387 Y122.133 E.01923
G1 X134.868 Y130.614 E.43887
M73 P46 R0
G3 X134.687 Y131.087 I-2.431 J-.66 E.01858
G1 X125.912 Y122.313 E.45404
M73 P47 R0
G2 X125.463 Y122.518 I.79 J2.324 E.01811
M73 P48 R0
G1 X134.481 Y131.536 E.46662
M73 P49 R0
G3 X134.252 Y131.962 I-2.22 J-.918 E.01772
G1 X125.038 Y122.748 E.47677
M73 P50 R0
G2 X124.646 Y123.01 I1.102 J2.07 E.01729
G1 X133.99 Y132.354 E.4835
M73 P52 R0
G3 X133.707 Y132.726 I-1.979 J-1.213 E.01712
G1 X124.273 Y123.292 E.48816
M73 P53 R0
G2 X123.918 Y123.592 I1.305 J1.903 E.01702
G1 X133.406 Y133.079 E.49092
M73 P54 R0
G1 X133.077 Y133.405 E.01694
G1 X123.595 Y123.923 E.49064
M73 P56 R0
G2 X123.291 Y124.274 I1.583 J1.677 E.01701
G1 X132.725 Y133.708 E.48813
M73 P57 R0
G3 X132.354 Y133.992 I-1.59 J-1.689 E.01711
G1 X123.006 Y124.643 E.48373
M73 P58 R0
G1 X122.75 Y125.042 E.01733
M73 P59 R0
G1 X131.959 Y134.251 E.47651
M73 P60 R0
G3 X131.534 Y134.481 I-1.349 J-1.984 E.0177
G1 X122.519 Y125.466 E.46649
M73 P61 R0
G2 X122.31 Y125.912 I2.1 J1.254 E.01805
G1 X131.087 Y134.688 E.45415
M73 P62 R0
G3 X130.615 Y134.871 I-1.138 J-2.244 E.01855
M73 P63 R0
G1 X122.127 Y126.383 E.43917
M73 P64 R0
G1 X121.985 Y126.896 E.01946
G1 X130.105 Y135.016 E.42016
M73 P65 R0
G3 X129.558 Y135.123 I-.806 J-2.651 E.02043
G1 X121.877 Y127.442 E.39747
M73 P66 R0
G2 X121.81 Y128.03 I2.87 J.626 E.02167
G1 X128.97 Y135.19 E.37051
M73 P68 R0
G3 X128.33 Y135.204 I-.391 J-3.158 E.02348
G1 X121.795 Y128.67 E.33813
M73 P69 R0
G2 X121.851 Y129.38 I3.542 J.078 E.02613
G1 X127.619 Y135.149 E.29847
M73 P70 R0
G3 X126.809 Y134.992 I.366 J-4.085 E.03026
G1 X122.009 Y130.193 E.24836
M73 P71 R0
G1 X122.057 Y130.392 E.00749
G1 X122.28 Y131.031 E.02476
G1 X122.356 Y131.195 E.00663
G1 X125.802 Y134.641 E.17832
M73 P72 R0
```

```
G3 X123.807 Y133.3 I2.526 J-5.915 E.0885
G1 X122.586 Y132.079 E.06316
M73 P73 R0
G1 E-.728 F1800
;WIPE_START
G1 F30000
G1 X123.435 Y132.928 E-.072
;WIPE_END
EXCLUDE_OBJECT_END NAME=Disc_id_0_copy_0
M106 S0
M106 P2 S0
;TYPE:Custom
; filament end gcode
;===== date: 20250109 =====================
M400 ; wait for buffer to clear
M140 S0 ;Turn-off bed
M106 S255 ;Cooling nozzle
M83
G92 E0 ; zero the extruder
G2 I1 J0 Z0.7 E-1 F3000 ; lower z a little
M73 P74 R0
G90
G1 Z100 F20000 ; Move print head up
M73 P94 R0
M204 S5000
M400
M83
G1 X202 F20000
M73 P95 R0
M400
G1 Y250 F20000
M73 P97 R0
G1 Y264.5 F1200
M73 P100 R0
M400
G92 E0
M104 S0 ;Turn-off hotend
M140 S0 ;Turn-off bed
M106 S0 ; turn off fan
M106 P2 S0 ; turn off remote part cooling fan
M106 P3 S0 ; turn off chamber cooling fan
M84 ;Disable all steppers
```

The various commands for machine functionality are quite straight-forward, with each added as a descriptive module.

```
    def setfansoff(self):
        self.writegc("M106 S0")

    def setfanspeed(self, fan, speed):
        self.writegc("M106 P", fan, " S", speed)

    def pauseforclearbuffer(self):
        self.writegc("M400 ; wait for buffer to clear")
```

3.5.6.2 Feed and Speed ratio

Note that certain commands will require setting values which will need to be tracked and used for calculations.

```
    def setfeedratio(self, feedratio):
        self.writegc("M220 S", feedratio)
        self.feedratio = feedratio

    def setspeedratio(self, speedratio):
        self.writegc("M221 S", speedratio)
        self.speedratio = speedratio
```

3.5.6.3 Time and Firmware for 3D printers

The various G-code commands are specific to firmware implementations such as https://www.klipper3d.org/G-Codes.html

Where CNC operations normally only are concerned about time in the moment, and pausing until a given time has elapsed, 3D operations, with their control of heating up filament, melting it, and extruding thin ribbons of it require a greater control over time and duration.

```
#Set extruder temperature: M104 [T<index>] [S<temperature>]
```

```
    def setextrudertemperature(self, temperature):
        self.writegc("M104 S" + str(temperature))
        self.extrudertemperature = temperature

#Set extruder temperature and wait: M109 [T<index>] S<temperature>
#Note: M109 always waits for temperature to settle at requested
    value
    def setandwaitforextrudertemperature(self, temperature):
        self.writegc("M109 S" + str(temperature) + "; set 
            temperature and wait for it to be reached")
        self.extrudertemperature = temperature

#Set bed temperature: M140 [S<temperature>]
    def setbedtemperature(self, temperature):
        self.writegc("M140 S" + str(temperature))
        self.bedtemperature = temperature

#Set bed temperature and wait: M190 S<temperature>
#Note: M190 always waits for temperature to settle at requested
    value
    def setandwaitforbedtemperature(self, temperature):
        self.writegc("M190 S" + str(temperature))
        self.bedtemperature = temperature
```

Certain commands are only needed for initialization, so may be grouped together in a single command:

```
    def initializeforprinting(self, nozzlediameter = 0.4,
        filamentdiameter = 1.75, extrusionwidth = 0.6, layerheight =
         0.2):
        self.writegc("G21  ; set units to millimeters")
        self.writegc("G90")
        self.writegc("M82  ; use absolute distances for extrusion")
        self.writegc("G28  ; home")
        self.writegc("M729 ; Clean Nozzle")
        self.nozzlediameter = nozzlediameter
        self.extrusionwidth = extrusionwidth
        self.layerheight = layerheight
        self.toolpaths = []
        self.feedrate = 0
        fr = filamentdiameter/2
        self.extrusion_normal_length = 1 / 3.14159 * (fr * fr)
```

```
    def liftandprimenozzle(self, liftfeed = 5000, extrusionfeed =
        2400):
        self.writegc("G1 Z5 F" + str(liftfeed) + " ; lift nozzle")
        self.writegc("G92 E0")
        self.writegc("G1 E-2 F" + str(extrusionfeed))
        self.writegc("G92 E0")

#Set acceleration: M204 S<value> OR M204 P<value> T<value>
#Note: If S is not specified and both P and T are specified, then
    the acceleration is set to the minimum of P and T. If only one
    of P or T is specified, the command has no effect.
    def setacceleration(self, acceleration):
        self.writegc("M204 S", acceleration)
        self.acceleration = acceleration

#Use absolute/relative distances for extrusion: M82, M83
    def setextrusionabsolute(self, acceleration):
        self.writegc("M83")
        self.extrusionabsolute = true
```

```
#Set build percentage: M73 P<percent>
    def setbuildpercentage(self, percent):
        self.writegc("M73 P", percent)
        self.percent = percent
```

The program https://github.com/FullControlXYZ/fullcontrol/blob/master/models/hex_adapter.ipynb suggests certain variables:

```
# printer/gcode parameters

design_name = 'hex_adapter'
nozzle_temp = 210
```

```
bed_temp = 40
print_speed = 1000
fan_percent = 100
printer_name='prusa_i3' # generic / ultimaker2plus / prusa_i3 / ender_3 / cr_10 / bambulab_x1 / toolchan
```

Movement commands add an E position aspect to the command which results in the Extruder advancing to that position so as to extrude a sufficient volume of filament to match the movement and the space which is intended to be filled. Modeling these in 3D without the complexity of managing the entire 3D model and tracking the elevation of the current position relative to the model at a given point in time will require that the user maintain the current layer thickness and ensure that if unsupported, the extruded plastic will be extruded with a fan speed and flow rate which will allow bridging from/to supported areas of the model.

Calculating the volume necessary/the amount extruded will require the nozzle size, the layer height, an estimate for how much the extruded filament will spread out/deform, and the diameter of the filament. Further potential complications include whether the first layer is being extruded (normally this is done at a quite slow speed to facilitate adhesion, which also serves as a chance to catch a problem at an early stage), or if a strand is an inside or outside wall or infill or bridging open space, if it is crossing an already extruded segment(?) and so forth.

```
; --- Start of G-code: Demonstration of Layer and Extrusion Concepts ---
G21 ; Set units to millimeters
G90 ; Use absolute positioning
M82 ; Set extruder to absolute mode
M104 S200 ; Set extruder temperature to 200řC
M140 S60 ; Set bed temperature to 60řC
M190 S60 ; Wait for bed to reach target temp
M109 S200 ; Wait for extruder to reach target temp
G28 ; Home all axes

; --- Initial test extrusion ---
G92 E0 ; Reset extruder position
G1 F100 E5 ; Extrude 5 mm of filament at low speed to prime the nozzle
; Purpose: Ensures clean flow and purges any residual filament

; --- First layer adhesion test ---
G1 Z0.2 ; Move nozzle to first layer height
G1 X10 Y10 F3000 ; Move to starting position
G1 F1800 ; Set slower speed for first layer
G1 E0.8 ; Slight retraction before starting
G1 X100 E10 ; Draw a line along X to test bed adhesion
; Comment: This line helps verify that the first layer sticks properly

; --- Outer wall generation ---
G1 Z0.2 ; Maintain layer height
G1 X100 Y100 E10 ; Move and extrude to start outer square
G1 X10 Y100 E10 ;
G1 X10 Y10 E10 ;
G1 X100 Y10 E10 ;
; Outer walls: Typically printed first to preserve dimensional accuracy

; --- Cornering adjustment ---
G1 F1200 ; Reduce speed at corners
G1 X100 Y100 E0.5 ;
; Comment: Slower cornering helps prevent blobbing and maintains sharp edges

; --- Inner wall generation ---
G1 F1800 ; Resume regular speed
G1 X95 Y95 E8 ;
G1 X15 Y95 E8 ;
G1 X15 Y15 E8 ;
G1 X95 Y15 E8 ;
; Comment: Inner walls follow outer walls to enhance structural strength

; --- Understanding extrusion width ---
; Parameters:
; - Nozzle = 0.4 mm
; - Layer height = 0.2 mm
; - Filament diameter = 1.75 mm

; Flow rate ~ (extrusion_width * layer_height) / ( * (filament_diameter/2)^2)
; Example calculation: (0.4 * 0.2) / ($\pi$ * (0.875)^2)  0.033 mmş/mm

; --- Smooth top layer strategy ---
G1 Z0.4 ; Move to top layer height
G1 X20 Y20 ;
G1 F1500 ;
G1 X90 E3 ; Lay down parallel top layer strokes
G1 X90 Y90 E3 ;
```

```
G1 X20 Y90 E3 ;
G1 X20 Y20 E3 ;
G1 F3000 ;
G1 X20 Y20 ;
G1 F1500 ;
G1 X90 E3 ; Repeat for second pass for smoothing
; Tip: Overlapping infill with slightly lower extrusion helps achieve a smooth finish

; --- Wrap up ---
G92 E0 ; Reset extruder
G1 E-2 F1800 ; Retract filament to prevent stringing
M104 S0 ; Turn off hotend
M140 S0 ; Turn off bed
G28 X0 ; Home X-axis
M84 ; Disable motors
; --- End of G-code demonstration ---
```

3D printing requires control of the extruder, and matching volumetric calculations (or, more accurately, volumetric calculations which then determine the rate of extrusion).

Previewing in 3D/programming for 3D extrusion will likely want previewing not just the extruded shape, but also tracking the volume of material extruded and how it relates to the volume of the object being filled/the intersection of a just-extruded region with previously extruded material, and how large a void is left (presumably those two volumes would match up).

One concern is that G2/G3 support apparently is not common/guaranteed in 3D printer firmwares:

> *available if a gcode_arcs config section is enabled*

https://www.klipper3d.org/G-Codes.html While it is possible to separately control the feed rate of the extrusion, and the length of material extruded:

```
G1 F100 E5 ; Extrude 5 mm of filament at low speed to prime the nozzle
```

The normal usage is to move at a preset Feed rate in terms of motion, and while that movement is being made, extrude a given length of material:

```
; --- First layer adhesion test ---
G1 Z0.2 ; Move nozzle to first layer height
G1 X10 Y10 F3000 ; Move to starting position
G1 F1800 ; Set slower speed for first layer
G1 E0.8 ; Slight retraction before starting
G1 X100 E10 ; Draw a line along X to test bed adhesion
; Comment: This line helps verify that the first layer sticks properly
```

In theory, if one had a layer height equal to the diameter of the filament, and wanted to extrude a circular cross-section of filament, the value for `E` would be equal to the distance traveled.

Apparently, the firmware control is limited so that the extrusion rate cannot be varied relative to the feed rate so that it is not possible to for example, decrease the speed/increase the extrusion rate, resulting in a trapezoidal extrusion.

Given all that, the idealized (normalized?) shape and dimensions of the extrusion would be controlled by:

- layer height (for height along Z)
- extrusion rate (for width in X/Y)

which would be previewed as a rounded cross section, so it should work to create a preview by calculating the volume of material which is being extruded, then determining the volume of a circle of radius layer height/2, subtract that from the extruded volume, then determine what width of rectangle cross section would be necessary at the specified length to make up the difference.

```
#Move (G0 or G1): G1 [X<pos>] [Y<pos>] [Z<pos>] [E<pos>] [F<speed>]
    def extrude(self, ex, ey, ez, extrusionwidth = 0, layerheight =
        0, feedrate = 0):
        if extrusionwidth > 0:
            self.extrusionwidth = extrusionwidth
        if layerheight > 0:
            self.layerheight = layerheight
        if feedrate > 0:
            self.feedrate = feedrate
        if self.extrusionwidth == self.layerheight:
            c = sphere(self.layerheight/2)
        else:
            ew = self.extrusionwidth
            lh = self.layerheight
            i = circle(lh/2)
            j = i.translate([0,lh/2,0])
            k = intersection(j,square([lh,lh]))
```

```
            l = k.translate([ew/2-lh/2,0,0])
            m = union(l, square([ew/2-lh/2, lh]))
            c = rotate_extrude(m)
        c = c.translate([0,0,-self.layerheight])
        tslist = hull(c.translate([self.xpos(), self.ypos(),self.
            zpos()]), c.translate([ex, ey, ez]))
        self.toolpaths.append(tslist)
        #volume =  ů r^2 ů length
        #       + extrusionwidth-layerheight ů layerheight ů
            length
        distance = math.dist([self.xpos(), self.ypos(), self.zpos()
            ], [ex, ey, ez])
        print("Distance␣=␣", distance)
        v = self.extrusionwidth-self.layerheight * self.layerheight
             * distance + 3.14159 * self.layerheight/2 * self.
            layerheight/2 * distance
        print("Volume␣=␣",v)
        el = self.extrusion_normal_length * v
        print("Extrusion␣length␣=␣",el)
        self.writegc("G01␣X" + str(ex) + "␣Y" + str(ey) + "␣Z␣" +
            str(ez) + "␣E" + str(el) + "␣F" + str(self.feedrate))
```

The system Fullcontrolgcode https://fullcontrolgcode.com/ affords a compleat system for programming a 3D printer. The implementation https://py2g.com/ as announced at: https://old.reddit.com/r/FullControl/comments/1mjgta3/i_made_an_online_ide_for_fullcontrol_py2gcom/ affords a straight-forward usage from which the following typical example code is pulled:

```
# see https://py2g.com/customize/grid-bins for a bonus interactive UI to use with this sketch

# ==============================================================================
# PARAMETERS
# ==============================================================================
layer_height = 0.4
line_width   = 1.2
start_x, start_y = 10, 10
grid_unit    = 25
units_x, units_y, units_z = 4, 8, 0.5
outer_radius = 5
tolerance = 0.05

flow_rate = 1.02 # fill in the gaps

bin_type_outer = True # set True to create a bin container

print_speed = 40 # highest speed you'd want to go
max_flow = 8 # in mm3/s
max_print_speed = max_flow / (layer_height*line_width) # highest speed you can go
print_speed = min(print_speed,max_print_speed)

printer_name = 'generic'
printer_settings = {
    'primer':         'travel',
    'print_speed':    print_speed*60,
    'travel_speed':   20*60,
    'nozzle_temp':    210,
    'bed_temp':       50,
    'fan_percent':    100,
    'extrusion_width':  line_width,
    'extrusion_height': layer_height * flow_rate
}


# ==============================================================================
# DERIVED DIMENSIONS
# ==============================================================================
len_x = units_x * grid_unit
len_y = units_y * grid_unit
len_z = units_z * grid_unit

lim_left   = start_x  + line_width/2 + tolerance/2
lim_right  = start_x  + len_x  - line_width/2 - tolerance/2
lim_bottom = start_y  + line_width/2 + tolerance/2
lim_top    = start_y  + len_y  - line_width/2 - tolerance/2

# set up outer bin dimensions
if bin_type_outer:
    lim_left   -= line_width + tolerance
```

```
    lim_right  += line_width + tolerance
    lim_bottom -= line_width + tolerance
    lim_top    += line_width + tolerance
    outer_radius += line_width + tolerance
    # make outer edge come to the same height as inner bins
    len_z += layer_height*2 + tolerance

ilim_left = lim_left + line_width*2
ilim_right = lim_right - line_width*2
ilim_bottom = lim_bottom + line_width*2
ilim_top = lim_top - line_width*2

outer_left   = lim_left
outer_right  = lim_right
outer_bottom = lim_bottom
outer_top    = lim_top

# ============================================================================
# HELPERS: Roundedrectangle boundaryfinders
# ============================================================================
def find_boundary_x(y, going_right=True):
    if ilim_bottom + outer_radius <= y <= ilim_top - outer_radius:
        return ilim_right if going_right else ilim_left
    # bottom arc
    if y < ilim_bottom + outer_radius:
        cy = ilim_bottom + outer_radius
        dy = abs(y - cy)
        dx = math.sqrt(max(0, outer_radius**2 - dy**2))
        cx = (ilim_right - outer_radius) if going_right else (ilim_left + outer_radius)
        return cx + ( dx if going_right else -dx )
    # top arc
    if y > ilim_top - outer_radius:
        cy = ilim_top - outer_radius
        dy = abs(y - cy)
        dx = math.sqrt(max(0, outer_radius**2 - dy**2))
        cx = (ilim_right - outer_radius) if going_right else (ilim_left + outer_radius)
        return cx + ( dx if going_right else -dx )
    return ilim_right if going_right else ilim_left

def find_boundary_y(x, going_up=True):
    if ilim_left + outer_radius <= x <= ilim_right - outer_radius:
        return ilim_top if going_up else ilim_bottom
    # left arc
    if x < ilim_left + outer_radius:
        cx = ilim_left + outer_radius
        dx = abs(x - cx)
        dy = math.sqrt(max(0, outer_radius**2 - dx**2))
        cy = (ilim_top - outer_radius) if going_up else (ilim_bottom + outer_radius)
        return cy + ( dy if going_up else -dy )
    # right arc
    if x > ilim_right - outer_radius:
        cx = ilim_right - outer_radius
        dx = abs(x - cx)
        dy = math.sqrt(max(0, outer_radius**2 - dx**2))
        cy = (ilim_top - outer_radius) if going_up else (ilim_bottom + outer_radius)
        return cy + ( dy if going_up else -dy )
    return ilim_top if going_up else ilim_bottom

# ============================================================================
# BUILD STEPS
# ============================================================================
steps    = []
arc_segs = 16
r        = line_width/2


wall_taper = 1.4
if bin_type_outer:
    wall_taper = 0.4

# helper function to draw an outer wall
def add_rounded_rectangle_wall(zh, r, inset = 0):
    rect_left   = outer_left + inset
    rect_right  = outer_right - inset
    rect_bottom = outer_bottom + inset
    rect_top    = outer_top - inset
    corners = [
        fc.Point(x=rect_right - r, y=rect_bottom + r, z=zh),  # br
```

```
        fc.Point(x=rect_right - r, y=rect_top    - r, z=zh),  # tr
        fc.Point(x=rect_left  + r, y=rect_top    - r, z=zh),  # tl
        fc.Point(x=rect_left  + r, y=rect_bottom + r, z=zh)   # bl
    ]
    steps.append(fc.Point(x=rect_right - r, y=rect_bottom, z=zh))
    steps.extend(fc.arcXY(corners[0], r, -math.pi/2, +math.pi/2, arc_segs))
    steps.append(fc.Point(x=rect_right, y=rect_top - r, z=zh))
    steps.extend(fc.arcXY(corners[1], r,  0,           math.pi/2, arc_segs))
    steps.append(fc.Point(x=rect_left + r, y=rect_top, z=zh))
    steps.extend(fc.arcXY(corners[2], r,  math.pi/2,   math.pi/2, arc_segs))
    steps.append(fc.Point(x=rect_left, y=rect_bottom + r, z=zh))
    steps.extend(fc.arcXY(corners[3], r,  math.pi,      math.pi/2, arc_segs))

# turn extruder on
steps.append(fc.Extruder(on=True))

# -------------------------------------------------------------------------
# LAYER 1: HORIZONTAL ZIG-ZAG
# -------------------------------------------------------------------------
z = layer_height
y = ilim_bottom
dir_h = +1   # +1 = leftright, -1 = rightleft

# prime at first point
x0 = find_boundary_x(y, going_right=(dir_h>0))
steps.append(fc.Point(x=x0, y=y, z=z))

while True:
    # travel to boundary
    xt = find_boundary_x(y, going_right=(dir_h>0))
    steps.append(fc.Point(x=xt, y=y, z=z))
    current_x = xt

    # next scan-line
    next_y = y + line_width
    if next_y > ilim_top:
        break

    # U-turn semicircle of radius r
    center = fc.Point(x=current_x, y=y + r, z=z)
    if dir_h > 0:
        # right edge: CCW half-circle from bottom to top
        steps.extend(fc.arcXY(center, r, -math.pi/2, +math.pi, arc_segs))
    else:
        # left edge:  CW half-circle from bottom to top
        steps.extend(fc.arcXY(center, r, -math.pi/2, -math.pi, arc_segs))

    y     = next_y
    dir_h = -dir_h

# outline the first layer
weld_offset = (wall_taper+0.5)*line_width
add_rounded_rectangle_wall(z, outer_radius - weld_offset, weld_offset)

# -------------------------------------------------------------------------
# LAYER 2: VERTICAL ZIG-ZAG
# -------------------------------------------------------------------------
z += layer_height
x = ilim_left
dir_v = +1   # +1 = bottomtop, -1 = topbottom

# prime at first point
y0 = find_boundary_y(x, going_up=(dir_v>0))
steps.append(fc.Point(x=x, y=y0, z=z))

while True:
    # travel to boundary
    yt = find_boundary_y(x, going_up=(dir_v>0))
    steps.append(fc.Point(x=x, y=yt, z=z))
    current_y = yt

    # next scan-line
    next_x = x + line_width
    if next_x > ilim_right:
        break

    # U-turn semicircle of radius r
    center = fc.Point(x=x + r, y=current_y, z=z)
```

```
    if dir_v > 0:
        # top edge: CCW half-circle from left to right
        steps.extend(fc.arcXY(center, r, math.pi, -math.pi, arc_segs))
    else:
        # bottom edge:  CW half-circle from left to right
        steps.extend(fc.arcXY(center, r, math.pi, +math.pi, arc_segs))

    x     = next_x
    dir_v = -dir_v

# ============================================================================
# WALLS WITH ROUNDED CORNERS (remaining layers)
# ============================================================================

weld_offset = (wall_taper+1.5)*line_width
add_rounded_rectangle_wall(z, outer_radius - weld_offset, weld_offset)
weld_offset = (wall_taper+0.75)*line_width
add_rounded_rectangle_wall(z, outer_radius - weld_offset, weld_offset)

while z < len_z:
    if wall_taper > 0:
        wall_taper -= layer_height/2
        wall_taper = max(wall_taper,0)
    add_rounded_rectangle_wall(z, outer_radius, wall_taper*line_width)
    z += layer_height

# repeat final wall and then quick ironing pass to smooth the top
add_rounded_rectangle_wall(z, outer_radius)
add_rounded_rectangle_wall(z, outer_radius)
steps.append(fc.Extruder(on=False))
z += layer_height/10 # lift a bit
add_rounded_rectangle_wall(z, outer_radius)
z += layer_height/10 # lift a bit
add_rounded_rectangle_wall(z, outer_radius)
z += layer_height # lift off
add_rounded_rectangle_wall(z, outer_radius) # maybe unnecessary
steps.append(fc.Point(z=z+20)) # lift after complete
```

3.6 Difference of Stock, Rapids, and Toolpaths

At the end of cutting it will be necessary to subtract the accumulated toolpaths and rapids from the stock.

For Python, the initial 3D model is stored in the variable `stock`:

```
gcpy     def stockandtoolpaths(self, option = "stockandtoolpaths"):
gcpy         if option == "stock":
gcpy             show(self.stock)
gcpy         elif option == "toolpaths":
gcpy             show(self.toolpaths)
gcpy         elif option == "rapids":
gcpy             show(self.rapids)
gcpy         else:
gcpy             part = self.stock.difference(self.rapids)
gcpy             part = self.stock.difference(self.toolpaths)
gcpy             show(part)
```

A separate set of commands for showing the outline of the currently selected tool and/or its shaft is useful for checking that a tool outline definition is correctly formed.

```
gcpy     def showtooloutline(self):
gcpy         to = union(self.tooloutline, self.shaftoutline)
gcpy         show(to)
gcpy
gcpy     def showtoolprofile(self):
gcpy         to = union(self.toolprofile, self.shaftprofile)
gcpy         show(to)
gcpy
gcpy     def showtoolshape(self):
gcpy         to = union(self.currenttoolshape, self.currenttoolshaft)
gcpy         show(to)
```

Note that because of the differences in behaviour between OpenPythonSCAD (the `show()` command results in an explicit display of the requested element) and OpenSCAD (there is an implicit mechanism where the 3D element which is returned is displayed), the most expedient mechanism is to have an explicit Python command which returns the 3D model:

```
    def returnstockandtoolpaths(self):
        part = self.stock.difference(self.toolpaths)
        return part
```

and then make use of that specific command for OpenSCAD:

```
module stockandtoolpaths(){
    gcp.returnstockandtoolpaths();
}
```

forgoing the options of showing toolpaths and/or rapids separately.

3.7 Output files

The `gcodepreview` class will write out DXF and/or G-code files.

3.7.1 Python and OpenSCAD File Handling

`writeln`

The class `gcodepreview` will need additional commands for opening files. The original implementation in RapSCAD used a command `writeln` — fortunately, this command is easily re-created in Python, though it is made as a separate file for each sort of file which may be opened. Note that the `dxf` commands will be wrapped up with `if/elif` blocks which will write to additional file(s) based on tool number as set up above.

```
    def writegc(self, *arguments):
        if self.generategcode == True:
            line_to_write = ""
            for element in arguments:
                line_to_write += element
            self.gc.write(line_to_write)
            self.gc.write("\n")

    def writedxf(self, toolnumber, *arguments):
#        global dxfclosed
        line_to_write = ""
        for element in arguments:
            line_to_write += element
        if self.generatedxf == True:
            if self.dxfclosed == False:
                self.dxf.write(line_to_write)
                self.dxf.write("\n")
        if self.generatedxfs == True:
            self.writedxfs(toolnumber, line_to_write)

    def writedxfs(self, toolnumber, line_to_write):
#        print("Processing writing toolnumber", toolnumber)
#        line_to_write = ""
#        for element in arguments:
#            line_to_write += element
        if (toolnumber == 0):
            return
        elif self.generatedxfs == True:
            if (self.large_square_tool_num == toolnumber):
                self.dxflgsq.write(line_to_write)
                self.dxflgsq.write("\n")
            if (self.small_square_tool_num == toolnumber):
                self.dxfsmsq.write(line_to_write)
                self.dxfsmsq.write("\n")
            if (self.large_ball_tool_num == toolnumber):
                self.dxflgbl.write(line_to_write)
                self.dxflgbl.write("\n")
            if (self.small_ball_tool_num == toolnumber):
                self.dxfsmbl.write(line_to_write)
                self.dxfsmbl.write("\n")
            if (self.large_V_tool_num == toolnumber):
                self.dxflgV.write(line_to_write)
                self.dxflgV.write("\n")
            if (self.small_V_tool_num == toolnumber):
                self.dxfsmV.write(line_to_write)
                self.dxfsmV.write("\n")
            if (self.DT_tool_num == toolnumber):
                self.dxfDT.write(line_to_write)
                self.dxfDT.write("\n")
            if (self.KH_tool_num == toolnumber):
                self.dxfKH.write(line_to_write)
                self.dxfKH.write("\n")
```

```
            if (self.Roundover_tool_num == toolnumber):
                self.dxfRt.write(line_to_write)
                self.dxfRt.write("\n")
            if (self.MISC_tool_num == toolnumber):
                self.dxfMt.write(line_to_write)
                self.dxfMt.write("\n")
```

which commands will accept a series of arguments and then write them out to a file object for the appropriate file. Note that the DXF files for specific tools will expect that the tool numbers be set in the matching variables from the template. Further note that while it is possible to use tools which are not so defined, the toolpaths will not be written into DXF files for any tool numbers which do not match the variables from the template (but will appear in the main `.dxf`).

opengcodefile
opendxffile

For writing to files it will be necessary to have commands for opening the files: `opengcodefile` and `opendxffile` which will set the associated defaults. There is a separate function for each type of file, and for DXFs, there are multiple file instances, one for each combination of different type and size of tool which it is expected a project will work with. Each such file will be suffixed with the tool number.

There will need to be matching OpenSCAD modules for the Python functions:

```
module opendxffile(basefilename){
    gcp.opendxffile(basefilename);
}

module opendxffiles(Base_filename, large_square_tool_num, small_square_tool_num, large_ball_tool_num, small_ball_tool_num, large_V_tool_num, small_V_tool_num, DT_tool_num, KH_tool_num, Roundover_tool_num, MISC_tool_num) {
    gcp.opendxffiles(Base_filename, large_square_tool_num, small_square_tool_num, large_ball_tool_num, small_ball_tool_num, large_V_tool_num, small_V_tool_num, DT_tool_num, KH_tool_num, Roundover_tool_num, MISC_tool_num);
}
```

opengcodefile

With matching OpenSCAD commands: `opengcodefile` for OpenSCAD:

```
module opengcodefile(basefilename, currenttoolnum, toolradius, plunge, feed, speed) {
    gcp.opengcodefile(basefilename, currenttoolnum, toolradius, plunge, feed, speed);
}
```

and Python:

```
    def opengcodefile(self, basefilename = "export",
                      currenttoolnum = 102,
                      toolradius = 3.175,
                      plunge = 400,
                      feed = 1600,
                      speed = 10000
                      ):
        self.basefilename = basefilename
        self.currenttoolnum = currenttoolnum
        self.toolradius = toolradius
        self.plunge = plunge
        self.feed = feed
        self.speed = speed
        if self.generategcode == True:
            self.gcodefilename = basefilename + self.gcodefilext
            self.gc = open(self.gcodefilename, "w")
            self.writegc("(Design File: " + self.basefilename + ")")

    def opendxffile(self, basefilename = "export"):
        self.basefilename = basefilename
#         global generatedxfs
#         global dxfclosed
        self.dxfclosed = False
        self.dxfcolor = "Black"
        if self.generatedxf == True:
            self.generatedxfs = False
            self.dxffilename = basefilename + ".dxf"
            self.dxf = open(self.dxffilename, "w")
            self.dxfpreamble(-1)

    def opendxffiles(self, basefilename = "export",
```

```
                        large_square_tool_num = 0,
                        small_square_tool_num = 0,
                        large_ball_tool_num = 0,
                        small_ball_tool_num = 0,
                        large_V_tool_num = 0,
                        small_V_tool_num = 0,
                        DT_tool_num = 0,
                        KH_tool_num = 0,
                        Roundover_tool_num = 0,
                        MISC_tool_num = 0):
#        global generatedxfs
        self.basefilename = basefilename
        self.generatedxfs = True
        self.large_square_tool_num = large_square_tool_num
        self.small_square_tool_num = small_square_tool_num
        self.large_ball_tool_num = large_ball_tool_num
        self.small_ball_tool_num = small_ball_tool_num
        self.large_V_tool_num = large_V_tool_num
        self.small_V_tool_num = small_V_tool_num
        self.DT_tool_num = DT_tool_num
        self.KH_tool_num = KH_tool_num
        self.Roundover_tool_num = Roundover_tool_num
        self.MISC_tool_num = MISC_tool_num
        if self.generatedxf == True:
            if (large_square_tool_num > 0):
                self.dxflgsqfilename = basefilename + str(large_square_tool_num) + ".dxf"
#                print("Opening ", str(self.dxflgsqfilename))
                self.dxflgsq = open(self.dxflgsqfilename, "w")
            if (small_square_tool_num > 0):
#                print("Opening small square")
                self.dxfsmsqfilename = basefilename + str(small_square_tool_num) + ".dxf"
                self.dxfsmsq = open(self.dxfsmsqfilename, "w")
            if (large_ball_tool_num > 0):
#                print("Opening large ball")
                self.dxflgblfilename = basefilename + str(large_ball_tool_num) + ".dxf"
                self.dxflgbl = open(self.dxflgblfilename, "w")
            if (small_ball_tool_num > 0):
#                print("Opening small ball")
                self.dxfsmblfilename = basefilename + str(small_ball_tool_num) + ".dxf"
                self.dxfsmbl = open(self.dxfsmblfilename, "w")
            if (large_V_tool_num > 0):
#                print("Opening large V")
                self.dxflgVfilename = basefilename + str(large_V_tool_num) + ".dxf"
                self.dxflgV = open(self.dxflgVfilename, "w")
            if (small_V_tool_num > 0):
#                print("Opening small V")
                self.dxfsmVfilename = basefilename + str(small_V_tool_num) + ".dxf"
                self.dxfsmV = open(self.dxfsmVfilename, "w")
            if (DT_tool_num > 0):
#                print("Opening DT")
                self.dxfDTfilename = basefilename + str(DT_tool_num) + ".dxf"
                self.dxfDT = open(self.dxfDTfilename, "w")
            if (KH_tool_num > 0):
#                print("Opening KH")
                self.dxfKHfilename = basefilename + str(KH_tool_num) + ".dxf"
                self.dxfKH = open(self.dxfKHfilename, "w")
            if (Roundover_tool_num > 0):
#                print("Opening Rt")
                self.dxfRtfilename = basefilename + str(Roundover_tool_num) + ".dxf"
                self.dxfRt = open(self.dxfRtfilename, "w")
            if (MISC_tool_num > 0):
#                print("Opening Mt")
                self.dxfMtfilename = basefilename + str(MISC_tool_num) + ".dxf"
                self.dxfMt = open(self.dxfMtfilename, "w")
```

For each DXF file, there will need to be a Preamble in addition to opening the file in the file system:

```
        if (large_square_tool_num > 0):
            self.dxfpreamble(large_square_tool_num)
        if (small_square_tool_num > 0):
            self.dxfpreamble(small_square_tool_num)
        if (large_ball_tool_num > 0):
            self.dxfpreamble(large_ball_tool_num)
        if (small_ball_tool_num > 0):
            self.dxfpreamble(small_ball_tool_num)
        if (large_V_tool_num > 0):
            self.dxfpreamble(large_V_tool_num)
        if (small_V_tool_num > 0):
            self.dxfpreamble(small_V_tool_num)
        if (DT_tool_num > 0):
            self.dxfpreamble(DT_tool_num)
        if (KH_tool_num > 0):
            self.dxfpreamble(KH_tool_num)
        if (Roundover_tool_num > 0):
            self.dxfpreamble(Roundover_tool_num)
        if (MISC_tool_num > 0):
            self.dxfpreamble(MISC_tool_num)
```

Note that the commands which interact with files include checks to see if said files are being generated.

Future considerations:

- Multiple Preview Modes:
- Fast Preview: Write all movements with both begin and end positions into a list for a specific tool — as this is done, check for a previous movement between those positions and compare depths and tool number — keep only the deepest movement for a given tool.
- Motion Preview: Work up a 3D model of the machine and actually show the stock in relation to it,

3.7.2 DXF Overview

Elements in DXFs are represented as lines or arcs. A minimal file showing both:

```
0
SECTION
2
ENTITIES
0
LWPOLYLINE
90
2
70
0
43
0
10
-31.375
20
-34.9152
10
-31.375
20
-18.75
0
ARC
10
-54.75
20
-37.5
40
4
50
0
51
90
0
ENDSEC
0
EOF
```

3.7.2.1 Writing to DXF files When the command to open `.dxf` files is called it is passed all of the variables for the various tool types/sizes, and based on a value being greater than zero, the matching file is opened, and in addition, the main DXF which is always written to is opened as well. On the gripping hand, each element which may be written to a DXF file will have a user module as well as an internal module which will be called by it so as to write to the file for the current tool. It will be necessary for the `dxfwrite` command to evaluate the tool number which is passed in, and to use an appropriate command or set of commands to then write out to the appropriate file for a given tool (if positive) or not do anything (if zero), and to write to the master file if a negative value is passed in (this allows the various DXF template commands to be written only once and then called at need).

dxfwrite

Each tool has a matching command for each tool/size combination:

- Ball nose, large (lgbl) `writedxflgbl`
- Ball nose, small (smbl) `writedxfsmbl`
- Square, large (lgsq) `writedxflgsq`
- Square, small (smsq) `writedxfsmsq`
- V, large (lgV) `writedxflgV`
- V, small (smV) `writedxfsmV`
- Keyhole (KH) `writedxfKH`
- Dovetail (DT) `writedxfDT`

dxfpreamble

This module requires that the tool number be passed in, and after writing out `dxfpreamble`, that value will be used to write out to the appropriate file with a series of `if` statements.

```
    def dxfpreamble(self, tn):
#        self.writedxf(tn, str(tn))
        self.writedxf(tn, "0")
        self.writedxf(tn, "SECTION")
        self.writedxf(tn, "2")
        self.writedxf(tn, "ENTITIES")
```

3.7.2.1.1 DXF Lines and Arcs

There are several elements which may be written to a DXF:

- a line `dxfline`
- connected lines `beginpolyline/addvertex/closepolyline`
- arc `dxfarc`
- circle — a notable option would be for the arc to close on itself, creating a circle `dxfcircle`

DXF orders arcs counter-clockwise:



Note that arcs of greater than 90 degrees are not rendered accurately (in certain applications at least), so, for the sake of precision, they should be limited to a swing of 90 degrees or less. Further note that 4 arcs may be stitched together to make a circle:

```
dxfarc(10, 10, 5,   0,  90, small_square_tool_num);
dxfarc(10, 10, 5,  90, 180, small_square_tool_num);
dxfarc(10, 10, 5, 180, 270, small_square_tool_num);
dxfarc(10, 10, 5, 270, 360, small_square_tool_num);
```

The DXF file format supports colors defined by AutoCAD's indexed color system:

Color Code	Color Name
0	Black (or Foreground)
1	Red
2	Yellow
3	Green
4	Cyan
5	Blue
6	Magenta
7	White (or Background)
8	Dark Gray
9	Light Gray

Color codes 10–255 represent additional colors, with hues varying based on RGB values. Obviously, a command to manage adding the color commands would be:

```
    def setdxfcolor(self, color):
        self.dxfcolor = color
        self.cutcolor = color

    def writedxfcolor(self, tn):
            self.writedxf(tn, "8")
            if (self.dxfcolor == "Black"):
                self.writedxf(tn, "Layer_Black")
            if (self.dxfcolor == "Red"):
                self.writedxf(tn, "Layer_Red")
            if (self.dxfcolor == "Yellow"):
                self.writedxf(tn, "Layer_Yellow")
            if (self.dxfcolor == "Green"):
                self.writedxf(tn, "Layer_Green")
            if (self.dxfcolor == "Cyan"):
                self.writedxf(tn, "Layer_Cyan")
            if (self.dxfcolor == "Blue"):
                self.writedxf(tn, "Layer_Blue")
            if (self.dxfcolor == "Magenta"):
                self.writedxf(tn, "Layer_Magenta")
            if (self.dxfcolor == "White"):
                self.writedxf(tn, "Layer_White")
            if (self.dxfcolor == "Dark Gray"):
                self.writedxf(tn, "Layer_Dark_Gray")
            if (self.dxfcolor == "Light Gray"):
                self.writedxf(tn, "Layer_Light_Gray")

            self.writedxf(tn, "62")
            if (self.dxfcolor == "Black"):
                self.writedxf(tn, "0")
            if (self.dxfcolor == "Red"):
                self.writedxf(tn, "1")
            if (self.dxfcolor == "Yellow"):
                self.writedxf(tn, "2")
            if (self.dxfcolor == "Green"):
                self.writedxf(tn, "3")
            if (self.dxfcolor == "Cyan"):
                self.writedxf(tn, "4")
            if (self.dxfcolor == "Blue"):
                self.writedxf(tn, "5")
            if (self.dxfcolor == "Magenta"):
                self.writedxf(tn, "6")
            if (self.dxfcolor == "White"):
                self.writedxf(tn, "7")
            if (self.dxfcolor == "Dark Gray"):
                self.writedxf(tn, "8")
            if (self.dxfcolor == "Light Gray"):
                self.writedxf(tn, "9")
```

```
module setdxfcolor(color){
    gcp.setdxfcolor(color);
}
```

A further refinement would be to connect multiple line segments/arcs into a larger polyline, but since most CAM tools implicitly join elements on import, that is not necessary.

There are three possible interactions for DXF elements and toolpaths:

- describe the motion of the tool
- define a perimeter of an area which will be cut by a tool

- define a centerpoint for a specialty toolpath such as Drill or Keyhole

and it is possible that multiple such elements could be instantiated for a given toolpath.

When writing out to a DXF file there is a pair of commands, a public facing command which takes in a tool number in addition to the coordinates which then writes out to the main DXF file and then calls an internal command to which repeats the call with the tool number so as to write it out to the matching file.

```
    def dxfline(self, tn, xbegin, ybegin, xend, yend):
        self.writedxf(tn, "0")
        self.writedxf(tn, "LINE")
#
        self.writedxfcolor(tn)
#
        self.writedxf(tn, "10")
        self.writedxf(tn, str(xbegin))
        self.writedxf(tn, "20")
        self.writedxf(tn, str(ybegin))
        self.writedxf(tn, "30")
        self.writedxf(tn, "0.0")
        self.writedxf(tn, "11")
        self.writedxf(tn, str(xend))
        self.writedxf(tn, "21")
        self.writedxf(tn, str(yend))
        self.writedxf(tn, "31")
        self.writedxf(tn, "0.0")
```

In addition to `dxfline` which allows creating a line without consideration of context, there is also a `dxfpolyline` which will create a continuous/joined sequence of line segments which requires beginning it, adding vertexes, and then when done, ending the sequence.

First, begin the polyline:

```
    def beginpolyline(self, tn):#, xbegin, ybegin
        self.writedxf(tn, "0")
        self.writedxf(tn, "POLYLINE")
        self.writedxf(tn, "8")
        self.writedxf(tn, "default")
        self.writedxf(tn, "66")
        self.writedxf(tn, "1")
#
        self.writedxfcolor(tn)
#
#        self.writedxf(tn, "10")
#        self.writedxf(tn, str(xbegin))
#        self.writedxf(tn, "20")
#        self.writedxf(tn, str(ybegin))
#        self.writedxf(tn, "30")
#        self.writedxf(tn, "0.0")
        self.writedxf(tn, "70")
        self.writedxf(tn, "0")
```

then add as many vertexes as are wanted:

```
    def addvertex(self, tn, xend, yend):
        self.writedxf(tn, "0")
        self.writedxf(tn, "VERTEX")
        self.writedxf(tn, "8")
        self.writedxf(tn, "default")
        self.writedxf(tn, "70")
        self.writedxf(tn, "32")
        self.writedxf(tn, "10")
        self.writedxf(tn, str(xend))
        self.writedxf(tn, "20")
        self.writedxf(tn, str(yend))
        self.writedxf(tn, "30")
        self.writedxf(tn, "0.0")
```

then end the sequence:

```
    def closepolyline(self, tn):
        self.writedxf(tn, "0")
        self.writedxf(tn, "SEQEND")
```

For arcs, there are specific commands for writing out the DXF and G-code files. Note that for the G-code version it will be necessary to calculate the end-position, and to determine if the arc is clockwise or no (G2 vs. G3).

```
    def dxfarc(self, tn, xcenter, ycenter, radius, anglebegin, endangle):
        if (self.generatedxf == True):
            self.writedxf(tn, "0")
            self.writedxf(tn, "ARC")
#
            self.writedxfcolor(tn)
#
            self.writedxf(tn, "10")
            self.writedxf(tn, str(xcenter))
            self.writedxf(tn, "20")
            self.writedxf(tn, str(ycenter))
            self.writedxf(tn, "40")
            self.writedxf(tn, str(radius))
            self.writedxf(tn, "50")
            self.writedxf(tn, str(anglebegin))
            self.writedxf(tn, "51")
            self.writedxf(tn, str(endangle))

    def gcodearc(self, tn, xcenter, ycenter, radius, anglebegin, endangle):
        if (self.generategcode == True):
            self.writegc(tn, "(0)")
```

The various textual versions are quite obvious, and due to the requirements of G-code, it is straight-forward to include the G-code in them if it is wanted.

```
    def cutarcNECCdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 0, 90)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
#        if self.generatepaths == True:
#            print("Unioning cutarcNECCdxf toolpath")
        self.arcloop(1, 90, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
#        else:
#            toolpath = self.arcloop(1, 90, xcenter, ycenter, radius)
#            print("Returning cutarcNECCdxf toolpath")
        return toolpath

    def cutarcNWCCdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 90, 180)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
#        if self.generatepaths == True:
#            self.arcloop(91, 180, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
#        else:
        toolpath = self.arcloop(91, 180, xcenter, ycenter, radius)
        return toolpath

    def cutarcSWCCdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
```

```
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 180, 270)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
        if self.generatepaths == True:
            self.arcloop(181, 270, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
        else:
            toolpath = self.arcloop(181, 270, xcenter, ycenter, radius)
            return toolpath

    def cutarcSECCdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 270, 360)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
        if self.generatepaths == True:
            self.arcloop(271, 360, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
        else:
            toolpath = self.arcloop(271, 360, xcenter, ycenter, radius)
            return toolpath

    def cutarcNECWdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 0, 90)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
        if self.generatepaths == True:
            self.narcloop(89, 0, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
        else:
            toolpath = self.narcloop(89, 0, xcenter, ycenter, radius)
            return toolpath

    def cutarcSECWdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 270, 360)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
        if self.generatepaths == True:
            self.narcloop(359, 270, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
```

```
        else:
            toolpath = self.narcloop(359, 270, xcenter, ycenter, radius)
            return toolpath

    def cutarcSWCWdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 180, 270)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
        if self.generatepaths == True:
            self.narcloop(269, 180, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
        else:
            toolpath = self.narcloop(269, 180, xcenter, ycenter, radius)
            return toolpath

    def cutarcNWCWdxf(self, ex, ey, ez, xcenter, ycenter, radius):
#        global toolpath
#        toolpath = self.currenttool()
#        toolpath = toolpath.translate([self.xpos(), self.ypos(), self.zpos()])
        self.dxfarc(self.currenttoolnumber(), xcenter, ycenter, radius, 90, 180)
        if (self.zpos == ez):
            self.settzpos(0)
        else:
            self.settzpos((self.zpos()-ez)/90)
#        self.setxpos(ex)
#        self.setypos(ey)
#        self.setzpos(ez)
        if self.generatepaths == True:
            self.narcloop(179, 90, xcenter, ycenter, radius)
#            self.toolpaths = self.toolpaths.union(toolpath)
        else:
            toolpath = self.narcloop(179, 90, xcenter, ycenter, radius)
            return toolpath
```

Using such commands to create a circle is quite straight-forward:

```
cutarcNECCdxf(-stockXwidth/4, stockYheight/4+stockYheight/16, -stockZthickness, -stockXwidth/4, stockYh
cutarcNWCCdxf(-(stockXwidth/4+stockYheight/16), stockYheight/4, -stockZthickness, -stockXwidth/4, stock
cutarcSWCCdxf(-stockXwidth/4, stockYheight/4-stockYheight/16, -stockZthickness, -stockXwidth/4, stockYh
cutarcSECCdxf(-(stockXwidth/4-stockYheight/16), stockYheight/4, -stockZthickness, -stockXwidth/4, stock
```

```
    def arcCCgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.writegc("G03␣X", str(ex), "␣Y", str(ey), "␣Z", str(ez), "␣R", str(radius))

    def arcCWgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.writegc("G02␣X", str(ex), "␣Y", str(ey), "␣Z", str(ez), "␣R", str(radius))
```

The above commands may be called if G-code is also wanted with writing out G-code added:

```
    def cutarcNECCdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCCgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == True:
            self.cutarcNECCdxf(ex, ey, ez, xcenter, ycenter, radius)
        else:
            return self.cutarcNECCdxf(ex, ey, ez, xcenter, ycenter, radius)

```

```
    def cutarcNWCCdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCCgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == False:
            return self.cutarcNWCCdxf(ex, ey, ez, xcenter, ycenter, radius)

    def cutarcSWCCdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCCgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == False:
            return self.cutarcSWCCdxf(ex, ey, ez, xcenter, ycenter, radius)

    def cutarcSECCdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCCgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == False:
            return self.cutarcSECCdxf(ex, ey, ez, xcenter, ycenter, radius)

    def cutarcNECWdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCWgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == False:
            return self.cutarcNECWdxf(ex, ey, ez, xcenter, ycenter, radius)

    def cutarcSECWdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCWgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == False:
            return self.cutarcSECWdxf(ex, ey, ez, xcenter, ycenter, radius)

    def cutarcSWCWdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCWgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == False:
            return self.cutarcSWCWdxf(ex, ey, ez, xcenter, ycenter, radius)

    def cutarcNWCWdxfgc(self, ex, ey, ez, xcenter, ycenter, radius):
        self.arcCWgc(ex, ey, ez, xcenter, ycenter, radius)
        if self.generatepaths == False:
            return self.cutarcNWCWdxf(ex, ey, ez, xcenter, ycenter, radius)
```

```
module cutarcNECCdxfgc(ex, ey, ez, xcenter, ycenter, radius){
    gcp.cutarcNECCdxfgc(ex, ey, ez, xcenter, ycenter, radius);
}

module cutarcNWCCdxfgc(ex, ey, ez, xcenter, ycenter, radius){
    gcp.cutarcNWCCdxfgc(ex, ey, ez, xcenter, ycenter, radius);
}

module cutarcSWCCdxfgc(ex, ey, ez, xcenter, ycenter, radius){
    gcp.cutarcSWCCdxfgc(ex, ey, ez, xcenter, ycenter, radius);
}

module cutarcSECCdxfgc(ex, ey, ez, xcenter, ycenter, radius){
    gcp.cutarcSECCdxfgc(ex, ey, ez, xcenter, ycenter, radius);
}
```

3.7.3 G-code Overview

The G-code commands and their matching modules may include (but are not limited to):

Command/Module	G-code

`opengcodefile(s)(...); setupstock(...)`	`(export.nc)`
	`(stockMin: -109.5, -75mm, -8.35mm)`
	`(stockMax:109.5mm, 75mm, 0.00mm)`
	`(STOCK/BLOCK, 219, 150, 8.35, 109.5, 75, 8.35)`
	`G90`
	`G21`

`movetosafez()`	`(Move to safe Z to avoid workholding)` `G53G0Z-5.000`

`toolchange(...);`	`(TOOL/MILL, 3.17, 0.00, 0.00, 0.00)`
	`M6T102`
	`M03S16000`

`cutoneaxis_setfeed(...);`	`(PREPOSITION FOR RAPID PLUNGE)`
	`G0X0Y0`
	`Z0.25`
	`G1Z0F100`
	`G1 X109.5 Y75 Z-8.35F400`
	`Z9`

`cutwithfeed(...);`	
`closegcodefile();`	`M05` `M02`

Conversely, the G-code commands which are supported are generated by the following modules:

G-code	Command/Module

`(Design File: )`
`(stockMin:0.00mm, -152.40mm, -34.92mm)`
`(stockMax:109.50mm, -77.40mm, 0.00mm)`
`(STOCK/BLOCK, 109.50, 75.00, 34.92, 0.00, 152.40, 34.92)`
`G90`
`G21`
	`opengcodefile(s)(...); setupstock(.`

`(Move to safe Z to avoid workholding)` `G53G0Z-5.000`	`movetosafez()`

`(Toolpath: Contour Toolpath 1)`
`M05`
`(TOOL/MILL, 3.17, 0.00, 0.00, 0.00)`
`M6T102`
`M03S10000`
	`toolchange(...);`

`(PREPOSITION FOR RAPID PLUNGE)`	`writecomment(...)`
`G0X0.000Y-152.400` `Z0.250`	`rapid(...)` `rapid(...)`

`G1Z-1.000F203.2`
`X109.500Y-77.400F508.0`
`X57.918Y16.302Z-0.726`
`Y22.023Z-1.023`
`X61.190Z-0.681`
`Y21.643`
`X57.681`
`Z12.700`
	`cutwithfeed(...);`
	`cutwithfeed(...);`

`M05` `M02`	`closegcodefile();`

The implication here is that it should be possible to read in a G-code file, and for each line/command instantiate a matching command so as to create a 3D model/preview of the file. This is addressed by making specialized commands for movement which correspond to the various axis combinations (XYZ, XY, XZ, YZ, X, Y, Z).

A further consideration is that rather than hard-coding all possibilities or any changes, having an option for a "post-processor" will be far more flexible.

Described at: https://carbide3d.com/hub/faq/create-pro-custom-post-processor/ the necessary hooks would be:

- onOpen
- onClose
- onSection (which is where tool changes are defined, since "section" in this case is segmented per tool)

closegcodefile
closedxffile

3.7.3.1 Closings At the end of the program it will be necessary to close each file using the commands: `closegcodefile`, and `closedxffile`. In some instances it may be necessary to write additional information, depending on the file format. Note that these commands will need to be within the `gcodepreview class`.

```
    def dxfpostamble(self, tn):
#        self.writedxf(tn, str(tn))
        self.writedxf(tn, "0")
        self.writedxf(tn, "ENDSEC")
        self.writedxf(tn, "0")
        self.writedxf(tn, "EOF")
```

```
    def gcodepostamble(self):
        if self.generatecut == True:
            self.writegc("Z12.700")
            self.writegc("M05")
            self.writegc("M02")
        if self.generateprint == True:
            self.writegc("G92␣E0")
            self.writegc("M107␣␣␣␣;␣turn␣off␣cooling␣fans")
            self.writegc("M104␣S0␣;␣turn␣off␣temperature")
            self.writegc("G28␣X0␣␣;␣home␣X␣axis")
            self.writegc("M84␣␣␣␣␣;␣disable␣motors")
```

dxfpostamble

It will be necessary to call the `dxfpostamble` (with appropriate checks and trappings so as to ensure that each `dxf` file is ended and closed so as to be valid.

```
    def closegcodefile(self):
        if self.generategcode == True:
            self.gcodepostamble()
            self.gc.close()

    def closedxffile(self):
        if self.generatedxf == True:
#            global dxfclosed
            self.dxfpostamble(-1)
#            self.dxfclosed = True
            self.dxf.close()

    def closedxffiles(self):
        if self.generatedxfs == True:
            if (self.large_square_tool_num > 0):
                self.dxfpostamble(self.large_square_tool_num)
            if (self.small_square_tool_num > 0):
                self.dxfpostamble(self.small_square_tool_num)
            if (self.large_ball_tool_num > 0):
                self.dxfpostamble(self.large_ball_tool_num)
            if (self.small_ball_tool_num > 0):
                self.dxfpostamble(self.small_ball_tool_num)
            if (self.large_V_tool_num > 0):
                self.dxfpostamble(self.large_V_tool_num)
            if (self.small_V_tool_num > 0):
                self.dxfpostamble(self.small_V_tool_num)
            if (self.DT_tool_num > 0):
                self.dxfpostamble(self.DT_tool_num)
            if (self.KH_tool_num > 0):
                self.dxfpostamble(self.KH_tool_num)
            if (self.Roundover_tool_num > 0):
                self.dxfpostamble(self.Roundover_tool_num)
            if (self.MISC_tool_num > 0):
                self.dxfpostamble(self.MISC_tool_num)

            if (self.large_square_tool_num > 0):
                self.dxflgsq.close()
            if (self.small_square_tool_num > 0):
                self.dxfsmsq.close()
            if (self.large_ball_tool_num > 0):
                self.dxflgbl.close()
            if (self.small_ball_tool_num > 0):
                self.dxfsmbl.close()
            if (self.large_V_tool_num > 0):
                self.dxflgV.close()
            if (self.small_V_tool_num > 0):
                self.dxfsmV.close()
            if (self.DT_tool_num > 0):
                self.dxfDT.close()
```

```
            if (self.KH_tool_num > 0):
                self.dxfKH.close()
            if (self.Roundover_tool_num > 0):
                self.dxfRt.close()
            if (self.MISC_tool_num > 0):
                self.dxfMt.close()
```

closegcodefile closedxffile dxfpostamble

The commands: closegcodefile, and closedxffile are used to close the files at the end of a program. For efficiency, each references the command: dxfpostamble which when called provides the boilerplate needed at the end of their respective files.

```
module closegcodefile(){
    gcp.closegcodefile();
}

module closedxffiles(){
    gcp.closedxffiles();
}

module closedxffile(){
    gcp.closedxffile();
}
```

3.8 Cutting shapes and expansion

Certain basic shapes (arcs, circles, rectangles), will be incorporated in the main code. Other shapes will be added as they are developed, and of course the user is free to develop their own systems.

It is most expedient to test out new features in a new/separate file insofar as the file structures will allow (tool definitions for example will need to consolidated in 3.4.1.1) which will need to be included in the projects which will make use of said features until such time as they are added into the main gcodepreview.scad file.

A basic requirement for two-dimensional regions will be to define them so as to cut them out. Two different geometric treatments will be necessary: modeling the geometry which defines the region to be cut out (output as a DXF); and modeling the movement of the tool, the toolpath which will be used in creating the 3D model and outputting the G-code.

3.8.1 Building blocks

The outlines of shapes will be defined using:

- lines — dxfline
- arcs — dxfarc

It may be that splines or Bézier curves will be added as well.

3.8.1.1 List of shapes

In the TUG presentation/paper: http://tug.org/TUGboat/tb40-2/tb125adams-3d.pdf a list of 2D shapes was put forward — which of these will need to be created, or if some more general solution will be put forward is uncertain. For the time being, shapes will be implemented on an as-needed basis, as modified by the interaction with the requirements of toolpaths. Shapes for which code exists (or is trivially coded) are indicated by Forest Green — for those which have sub-classes, if all are feasible only the higher level is so called out.

- 0
  - circle — dxfcircle
  - ellipse (oval) (requires some sort of non-arc curve)
    * egg-shaped
  - annulus (one circle within another, forming a ring) — handled by nested circles
  - superellipse (see astroid below)
- 1
  - cone with rounded end (arc)—see also "sector" under 3 below
- 2
  - semicircle/circular/half-circle segment (arc and a straight line); see also sector below
  - arch—curve possibly smoothly joining a pair of straight lines with a flat bottom
  - lens/vesica piscis (two convex curves)
  - lune/crescent (one convex, one concave curve)
  - heart (two curves)

  - tomoe (comma shape)—non-arc curves

- 3
  - triangle
    - equilateral
    - isosceles
    - right triangle
    - scalene
  - (circular) sector (two straight edges, one convex arc)
    - quadrant (90°)
    - sextants (60°)
    - octants (45°)
  - deltoid curve (three concave arcs)
  - Reuleaux triangle (three convex arcs)
  - arbelos (one convex, two concave arcs)
  - two straight edges, one concave arc—an example is the hyperbolic sector[1]
  - two convex, one concave arc

- 4
  - rectangle (including square) — `dxfrectangle`, `dxfrectangleround`
  - parallelogram
  - rhombus
  - trapezoid/trapezium
  - kite
  - ring/annulus segment (straight line, concave arc, straight line, convex arc)
  - astroid (four concave arcs)
  - salinon (four semicircles)
  - three straight lines and one concave arc

Note that most shapes will also exist in a rounded form where sharp angles/points are replaced by arcs/portions of circles, with the most typical being `dxfrectangleround`.

Is the list of shapes for which there are not widely known names interesting for its lack of notoriety?

- two straight edges, one concave arc—oddly, an asymmetric form (hyperbolic sector) has a name, but not the symmetrical—while the colloquial/prosaic "arrowhead" was considered, it was rejected as being better applied to the shape below. (It's also the shape used for the spaceship in the game Asteroids (or Hyperspace), but that is potentially confusing with astroid.) At the conference, Dr. Knuth suggested "dart" as a suitable term.
- two convex, one concave arc—with the above named, the term "arrowhead" is freed up to use as the name for this shape.
- three straight lines and one concave arc.

The first in particular is sorely needed for this project (it's the result of inscribing a circle in a square or other regular geometric shape). Do these shapes have names in any other languages which might be used instead?

These shapes will then be used in constructing toolpaths. The program Carbide Create has toolpath types and options which are as follows:

- Contour — No Offset — the default, this is already supported in the existing code
- Contour — Outside Offset
- Contour — Inside Offset
- Pocket — such toolpaths/geometry should include the rounding of the tool at the corners, c.f., `dxfrectangleround`
- Drill — note that this is implemented as the plunging of a tool centered on a circle and normally that circle is the same diameter as the tool which is used.
- Keyhole — also beginning from a circle, the command for this also models the areas which should be cleared for the sake of reducing wear on the tool and ensuring chip clearance

Some further considerations:

[1] en.wikipedia.org/wiki/Hyperbolic_sector and www.reddit.com/r/Geometry/comments/bkbzgh/is_there_a_name_for_a_3_pointed_figure_with_two

- relationship of geometry to toolpath — arguably there should be an option for each toolpath (we will use Carbide Create as a reference implementation) which is to be supported. Note that there are several possibilities: modeling the tool movement, describing the outline which the tool will cut, modeling a reference shape for the toolpath
- tool geometry — support is included for specialty tooling such as dovetail cutters allowing one to to get an accurate 3D model, including for tooling which undercuts since they cannot be modeled in Carbide Create.
- Starting and Max Depth — are there CAD programs which will make use of Z-axis information in a DXF? — would it be possible/necessary to further differentiate the DXF geometry? (currently written out separately for each toolpath in addition to one combined file) — would supporting layers be an option?

3.8.1.1.1 circles

Circles are made up of a series of arcs:

```
    def dxfcircle(self, tool_num, xcenter, ycenter, radius):
        self.dxfarc(tool_num, xcenter, ycenter, radius,  0, 90)
        self.dxfarc(tool_num, xcenter, ycenter, radius, 90, 180)
        self.dxfarc(tool_num, xcenter, ycenter, radius, 180, 270)
        self.dxfarc(tool_num, xcenter, ycenter, radius, 270, 360)
```

Actually cutting the circle is much the same, with the added consideration of entry point if Z height is not above the surface of the stock/already removed material, directionality (counter-clockwise vs. clockwise), and depth (beginning and end depths must be specified which should allow usage of this for thread-cutting and similar purposes).

Center is specified, but the actual entry point is the right-most edge.

```
    def cutcircleCC(self, xcenter, ycenter, bz, ez, radius):
        self.setzpos(bz)
        self.cutquarterCCNE(xcenter, ycenter + radius, self.zpos() + ez/4, radius)
        self.cutquarterCCNW(xcenter - radius, ycenter, self.zpos() + ez/4, radius)
        self.cutquarterCCSW(xcenter, ycenter - radius, self.zpos() + ez/4, radius)
        self.cutquarterCCSE(xcenter + radius, ycenter, self.zpos() + ez/4, radius)

    def cutcircleCCdxf(self, xcenter, ycenter, bz, ez, radius):
        self.cutcircleCC(self, xcenter, ycenter, bz, ez, radius)
        self.dxfcircle(self, tool_num, xcenter, ycenter, radius)
```

A Drill toolpath is a simple plunge operation which will have a matching circle to define it.

3.8.1.1.2 rectangles

There are two obvious forms for rectangles, square cornered and rounded:

```
    def dxfrectangle(self, tool_num, xorigin, yorigin, xwidth, yheight, corners = "Square", radius = 6):
        if corners == "Square":
            self.dxfline(tool_num, xorigin, yorigin, xorigin + xwidth, yorigin)
            self.dxfline(tool_num, xorigin + xwidth, yorigin, xorigin + xwidth, yorigin + yheight)
            self.dxfline(tool_num, xorigin + xwidth, yorigin + yheight, xorigin, yorigin + yheight)
            self.dxfline(tool_num, xorigin, yorigin + yheight, xorigin, yorigin)
        elif corners == "Fillet":
            self.dxfrectangleround(tool_num, xorigin, yorigin, xwidth, yheight, radius)
        elif corners == "Chamfer":
            self.dxfrectanglechamfer(tool_num, xorigin, yorigin, xwidth, yheight, radius)
        elif corners == "Flipped Fillet":
            self.dxfrectangleflippedfillet(tool_num, xorigin, yorigin, xwidth, yheight, radius)
```

Note that the rounded shape below would be described as a rectangle with the “Fillet” corner treatment in Carbide Create.

```
    def dxfrectangleround(self, tool_num, xorigin, yorigin, xwidth, yheight, radius):
# begin section
```

```
        self.writedxf(tool_num, "0")
        self.writedxf(tool_num, "SECTION")
        self.writedxf(tool_num, "2")
        self.writedxf(tool_num, "ENTITIES")
        self.writedxf(tool_num, "0")
        self.writedxf(tool_num, "LWPOLYLINE")
        self.writedxf(tool_num, "5")
        self.writedxf(tool_num, "4E")
        self.writedxf(tool_num, "100")
        self.writedxf(tool_num, "AcDbEntity")
        self.writedxf(tool_num, "8")
        self.writedxf(tool_num, "0")
        self.writedxf(tool_num, "6")
        self.writedxf(tool_num, "ByLayer")
#
        self.writedxfcolor(tool_num)
#
        self.writedxf(tool_num, "370")
        self.writedxf(tool_num, "-1")
        self.writedxf(tool_num, "100")
        self.writedxf(tool_num, "AcDbPolyline")
        self.writedxf(tool_num, "90")
        self.writedxf(tool_num, "8")
        self.writedxf(tool_num, "70")
        self.writedxf(tool_num, "1")
        self.writedxf(tool_num, "43")
        self.writedxf(tool_num, "0")
#1 upper right corner before arc (counter-clockwise)
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin + xwidth))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin + yheight - radius))
        self.writedxf(tool_num, "42")
        self.writedxf(tool_num, "0.414213562373095")
#2 upper right corner after arc
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin + xwidth - radius))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin + yheight))
#3 upper left corner before arc (counter-clockwise)
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin + radius))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin + yheight))
        self.writedxf(tool_num, "42")
        self.writedxf(tool_num, "0.414213562373095")
#4 upper left corner after arc
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin + yheight - radius))
#5 lower left corner before arc (counter-clockwise)
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin + radius))
        self.writedxf(tool_num, "42")
        self.writedxf(tool_num, "0.414213562373095")
#6 lower left corner after arc
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin + radius))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin))
#7 lower right corner before arc (counter-clockwise)
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin + xwidth - radius))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin))
        self.writedxf(tool_num, "42")
        self.writedxf(tool_num, "0.414213562373095")
#8 lower right corner after arc
        self.writedxf(tool_num, "10")
        self.writedxf(tool_num, str(xorigin + xwidth))
        self.writedxf(tool_num, "20")
        self.writedxf(tool_num, str(yorigin + radius))
# end current section
        self.writedxf(tool_num, "0")
        self.writedxf(tool_num, "SEQEND")
```

So we add the balance of the corner treatments which are decorative (and easily implemented).

Chamfer:

```
    def dxfrectanglechamfer(self, tool_num, xorigin, yorigin, xwidth, yheight, radius):
        self.dxfline(tool_num, xorigin + radius, yorigin, xorigin, yorigin + radius)
        self.dxfline(tool_num, xorigin, yorigin + yheight - radius, xorigin + radius, yorigin + yheight)
        self.dxfline(tool_num, xorigin + xwidth - radius, yorigin + yheight, xorigin + xwidth, yorigin + yheight - radius)
        self.dxfline(tool_num, xorigin + xwidth - radius, yorigin, xorigin + xwidth, yorigin + radius)

        self.dxfline(tool_num, xorigin + radius, yorigin, xorigin + xwidth - radius, yorigin)
        self.dxfline(tool_num, xorigin + xwidth, yorigin + radius, xorigin + xwidth, yorigin + yheight - radius)
        self.dxfline(tool_num, xorigin + xwidth - radius, yorigin + yheight, xorigin + radius, yorigin + yheight)
        self.dxfline(tool_num, xorigin, yorigin + yheight - radius, xorigin, yorigin + radius)
```

Flipped Fillet:

```
    def dxfrectangleflippedfillet(self, tool_num, xorigin, yorigin, xwidth, yheight, radius):
        self.dxfarc(tool_num, xorigin, yorigin, radius,  0, 90)
        self.dxfarc(tool_num, xorigin + xwidth, yorigin, radius, 90, 180)
        self.dxfarc(tool_num, xorigin + xwidth, yorigin + yheight, radius, 180, 270)
        self.dxfarc(tool_num, xorigin, yorigin + yheight, radius, 270, 360)

        self.dxfline(tool_num, xorigin + radius, yorigin, xorigin + xwidth - radius, yorigin)
        self.dxfline(tool_num, xorigin + xwidth, yorigin + radius, xorigin + xwidth, yorigin + yheight - radius)
        self.dxfline(tool_num, xorigin + xwidth - radius, yorigin + yheight, xorigin + radius, yorigin + yheight)
        self.dxfline(tool_num, xorigin, yorigin + yheight - radius, xorigin, yorigin + radius)
```

Cutting rectangles while writing out their perimeter in the DXF files (so that they may be assigned a matching toolpath in a traditional CAM program upon import) will require the origin coordinates, height and width and depth of the pocket, and the tool # so that the corners may have a radius equal to the tool which is used. Whether a given module is an interior pocket or an outline (interior or exterior) will be determined by the specifics of the module and its usage/positioning, with `outline` being added to those modules which cut perimeter.

A further consideration is that cut orientation as an option should be accounted for if writing out G-code, as well as stepover, and the nature of initial entry (whether ramping in would be implemented, and if so, at what angle). Advanced toolpath strategies such as trochoidal milling could also be implemented.

`cutrectangle` The routine `cutrectangle` cuts the outline of a rectangle creating rounded corners.

```
    def cutrectangle(self, tool_num, bx, by, bz, xwidth, yheight, zdepth):
        self.cutline(bx, by, bz)
        self.cutline(bx, by, bz - zdepth)
        self.cutline(bx + xwidth, by, bz - zdepth)
        self.cutline(bx + xwidth, by + yheight, bz - zdepth)
        self.cutline(bx, by + yheight, bz - zdepth)
        self.cutline(bx, by, bz - zdepth)

    def cutrectangledxf(self, tool_num, bx, by, bz, xwidth, yheight, zdepth):
        self.cutrectangle(tool_num, bx, by, bz, xwidth, yheight, zdepth)
        self.dxfrectangle(tool_num, bx, by, xwidth, yheight, "Square")
```

The rounded forms instantiate a radius:

```
    def cutrectangleround(self, tool_num, bx, by, bz, xwidth,
```

```
                yheight, zdepth, radius):
#               self.rapid(bx + radius, by, bz)
                self.cutline(bx + radius, by, bz + zdepth)
                self.cutline(bx + xwidth - radius, by, bz + zdepth)
                self.cutquarterCCSE(bx + xwidth, by + radius, bz + zdepth,
                    radius)
                self.cutline(bx + xwidth, by + yheight - radius, bz +
                    zdepth)
                self.cutquarterCCNE(bx + xwidth - radius, by + yheight, bz
                    + zdepth, radius)
                self.cutline(bx + radius, by + yheight, bz + zdepth)
                self.cutquarterCCNW(bx, by + yheight - radius, bz + zdepth,
                     radius)
                self.cutline(bx, by + radius, bz + zdepth)
                self.cutquarterCCSW(bx + radius, by, bz + zdepth, radius)

        def cutrectanglerounddxf(self, tool_num, bx, by, bz, xwidth,
                yheight, zdepth, radius):
                self.cutrectangleround(tool_num, bx, by, bz, xwidth,
                    yheight, zdepth, radius)
                self.dxfrectangleround(tool_num, bx, by, xwidth, yheight,
                    radius)
```

cutkeyhole toolpath

3.8.1.1.3 Keyhole toolpath and undercut tooling The first topologically unusual toolpath is `cutkeyhole toolpath` — where other toolpaths have a direct correspondence between the associated geometry and the area cut, that Keyhole toolpaths may be used with tooling which undercuts and which will result in the creation of two different physical physical regions: the visible surface matching the union of the tool perimeter at the entry point and the linear movement of the shaft and the larger region of the tool perimeter at the depth which the tool is plunged to and moved along.

Tooling for such toolpaths is defined at paragraph 3.5.1

The interface which is being modeled is that of Carbide Create:



Hence the parameters:

- Starting Depth == `kh_start_depth`
- Max Depth == `kh_max_depth`
- Angle == `kht_direction`
- Length == `kh_distance`
- Tool == `kh_tool_num`

Due to the possibility of rotation, for the in-between positions there are more cases than one would think — for each quadrant there are the following possibilities:

- one node on the clockwise side is outside of the quadrant
- two nodes on the clockwise side are outside of the quadrant
- all nodes are w/in the quadrant
- one node on the counter-clockwise side is outside of the quadrant
- two nodes on the counter-clockwise side are outside of the quadrant

Supporting all of these would require trigonometric comparisons in the `if...else` blocks, so only the 4 quadrants, N, S, E, and W will be supported in the initial version. This will be done by wrapping the command with a version which only accepts those options:

```
    def cutkeyholegcdxf(self, kh_tool_num, kh_start_depth, kh_max_depth, kht_direction, kh_distance):
        if (kht_direction == "N"):
            toolpath = self.cutKHgcdxf(kh_tool_num, kh_start_depth, kh_max_depth, 90, kh_distance)
        elif (kht_direction == "S"):
            toolpath = self.cutKHgcdxf(kh_tool_num, kh_start_depth, kh_max_depth, 270, kh_distance)
        elif (kht_direction == "E"):
            toolpath = self.cutKHgcdxf(kh_tool_num, kh_start_depth, kh_max_depth, 0, kh_distance)
        elif (kht_direction == "W"):
            toolpath = self.cutKHgcdxf(kh_tool_num, kh_start_depth, kh_max_depth, 180, kh_distance)
#         if self.generatepaths == True:
#             self.toolpaths = union([self.toolpaths, toolpath])
        return toolpath
#         else:
#             return cube([0.01, 0.01, 0.01])
```

```
module cutkeyholegcdxf(kh_tool_num, kh_start_depth, kh_max_depth, kht_direction, kh_distance){
    gcp.cutkeyholegcdxf(kh_tool_num, kh_start_depth, kh_max_depth, kht_direction, kh_distance);
}
```

`cutKHgcdxf` The original version of the command, `cutKHgcdxf` retains an interface which allows calling it for arbitrary beginning and ending points of an arc.

Note that code is still present for the partial calculation of one quadrant (for the case of all nodes within the quadrant). The first task is to place a circle at the origin which is invariant of angle:

```
    def cutKHgcdxf(self, kh_tool_num, kh_start_depth, kh_max_depth, kh_angle, kh_distance):
        oXpos = self.xpos()
        oYpos = self.ypos()
        self.dxfKH(kh_tool_num, self.xpos(), self.ypos(), kh_start_depth, kh_max_depth, kh_angle, kh_distance)
        toolpath = self.cutline(self.xpos(), self.ypos(), -kh_max_depth)
        self.setxpos(oXpos)
        self.setypos(oYpos)
#         if self.generatepaths == False:
        return toolpath
#         else:
#             return cube([0.001, 0.001, 0.001])
```

```
    def dxfKH(self, kh_tool_num, oXpos, oYpos, kh_start_depth, kh_max_depth, kh_angle, kh_distance):
#         oXpos = self.xpos()
#         oYpos = self.ypos()
#Circle at entry hole
        self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 7), 0, 90)
        self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 7), 90, 180)
        self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 7), 180, 270)
        self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 7), 270, 360)
```

Then it will be necessary to test for each possible case in a series of If Else blocks:

```
#pre-calculate needed values
        r = self.tool_radius(kh_tool_num, 7)
#         print(r)
        rt = self.tool_radius(kh_tool_num, 1)
#         print(rt)
        ro = math.sqrt((self.tool_radius(kh_tool_num, 1))**2-(self.tool_radius(kh_tool_num, 7))**2)
#         print(ro)
        angle = math.degrees(math.acos(ro/rt))
#Outlines of entry hole and slot
        if (kh_angle == 0):
#Lower left of entry hole
            self.dxfarc(kh_tool_num, self.xpos(), self.ypos(), self.tool_radius(kh_tool_num, 1), 180, 270)
#Upper left of entry hole
            self.dxfarc(kh_tool_num, self.xpos(), self.ypos(), self.tool_radius(kh_tool_num, 1), 90, 180)
#Upper right of entry hole
#             self.dxfarc(kh_tool_num, self.xpos(), self.ypos(), rt, 41.810, 90)
            self.dxfarc(kh_tool_num, self.xpos(), self.ypos(), rt, angle, 90)
#Lower right of entry hole
            self.dxfarc(kh_tool_num, self.xpos(), self.ypos(), rt, 270, 360-angle)
#             self.dxfarc(kh_tool_num, self.xpos(), self.ypos(), self.tool_radius(kh_tool_num, 1), 270, 270+math.acos(self.tool_diameter(kh_tool_num, 5)/self.tool_diameter(kh_tool_num, 1)))
#Actual line of cut
#             self.dxfline(kh_tool_num, self.xpos(), self.ypos(), self.xpos()+kh_distance, self.ypos())
#upper right of end of slot (kh_max_depth+4.36))/2
            self.dxfarc(kh_tool_num, self.xpos()+kh_distance, self.ypos(), self.tool_diameter(kh_tool_num, (kh_max_depth+4.36))/2, 0, 90)
#lower right of end of slot
            self.dxfarc(kh_tool_num, self.xpos()+kh_distance, self.ypos(), self.tool_diameter(kh_tool_num, (kh_max_depth+4.36))/2, 270, 360)
#upper right slot
            self.dxfline(kh_tool_num, self.xpos()+ro, self.ypos()-(self.tool_diameter(kh_tool_num, 7)/2), self.xpos()+kh_distance, self.ypos()-(self.tool_diameter(kh_tool_num, 7)/2))
#             self.dxfline(kh_tool_num, self.xpos()+(math.sqrt((self.tool_diameter(kh_tool_num, 1)^2)-(self.tool_diameter(kh_tool_num, 5)^2))/2), self.ypos()+self.tool_diameter(kh_tool_num, (kh_max_depth))/2, ( (kh_max_depth-6.34))/2)^2-(self.tool_diameter(kh_tool_num, (kh_max_depth-6.34))/2)^2, self.xpos()+kh_distance, self.ypos()+self.tool_diameter(kh_tool_num, (kh_max_depth))/2, kh_tool_num)
#end position at top of slot
#lower right slot
            self.dxfline(kh_tool_num, self.xpos()+ro, self.ypos()+(self.tool_diameter(kh_tool_num, 7)/2), self.xpos()+kh_distance, self.ypos()+(self.tool_diameter(kh_tool_num, 7)/2))
#         dxfline(kh_tool_num, self.xpos()+(math.sqrt((self.tool_diameter(kh_tool_num, 1)^2)-(self.tool_diameter(kh_tool_num, 5)^2))/2), self.ypos()-self.tool_diameter(kh_tool_num, (kh_max_depth))/2, ( (kh_max_depth-6.34))/2)^2-(self.tool_diameter(kh_tool_num, (kh_max_depth-6.34))/2)^2, self.xpos()+kh_distance, self.ypos()-self.tool_diameter(kh_tool_num, (kh_max_depth))/2, KH_tool_num)
#end position at top of slot
#    hull(){
#      translate([xpos(), ypos(), zpos()]){
#        keyhole_shaft(6.35, 9.525);
#      }
#      translate([xpos(), ypos(), zpos()-kh_max_depth]){
#        keyhole_shaft(6.35, 9.525);
#      }
#    }
#    hull(){
#      translate([xpos(), ypos(), zpos()-kh_max_depth]){
```

```
#        keyhole_shaft(6.35, 9.525);
#      }
#      translate([xpos()+kh_distance, ypos(), zpos()-kh_max_depth]) {
#        keyhole_shaft(6.35, 9.525);
#      }
#    }
#    cutwithfeed(getxpos(), getypos(), -kh_max_depth, feed);
#    cutwithfeed(getxpos()+kh_distance, getypos(), -kh_max_depth, feed);
#    setxpos(getxpos()-kh_distance);
#  } else if (kh_angle > 0 && kh_angle < 90) {
#//echo(kh_angle);
#  dxfarc(getxpos(), getypos(), tool_diameter(KH_tool_num, (kh_max_depth))/2, 90+kh_angle, 180+kh_angle, KH_tool_num);
#  dxfarc(getxpos(), getypos(), tool_diameter(KH_tool_num, (kh_max_depth))/2, 180+kh_angle, 270+kh_angle, KH_tool_num);
#dxfarc(getxpos(), getypos(), tool_diameter(KH_tool_num, (kh_max_depth))/2, kh_angle+asin((tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2)/(tool_diameter(KH_tool_num, (kh_max_depth))/2)), 90+kh_angle, KH_tool_num);
#dxfarc(getxpos(), getypos(), tool_diameter(KH_tool_num, (kh_max_depth))/2, 270+kh_angle, 360+kh_angle-asin((tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2)/(tool_diameter(KH_tool_num, (kh_max_depth))/2)), KH_tool_num);
#dxfarc(getxpos()+(kh_distance*cos(kh_angle)),
#  getypos()+(kh_distance*sin(kh_angle)), tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2, 0+kh_angle, 90+kh_angle, KH_tool_num);
#dxfarc(getxpos()+(kh_distance*cos(kh_angle)), getypos()+(kh_distance*sin(kh_angle)), tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2, 270+kh_angle, 360+kh_angle, KH_tool_num);
#dxfline( getxpos()+tool_diameter(KH_tool_num, (kh_max_depth))/2*cos(kh_angle+asin((tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2)/(tool_diameter(KH_tool_num, (kh_max_depth))/2))),
# getypos()+tool_diameter(KH_tool_num, (kh_max_depth))/2*sin(kh_angle+asin((tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2)/(tool_diameter(KH_tool_num, (kh_max_depth))/2))),
# getxpos()+(kh_distance*cos(kh_angle))-((tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2)*sin(kh_angle)),
# getypos()+(kh_distance*sin(kh_angle))+((tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2)*cos(kh_angle)), KH_tool_num);
#//echo("a", tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2);
#//echo("c", tool_diameter(KH_tool_num, (kh_max_depth))/2);
#echo("Aangle", asin((tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2)/(tool_diameter(KH_tool_num, (kh_max_depth))/2)));
#//echo(kh_angle);
# cutwithfeed(getxpos()+(kh_distance*cos(kh_angle)), getypos()+(kh_distance*sin(kh_angle)), -kh_max_depth, feed);
#            toolpath = toolpath.union(self.cutline(self.xpos()+kh_distance, self.ypos(), -kh_max_depth))
        elif (kh_angle == 90):
#Lower left of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 1), 180, 270)
#Lower right of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 1), 270, 360)
#left slot
            self.dxfline(kh_tool_num, oXpos-r, oYpos+ro, oXpos-r, oYpos+kh_distance)
#right slot
            self.dxfline(kh_tool_num, oXpos+r, oYpos+ro, oXpos+r, oYpos+kh_distance)
#upper left of end of slot
            self.dxfarc(kh_tool_num, oXpos, oYpos+kh_distance, r, 90, 180)
#upper right of end of slot
            self.dxfarc(kh_tool_num, oXpos, oYpos+kh_distance, r, 0, 90)
#Upper right of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, rt, 0, 90-angle)
#Upper left of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, rt, 90+angle, 180)
#            toolpath = toolpath.union(self.cutline(oXpos, oYpos+kh_distance, -kh_max_depth))
        elif (kh_angle == 180):
#Lower right of entry hole
```

```
            self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 1), 270, 360)
#Upper right of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 1), 0, 90)
#Upper left of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, rt, 90, 180-angle)
#Lower left of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, rt, 180+angle, 270)
#upper slot
            self.dxfline(kh_tool_num, oXpos-ro, oYpos-r, oXpos-kh_distance, oYpos-r)
#lower slot
            self.dxfline(kh_tool_num, oXpos-ro, oYpos+r, oXpos-kh_distance, oYpos+r)
#upper left of end of slot
            self.dxfarc(kh_tool_num, oXpos-kh_distance, oYpos, r, 90, 180)
#lower left of end of slot
            self.dxfarc(kh_tool_num, oXpos-kh_distance, oYpos, r, 180, 270)
#            toolpath = toolpath.union(self.cutline(oXpos-kh_distance, oYpos, -kh_max_depth))
        elif (kh_angle == 270):
#Upper left of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 1), 90, 180)
#Upper right of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, self.tool_radius(kh_tool_num, 1), 0, 90)
#left slot
            self.dxfline(kh_tool_num, oXpos-r, oYpos-ro, oXpos-r, oYpos-kh_distance)
#right slot
            self.dxfline(kh_tool_num, oXpos+r, oYpos-ro, oXpos+r, oYpos-kh_distance)
#lower left of end of slot
            self.dxfarc(kh_tool_num, oXpos, oYpos-kh_distance, r, 180, 270)
#lower right of end of slot
            self.dxfarc(kh_tool_num, oXpos, oYpos-kh_distance, r, 270, 360)
#lower right of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, rt, 180, 270-angle)
#lower left of entry hole
            self.dxfarc(kh_tool_num, oXpos, oYpos, rt, 270+angle, 360)
#            toolpath = toolpath.union(self.cutline(oXpos, oYpos-kh_distance, -kh_max_depth))
#        print(self.zpos())
#        self.setxpos(oXpos)
#        self.setypos(oYpos)
#        if self.generatepaths == False:
#            return toolpath

#  } else if (kh_angle == 90) {
#    //Lower left of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 180, 270, KH_tool_num);
#    //Lower right of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 270, 360, KH_tool_num);
#    //Upper right of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 0, acos(tool_diameter(KH_tool_num, 5)/tool_diameter(KH_tool_num, 1)), KH_tool_num);
#    //Upper left of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 180-acos(tool_diameter(KH_tool_num, 5)/tool_diameter(KH_tool_num, 1)), 180, KH_tool_num);
#    //Actual line of cut
#    dxfline(getxpos(), getypos(), getxpos(), getypos()+kh_distance);
#    //upper right of slot
#    dxfarc(getxpos(), getypos()+kh_distance, tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2, 0, 90, KH_tool_num);
#    //upper left of slot
#    dxfarc(getxpos(), getypos()+kh_distance, tool_diameter(
```

```
KH_tool_num, (kh_max_depth+6.35))/2, 90, 180, KH_tool_num);
gcpy #     //right of slot
gcpy #     dxfline(
gcpy #         getxpos()+tool_diameter(KH_tool_num, (kh_max_depth))/2,
gcpy #         getypos()+(math.sqrt((tool_diameter(KH_tool_num, 1)^2)-(tool_diameter(KH_tool_num, 5)^2))/2), //( (kh_max_depth-6.34))/2)^2-(tool_diameter(KH_tool_num, (kh_max_depth-6.34))/2)^2,
gcpy #         getxpos()+tool_diameter(KH_tool_num, (kh_max_depth))/2,
gcpy #     //end position at top of slot
gcpy #         getypos()+kh_distance,
gcpy #         KH_tool_num);
gcpy #     dxfline(getxpos()-tool_diameter(KH_tool_num, (kh_max_depth))/2, getypos()+(math.sqrt((tool_diameter(KH_tool_num, 1)^2)-(tool_diameter(KH_tool_num, 5)^2))/2), getxpos()-tool_diameter(KH_tool_num, (kh_max_depth+6.35))/2, getypos()+kh_distance, KH_tool_num);
gcpy #     hull(){
gcpy #       translate([xpos(), ypos(), zpos()]){
gcpy #         keyhole_shaft(6.35, 9.525);
gcpy #       }
gcpy #       translate([xpos(), ypos(), zpos()-kh_max_depth]){
gcpy #         keyhole_shaft(6.35, 9.525);
gcpy #       }
gcpy #     }
gcpy #     hull(){
gcpy #       translate([xpos(), ypos(), zpos()-kh_max_depth]){
gcpy #         keyhole_shaft(6.35, 9.525);
gcpy #       }
gcpy #       translate([xpos(), ypos()+kh_distance, zpos()-kh_max_depth]){
gcpy #         keyhole_shaft(6.35, 9.525);
gcpy #       }
gcpy #     }
gcpy #     cutwithfeed(getxpos(), getypos(), -kh_max_depth, feed);
gcpy #     cutwithfeed(getxpos(), getypos()+kh_distance, -kh_max_depth, feed);
gcpy #     setypos(getypos()-kh_distance);
gcpy #   } else if (kh_angle == 180) {
gcpy #     //Lower right of entry hole
gcpy #     dxfarc(getxpos(), getypos(), 9.525/2, 270, 360, KH_tool_num);
gcpy #     //Upper right of entry hole
gcpy #     dxfarc(getxpos(), getypos(), 9.525/2, 0, 90, KH_tool_num);
gcpy #     //Upper left of entry hole
gcpy #     dxfarc(getxpos(), getypos(), 9.525/2, 90, 90+acos(tool_diameter(KH_tool_num, 5)/tool_diameter(KH_tool_num, 1)), KH_tool_num);
gcpy #     //Lower left of entry hole
gcpy #     dxfarc(getxpos(), getypos(), 9.525/2, 270-acos(tool_diameter(KH_tool_num, 5)/tool_diameter(KH_tool_num, 1)), 270, KH_tool_num);
gcpy #     //upper left of slot
gcpy #     dxfarc(getxpos()-kh_distance, getypos(), tool_diameter(KH_tool_num, (kh_max_depth+6.35))/2, 90, 180, KH_tool_num);
gcpy #     //lower left of slot
gcpy #     dxfarc(getxpos()-kh_distance, getypos(), tool_diameter(KH_tool_num, (kh_max_depth+6.35))/2, 180, 270, KH_tool_num);
gcpy #     //Actual line of cut
gcpy #     dxfline(getxpos(), getypos(), getxpos()-kh_distance, getypos());
gcpy #     //upper left slot
gcpy #     dxfline(
gcpy #         getxpos()-(math.sqrt((tool_diameter(KH_tool_num, 1)^2)-(tool_diameter(KH_tool_num, 5)^2))/2),
gcpy #         getypos()+tool_diameter(KH_tool_num, (kh_max_depth))/2, //( (kh_max_depth-6.34))/2)^2-(tool_diameter(KH_tool_num, (kh_max_depth-6.34))/2)^2,
gcpy #         getxpos()-kh_distance,
gcpy #     //end position at top of slot
gcpy #         getypos()+tool_diameter(KH_tool_num, (kh_max_depth))/2,
gcpy #         KH_tool_num);
gcpy #     //lower right slot
gcpy #     dxfline(
gcpy #         getxpos()-(math.sqrt((tool_diameter(KH_tool_num, 1)^2)-(tool_diameter(KH_tool_num, 5)^2))/2),
gcpy #         getypos()-tool_diameter(KH_tool_num, (kh_max_depth))/2, //( (kh_max_depth-6.34))/2)^2-(tool_diameter(KH_tool_num, (kh_max_depth-6.34))/2)^2,
gcpy #         getxpos()-kh_distance,
```

```
#    //end position at top of slot
#        getypos()-tool_diameter(KH_tool_num, (kh_max_depth))/2,
#        KH_tool_num);
#    hull(){
#      translate([xpos(), ypos(), zpos()]){
#        keyhole_shaft(6.35, 9.525);
#      }
#      translate([xpos(), ypos(), zpos()-kh_max_depth]){
#        keyhole_shaft(6.35, 9.525);
#      }
#    }
#    hull(){
#      translate([xpos(), ypos(), zpos()-kh_max_depth]){
#        keyhole_shaft(6.35, 9.525);
#      }
#      translate([xpos()-kh_distance, ypos(), zpos()-kh_max_depth]){
#        keyhole_shaft(6.35, 9.525);
#      }
#    }
#    cutwithfeed(getxpos(), getypos(), -kh_max_depth, feed);
#    cutwithfeed(getxpos()-kh_distance, getypos(), -kh_max_depth, feed);
#    setxpos(getxpos()+kh_distance);
#  } else if (kh_angle == 270) {
#    //Upper right of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 0, 90, KH_tool_num);
#    //Upper left of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 90, 180, KH_tool_num);
#    //lower right of slot
#    dxfarc(getxpos(), getypos()-kh_distance, tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2, 270, 360, KH_tool_num);
#    //lower left of slot
#    dxfarc(getxpos(), getypos()-kh_distance, tool_diameter(KH_tool_num, (kh_max_depth+4.36))/2, 180, 270, KH_tool_num);
#    //Actual line of cut
#    dxfline(getxpos(), getypos(), getxpos(), getypos()-kh_distance);
#    //right of slot
#    dxfline(
#        getxpos()+tool_diameter(KH_tool_num, (kh_max_depth))/2,
#        getypos()-(math.sqrt((tool_diameter(KH_tool_num, 1)^2)-(tool_diameter(KH_tool_num, 5)^2))/2), //( (kh_max_depth-6.34))/2)^2-(tool_diameter(KH_tool_num, (kh_max_depth-6.34))/2)^2,
#        getxpos()+tool_diameter(KH_tool_num, (kh_max_depth))/2,
#    //end position at top of slot
#        getypos()-kh_distance,
#        KH_tool_num);
#    //left of slot
#    dxfline(
#        getxpos()-tool_diameter(KH_tool_num, (kh_max_depth))/2,
#        getypos()-(math.sqrt((tool_diameter(KH_tool_num, 1)^2)-(tool_diameter(KH_tool_num, 5)^2))/2), //( (kh_max_depth-6.34))/2)^2-(tool_diameter(KH_tool_num, (kh_max_depth-6.34))/2)^2,
#        getxpos()-tool_diameter(KH_tool_num, (kh_max_depth))/2,
#    //end position at top of slot
#        getypos()-kh_distance,
#        KH_tool_num);
#    //Lower right of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 360-acos(tool_diameter(KH_tool_num, 5)/tool_diameter(KH_tool_num, 1)), 360, KH_tool_num);
#    //Lower left of entry hole
#    dxfarc(getxpos(), getypos(), 9.525/2, 180, 180+acos(tool_diameter(KH_tool_num, 5)/tool_diameter(KH_tool_num, 1)), KH_tool_num);
#    hull(){
#      translate([xpos(), ypos(), zpos()]){
#        keyhole_shaft(6.35, 9.525);
#      }
#      translate([xpos(), ypos(), zpos()-kh_max_depth]){
#        keyhole_shaft(6.35, 9.525);
#      }
#    }
#    hull(){
#      translate([xpos(), ypos(), zpos()-kh_max_depth]){
#        keyhole_shaft(6.35, 9.525);
#      }
```

```
#      translate([xpos(), ypos()-kh_distance, zpos()-kh_max_depth])
    {
#        keyhole_shaft(6.35, 9.525);
#      }
#    }
#    cutwithfeed(getxpos(), getypos(), -kh_max_depth, feed);
#    cutwithfeed(getxpos(), getypos()-kh_distance, -kh_max_depth,
    feed);
#    setypos(getypos()+kh_distance);
#  }
#}
```

3.8.1.1.4 Dovetail joinery and tooling

One focus of this project from the beginning has been cutting joinery. The first such toolpath to be developed is half-blind dovetails, since they are intrinsically simple to calculate since their geometry is dictated by the geometry of the tool.

BlocksCAD project page at: https://www.blockscad3d.com/community/projects/1941456 and discussion at: https://community.carbide3d.com/t/tool-paths-for-different-sized-dovetail-bit 89098

Making such cuts will require dovetail tooling such as:

- 808079 https://www.amanatool.com/45828-carbide-tipped-dovetail-8-deg-x-1-2-dia-x-825-x-1 html
- 814 https://www.leevalley.com/en-us/shop/tools/power-tool-accessories/router-bits/30172-dovetail-bits?item=18J1607

Two commands are required:

```
    def cut_pins(self, Joint_Width, stockZthickness,
        Number_of_Dovetails, Spacing, Proportion, DTT_diameter,
        DTT_angle):
        DTO = Tan(DTT_angle) * (stockZthickness * Proportion)
        DTR = DTT_diameter/2 - DTO
        cpr = self.rapidXY(0, stockZthickness + Spacing/2)
        ctp = self.cutlinedxfgc(self.xpos(), self.ypos(), -
            stockZthickness * Proportion)
#        ctp = ctp.union(self.cutlinedxfgc(Joint_Width / (
    Number_of_Dovetails * 2), self.ypos(), -stockZthickness *
    Proportion))
        i = 1
        while i < Number_of_Dovetails * 2:
#            print(i)
            ctp = ctp.union(self.cutlinedxfgc(i * (Joint_Width / (
                Number_of_Dovetails * 2)), self.ypos(), -
                stockZthickness * Proportion))
            ctp = ctp.union(self.cutlinedxfgc(i * (Joint_Width / (
                Number_of_Dovetails * 2)), (stockZthickness +
                Spacing) + (stockZthickness * Proportion) - (
                DTT_diameter/2), -(stockZthickness * Proportion)))
            ctp = ctp.union(self.cutlinedxfgc(i * (Joint_Width / (
                Number_of_Dovetails * 2)), stockZthickness + Spacing
                /2, -(stockZthickness * Proportion)))
            ctp = ctp.union(self.cutlinedxfgc((i + 1) * (
                Joint_Width / (Number_of_Dovetails * 2)),
                stockZthickness + Spacing/2,-(stockZthickness *
                Proportion)))
            self.dxfrectangleround(self.currenttoolnumber(),
                i * (Joint_Width / (Number_of_Dovetails * 2))-DTR,
                stockZthickness + (Spacing/2) - DTR,
                DTR * 2,
                (stockZthickness * Proportion) + Spacing/2 + DTR *
                    2 - (DTT_diameter/2),
                DTR)
            i += 2
        self.rapidZ(0)
        return ctp
```

and

```
    def cut_tails(self, Joint_Width, stockZthickness,
        Number_of_Dovetails, Spacing, Proportion, DTT_diameter,
        DTT_angle):
        DTO = Tan(DTT_angle) * (stockZthickness * Proportion)
        DTR = DTT_diameter/2 - DTO
        cpr = self.rapidXY(0, 0)
```

```
        ctp = self.cutlinedxfgc(self.xpos(), self.ypos(), -stockZthickness * Proportion)
        ctp = ctp.union(self.cutlinedxfgc(
            Joint_Width / (Number_of_Dovetails * 2) - (DTT_diameter - DTO),
            self.ypos(),
            -stockZthickness * Proportion))
        i = 1
        while i < Number_of_Dovetails * 2:
            ctp = ctp.union(self.cutlinedxfgc(
                i * (Joint_Width / (Number_of_Dovetails * 2)) - (DTT_diameter - DTO),
                stockZthickness * Proportion - DTT_diameter / 2,
                -(stockZthickness * Proportion)))
            ctp = ctp.union(self.cutarcCWdxf(180, 90,
                i * (Joint_Width / (Number_of_Dovetails * 2)),
                stockZthickness * Proportion - DTT_diameter / 2,
#                self.ypos(),
                DTT_diameter - DTO, 0, 1))
            ctp = ctp.union(self.cutarcCWdxf(90, 0,
                i * (Joint_Width / (Number_of_Dovetails * 2)),
                stockZthickness * Proportion - DTT_diameter / 2,
                DTT_diameter - DTO, 0, 1))
            ctp = ctp.union(self.cutlinedxfgc(
                i * (Joint_Width / (Number_of_Dovetails * 2)) + (DTT_diameter - DTO),
                0,
                -(stockZthickness * Proportion)))
            ctp = ctp.union(self.cutlinedxfgc(
                (i + 2) * (Joint_Width / (Number_of_Dovetails * 2)) - (DTT_diameter - DTO),
                0,
                -(stockZthickness * Proportion)))
            i += 2
        self.rapidZ(0)
        self.rapidXY(0, 0)
        ctp = ctp.union(self.cutlinedxfgc(self.xpos(), self.ypos(), -stockZthickness * Proportion))
        self.dxfarc(self.currenttoolnumber(), 0, 0, DTR, 180, 270)
        self.dxfline(self.currenttoolnumber(), -DTR, 0, -DTR, stockZthickness + DTR)
        self.dxfarc(self.currenttoolnumber(), 0, stockZthickness + DTR, DTR, 90, 180)
        self.dxfline(self.currenttoolnumber(), 0, stockZthickness + DTR * 2, Joint_Width, stockZthickness + DTR * 2)
        i = 0
        while i < Number_of_Dovetails * 2:
            ctp = ctp.union(self.cutline(i * (Joint_Width / (Number_of_Dovetails * 2)), stockZthickness + DTO, -(stockZthickness * Proportion)))
            ctp = ctp.union(self.cutline((i+2) * (Joint_Width / (Number_of_Dovetails * 2)), stockZthickness + DTO, -(stockZthickness * Proportion)))
            ctp = ctp.union(self.cutline((i+2) * (Joint_Width / (Number_of_Dovetails * 2)), 0, -(stockZthickness * Proportion)))
            self.dxfarc(self.currenttoolnumber(), i * (Joint_Width / (Number_of_Dovetails * 2)), 0, DTR, 270, 360)
            self.dxfline(self.currenttoolnumber(),
                i * (Joint_Width / (Number_of_Dovetails * 2)) + DTR,
                0,
                i * (Joint_Width / (Number_of_Dovetails * 2)) + DTR, stockZthickness * Proportion - DTT_diameter / 2)
            self.dxfarc(self.currenttoolnumber(), (i + 1) * (Joint_Width / (Number_of_Dovetails * 2)), stockZthickness * Proportion - DTT_diameter / 2, (Joint_Width / (Number_of_Dovetails * 2)) - DTR, 90, 180)
            self.dxfarc(self.currenttoolnumber(), (i + 1) * (Joint_Width / (Number_of_Dovetails * 2)), stockZthickness * Proportion - DTT_diameter / 2, (Joint_Width / (Number_of_Dovetails * 2)) - DTR, 0, 90)
            self.dxfline(self.currenttoolnumber(),
                (i + 2) * (Joint_Width / (Number_of_Dovetails * 2)) - DTR,
```

```
                    0,
                    (i + 2) * (Joint_Width / (Number_of_Dovetails * 2)) - DTR, stockZthickness * Proportion - DTT_diameter / 2)
                self.dxfarc(self.currenttoolnumber(), (i + 2) * (Joint_Width / (Number_of_Dovetails * 2)), 0, DTR, 180, 270)
                i += 2
            self.dxfarc(self.currenttoolnumber(), Joint_Width, stockZthickness + DTR, DTR, 0, 90)
            self.dxfline(self.currenttoolnumber(), Joint_Width + DTR, stockZthickness + DTR, Joint_Width + DTR, 0)
            self.dxfarc(self.currenttoolnumber(), Joint_Width, 0, DTR, 270, 360)
            return ctp
```

which are used as:

```
toolpaths = gcp.cut_pins(stockXwidth, stockZthickness, Number_of_Dovetails, Spacing, Proportion, DTT_dia

toolpaths.append(gcp.cut_tails(stockXwidth, stockZthickness, Number_of_Dovetails, Spacing, Proportion, I
```

Future versions may adjust the parameters passed in, having them calculate from the specifications for the currently active dovetail tool.

3.8.1.1.5 Full-blind box joints

BlocksCAD project page at: https://www.blockscad3d.com/community/projects/1943966 and discussion at: https://community.carbide3d.com/t/full-blind-box-joints-in-carbide-create/53329

Full-blind box joints will require 3 separate tools:

- small V tool — this will be needed to make a cut along the edge of the joint
- small square tool — this should be the same diameter as the small V tool
- large V tool — this will facilitate the stock being of a greater thickness and avoid the need to make multiple cuts to cut the blind miters at the ends of the joint

Two different versions of the commands will be necessary, one for each orientation:

- horizontal
- vertical

and then the internal commands for each side will in turn need separate versions:

```
    def Full_Blind_Finger_Joint_square(self, bx, by, orientation, side, width, thickness, Number_of_Pins, largeVdiameter, smallDiameter, normalormirror = "Default"):
    # Joint_Orientation = "Horizontal" "Even" == "Lower", "Odd" == "Upper"
    # Joint_Orientation = "Vertical" "Even" == "Left", "Odd" == "Right"
        if (orientation == "Vertical"):
            if (normalormirror == "Default" and side != "Both"):
                if (side == "Left"):
                    normalormirror = "Even"
                if (side == "Right"):
                    normalormirror = "Odd"
        if (orientation == "Horizontal"):
            if (normalormirror == "Default" and side != "Both"):
                if (side == "Lower"):
                    normalormirror = "Even"
                if (side == "Upper"):
                    normalormirror = "Odd"
        Finger_Width = ((Number_of_Pins * 2) - 1) * smallDiameter * 1.1
        Finger_Origin = width/2 - Finger_Width/2
        rapid = self.rapidZ(0)
        self.setdxfcolor("Cyan")
        rapid = rapid.union(self.rapidXY(bx, by))
        toolpath = (self.Finger_Joint_square(bx, by, orientation, side, width, thickness, Number_of_Pins, Finger_Origin, smallDiameter))
        if (orientation == "Vertical"):
            if (side == "Both"):
                toolpath = self.cutrectanglerounddxf(self.currenttoolnum, bx - (thickness - smallDiameter/2), by-smallDiameter/2, 0, (thickness * 2) - smallDiameter, width+smallDiameter, (smallDiameter / 2) / Tan(45), smallDiameter/2)
```

```
            if (side == "Left"):
                toolpath = self.cutrectanglerounddxf(self.currenttoolnum, bx - (smallDiameter/2), by-smallDiameter/2, 0, thickness, width+smallDiameter, ((smallDiameter / 2) / Tan(45)), smallDiameter/2)
            if (side == "Right"):
                toolpath = self.cutrectanglerounddxf(self.currenttoolnum, bx - (thickness - smallDiameter/2), by-smallDiameter/2, 0, thickness, width+smallDiameter, ((smallDiameter / 2) / Tan(45)), smallDiameter/2)
        toolpath = toolpath.union(self.Finger_Joint_square(bx, by, orientation, side, width, thickness, Number_of_Pins, Finger_Origin, smallDiameter))
        if (orientation == "Horizontal"):
            if (side == "Both"):
                toolpath = self.cutrectanglerounddxf(
                    self.currenttoolnum,
                    bx-smallDiameter/2,
                    by - (thickness - smallDiameter/2),
                    0,
                    width+smallDiameter,
                    (thickness * 2) - smallDiameter,
                    (smallDiameter / 2) / Tan(45),
                    smallDiameter/2)
            if (side == "Lower"):
                toolpath = self.cutrectanglerounddxf(
                    self.currenttoolnum,
                    bx - (smallDiameter/2),
                    by - smallDiameter/2,
                    0,
                    width+smallDiameter,
                    thickness,
                    ((smallDiameter / 2) / Tan(45)),
                    smallDiameter/2)
            if (side == "Upper"):
                toolpath = self.cutrectanglerounddxf(
                    self.currenttoolnum,
                    bx - smallDiameter/2,
                    by - (thickness - smallDiameter/2),
                    0,
                    width+smallDiameter,
                    thickness,
                    ((smallDiameter / 2) / Tan(45)),
                    smallDiameter/2)
        toolpath = toolpath.union(self.Finger_Joint_square(bx, by, orientation, side, width, thickness, Number_of_Pins, Finger_Origin, smallDiameter))
        return toolpath

    def Finger_Joint_square(self, bx, by, orientation, side, width, thickness, Number_of_Pins, Finger_Origin, smallDiameter, normalormirror = "Default"):
        jointdepth = -(thickness - (smallDiameter / 2) / Tan(45))
    # Joint_Orientation = "Horizontal" "Even" == "Lower", "Odd" == "Upper"
    # Joint_Orientation = "Vertical" "Even" == "Left", "Odd" == "Right"
        if (orientation == "Vertical"):
            if (normalormirror == "Default" and side != "Both"):
                if (side == "Left"):
                     normalormirror = "Even"
                if (side == "Right"):
                     normalormirror = "Odd"
        if (orientation == "Horizontal"):
            if (normalormirror == "Default" and side != "Both"):
                if (side == "Lower"):
                     normalormirror = "Even"
                if (side == "Upper"):
                     normalormirror = "Odd"
        radius = smallDiameter/2
        jointwidth = thickness - smallDiameter
        toolpath = self.currenttool()
        rapid = self.rapidZ(0)
        self.setdxfcolor("Blue")
        toolpath = toolpath.union(self.cutlineZgcfeed(jointdepth,1000))
```

```
    self.beginpolyline(self.currenttool())
    if (orientation == "Vertical"):
        rapid = rapid.union(self.rapidXY(bx, by + Finger_Origin))
        self.addvertex(self.currenttoolnumber(), self.xpos(), self.ypos())
        toolpath = toolpath.union(self.cutlineZgcfeed(jointdepth,1000))
        i = 0
        while i <= Number_of_Pins - 1:
            if (side == "Right"):
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + smallDiameter + radius/5, jointdepth))
            if (side == "Left" or side == "Both"):
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + radius, jointdepth))
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + jointwidth, self.ypos(), jointdepth))
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + radius/5, jointdepth))
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos() - jointwidth, self.ypos(), jointdepth))
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + radius, jointdepth))
            if (side == "Left"):
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + smallDiameter + radius/5, jointdepth))
            if (side == "Right" or side == "Both"):
                if (i < (Number_of_Pins - 1)):
#                    print(i)
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + radius, jointdepth))
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos() - jointwidth, self.ypos(), jointdepth))
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + radius/5, jointdepth))
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + jointwidth, self.ypos(), jointdepth))
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + radius, jointdepth))
            i += 1
# Joint_Orientation = "Horizontal" "Even" == "Lower", "Odd" == "Upper"
    if (orientation == "Horizontal"):
        rapid = rapid.union(self.rapidXY(bx + Finger_Origin, by))
        self.addvertex(self.currenttoolnumber(), self.xpos(), self.ypos())
        toolpath = toolpath.union(self.cutlineZgcfeed(jointdepth,1000))
        i = 0
        while i <= Number_of_Pins - 1:
            if (side == "Upper"):
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + smallDiameter + radius/5, self.ypos(), jointdepth))
            if (side == "Lower" or side == "Both"):
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + radius, self.ypos(), jointdepth))
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + jointwidth, jointdepth))
                toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + radius/5, self.ypos(), jointdepth))
```

```
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() - jointwidth, jointdepth))
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + radius, self.ypos(), jointdepth))
                if (side == "Lower"):
                    toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + smallDiameter + radius/5, self.ypos(), jointdepth))
                if (side == "Upper" or side == "Both"):
                    if (i < (Number_of_Pins - 1)):
#                         print(i)
                        toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + radius, self.ypos(), jointdepth))
                        toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() - jointwidth, jointdepth))
                        toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + radius/5, self.ypos(), jointdepth))
                        toolpath = toolpath.union(self.cutvertexdxf(self.xpos(), self.ypos() + jointwidth, jointdepth))
                        toolpath = toolpath.union(self.cutvertexdxf(self.xpos() + radius, self.ypos(), jointdepth))
                i += 1
        self.closepolyline(self.currenttoolnumber())
        return toolpath

    def Full_Blind_Finger_Joint_smallV(self, bx, by, orientation, side, width, thickness, Number_of_Pins, largeVdiameter, smallDiameter):
        rapid = self.rapidZ(0)
#       rapid = rapid.union(self.rapidXY(bx, by))
        self.setdxfcolor("Red")
        if (orientation == "Vertical"):
            rapid = rapid.union(self.rapidXY(bx, by - smallDiameter/6))
            toolpath = self.cutlineZgcfeed(-thickness,1000)
            toolpath = self.cutlinedxfgc(bx, by + width + smallDiameter/6, - thickness)
        if (orientation == "Horizontal"):
            rapid = rapid.union(self.rapidXY(bx - smallDiameter/6, by))
            toolpath = self.cutlineZgcfeed(-thickness,1000)
            toolpath = self.cutlinedxfgc(bx + width + smallDiameter/6, by, -thickness)
#           rapid = self.rapidZ(0)

        return toolpath

    def Full_Blind_Finger_Joint_largeV(self, bx, by, orientation, side, width, thickness, Number_of_Pins, largeVdiameter, smallDiameter):
        radius = smallDiameter/2
        rapid = self.rapidZ(0)
        Finger_Width = ((Number_of_Pins * 2) - 1) * smallDiameter * 1.1
        Finger_Origin = width/2 - Finger_Width/2
#       rapid = rapid.union(self.rapidXY(bx, by))
#  Joint_Orientation = "Horizontal" "Even" == "Lower", "Odd" == "Upper"
#  Joint_Orientation = "Vertical" "Even" == "Left", "Odd" == "Right"
        if (orientation == "Vertical"):
            rapid = rapid.union(self.rapidXY(bx, by))
            toolpath = self.cutlineZgcfeed(-thickness,1000)
            toolpath = toolpath.union(self.cutlinedxfgc(bx, by + Finger_Origin, -thickness))
            rapid = self.rapidZ(0)
            rapid = rapid.union(self.rapidXY(bx, by + width - Finger_Origin))
            self.setdxfcolor("Blue")
            toolpath = toolpath.union(self.cutlineZgcfeed(-thickness,1000))
```

```
                toolpath = toolpath.union(self.cutlinedxfgc(bx, by + width, -thickness))
                if (side == "Left" or side == "Both"):
                    rapid = self.rapidZ(0)
                    self.setdxfcolor("Dark Gray")
                    rapid = rapid.union(self.rapidXY(bx+thickness-(smallDiameter / 2) / Tan(45), by - radius/2))
                    toolpath = toolpath.union(self.cutlineZgcfeed(-(smallDiameter / 2) / Tan(45),10000))
                    toolpath = toolpath.union(self.cutlinedxfgc(bx+thickness-(smallDiameter / 2) / Tan(45), by + width + radius/2, -(smallDiameter / 2) / Tan(45)))
                    rapid = self.rapidZ(0)
                    self.setdxfcolor("Green")
                    rapid = rapid.union(self.rapidXY(bx+thickness/2, by+width))
                    toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                    toolpath = toolpath.union(self.cutlinedxfgc(bx+thickness/2, by + width -thickness, -thickness/2))
                    rapid = self.rapidZ(0)
                    rapid = rapid.union(self.rapidXY(bx+thickness/2, by))
                    toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                    toolpath = toolpath.union(self.cutlinedxfgc(bx+thickness/2, by +thickness, -thickness/2))
                if (side == "Right" or side == "Both"):
                    rapid = self.rapidZ(0)
                    self.setdxfcolor("Dark Gray")
                    rapid = rapid.union(self.rapidXY(bx-(thickness-(smallDiameter / 2) / Tan(45)), by - radius/2))
                    toolpath = toolpath.union(self.cutlineZgcfeed(-(smallDiameter / 2) / Tan(45),10000))
                    toolpath = toolpath.union(self.cutlinedxfgc(bx-(thickness-(smallDiameter / 2) / Tan(45)), by + width + radius/2, -(smallDiameter / 2) / Tan(45)))
                    rapid = self.rapidZ(0)
                    self.setdxfcolor("Green")
                    rapid = rapid.union(self.rapidXY(bx-thickness/2, by+width))
                    toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                    toolpath = toolpath.union(self.cutlinedxfgc(bx-thickness/2, by + width -thickness, -thickness/2))
                    rapid = self.rapidZ(0)
                    rapid = rapid.union(self.rapidXY(bx-thickness/2, by))
                    toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                    toolpath = toolpath.union(self.cutlinedxfgc(bx-thickness/2, by +thickness, -thickness/2))
        # Joint_Orientation = "Horizontal" "Even" == "Lower", "Odd" == "Upper"
            if (orientation == "Horizontal"):
                rapid = rapid.union(self.rapidXY(bx, by))
                self.setdxfcolor("Blue")
                toolpath = self.cutlineZgcfeed(-thickness,1000)
                toolpath = toolpath.union(self.cutlinedxfgc(bx + Finger_Origin, by, -thickness))
                rapid = rapid.union(self.rapidZ(0))
                rapid = rapid.union(self.rapidXY(bx + width - Finger_Origin, by))
                toolpath = toolpath.union(self.cutlineZgcfeed(-thickness,1000))
                toolpath = toolpath.union(self.cutlinedxfgc(bx + width, by, -thickness))
                if (side == "Lower" or side == "Both"):
                    rapid = self.rapidZ(0)
                    self.setdxfcolor("Dark Gray")
                    rapid = rapid.union(self.rapidXY(bx - radius, by+thickness-(smallDiameter / 2) / Tan(45)))
                    toolpath = toolpath.union(self.cutlineZgcfeed(-(smallDiameter / 2) / Tan(45),10000))
```

```
                toolpath = toolpath.union(self.cutlinedxfgc(bx + width + radius, by+thickness-(smallDiameter / 2) / Tan(45), -(smallDiameter / 2) / Tan(45)))
                rapid = self.rapidZ(0)
                self.setdxfcolor("Green")
                rapid = rapid.union(self.rapidXY(bx+width, by+thickness/2))
                toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                toolpath = toolpath.union(self.cutlinedxfgc(bx + width -thickness, by+thickness/2, -thickness/2))
                rapid = self.rapidZ(0)
                rapid = rapid.union(self.rapidXY(bx, by+thickness/2))
                toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                toolpath = toolpath.union(self.cutlinedxfgc(bx + thickness, by+thickness/2, -thickness/2))
            if (side == "Upper" or side == "Both"):
                rapid = self.rapidZ(0)
                self.setdxfcolor("Dark Gray")
                rapid = rapid.union(self.rapidXY(bx - radius, by-(thickness-(smallDiameter / 2) / Tan(45))))
                toolpath = toolpath.union(self.cutlineZgcfeed(-(smallDiameter / 2) / Tan(45),10000))
                toolpath = toolpath.union(self.cutlinedxfgc(bx + width + radius, by-(thickness-(smallDiameter / 2) / Tan(45)), -(smallDiameter / 2) / Tan(45)))
                rapid = self.rapidZ(0)
                self.setdxfcolor("Green")
                rapid = rapid.union(self.rapidXY(bx+width, by-thickness/2))
                toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                toolpath = toolpath.union(self.cutlinedxfgc(bx + width -thickness, by-thickness/2, -thickness/2))
                rapid = self.rapidZ(0)
                rapid = rapid.union(self.rapidXY(bx, by-thickness/2))
                toolpath = toolpath.union(self.cutlineZgcfeed(-thickness/2,1000))
                toolpath = toolpath.union(self.cutlinedxfgc(bx + thickness, by-thickness/2, -thickness/2))
        rapid = self.rapidZ(0)
        return toolpath

    def Full_Blind_Finger_Joint(self, bx, by, orientation, side, width, thickness, largeVdiameter, smallDiameter, normalormirror = "Default", squaretool = 102, smallV = 390, largeV = 301):
        Number_of_Pins = int(((width - thickness * 2) / (smallDiameter * 2.2) / 2) + 0.0) * 2 + 1
#         print("Number of Pins: ",Number_of_Pins)
        self.movetosafeZ()
        self.toolchange(squaretool, 17000)
        toolpath = self.Full_Blind_Finger_Joint_square(bx, by, orientation, side, width, thickness, Number_of_Pins, largeVdiameter, smallDiameter)
        self.movetosafeZ()
        self.toolchange(smallV, 17000)
        toolpath = toolpath.union(self.Full_Blind_Finger_Joint_smallV(bx, by, orientation, side, width, thickness, Number_of_Pins, largeVdiameter, smallDiameter))
        self.toolchange(largeV, 17000)
        toolpath = toolpath.union(self.Full_Blind_Finger_Joint_largeV(bx, by, orientation, side, width, thickness, Number_of_Pins, largeVdiameter, smallDiameter))
        return toolpath
```

3.9 (Reading) G-code Files

With all other features in place, it becomes possible to read in a G-code file and then create a 3D preview of how it will cut.

First, a template file will be necessary:

```
#Requires OpenPythonSCAD, so load support for 3D modeling in that
    tool:
from openscad import *

#The gcodepreview library must be loaded, either from github (first
     line below) or from a local library (second line below),
    uncomment one and comment out the other, depending on where one
    wishes to load from
#nimport("https://raw.githubusercontent.com/WillAdams/gcodepreview/
    refs/heads/main/gcodepreview.py")
from gcodepreview import *

#The file to be loaded must be specified:
#gc_file = "filename_of_G-code_file_to_process.gcodefilext"
#
#if using windows the full filepath should be provided with
    backslashes replaced with double backslashes and wrapped in
    quotes since it is provided as a string:
gc_file = "C:\\Users\\willa\\OneDrive\\Desktop\\19mm_1_32_depth.nc"

#Create the gcodepreview object:
gcp = gcodepreview("cut", False, False)

#Process the file
gcp.previewgcodefile(gc_file)
```

previewgcodefile Which simply needs to call the previewgcodefile command:

```
    def previewgcodefile(self, gc_file):
        gc_file = open(gc_file, 'r')
        gcfilecontents = []
        with gc_file as file:
            for line in file:
                command = line
                gcfilecontents.append(line)

        numlinesfound = 0
        for line in gcfilecontents:
#            print(line)
            if line[:10] == "(stockMin:":
                subdivisions = line.split()
                extentleft = float(subdivisions[0][10:-3])
                extentfb = float(subdivisions[1][:-3])
                extentd = float(subdivisions[2][:-3])
                numlinesfound = numlinesfound + 1
            if line[:13] == "(STOCK/BLOCK,":
                subdivisions = line.split()
                sizeX = float(subdivisions[0][13:-1])
                sizeY = float(subdivisions[1][:-1])
                sizeZ = float(subdivisions[4][:-1])
                numlinesfound = numlinesfound + 1
            if line[:3] == "G21":
                units = "mm"
                numlinesfound = numlinesfound + 1
            if numlinesfound >=3:
                break
#            print(numlinesfound)
```

Once the initial parameters are parsed, the stock may be set up:

```
        self.setupcuttingarea(sizeX, sizeY, sizeZ, extentleft,
            extentfb, extentd)

        commands = []
        for line in gcfilecontents:
            Xc = 0
            Yc = 0
            Zc = 0
            Fc = 0
            Xp = 0.0
            Yp = 0.0
            Zp = 0.0
            if line == "G53G0Z-5.000\n":
                 self.movetosafeZ()
            if line[:3] == "M6T":
                tool = int(line[3:])
                self.toolchange(tool)
```

Processing tool changes will require examining lines such as:

```
;TOOL/MILL, Diameter, Corner radius, Height, Taper Angle

;TOOL/CRMILL, Diameter1, Diameter2, Radius, Height, Length

;TOOL/CHAMFER, Diameter, Point Angle, Height
```

which once parsed will be passed to a command which uses them to set the variables necessary to effect the toolchange:

```
if line[:11] == "(TOOL/MILL,"
    subdivisions = line.split()
    diameter = float(subdivisions[1][:-3])
    cornerradius = float(subdivisions[2][:-3])
    height = float(subdivisions[3][:-3])
    taperangle = float(subdivisions[4][:-3])
    self.settoolparameters("mill", diameter, cornerradius, height, taperangle)

if line[:14] == "(TOOL/CHAMFER,"
    subdivisions = line.split()
    tipdiameter = float(subdivisions[1][:-3])
    diameter = float(subdivisions[2][:-3])
    radius = float(subdivisions[3][:-3])
    height = float(subdivisions[4][:-3])
    length = float(subdivisions[4][:-3])
    self.settoolparameters("chamfer", tipdiameter, diameter, radius, height, length)
```

```
            if line[:2] == "G0":
                machinestate = "rapid"
            if line[:2] == "G1":
                machinestate = "cutline"
            if line[:2] == "G0" or line[:2] == "G1" or line[:1] == "X" or line[:1] == "Y" or line[:1] == "Z":
                if "F" in line:
                    Fplus = line.split("F")
                    Fc = 1
                    fr = float(Fplus[1])
                    line = Fplus[0]
                if "Z" in line:
                    Zplus = line.split("Z")
                    Zc = 1
                    Zp = float(Zplus[1])
                    line = Zplus[0]
                if "Y" in line:
                    Yplus = line.split("Y")
                    Yc = 1
                    Yp = float(Yplus[1])
                    line = Yplus[0]
                if "X" in line:
                    Xplus = line.split("X")
                    Xc = 1
                    Xp = float(Xplus[1])
                if Zc == 1:
                    if Yc == 1:
                        if Xc == 1:
                            if machinestate == "rapid":
                                command = "rapidXYZ(" + str(Xp) + ",␣" + str(Yp) + ",␣" + str(Zp) + ")"
                                self.rapidXYZ(Xp, Yp, Zp)
                            else:
                                command = "cutlineXYZ(" + str(Xp) + ",␣" + str(Yp) + ",␣" + str(Zp) + ")"
                                self.cutlineXYZ(Xp, Yp, Zp)
                        else:
                            if machinestate == "rapid":
                                command = "rapidYZ(" + str(Yp) + ",␣" + str(Zp) + ")"
                                self.rapidYZ(Yp, Zp)
                            else:
                                command = "cutlineYZ(" + str(Yp) + ",␣" + str(Zp) + ")"
                                self.cutlineYZ(Yp, Zp)
```

```
                    else:
                        if Xc == 1:
                            if machinestate == "rapid":
                                command = "rapidXZ(" + str(Xp) + ", " + str(Zp) + ")"
                                self.rapidXZ(Xp, Zp)
                            else:
                                command = "cutlineXZ(" + str(Xp) + ", " + str(Zp) + ")"
                                self.cutlineXZ(Xp, Zp)
                        else:
                            if machinestate == "rapid":
                                command = "rapidZ(" + str(Zp) + ")"
                                self.rapidZ(Zp)
                            else:
                                command = "cutlineZ(" + str(Zp) + ")"
                                self.cutlineZ(Zp)
                else:
                    if Yc == 1:
                        if Xc == 1:
                            if machinestate == "rapid":
                                command = "rapidXY(" + str(Xp) + ", " + str(Yp) + ")"
                                self.rapidXY(Xp, Yp)
                            else:
                                command = "cutlineXY(" + str(Xp) + ", " + str(Yp) + ")"
                                self.cutlineXY(Xp, Yp)
                        else:
                            if machinestate == "rapid":
                                command = "rapidY(" + str(Yp) + ")"
                                self.rapidY(Yp)
                            else:
                                command = "cutlineY(" + str(Yp) + ")"
                                self.cutlineY(Yp)
                    else:
                        if Xc == 1:
                            if machinestate == "rapid":
                                command = "rapidX(" + str(Xp) + ")"
                                self.rapidX(Xp)
                            else:
                                command = "cutlineX(" + str(Xp) + ")"
                                self.cutlineX(Xp)
                commands.append(command)
#                print(line)
#                print(command)
#                print(machinestate, Xc, Yc, Zc)
#                print(Xp, Yp, Zp)
#                print("/n")

#        for command in commands:
#            print(command)

#        show(self.stockandtoolpaths())
        self.stockandtoolpaths()
```

4 Notes

4.1 Other Resources

4.1.1 Coding Style

A notable influence on the coding style in this project is John Ousterhout's *A Philosophy of Software Design*[SoftwareDesign]. Complexity is managed by the overall design and structure of the code, structuring it so that each component may be worked with on an individual basis, hiding the maximum information, and exposing the maximum functionality, with names selected so as to express their functionality/usage.

Red Flags to avoid include:

- Shallow Module
- Information Leakage
- Temporal Decomposition

- Overexposure
- Pass-Through Method
- Repetition
- Special-General Mixture
- Conjoined Methods
- Comment Repeats Code
- Implementation Documentation Contaminates Interface
- Vague Name
- Hard to Pick Name
- Hard to Describe
- Nonobvious Code

4.1.2 Coding References

https://thewhitetulip.gitbook.io/py/06-file-handling

4.1.3 Documentation Style

https://diataxis.fr/ (originally developed at: https://docs.divio.com/documentation-system/) — divides documentation along two axes:

- Action (Practical) vs. Cognition (Theoretical)
- Acquisition (Studying) vs. Application (Working)

resulting in a matrix of:



where:

1. readme.md — (Overview) Explanation (understanding-oriented)
2. Templates — Tutorials (learning-oriented)
3. gcodepreview — How-to Guides (problem-oriented)
4. Index — Reference (information-oriented)

Straddling the boundary between coding and documenation are `docstrings` and general coding style with the latter discussed at: https://peps.python.org/pep-0008/

Holidays

Holidays are from https://nationaltoday.com/

DXFs

http://www.paulbourke.net/dataformats/dxf/
https://paulbourke.net/dataformats/dxf/min3d.html

4.2 Future

4.2.1 Images

Would it be helpful to re-create code algorithms/sections using OpenSCAD Graph Editor so as to represent/illustrate the program?

4.2.2 Bézier curves in 2 dimensions

Take a Bézier curve definition and approximate it as arcs and write them into a DXF?
https://pomax.github.io/bezierinfo/
https://ciechanow.ski/curves-and-surfaces/
https://www.youtube.com/watch?v=aVwxzDHniEw
c.f., https://linuxcnc.org/docs/html/gcode/g-code.html#gcode:g5

4.2.3 Bézier curves in 3 dimensions

One question is how many Bézier curves would it be necessary to have to define a surface in 3 dimensions. Attributes for this which are desirable/necessary:

- concise — a given Bézier curve should be represented by just the point coordinates, so two on-curve points, two off-curve points, each with a pair of coordinates
- For a given shape/region it will need to be possible to have a matching definition exactly match up with it so that one could piece together a larger more complex shape from smaller/simpler regions
- similarly it will be necessary for it to be possible to sub-divide a defined region — for example it should be possible if one had 4 adjacent regions, then the four quadrants at the intersection of the four regions could be used to construct a new region — is it possible to derive a new Bézier curve from half of two other curves?

For the three planes:

- XY
- XZ
- ZY

it should be possible to have three Bézier curves (left-most/right-most or front-back or top/bottom for two, and a mid-line for the third), so a region which can be so represented would be definable by:

```
3 planes * 3 Béziers * (2 on-curve + 2 off-curve points) == 36 coordinate pairs
```

which is a marked contrast to representations such as:
https://github.com/DavidPhillipOster/Teapot
and regions which could not be so represented could be sub-divided until the representation is workable.

Or, it may be that fewer (only two?) curves are needed:



https://pages.mtu.edu/~shene/COURSES/cs3621/NOTES/notes.html

c.f., https://github.com/BelfrySCAD/BOSL2/wiki/nurbs.scad and https://old.reddit.com/r/OpenPythonSCAD/comments/1gjcz4z/pythonscad_will_get_a_new_spline_function/

4.2.4 Mathematics

https://elementsofprogramming.com/

References

[ConstGeom] Walmsley, Brian. *Construction Geometry*. 2d ed., Centennial College Press, 1981.

[MkCalc] Horvath, Joan, and Rich Cameron. *Make: Calculus: Build models to learn, visualize, and explore*. First edition., Make: Community LLC, 2022.

[MkGeom] Horvath, Joan, and Rich Cameron. *Make: Geometry: Learn by 3D Printing, Coding and Exploring*. First edition., Make: Community LLC, 2021.

[MkTrig] Horvath, Joan, and Rich Cameron. *Make: Trigonometry: Build your way from triangles to analytic geometry*. First edition., Make: Community LLC, 2023.

[PractShopMath] Begnal, Tom. *Practical Shop Math: Simple Solutions to Workshop Fractions, Formulas + Geometric Shapes*. Updated edition, Spring House Press, 2018.

[RS274] Thomas R. Kramer, Frederick M. Proctor, Elena R. Messina. https://tsapps.nist.gov/publication/get_pdf.cfm?pub_id=823374 https://www.nist.gov/publications/nist-rs274ngc-interpreter-version-3

[SoftwareDesign] Ousterhout, John K. *A Philosophy of Software Design*. First Edition., Yaknyam Press, Palo Alto, Ca., 2018

Command Glossary

. 25

setupstock setupstock(200, 100, 8.35, "Top", "Lower-left", 8.35). 23

Index

Routines

Variables