

# Homework 1

## FE 621 – Methods in Computational Finance

Justin Zachery

February 2026

### Contents

<b>1</b>	<b>Section 1: Data Gathering Component (Questions 1–4)</b>	<b>2</b>
1.1	Question 1: Data Download Program . . . . .	2
1.2	Question 2: Downloaded Assets and Data Sets . . . . .	2
1.3	Question 3: Description of Assets . . . . .	2
1.4	Question 4: Recorded Market Information . . . . .	3
<b>2</b>	<b>Section 2: Analysis of the Data (Questions 5–12)</b>	<b>4</b>
2.1	Question 5: Black–Scholes Pricing Model . . . . .	4
2.2	Question 6: Implied Volatility via Bisection Method . . . . .	4
2.3	Question 7: Newton/Secant Method . . . . .	4
2.4	Question 8: Implied Volatility Table and Discussion . . . . .	4
2.5	Question 9: Put–Call Parity . . . . .	5
2.6	Question 10: Volatility Smile Plots . . . . .	6
2.7	Question 11: Greeks . . . . .	10
2.8	Question 12: Pricing Using DATA2 . . . . .	10
<b>3</b>	<b>Section 3: Numerical Integration – AMM Fee Revenue (Questions 13–15)</b>	<b>11</b>
3.1	Question 13: Derive Swap Amounts . . . . .	11
3.2	Question 14: Expected Fee Revenue (Trapezoidal Rule) . . . . .	14
3.3	Question 15: Optimal Fee Rate . . . . .	14
<b>A</b>	<b>Appendix: R Code Implementation</b>	<b>17</b>
A.1	Part 1: Data Gathering (Questions 1–4) . . . . .	17
A.2	Part 2: Option Pricing and Analysis (Questions 5–12) . . . . .	23
A.3	Part 3: Numerical Integration and AMM Fee Analysis (Questions 13–15) . . . . .	45

# 1 Section 1: Data Gathering Component (Questions 1–4)

## 1.1 Question 1: Data Download Program

I utilized R programming language for this assignment and pulled data from Yahoo Finance with the library quantmod in R. Please see Appendix Section 1 to see the code for this, as well as the BONUS part, which is downloading multiple assets and saving them in a single CSV file.

## 1.2 Question 2: Downloaded Assets and Data Sets

TSLA, SPY, and ^VIX data were downloaded for two consecutive trading days. The first day's data set is referred to as DATA1, which was January 29th, 2026, and the second day's data set is referred to as DATA2, which is January 30th, 2026. The code implementation is provided in Appendix Section 1.

The reason there are so many maturities is that they allow for more interaction with the market, which, in turn, is beneficial for the overall market. Having more interaction with the market allows for more accurate volatility, making it easier to manage risk.

## 1.3 Question 3: Description of Assets

This section explains TSLA, SPY (ETF), and ^VIX and their respective market purposes. There is no coding component for this.

**TSLA:** Tesla, Inc. common stock traded on the U.S. equity market. It represents ownership in Tesla and is used as the underlying asset for its listed equity options.

**SPY:** The SPDR S&P 500 ETF Trust. This exchange-traded fund tracks the performance of the S&P 500 Index, which represents approximately 500 large-cap U.S. companies. It is commonly used as a proxy for overall U.S. equity market performance.

**^VIX:** The CBOE Volatility Index (VIX). It measures the market's expectation of 30-day forward-looking volatility implied by S&P 500 index options. It is commonly interpreted as a measure of market uncertainty or risk sentiment.

The variance used in the VIX calculation is given by:

$$\sigma^2 = \frac{2}{T} \sum_i \frac{\Delta K_i}{K_i^2} e^{RT} Q(K_i) - \frac{1}{T} \left( \frac{F}{K_0} - 1 \right)^2 \quad (1)$$

The VIX index level is then computed as:

$$\text{VIX} = 100 \times \sqrt{\sigma^2} \quad (2)$$

where  $\sigma^2$  represents the 30-day forward variance,  $T$  is time to expiration (in years),  $F$  is the forward index level,  $K_i$  are the strike prices,  $K_0$  is the first strike below the forward level,  $R$  is the risk-free interest rate,  $Q(K_i)$  is the midpoint option quote, and  $\Delta K_i$  is half the difference between adjacent strike prices.

To provide information on option expiration, I used the dates February 20th, March 20th, and April 17th for TSLA and SPY. For VIX, I used the expirations on February 18th, March 18th, and April 15th. For these 3 entities I used the year 2026.

#### 1.4 Question 4: Recorded Market Information

This section discusses the recorded underlying prices, short-term rate selection and conversion, and time-to-maturity calculations. The code implementation is provided in the Appendix Section 1.

Table 1: Recorded Underlying Prices at Time of Data Download

Asset	Price ( $S_0$ )
TSLA	415.6069
SPY	684.4450
^VIX	19.56

The short-term risk-free interest rate was obtained from the website provided in the assignment handout. The reported annualized rate was  $r = 0.0364$  (3.64%) for both January 29 and January 30.

The time to maturity was calculated as:

$$T = \frac{\text{Expiration Date} - \text{Valuation Date}}{365} \quad (3)$$

where  $T$  represents time to maturity in years.

Table 2: Time to Maturity (in Years)

Maturity	$T$ (Years)
February	0.0411
March	0.1178
April	0.1945

## 2 Section 2: Analysis of the Data (Questions 5–12)

### 2.1 Question 5: Black–Scholes Pricing Model

The code implementation is provided in the Appendix Section 2.

### 2.2 Question 6: Implied Volatility via Bisection Method

The code implementation is provided in the Appendix Section 2.

Table 3: Implied Volatility Results (Bisection Method)

Symbol	$S_0$	$\tau$	$K_{ATM}$	IV Call	IV Put	Avg IV (ATM)	Avg IV (Band)	Exp
"TSLA"	415.6069	0.0602739726027397	415	0.253514330182448	0.252685565015502	0.253099947598975	0.254073950164078	"Feb"
"TSLA"	415.6069	0.136986301369863	415	0.373682485422418	0.371977420393825	0.372829952908121	0.373069365626188	"Mar"
"TSLA"	415.6069	0.213698630136986	415	0.412212708238527	0.40921390602738	0.410713307132954	0.409591169592913	"Apr"
"SPY"	684.445	0.0602739726027397	684	0.102693449415997	0.100874502285756	0.101783975850876	0.104900513138873	"Feb"
"SPY"	684.445	0.136986301369863	684	0.140157214965206	0.147016534740545	0.143586874852875	0.142268640382177	"Mar"
"SPY"	684.445	0.213698630136986	684	0.143564681440361	0.155954882736295	0.149759782088328	0.148956898079516	"Apr"

From looking at the table (Avg IV ATM) represents the average implied volatility and the (Avg IV Band) is volatilities that correspond to the moneyness band of 0.95 - 1.05.

### 2.3 Question 7: Newton/Secant Method

The code implementation is provided in the Appendix Section 2.

Table 4: Implied Volatility Results (Newton Method)

Symbol	$S_0$	$\tau$	$K_{ATM}$	IV Call	IV Put	Avg IV (ATM)	Avg IV (Band)	Exp
"TSLA"	415.6069	0.0602739726027397	415	0.253514328811013	0.252685568097168	0.253099948454091	0.254073952397063	"Feb"
"TSLA"	415.6069	0.136986301369863	415	0.373682486022191	0.371977423445579	0.372829954733885	0.373069365041715	"Mar"
"TSLA"	415.6069	0.213698630136986	415	0.412212717707192	0.409213909899751	0.410713313803472	0.409591172695303	"Apr"
"SPY"	684.445	0.0602739726027397	684	0.102693453311981	0.100874501431872	0.101783977371926	0.104900519862958	"Feb"
"SPY"	684.445	0.136986301369863	684	0.140157221859893	0.147016529009678	0.143586875434786	0.142268640863372	"Mar"
"SPY"	684.445	0.213698630136986	684	0.143564686691922	0.155954881094711	0.149759783893317	0.148956898963527	"Apr"

Table 5: Convergence Time Comparison (Milliseconds)

Method	Min	LQ	Mean	Median	UQ	Max	Runs
"Bisection"	0.14454	0.1473915	0.15572129	0.1494105	0.151711	0.244599	100
"Newton"	0.030241	0.0317955	0.03730057	0.033184	0.0364805	0.081495	100

From looking at the table, it is apparent that Newton's method has a more efficient convergence time than bisection. This makes sense because Newton's method is a quadratic convergence, while bisection is a linear convergence.

### 2.4 Question 8: Implied Volatility Table and Discussion

The code implementation is provided in the Appendix Section 2.

I will be using the implied volatilities calculated from Q6 with the bisection method.

Table 6: Implied Volatility Summary by Maturity (Q8)

Symbol	Exp	$\tau$	$K_{\text{ATM}}$	IV Call	IV Put	Avg IV (ATM)	Avg IV (Band)
"SPY"	"Apr"	0.213699	684	0.143565	0.155955	0.14976	0.148957
"SPY"	"Feb"	0.060274	684	0.102693	0.100875	0.101784	0.104901
"SPY"	"Mar"	0.136986	684	0.140157	0.147017	0.143587	0.142269
"TSLA"	"Apr"	0.213699	415	0.412213	0.409214	0.410713	0.409591
"TSLA"	"Feb"	0.060274	415	0.253514	0.252686	0.2531	0.254074
"TSLA"	"Mar"	0.136986	415	0.373682	0.371977	0.37283	0.373069

From looking at the implied volatilities of SPY and TSLA it is apparent that TSLA has a higher implied volatility than SPY this would make sense since SPY represents a group of stocks, while TSLA is a singular stock.

The current value of VIX is 21.09. Which is slightly higher than the IV calculated for SPY. This is because the VIX represents a 30-day period, so this could indicate that volatility will rise in the coming month for SPY. From the table, looking at volatility as maturity increases, it shows that as you increase the maturity time, the volatility increases. This is because there is more uncertainty farther out in the market.

When looking at options that are out of the money and in the money, it is apparent that as an option becomes more in the money, the volatility decreases.

## 2.5 Question 9: Put–Call Parity

The code implementation is provided in the Appendix Section 2.

When looking at the option prices these are for stocks that are At The Money (ATM), so there are some options that fall above this with the bid and ask and some fall below this for the bid and ask. The farther the stock is above this price, the more Out of The Money (OTM) the option is, and if it is below this price, then it is considered In The Money (ITM).

Table 7: ATM Option Prices Used for Put–Call Parity (Q9)

Symbol	Type	Price	Month
"TSLA"	"Call"	11.0414	"Feb"
"TSLA"	"Put"	9.5586	"Feb"
"TSLA"	"Call"	24.0961	"Mar"
"TSLA"	"Put"	21.5289	"Mar"
"TSLA"	"Call"	33.1225	"Apr"
"TSLA"	"Put"	29.5275	"Apr"
"SPY"	"Call"	7.769	"Feb"
"SPY"	"Put"	5.946	"Feb"
"SPY"	"Call"	16.8171	"Mar"
"SPY"	"Put"	12.2829	"Mar"
"SPY"	"Call"	22.6049	"Apr"
"SPY"	"Put"	15.3151	"Apr"

## 2.6 Question 10: Volatility Smile Plots

The code implementation is provided in the Appendix Section 2. As well as the BONUS part which is the 3D plots.

From looking at the plots below as you increase the maturity, the curve gets less sharp or flatter. Meaning the curve is less pronounced. This is because it is looking at a window that is larger so short term jumps in the market have less of an affect.

### TSLA Implied Volatility vs Strike (Closest Maturity: Feb )




Figure 1: TSLA Implied Volatility Plot 1

### TSLA Implied Volatility Smile (3 Maturities)




Figure 2: TSLA Implied Volatility Plot 2

### TSLA Implied Volatility Surface: $IV = f(\text{Tau}, K)$




Figure 3: TSLA Implied Volatility Plot 3

### SPY Implied Volatility vs Strike (Closest Maturity: Feb )




Figure 4: SPY Implied Volatility Plot 1






Figure 5: SPY Implied Volatility Plot 2




Figure 6: SPY Implied Volatility Plot 3

## 2.7 Question 11: Greeks

The code implementation is provided in the Appendix Section 2.

Delta represents the first order derivative of the option, gamma is the 2nd order derivative, and vega is the measure of how much an option's price changes depending on 1 percent volatility change.

Most Values are the same for both methods, but there is a difference in the delta and gamma values. The Black-Scholes method seems to overpredict the values, while the Finite Difference method seems to underpredict the values. They both got the same Vega values.

Table 8: Greeks Comparison: Black-Scholes vs Finite Difference (Q11)

Symbol	Exp	Method	$S_0$	$K$	$\tau$	$\sigma$	$\Delta$	$\Gamma$	Vega
"SPY"	"Apr"	"BS"	684.445	684	0.213699	0.143565	0.563634	0.008671	124.617
"SPY"	"Apr"	"FD"	684.445	684	0.213699	0.143565	0.563298	0.008655	124.617
"SPY"	"Feb"	"BS"	684.445	684	0.060274	0.102693	0.549906	0.022938	66.511631
"SPY"	"Feb"	"FD"	684.445	684	0.060274	0.102693	0.548384	0.022649	66.511631
"SPY"	"Mar"	"BS"	684.445	684	0.136986	0.140157	0.553535	0.011135	100.150534
"SPY"	"Mar"	"FD"	684.445	684	0.136986	0.140157	0.553081	0.011102	100.150534
"TSLA"	"Apr"	"BS"	415.607	415	0.213699	0.412213	0.557158	0.004986	75.858709
"TSLA"	"Apr"	"FD"	415.607	415	0.213699	0.412213	0.557097	0.004985	75.858709
"TSLA"	"Feb"	"BS"	415.607	415	0.060274	0.253514	0.535797	0.015361	40.541957
"TSLA"	"Feb"	"FD"	415.607	415	0.060274	0.253514	0.535538	0.015329	40.541957
"TSLA"	"Mar"	"BS"	415.607	415	0.136986	0.373682	0.546083	0.006894	60.956629
"TSLA"	"Mar"	"FD"	415.607	415	0.136986	0.373682	0.545996	0.006891	60.956629

## 2.8 Question 12: Pricing Using DATA2

The code implementation is provided in the Appendix Section 2.

Table 9: Black-Scholes ATM Prices Using Estimated Volatility (Q12)

Symbol	Exp	Type	$S_0$	$K$	$\tau$	$\sigma$	BS Price
"TSLA"	"Feb"	"Call"	430.410003662109	415	0.057534	0.253514	20.372881
"TSLA"	"Feb"	"Put"	430.410003662109	415	0.057534	0.252686	4.067319
"TSLA"	"Mar"	"Call"	430.410003662109	415	0.134247	0.373682	32.771813
"TSLA"	"Mar"	"Put"	430.410003662109	415	0.134247	0.371977	15.238689
"TSLA"	"Apr"	"Call"	430.410003662109	415	0.210959	0.412213	41.909107
"TSLA"	"Apr"	"Put"	430.410003662109	415	0.210959	0.409214	23.100466
"SPY"	"Feb"	"Call"	691.969970703125	684	0.057534	0.102693	12.469328
"SPY"	"Feb"	"Put"	691.969970703125	684	0.057534	0.100875	2.966154
"SPY"	"Mar"	"Call"	691.969970703125	684	0.134247	0.140157	20.427985
"SPY"	"Mar"	"Put"	691.969970703125	684	0.134247	0.147017	9.778697
"SPY"	"Apr"	"Call"	691.969970703125	684	0.210959	0.143565	25.390726
"SPY"	"Apr"	"Put"	691.969970703125	684	0.210959	0.155955	13.683617

### 3 Section 3: Numerical Integration – AMM Fee Revenue (Questions 13–15)

#### 3.1 Question 13: Derive Swap Amounts

Provide the derivation of swap amounts  $x$  and  $y$  under Case 1 and Case 2.

**Part 3(a): Liquidity changes under a fee  $\gamma$**

**Case 1:** ( $S_{t+1} > P_t/(1 - \gamma)$ ). **Given:**

$$x_{t+1} = x_t - \text{Delta}_x \quad (4)$$

$$y_{t+1} = y_t + (1 - \gamma)\text{Delta}_y \quad (5)$$

$$\text{Delta}_x > 0, \quad \text{Delta}_y > 0. \quad (6)$$

**Boundary Conditions**

$$\frac{P_{t+1}}{1 - \gamma} = \frac{y_{t+1}}{x_{t+1}} \cdot \frac{1}{1 - \gamma} = S_{t+1} \quad (7)$$

Multiplying both sides by  $(1 - \gamma)$ ,

$$P_{t+1} = \frac{y_{t+1}}{x_{t+1}} = S_{t+1}(1 - \gamma) \quad (8)$$

$$\frac{y_{t+1}}{x_{t+1}} = S_{t+1}(1 - \gamma) \quad (9)$$

$$y_{t+1} = S_{t+1}(1 - \gamma) x_{t+1}. \quad (10)$$

**Given:**

$$x_{t+1}y_{t+1} = k, \quad y_{t+1} = \frac{k}{x_{t+1}} \quad (11)$$

**Solving for  $x_{t+1}$**

$$k = S_{t+1}(1 - \gamma) x_{t+1} \cdot x_{t+1} \quad (12)$$

$$= S_{t+1}(1 - \gamma) x_{t+1}^2 \quad (13)$$

$$\frac{k}{S_{t+1}(1 - \gamma)} = x_{t+1}^2 \quad (14)$$

$$x_{t+1} = \sqrt{\frac{k}{S_{t+1}(1 - \gamma)}} \quad (15)$$

**Solving for  $y_{t+1}$**

$$y_{t+1} = S_{t+1}(1 - \gamma) \frac{k}{x_{t+1}} \quad (16)$$

$$y_{t+1}^2 = k S_{t+1}(1 - \gamma) \quad (17)$$

$$y_{t+1} = \sqrt{k S_{t+1}(1 - \gamma)} \quad (18)$$

**Given:**

$$x_{t+1} = x_t - Delta_x \quad (19)$$

$$Delta_x(S) = x_t - \sqrt{\frac{k}{S_{t+1}(1 - \gamma)}}$$

**Given:**

$$y_{t+1} = y_t + (1 - \gamma)Delta_y \quad (20)$$

$$Delta_y(S) = \frac{\sqrt{k S_{t+1}(1 - \gamma)} - y_t}{1 - \gamma}$$

**Case 2:** ( $S_{t+1} < P_t(1 - \gamma)$ ). **Given:**

$$x_{t+1} = x_t + (1 - \gamma)Delta_x \quad (21)$$

$$y_{t+1} = y_t - Delta_y \quad (22)$$

$$Delta_x > 0, \quad Delta_y > 0. \quad (23)$$

**Boundary Condition**

$$P_{t+1}(1 - \gamma) = \frac{y_{t+1}}{x_{t+1}}(1 - \gamma) = S_{t+1} \quad (24)$$

Dividing both sides by  $(1 - \gamma)$ ,

$$P_{t+1} = \frac{y_{t+1}}{x_{t+1}} = \frac{S_{t+1}}{1 - \gamma} \quad (25)$$

$$\frac{y_{t+1}}{x_{t+1}} = \frac{S_{t+1}}{1 - \gamma} \quad (26)$$

$$y_{t+1} = \frac{S_{t+1}}{1 - \gamma} x_{t+1} \quad (27)$$

**Given:**

$$x_{t+1}y_{t+1} = k, \quad y_{t+1} = \frac{k}{x_{t+1}} \quad (28)$$

$$k = \frac{S_{t+1}}{1 - \gamma} x_{t+1}^2 \quad (29)$$

$$x_{t+1} = \sqrt{\frac{k(1 - \gamma)}{S_{t+1}}} \quad (30)$$

**Given:**

$$x_{t+1} = x_t + (1 - \gamma)Delta_x \quad (31)$$

$$x_{t+1} - x_t = (1 - \gamma)Delta_x \quad (32)$$

$$Delta_x = \frac{x_{t+1} - x_t}{1 - \gamma} \quad (33)$$

$$Delta_x(S) = \frac{\sqrt{\frac{k(1-\gamma)}{S_{t+1}}} - x_t}{1 - \gamma}$$

**Given:**

$$y_{t+1} = y_t - Delta_y \quad (34)$$

$$y_t - y_{t+1} = Delta_y \quad (35)$$

$$Delta_y(S) = y_t - \sqrt{\frac{kS_{t+1}}{1 - \gamma}}$$

### 3.2 Question 14: Expected Fee Revenue (Trapezoidal Rule)

The code implementation is provided in the Appendix Section 3.

The Expected Revenue Value is 0.0085176...

### 3.3 Question 15: Optimal Fee Rate

The code implementation is provided in the Appendix Section 3.

Table 10: Expected Fee Revenue  $E[R]$  for Different  $(\sigma, \gamma)$ 

$\sigma$	$\gamma$	$E[R]$
0.2	0.001	0.00368521805400986
0.6	0.001	0.0119233746160056
1	0.001	0.0200607211429745
0.2	0.003	0.00852203387382362
0.6	0.003	0.0329832890066009
1	0.003	0.0573837575055382
0.2	0.01	0.00943035729877614
0.6	0.01	0.0810823373662479
1	0.01	0.16068988312124

Above is a table with values requested in (c), as well as the graph below of sigma vs gamma\*(sigma). The plot suggests that for low volatility, a low fee rate is optimal, but once volatility approaches approximately 0.18 the fee rate needs to increase.

Table 11: Optimal Fee Rate  $\gamma^*(\sigma)$  and Maximum Expected Revenue

$\sigma$	$\gamma^*(\sigma)$	$\max E[R]$
0.2	0.01	0.00943035729877614
0.6	0.01	0.0810823373662479
1	0.01	0.16068988312124




Figure 7: Optimal Fee Rate  $\gamma^*(\sigma)$  as a Function of Volatility



## A Appendix: R Code Implementation

This appendix contains the complete R code used to complete all parts of Homework 1.

### A.1 Part 1: Data Gathering (Questions1–4)

Listing 1: Part 1: Data Gathering

```
1 # Part 1
2 #####
3 # Q1) Write a function to connect to sources and download data from one
4 # of the
5 # following sources: GOOGLE finance, Yahoo Finance, or Bloomberg
6 # I will be using Yahoo Finance
7
8 # Run the next lines if packages is are not installed
9 # install.packages("quantmod")
10 # install.packages("dplyr")
11 # install.packages("tidyr")
12
13 library(quantmod)
14 library(dplyr)
15 library(tidyr)
16
17 # Function for getting data from Yahoo Finance Equities
18 get_equity_data <- function(symbol, start_date, end_date) {
19   data <- getSymbols(Symbols = symbol,
20                     src = "yahoo",
21                     from = start_date,
22                     to = end_date,
23                     auto.assign = FALSE)
24
25   # Convert time series object into a tabular data frame with explicit
26   # date column
27   data_frame <- data.frame(Date = as.Date(index(data)),
28                             coredata(data),
29                             row.names = NULL,
30                             check.names = FALSE)
31
32   # Clean column names to remove Symbol identifier
33   names(data_frame) <- gsub("^.*\\.\\.", "", names(data_frame))
34
35   # Remove rows with duplicate dates - only keep first occurrence
36   data_frame <- data_frame[!duplicated(data_frame$Date), ]
```

```

35
36 # Sort by date
37 data_frame <- data_frame[order(data_frame$Date), ]
38
39 return(data_frame)
40 }
41
42
43 # Function to download multiple equity assets and combine into single
    frame
44 download_equity_data <- function(symbols, start_date, end_date) {
45   sym_data <- list() # Initialize
46
47   # Get data for provided symbols
48   for (i in seq_along(symbols)) {
49     temp <- get_equity_data(symbols[i], start_date, end_date)
50
51     # Add Ticker column
52     temp$Ticker <- symbols[i]
53
54     sym_data[[i]] <- temp
55   }
56
57   # Combine all equity data into single frame and sort by Date and Ticker
58   all_data <- arrange(bind_rows(sym_data), Date, Ticker)
59
60   return(all_data)
61 }
62
63 # Function for getting option chain data
64 get_option_data <- function(symbol, exp_date) {
65   chain <- getOptionChain(Symbols = symbol, Exp = exp_date)
66
67   # Check if option data exists
68   if (is.null(chain$calls) && is.null(chain$puts)) {
69     message("No options exist for ", symbol, " at expiration date",
70             exp_date)
71     return(data.frame())
72   }
73
74   # Separate data into calls and puts
75   calls <- chain$calls
76   puts <- chain$puts

```

```

77 # Convert NULL to empty data frames for merging
78 if (is.null(calls))
79   calls <- data.frame()
80 if (is.null(puts))
81   puts <- data.frame()
82
83 # Add label, expiration date, and ticker symbol to calls
84 if (nrow(calls) > 0) {
85   calls$Type <- "Call"
86   calls$Expiration <- exp_date
87   calls$Ticker <- symbol
88 }
89
90 # Add label, expiration date, and ticker symbol to puts
91 if (nrow(puts) > 0) {
92   puts$Type <- "Put"
93   puts$Expiration <- exp_date
94   puts$Ticker <- symbol
95 }
96
97 # Combine calls and puts into single data frame
98 data_frame <- rbind(calls, puts)
99 rownames(data_frame) <- NULL
100
101 # Ensure merge produced a valid row
102 if (nrow(data_frame) == 0)
103   return(data.frame())
104
105 # Clean column names to remove Symbol identifier
106 names(data_frame) <- gsub("^.*\\.", "", names(data_frame))
107
108 # Remove duplicate options
109 data_frame <- data_frame[!duplicated(data_frame), ]
110
111 # Sort data by expiration date
112 data_frame <- data_frame[order(data_frame$Expiration), ]
113
114 return(data_frame)
115 }
116
117
118 # Function to download multiple assets' option-chain data and combine
119   into single frame
119 download_option_data <- function(symbol_expirations) {

```

```

120     opt_data <- list() # Initialize
121     idx <- 1
122
123     for (symbol in names(symbol_expirations)) {
124         for (expires in symbol_expirations[[symbol]]) {
125             temp <- get_option_data(symbol, expires)
126
127             # Ensure symbol and expiration date produced data
128             if (nrow(temp) > 0) {
129                 opt_data[[idx]] <- temp
130                 idx <- idx + 1 # Increment index for next data
131             }
132         }
133     }
134
135     # Ensure option data was collected
136     if (length(opt_data) == 0)
137         return(data.frame())
138
139     # Combine option data and sort based on Ticker, Expiration, Type,
140     # Strike
141     all_opts <- arrange(bind_rows(opt_data), Ticker, Expiration, Type,
142                          Strike)
143
144     return(all_opts)
145 }
146
147 # This is BONUS for Q1
148 # Download multiple assets, combines them with the associated time
149 # column, and
150 # save the data into a CSV file.
151
152 symbols <- c("TSLA", "SPY", "^VIX")
153
154 symbol_expirations <- list(
155     "TSLA" = c("2026-02-20", "2026-03-20", "2026-04-17"),
156     "SPY" = c("2026-02-20", "2026-03-20", "2026-04-17"),
157     "^VIX" = c("2026-02-18", "2026-03-18", "2026-04-15")
158 )
159
160 EQ_data <- download_equity_data(symbols, "2026-01-29", "2026-01-31")
161 Option_data <- download_option_data(symbol_expirations)
162
163 # Create output data folder if it does not exist

```

```

161 data_folder = "./data"
162 if (!dir.exists(data_folder))
163   dir.create(data_folder)
164
165 # Save equity and option data to CSV files
166 write.csv(EQ_data, file.path(data_folder, "EQ_data.csv"), row.names =
  FALSE)
167 write.csv(Option_data, file.path(data_folder, "Option_data.csv"),
  row.names = FALSE)
168
169 #####
170 # Q2) Using the function from part 1, pull data for TSLA, SPY, ^VIX
  splitting
171 # data into data1 and data2 data sets
172
173 TSLA_data1_EQ <- EQ_data[EQ_data$Ticker == "TSLA" & EQ_data$Date ==
  "2026-01-29", ]
174 TSLA_data2_EQ <- EQ_data[EQ_data$Ticker == "TSLA" & EQ_data$Date ==
  "2026-01-30", ]
175
176 TSLA_option_Feb <- Option_data[Option_data$Ticker == "TSLA" &
  Option_data$Expiration == "2026-02-20", ]
177 TSLA_option_Mar <- Option_data[Option_data$Ticker == "TSLA" &
  Option_data$Expiration == "2026-03-20", ]
178 TSLA_option_Apr <- Option_data[Option_data$Ticker == "TSLA" &
  Option_data$Expiration == "2026-04-17", ]
179
180 SPY_data1_EQ <- EQ_data[EQ_data$Ticker == "SPY" & EQ_data$Date ==
  "2026-01-29", ]
181 SPY_data2_EQ <- EQ_data[EQ_data$Ticker == "SPY" & EQ_data$Date ==
  "2026-01-30", ]
182
183 SPY_option_Feb <- Option_data[Option_data$Ticker == "SPY" &
  Option_data$Expiration == "2026-02-20", ]
184 SPY_option_Mar <- Option_data[Option_data$Ticker == "SPY" &
  Option_data$Expiration == "2026-03-20", ]
185 SPY_option_Apr <- Option_data[Option_data$Ticker == "SPY" &
  Option_data$Expiration == "2026-04-17", ]
186
187 VIX_data1_EQ <- EQ_data[EQ_data$Ticker == "^VIX" & EQ_data$Date ==
  "2026-01-29", ]
188 VIX_data2_EQ <- EQ_data[EQ_data$Ticker == "^VIX" & EQ_data$Date ==
  "2026-01-30", ]
189

```

```

190 VIX_option_Feb <- Option_data[Option_data$Ticker == "^VIX" &
    Option_data$Expiration == "2026-02-18", ]
191 VIX_option_Mar <- Option_data[Option_data$Ticker == "^VIX" &
    Option_data$Expiration == "2026-03-18", ]
192 VIX_option_Apr <- Option_data[Option_data$Ticker == "^VIX" &
    Option_data$Expiration == "2026-04-15", ]
193
194 #####
195 # Q4) Record underlying equity, ETF, or index price at the exact moment
    when data
196 # is downloaded and Time to Maturity
197
198 # Define function to compute underlying ETF or index price at download
199 get_underlying_price <- function(symbol) {
200     download_price <- as.numeric(getQuote(symbol)$Last)
201     return(download_price)
202 }
203
204 S0_TSLA <- get_underlying_price("TSLA")
205 S0_SPY <- get_underlying_price("SPY")
206 S0_VIX <- get_underlying_price("^VIX")
207
208 # Define function to compute time to maturity
209 time_to_maturity <- function(start_date, end_date) {
210     t2m <- as.numeric(as.Date(start_date) - as.Date(end_date)) / 365
211     return(t2m)
212 }
213
214 # Time to maturity Jan 29th
215 Tau_Feb1 <- time_to_maturity("2026-02-20", "2026-01-29")
216 Tau_Mar1 <- time_to_maturity("2026-03-20", "2026-01-29")
217 Tau_Apr1 <- time_to_maturity("2026-04-17", "2026-01-29")
218
219 # Time to maturity Jan 30th
220 Tau_Feb2 <- time_to_maturity("2026-02-20", "2026-01-30")
221 Tau_Mar2 <- time_to_maturity("2026-03-20", "2026-01-30")
222 Tau_Apr2 <- time_to_maturity("2026-04-17", "2026-01-30")
223
224 # Current Time to maturity
225 ttm_Feb <- time_to_maturity("2026-02-20", "2026-02-05")
226 ttm_Mar <- time_to_maturity("2026-03-20", "2026-02-05")
227 ttm_Apr <- time_to_maturity("2026-04-17", "2026-02-05")
228
229 # Save downloaded data and results for use in Part 2

```

```

230 save(
231     TSLA_data1_EQ, TSLA_data2_EQ,
232     SPY_data1_EQ, SPY_data2_EQ,
233     VIX_data1_EQ, VIX_data2_EQ,
234
235     TSLA_option_Feb, TSLA_option_Mar, TSLA_option_Apr,
236     SPY_option_Feb, SPY_option_Mar, SPY_option_Apr,
237     VIX_option_Feb, VIX_option_Mar, VIX_option_Apr,
238
239     S0_TSLA, S0_SPY, S0_VIX,
240
241     Tau_Feb1, Tau_Mar1, Tau_Apr1,
242     Tau_Feb2, Tau_Mar2, Tau_Apr2,
243     ttm_Feb, ttm_Mar, ttm_Apr,
244
245     file = file.path(data_folder, "Data_for_HW.RData")
246 )

```

## A.2 Part 2: Option Pricing and Analysis (Questions 5–12)

Listing 2: Part 2: Option Pricing and Analysis Code

```

1 # Part 2
2 #####
3 # Q5) Black-Scholes pricing functions
4
5 bs_call <- function(S0, K, r, tau, sigma) {
6     d1 <- (log(S0 / K) + (r + 0.5 * sigma^2) * tau) / (sigma * sqrt(tau))
7     d2 <- d1 - sigma * sqrt(tau)
8     price <- S0 * pnorm(d1) - K * exp(-r * tau) * pnorm(d2)
9     return(price)
10 }
11
12 bs_put <- function(S0, K, r, tau, sigma) {
13     d1 <- (log(S0 / K) + (r + 0.5 * sigma^2) * tau) / (sigma * sqrt(tau))
14     d2 <- d1 - sigma * sqrt(tau)
15     price <- K * exp(-r * tau) * pnorm(-d2) - S0 * pnorm(-d1)
16     return(price)
17 }
18
19 #####
20 # Q6) Bisection method for arbitrary function
21
22 bisection <- function(f, lower, upper, tol = 1e-6, max_iter = 200) {

```

```

23 f_low <- f(lower)
24 f_up <- f(upper)
25
26 # If no sign change, bisection cannot guarantee a root
27 if (!is.finite(f_low) || !is.finite(f_up) || (f_low * f_up > 0)) {
28   return(NA_real_)
29 }
30
31 for (i in 1:max_iter) {
32   mid <- (lower + upper) * 0.5
33   f_mid <- f(mid)
34
35   # Checking to see if finite
36   if (!is.finite(f_mid))
37     return(NA_real_)
38
39   # Checking if tolerance value is reached
40   if (abs(f_mid) < tol)
41     return(mid)
42
43   # Keep the side that has the sign change
44   if (f_low * f_mid < 0) {
45     upper <- mid
46     f_up <- f_mid
47   } else {
48     lower <- mid
49     f_low <- f_mid
50   }
51 }
52
53 # If max iterations reached, return midpoint
54 return(mid)
55 }
56
57
58 # Clean and prepare option data
59 prep_options <- function(option_df, S0_underlying) {
60
61   # Removing rows with 0 or NA vol values
62   op <- option_df[!is.na(option_df$Vol) & option_df$Vol > 0, ]
63
64   # Finding Value of the Option  $0.5 * (\text{Bid} + \text{Ask})$ 
65   op$Mid <- 0.5 * (op$Ask + op$Bid)
66

```



```

67 # Finding the distance between Strike and Spot
68 op$ATM_Dist <- abs(op$Strike - S0_underlying)
69
70 # Finding the minimum distance
71 ATM_strike <- op$Strike[which.min(op$ATM_Dist)]
72
73 # Returning the option data
74 return(list(op = op, ATM_strike = ATM_strike))
75 }
76
77
78 # Getting At-The-Money Call and Put Rows
79 get_ATM_options <- function(op, ATM_strike) {
80   ATM_call <- op[op$Strike == ATM_strike & op$Type == "Call", ]
81   ATM_put  <- op[op$Strike == ATM_strike & op$Type == "Put", ]
82
83   # Returning the call and put data
84   return(list(ATM_call = ATM_call, ATM_put = ATM_put))
85 }
86
87
88 # Compute Implied Volatility via Bisection Method for single option
89 implied_vol_bisection <- function(market_price, Type, S0, K, r, Tau, tol
   = 1e-6) {
90
91   # Define pricing error function f(sigma) = model - market
92   price_err <- function(sigma) {
93     if (Type == "Call")
94       model_price <- bs_call(S0, K, r, Tau, sigma)
95     else
96       model_price <- bs_put(S0, K, r, Tau, sigma)
97
98     return(model_price - market_price)
99   }
100
101   # Run bisection on wide range of sigma (i.e., very small vol to very
     large vol)
102   sigma_hat <- bisection(price_err, lower = 1e-6, upper = 5, tol = tol,
     max_iter = 100)
103
104   return(list(iv = sigma_hat, method = "Bisection"))
105 }
106
107

```

```

108 # Compute Average Implied Volatility in moneyness band using Bisection
    Method
109 avg_iv_bisection <- function(op, S0_underlying, Tau, r, tol = 1e-6,
110                               m_low = 0.95, m_high = 1.05) {
111   op$Moneyness <- S0_underlying / op$Strike
112   op_band <- op[op$Moneyness >= m_low & op$Moneyness <= m_high, ]
113
114   if (nrow(op_band) == 0)
115     return(NA_real_)
116
117   op_band$IV <- NA_real_ # Initialize value
118   op_band$Time <- NA_real_ # Initialize value
119
120   for (i in 1:nrow(op_band)) {
121     out_iv <- implied_vol_bisection(market_price = op_band$Mid[i],
122                                     Type = op_band$Type[i],
123                                     S0 = S0_underlying,
124                                     K = op_band$Strike[i],
125                                     r = r,
126                                     Tau = Tau,
127                                     tol = tol)
128     op_band$IV[i] <- out_iv$iv
129   }
130
131   return(mean(op_band$IV, na.rm = TRUE))
132 }
133
134
135 # Process data for a single chain (TSLA, SPY: Feb, Mar, Apr) via
    Bisection Method
136 run_chain_bisection <- function(symbol, option_df, S0_underlying, Tau,
137                                 r, tol = 1e-6) {
138   # Get prepared options data
139   op_data <- prep_options(option_df, S0_underlying)
140   op <- op_data$op
141   ATM_strike <- op_data$ATM_strike
142
143   # Get At-The_Money options call and put data
144   ATM <- get_ATM_options(op, ATM_strike)
145   ATM_call <- ATM$ATM_call
146   ATM_put <- ATM$ATM_put
147
148   # Bisection ATM call
149   IV_ATM_Call <- NA_real_ # Initialize value

```

```

150 if (nrow(ATM_call) > 0) {
151   out_call <- implied_vol_bisection(market_price = ATM_call$Mid,
152                                     Type = "Call",
153                                     S0 = S0_underlying,
154                                     K = ATM_call$Strike,
155                                     r = r,
156                                     Tau = Tau,
157                                     tol = tol)
158
159   IV_ATM_Call <- out_call$iv
160 }
161
162 # Bisection ATM call
163 IV_ATM_Put <- NA_real_ # Initialize value
164 if (nrow(ATM_put) > 0) {
165   out_put <- implied_vol_bisection(market_price = ATM_put$Mid,
166                                     Type = "Put",
167                                     S0 = S0_underlying,
168                                     K = ATM_put$Strike,
169                                     r = r,
170                                     Tau = Tau,
171                                     tol = tol)
172
173   IV_ATM_Put <- out_put$iv
174 }
175
176 Avg_IV_ATM <- mean(c(IV_ATM_Call, IV_ATM_Put), na.rm = TRUE)
177 Avg_IV_Moneyness <- avg_iv_bisection(op, S0_underlying, Tau, r, tol,
178                                     0.95, 1.05)
179
180 out_results <- data.frame(Symbol = symbol,
181                            S0 = S0_underlying,
182                            Tau = Tau,
183                            ATM_Strike = ATM_strike,
184                            IV_ATM_Call = IV_ATM_Call,
185                            IV_ATM_Put = IV_ATM_Put,
186                            Avg_IV_ATM = Avg_IV_ATM,
187                            Avg_IV_Moneyness = Avg_IV_Moneyness,
188                            stringsAsFactors = FALSE)
189
190 rownames(out_results) <- NULL
191 return(out_results)
192 }

```

```

193
194 # Build Bisection Method results table (TSLA + SPY, Feb/Mar/Apr)
195
196 # Load equity and option data and results generated in Part 1
197 load("./Data_for_HW.RData")
198
199 # Create output tables folder if it does not exist - used for report
200 table_folder = "./tables"
201
202 # This makes the folder for the first time you run the code
203 if (!dir.exists(table_folder))
204   dir.create(table_folder)
205
206 # Went to website provided in Homework PDF to get short-term interest
   rate of 3.64% for Jan 29th and Jan 30th then converted interest rate
   to number (i.e.,  $r = 3.64 / 100 = 0.0364$ )
207
208 r = 0.0364
209 tol = 1e-6 # Accuracy tolerance
210
211 # Define inputs in simple lists for chain processing
212 symbols <- c("TSLA", "SPY")
213 expiries <- c("Feb", "Mar", "Apr")
214
215 # Option Data
216 option_data <- list(
217   TSLA = list(Feb = TSLA_option_Feb, Mar = TSLA_option_Mar, Apr =
     TSLA_option_Apr),
218   SPY = list(Feb = SPY_option_Feb, Mar = SPY_option_Mar, Apr =
     SPY_option_Apr)
219 )
220
221 # Spot Price of Option Data
222 SO_values <- list(TSLA = SO_TSLA, SPY = SO_SPY)
223
224 # Expiration data
225 Tau_values <- list(Feb = Tau_Feb1, Mar = Tau_Mar1, Apr = Tau_Apr1)
226
227 # Generate results table for Bisection Method
228 bisection_results <- data.frame() # Initialize value
229
230 for (sym in symbols) {
231   for (exp in expiries) {

```

```

232     temp <- run_chain_bisection(sym, option_data[[sym]][[exp]],
233                               S0_values[[sym]],
234                               Tau_values[[exp]], r, tol)
235     temp$Expiries <- exp
236     bisection_results <- rbind(bisection_results, temp)
237   }
238 }
239 # Final output
240 View(bisection_results)
241 write.csv(bisection_results, file.path(table_folder,
242   "bisection_results.csv"),
243           row.names = FALSE)
244 #####
245 # Q7) Newton Method for arbitrary function
246 newton <- function(f, fprime, x0, tol = 1e-6, max_iter = 50) {
247   x <- x0 # Initialize
248
249   for (i in 1:max_iter) {
250     fx <- f(x)
251     fpx <- fprime(x)
252
253     # Stop if f(x) is close to zero or derivative is very small derivative
254     if (abs(fx) < tol || abs(fpx) < 1e-14) {
255       return(x)
256     }
257
258     # Newton update
259     x_new <- x - fx / fpx
260
261     # Volatility must be positive
262     if (!is.finite(x_new) || x_new <= 0) {
263       return(NA_real_)
264     }
265
266     # Stop if change is very small (converged)
267     if (abs(x_new - x) < tol) {
268       return(x_new)
269     }
270
271     x <- x_new
272   }
273 }

```

```

274     return(x)
275 }
276
277
278 # Black-Scholes Vega (dPrice/dSigma) for call/put
279 bs_vega <- function(S0, K, r, tau, sigma) {
280     d1 <- (log(S0 / K) + (r + 0.5 * sigma^2) * tau) / (sigma * sqrt(tau))
281     return(S0 * sqrt(tau) * dnorm(d1))
282 }
283
284
285 # Compute Implied Volatility via Newton Method for ONE option
286 implied_vol_newton <- function(market_price, Type, S0, K, r, Tau, sigma0
    = 0.20,
287                               tol = 1e-6, max_iter = 50) {
288     # If market price or time to maturity is non-finite or non-positive,
        return NA
289     # since implied volatility cannot be computed
290     if (!is.finite(market_price) || market_price <= 0 ||
291         !is.finite(Tau) || Tau <= 0)
292         return(list(iv = NA_real_, method = "Newton"))
293
294     # Define pricing error function f(sigma) = model - market
295     f <- function(sigma) {
296         if (Type == "Call")
297             bs_call(S0, K, r, Tau, sigma) - market_price
298         else
299             bs_put(S0, K, r, Tau, sigma) - market_price
300     }
301
302     # f'(sigma) = Vega(sigma)
303     fprime <- function(sigma) {
304         bs_vega(S0, K, r, Tau, sigma)
305     }
306
307     out <- newton(f, fprime, x0 = sigma0, tol = tol, max_iter = max_iter)
308     return(list(iv = out, method = "Newton"))
309 }
310
311
312 # Compute Average Implied Volatility in moneyness band using Newton Method
313 avg_iv_newton <- function(op, S0_underlying, Tau, r, tol = 1e-6, sigma0 =
    0.20,
314                           m_low = 0.95, m_high = 1.05) {

```

```

315 op$Moneyness <- S0_underlying / op$Strike
316 op_band <- op[op$Moneyness >= m_low & op$Moneyness <= m_high, ]
317
318 if (nrow(op_band) == 0)
319   return(NA_real_)
320
321 op_band$IV <- NA_real_ # Initialize value
322 op_band$Time <- NA_real_ # Initialize value
323
324 for (i in 1:nrow(op_band)) {
325   out_iv <- implied_vol_newton(market_price = op_band$Mid[i],
326                               Type = op_band$Type[i],
327                               S0 = S0_underlying,
328                               K = op_band$Strike[i],
329                               r = r,
330                               Tau = Tau,
331                               sigma0 = sigma0,
332                               tol = tol)
333   op_band$IV[i] <- out_iv$iv
334 }
335
336 return(mean(op_band$IV, na.rm = TRUE))
337 }
338
339 # Process data for a single chain (TSLA, SPY: Feb, Mar, Apr) via Newton
    Method
340 run_chain_newton <- function(symbol, option_df, S0_underlying, Tau, r,
341                             tol = 1e-6, sigma0 = 0.20) {
342   # Get prepared options data
343   op_data <- prep_options(option_df, S0_underlying)
344   op <- op_data$op
345   ATM_strike <- op_data$ATM_strike
346
347   # Get At-The_Money options call and put data
348   ATM <- get_ATM_options(op, ATM_strike)
349   ATM_call <- ATM$ATM_call
350   ATM_put <- ATM$ATM_put
351
352   # Newton ATM call
353   IV_ATM_Call <- NA_real_ # Initialize
354   if (nrow(ATM_call) > 0) {
355     out_call <- implied_vol_newton(market_price = ATM_call$Mid,
356                                   Type = "Call",
357                                   S0 = S0_underlying,

```

```

358         K = ATM_call$Strike,
359         r = r,
360         Tau = Tau,
361         sigma0 = sigma0,
362         tol = tol)
363
364     IV_ATM_Call <- out_call$iv
365 }
366
367 # Newton ATM put
368 IV_ATM_Put <- NA_real_ # Initialize
369 if (nrow(ATM_put) > 0) {
370     out_put <- implied_vol_newton(market_price = ATM_put$Mid,
371                                 Type = "Put",
372                                 S0 = S0_underlying,
373                                 K = ATM_put$Strike,
374                                 r = r,
375                                 Tau = Tau,
376                                 sigma0 = sigma0,
377                                 tol = tol)
378
379     IV_ATM_Put <- out_put$iv
380 }
381
382 Avg_IV_ATM <- mean(c(IV_ATM_Call, IV_ATM_Put), na.rm = TRUE)
383 Avg_IV_Moneyness <- avg_iv_newton(op, S0_underlying, Tau, r, tol,
384                                 sigma0,
385                                 0.95, 1.05)
386
387 out_results <- data.frame(Symbol = symbol,
388                           S0 = S0_underlying,
389                           Tau = Tau,
390                           ATM_Strike = ATM_strike,
391                           IV_ATM_Call = IV_ATM_Call,
392                           IV_ATM_Put = IV_ATM_Put,
393                           Avg_IV_ATM = Avg_IV_ATM,
394                           Avg_IV_Moneyness = Avg_IV_Moneyness,
395                           stringsAsFactors = FALSE)
396
397 rownames(out_results) <- NULL
398 return(out_results)
399 }
400

```



```

401
402 # Build Newton Method results table (TSLA + SPY, Feb/Mar/Apr)
403
404 # Initial guess for volatility [TSLA , SPY]
405 sigma0_vals <- c(TSLA = 0.4, SPY = 0.2)
406
407 newton_results <- data.frame() # Initialize
408
409 for (sym in symbols) {
410   # Getting correct value for sigma guess
411   sigma0 <- sigma0_vals[sym]
412
413   for (exp in expiries) {
414     temp <- run_chain_newton(sym, option_data[[sym]][[exp]],
415                             S0_values[[sym]],
416                             Tau_values[[exp]], r, tol, sigma0)
417     temp$Expiries <- exp
418     newton_results <- rbind(newton_results, temp)
419   }
420 }
421
422 # Final output
423 View(newton_results)
424 write.csv(newton_results, file.path(table_folder, "newton_results.csv"),
425           row.names = FALSE)
426
427 # Run the next line if package is not installed
428 # install.packages("microbenchmark")
429 library(microbenchmark) # Allows for microsecond times
430
431 # Compare run-time of Bisection and Newton methods averaged over N runs
432 compare_run_time <- function(option_df, S0_underlying, r, Tau, tol,
433                               sigma0, n_runs, table_folder){
434   op_data <- prep_options(option_df, S0_underlying)
435   op <- op_data$op
436   ATM_strike <- op_data$ATM_strike
437   ATM <- get_ATM_options(op, ATM_strike)
438   ATM_call <- ATM$ATM_call
439
440   # To obtain a statistically valid estimate of convergence time for each
441   # method,
442   # average run-time over n_runs runs using the same data and accuracy
443   # tolerance
444   output <- suppressWarnings(microbenchmark(

```

```

442     Bisection = implied_vol_bisection(market_price = ATM_call$Mid,
443                                     Type = "Call",
444                                     S0 = S0_underlying,
445                                     K = ATM_call$Strike,
446                                     r = r,
447                                     Tau = Tau,
448                                     tol = tol),
449     Newton = implied_vol_newton(market_price = ATM_call$Mid,
450                                Type = "Call",
451                                S0 = S0_underlying,
452                                K = ATM_call$Strike,
453                                r = r,
454                                Tau = Tau,
455                                sigma0 = sigma0,
456                                tol = tol),
457     times = n_runs,
458     unit = "ms" # milliseconds
459 ))
460
461 # Convert timing output to data frame for outputting to CSV file
462 time_summary <- as.data.frame(summary(output))
463
464 # Output to file
465 colnames(time_summary) <- c("Method", "Min", "LQ", "Mean", "Median",
466                             "UQ", "Max", "Runs")
467 View(time_summary)
468 write.csv(time_summary, file.path(table_folder, "time_comparison.csv"),
469           row.names = FALSE)
470 }
471
472 # Comparing convergence of Bisection and Newton methods
473 compare_run_time(TSLA_option_Feb, S0_TSLA, r, Tau_Feb1, tol, sigma0 = 0.2,
474                 n = 100, table_folder = table_folder)
475
476 #####
477 # Q8) Put data in LaTeX Table for comparison no need to code anything
478
479 # Generating table format
480 Q8_table <- bisection_results[, c("Symbol", "Expiries", "Tau", "ATM_Strike",
481                                 "IV_ATM_Call", "IV_ATM_Put", "Avg_IV_ATM", "Avg_IV_Mone
482
483 # Sorting
484 Q8_table <- Q8_table[order(Q8_table$Symbol, Q8_table$Expiries), ]

```

```

484 Q8_table$Tau <- round(Q8_table$Tau, 6)
485 Q8_table$ATM_Strike <- round(Q8_table$ATM_Strike, 2)
486 Q8_table$IV_ATM_Call <- round(Q8_table$IV_ATM_Call, 6)
487 Q8_table$IV_ATM_Put <- round(Q8_table$IV_ATM_Put, 6)
488 Q8_table$Avg_IV_ATM <- round(Q8_table$Avg_IV_ATM, 6)
489 Q8_table$Avg_IV_Moneyness <- round(Q8_table$Avg_IV_Moneyness, 6)
490
491 # Final output
492 rownames(Q8_table) <- NULL
493 View(Q8_table)
494 write.csv(Q8_table, file.path(table_folder, "Q8_table.csv"), row.names =
      FALSE)
495
496 # Getting the value of VIX right NOW
497 get_vix_now <- function() {
498   if (!requireNamespace("quantmod", quietly = TRUE)) return(NA_real_)
499   suppressWarnings({
500     vix_xts <- quantmod::getSymbols("^VIX", src = "yahoo", auto.assign =
      FALSE)
501     as.numeric(tail(quantmod::Cl(vix_xts), 1))
502   })
503 }
504
505 VIX_now <- get_vix_now()
506 message(sprintf("Current ^VIX (Yahoo close): %.2f", VIX_now))
507
508 #####
509 # Q9) Put-Call Parity
510
511 # Put-Call Parity (no dividends):  $C - P = S_0 - K \cdot \exp(-r \cdot \text{Tau})$ 
512 pc_parity_12rows <- function(symbol, option_df, S0_underlying, Tau, r) {
513   # Get prepared options data
514   op_data <- prep_options(option_df, S0_underlying)
515   op <- op_data$op
516   K <- op_data$ATM_strike
517
518   # Get At-The_Money options call and put data
519   ATM <- get_ATM_options(op, K)
520   call <- ATM$ATM_call
521   put <- ATM$ATM_put
522
523   PVK <- K * exp(-r * Tau)
524
525   # Parity prices

```

```

526 P_price <- call$Mid - S0_underlying + PVK
527 C_price <- put$Mid + S0_underlying - PVK
528
529 # Call row
530 call_row <- data.frame(Symbol = symbol,
531                        Type = "Call",
532                        Price = C_price,
533                        stringsAsFactors = FALSE)
534
535 # Put row
536 put_row <- data.frame(Symbol = symbol,
537                        Type = "Put",
538                        Price = P_price,
539                        stringsAsFactors = FALSE)
540
541 rbind(call_row, put_row)
542 }
543
544 # Build final Q9 table (12 rows, minimal)
545 Q9_display <- data.frame()
546
547 for (sym in symbols) {
548   for (exp in expiries) {
549     temp <- pc_parity_12rows(sym, option_data[[sym]][[exp]],
550                             S0_values[[sym]],
551                             Tau_values[[exp]], r)
552     temp$Month <- exp
553     Q9_display <- rbind(Q9_display, temp)
554   }
555 }
556
557 # Round prices to 4 digits after decimal
558 Q9_display$Price <- round(Q9_display$Price, 4)
559
560 # Final output
561 rownames(Q9_display) <- NULL
562 View(Q9_display)
563 write.csv(Q9_display, file.path(table_folder, "Q9_display.csv"),
564          row.names = FALSE)
565 #####
566 # Q10) Implied volatility plots vs strike K
567 # 1) 2D plot of IV vs K for the closest maturity (Feb)
568 # 2) 2D plot of IV vs K for Feb/Mar/Apr on the same plot (3 colors)

```

```

569 #      3) 3D plot of IV as a function of both K and Tau
570
571 # Create output plot folder if it does not exist - used for report
572 plot_folder = "./figures"
573 if (!dir.exists(plot_folder))
574   dir.create(plot_folder)
575
576 Type_plot <- "Call" # Keep consistent with Q6/Q7 focus on calls
577 closest_exp <- "Feb" # Closest-to-maturity in my setup
578
579
580 # Computing implied volatility for ALL strikes in one chain (one maturity)
581 compute_iv_all_strikes <- function(op, S0_underlying, Tau, r, Type =
582   "Call",
583                                     tol = 1e-6) {
584   strikes <- sort(unique(op$Strike))
585
586   out <- data.frame(Strike = strikes,
587                     IV = NA_real_,
588                     stringsAsFactors = FALSE)
589
590   for (j in 1:length(strikes)) {
591     K_j <- strikes[j]
592     row_j <- op[op$Strike == K_j & op$Type == Type, ]
593     if (nrow(row_j) == 0) next
594
595     out$IV[j] <- implied_vol_bisection(market_price = row_j$Mid,
596                                       Type = Type,
597                                       S0 = S0_underlying,
598                                       K = K_j,
599                                       r = r,
600                                       Tau = Tau,
601                                       tol = tol)$iv
602   }
603
604   return(out)
605 }
606
607 # Building implied vol data for Feb/Mar/Apr (for one symbol)
608 build_iv_data_Q10 <- function(symbol, option_data_sym, S0_underlying,
609   Tau_values,
610                                     r, tol = 1e-6, Type = "Call") {
611   iv_all <- data.frame() # Initialize

```

```

611
612 for (exp in names(option_data_sym)) {
613   op_temp <- prep_options(option_data_sym[[exp]], S0_underlying)$op
614
615   iv_df <- compute_iv_all_strikes(op = op_temp,
616                                   S0_underlying = S0_underlying,
617                                   Tau = Tau_values[[exp]],
618                                   r = r,
619                                   Type = Type,
620                                   tol = tol)
621
622   iv_df$Symbol <- symbol
623   iv_df$Expiries <- exp
624   iv_df$Tau <- Tau_values[[exp]]
625   iv_all <- rbind(iv_all, iv_df)
626 }
627
628 rownames(iv_all) <- NULL
629 return(iv_all)
630 }
631
632 # Building implied vol data (TSLA + SPY)
633 Q10_TSLA <- build_iv_data_Q10(symbol = "TSLA",
634                                option_data_sym = option_data$TSLA,
635                                S0_underlying = S0_values$TSLA,
636                                Tau_values = Tau_values,
637                                r = r,
638                                tol = tol,
639                                Type = Type_plot)
640
641 Q10_SPY <- build_iv_data_Q10(symbol = "SPY",
642                               option_data_sym = option_data$SPY,
643                               S0_underlying = S0_values$SPY,
644                               Tau_values = Tau_values,
645                               r = r,
646                               tol = tol,
647                               Type = Type_plot)
648
649 # Plot 1: Closest maturity only (IV vs K) for closest maturity
650 plot_iv_closest_maturity <- function(iv_data, symbol, exp_to_plot,
651                                       plot_folder) {
652   df <- iv_data[iv_data$Symbol == symbol & iv_data$Expiries ==
653                 exp_to_plot, ]

```

```

653
654 # Keep only good points (Strike, IV must all be finite)
655 df <- df[is.finite(df$Strike) & is.finite(df$IV), ]
656
657 # Setup PNG output file
658 plot_filename <- paste0("plot_1_", symbol, ".png")
659 full_path <- file.path(plot_folder, plot_filename)
660 png(full_path, width = 6, height = 4.5, units = "in", res = 300)
661
662 # Generate plot
663 plot(df$Strike, df$IV, xlab = "Strike K", ylab = "Implied Volatility
      IV",
664       main = paste(symbol, "Implied Volatility vs Strike (Closest
      Maturity:", exp_to_plot, ")"),
665       pch = 16)
666 grid()
667 invisible(dev.off()) # Close output file
668 }
669
670 # Plot data
671 plot_iv_closest_maturity(Q10_TSLA, "TSLA", closest_exp, plot_folder)
672 plot_iv_closest_maturity(Q10_SPY, "SPY", closest_exp, plot_folder)
673
674
675 # Plot 2: Feb/Mar/Apr on same plot (3 colors, 3 sets of points)
676 plot_iv_three_maturities <- function(iv_data, symbol, plot_folder) {
677   df <- iv_data[iv_data$Symbol == symbol, ]
678
679   # Keep only good points (Strike, IV, Tau must all be finite)
680   df <- df[is.finite(df$Strike) & is.finite(df$IV) & is.finite(df$Tau), ]
681
682   # Separate individual maturities
683   df_feb <- df[df$Expiries == "Feb" & is.finite(df$IV), ]
684   df_mar <- df[df$Expiries == "Mar" & is.finite(df$IV), ]
685   df_apr <- df[df$Expiries == "Apr" & is.finite(df$IV), ]
686
687   y_min <- min(df$IV, na.rm = TRUE)
688   y_max <- max(df$IV, na.rm = TRUE)
689
690   # Setup PNG output file
691   plot_filename <- paste0("plot_2_", symbol, ".png")
692   full_path <- file.path(plot_folder, plot_filename)
693   png(full_path, width = 6, height = 4.5, units = "in", res = 300)
694

```

```

695 # Generate plot
696 plot(df_feb$Strike, df_feb$IV, xlab = "Strike K", ylab = "Implied
    Volatility IV",
697       main = paste(symbol, "Implied Volatility Smile (3 Maturities)"),
698       pch = 16, ylim = c(y_min, y_max))
699
700 points(df_mar$Strike, df_mar$IV, col = 2, pch = 16)
701 points(df_apr$Strike, df_apr$IV, col = 4, pch = 16)
702
703 legend("topright", legend = c("Feb", "Mar", "Apr"),
704       col = c(1, 2, 4), pch = 16, bty = "n")
705 grid()
706 invisible(dev.off()) # Close output file
707 }
708
709 # Plot data
710 plot_iv_three_maturities(Q10_TSLA, "TSLA", plot_folder)
711 plot_iv_three_maturities(Q10_SPY, "SPY", plot_folder)
712
713 # BONUS 3D Plot
714 # 3D plot library package
715 # Run the next line if package is not installed
716 # install.packages("scatterplot3d")
717
718 library(scatterplot3d)
719
720 # Plot 3: 3D plot of Implied Volatility as a function of both Strike and
    Maturity
721 plot_iv_3d <- function(iv_data, symbol, expiries, plot_folder) {
722   df <- iv_data[iv_data$Symbol == symbol, ]
723
724   # Keep only good points (Strike, IV, Tau must all be finite)
725   df <- df[is.finite(df$Strike) & is.finite(df$IV) & is.finite(df$Tau), ]
726
727   # Ensure consistent color mapping for maturities
728   df$Expiries <- factor(df$Expiries, levels = expiries)
729   cols <- as.numeric(df$Expiries) # 1 - Feb, 2 - Mar, 3 - Apr
730
731   # Setup PNG output file
732   plot_filename <- paste0("plot_3_", symbol, ".png")
733   full_path <- file.path(plot_folder, plot_filename)
734   png(full_path, width = 6, height = 4.5, units = "in", res = 300)
735
736   # 3D scatter: x = K, y = Tau, z = IV

```



```

737 par(mar = c(5, 8, 4, 8)) # Increase right margin for legend
738 scatterplot3d::scatterplot3d(df$Strike, df$Tau, df$IV,
739   xlab = "Strike K", ylab = "Maturity Tau (years)", zlab = "Implied
      Volatility IV",
740   main = paste(symbol, "Implied Volatility Surface: IV = f(Tau, K)",
741   pch = 16, color = cols, angle = 145)
742
743 par(xpd = NA)
744 legend("topright", inset = c(-0.04, -0.05),
745   legend = expiries, col = seq_along(expiries),
746   pch = 16, bty = "n")
747
748 invisible(dev.off()) # Close output file
749 }
750
751 # Plotting data
752 plot_iv_3d(Q10_TSLA, "TSLA", expiries, plot_folder)
753 plot_iv_3d(Q10_SPY, "SPY", expiries, plot_folder)
754
755 #####
756 # Q11) Greeks (CALL): Delta, Gamma, Vega
757 # Compare Black-Scholes closed-form (BS) vs Finite Difference (FD)
758
759 bs_call_greeks <- function(S0, K, r, tau, sigma) {
760   d1 <- (log(S0 / K) + (r + 0.5 * sigma^2) * tau) / (sigma * sqrt(tau))
761
762   # Sensitivity of option price to underlying price
763   Delta <- pnorm(d1)
764
765   # Curvature of option price w.r.t. underlying price
766   Gamma <- dnorm(d1) / (S0 * sigma * sqrt(tau))
767
768   # Sensitivity of option price to volatility
769   Vega <- S0 * dnorm(d1) * sqrt(tau)
770
771   return(list(Delta = Delta, Gamma = Gamma, Vega = Vega))
772 }
773
774
775 fd_call_greeks <- function(S0, K, r, tau, sigma, hS_frac = 0.01, hSigma =
      1e-4) {
776   hS <- hS_frac * S0
777
778   C0 <- bs_call(S0, K, r, tau, sigma)

```

```

779 C_up <- bs_call(S0 + hS, K, r, tau, sigma)
780 C_dn <- bs_call(S0 - hS, K, r, tau, sigma)
781
782 # Sensitivity of option price to underlying price
783 Delta <- (C_up - C_dn) / (2 * hS)
784
785 # Curvature of option price with respect to underlying price
786 Gamma <- (C_up - 2*C0 + C_dn) / (hS^2)
787
788 C_sig_up <- bs_call(S0, K, r, tau, sigma + hSigma)
789 C_sig_dn <- bs_call(S0, K, r, tau, sigma - hSigma)
790
791 # Sensitivity of option price to volatility
792 Vega <- (C_sig_up - C_sig_dn) / (2 * hSigma)
793
794 return(list(Delta = Delta, Gamma = Gamma, Vega = Vega))
795 }
796
797 # Creating columns for the table
798 Q11_table <- data.frame() # Initialize
799
800 for (sym in symbols) {
801   for (exp in expiries) {
802     row_res <- bisection_results[bisection_results$Symbol == sym &
803                                   bisection_results$Expiries == exp, ]
804
805     S0_use <- row_res$S0
806     K_use <- row_res$ATM_Strike
807     Tau_use <- row_res$Tau
808     sig_use <- row_res$IV_ATM_Call
809
810     g_bs <- bs_call_greeks(S0_use, K_use, r, Tau_use, sig_use)
811     g_fd <- fd_call_greeks(S0_use, K_use, r, Tau_use, sig_use)
812
813     row_bs <- data.frame(Symbol = sym,
814                           Expiries = exp,
815                           Greek_Method = "BS",
816                           S0 = S0_use,
817                           K = K_use,
818                           Tau = Tau_use,
819                           Sigma = sig_use,
820                           Delta = g_bs$Delta,
821                           Gamma = g_bs$Gamma,
822                           Vega = g_bs$Vega,
823                           stringsAsFactors = FALSE)

```

```

823
824     row_fd <- data.frame(Symbol = sym,
825                           Expiries = exp,
826                           Greek_Method = "FD",
827                           S0 = S0_use,
828                           K = K_use,
829                           Tau = Tau_use,
830                           Sigma = sig_use,
831                           Delta = g_fd$Delta,
832                           Gamma = g_fd$Gamma,
833                           Vega = g_fd$Vega,
834                           stringsAsFactors = FALSE)
835
836     Q11_table <- rbind(Q11_table, row_bs, row_fd)
837   }
838 }
839
840 Q11_table$S0 <- round(Q11_table$S0, 3)
841 Q11_table$K <- round(Q11_table$K, 3)
842 Q11_table$Tau <- round(Q11_table$Tau, 6)
843 Q11_table$Sigma <- round(Q11_table$Sigma, 6)
844 Q11_table$Delta <- round(Q11_table$Delta, 6)
845 Q11_table$Gamma <- round(Q11_table$Gamma, 6)
846 Q11_table$Vega <- round(Q11_table$Vega, 6)
847
848 Q11_table <- Q11_table[order(Q11_table$Symbol, Q11_table$Expiries,
849                             Q11_table$Greek_Method), ]
850
851 # Final output
852 rownames(Q11_table) <- NULL
853 View(Q11_table)
854 write.csv(Q11_table, file.path(table_folder, "Q11_table.csv"),
855           row.names = FALSE)
856
857 #####
858 # Q12) Process second day of equity and option data
859
860 # DATA2 short-term interest rate (Jan 30)
861 r <- 0.0364
862
863 # DATA2 spot prices from your saved equity data
864 S0_TSLA_2 <- as.numeric(tail(TSLA_data2_EQ$Close, 1))
865 S0_SPY_2 <- as.numeric(tail(SPY_data2_EQ$Close, 1))

```

```

866 S0_values2 <- list(TSLA = S0_TSLA_2, SPY = S0_SPY_2)
867 Tau_values2 <- list(Feb = Tau_Feb2, Mar = Tau_Mar2, Apr = Tau_Apr2)
868
869 # Q12: price DATA2 ATM options using DATA1 implied vols (by maturity)
870 Q12_ATM_prices <- data.frame() # Initialize
871
872 for (sym in symbols) {
873   for (exp in expiries) {
874     row1 <- bisection_results[bisection_results$Symbol == sym &
875                               bisection_results$Expiries == exp, ]
876     K_ATM <- row1$ATM_Strike
877
878     sigma_call <- row1$IV_ATM_Call # DATA1 sigma
879     sigma_put <- row1$IV_ATM_Put # DATA1 sigma
880
881     S0_2 <- S0_values2[[sym]] # DATA2 spot
882     Tau_2 <- Tau_values2[[exp]] # DATA2 tau
883
884     # Price in DATA2 using DATA1 sigma
885     C2 <- bs_call(S0 = S0_2, sigma = sigma_call, tau = Tau_2, K = K_ATM,
886                  r = r)
887     P2 <- bs_put(S0 = S0_2, sigma = sigma_put, tau = Tau_2, K = K_ATM, r
888                = r)
889
890     Q12_ATM_prices <- rbind(Q12_ATM_prices,
891                             data.frame(Symbol=sym, Expiries=exp,
892                                         Type="Call",
893                                         S0_DATA2=S0_2, K=K_ATM,
894                                         Tau_DATA2=Tau_2,
895                                         Sigma_DATA1=sigma_call,
896                                         BS_Price_DATA2=C2,
897                                         stringsAsFactors=FALSE),
898                             data.frame(Symbol=sym, Expiries=exp,
899                                         Type="Put",
900                                         S0_DATA2=S0_2, K=K_ATM,
901                                         Tau_DATA2=Tau_2,
902                                         Sigma_DATA1=sigma_put,
903                                         BS_Price_DATA2=P2,
904                                         stringsAsFactors=FALSE))
905   }
906 }
907
908 Q12_ATM_prices$BS_Price_DATA2 <- round(Q12_ATM_prices$BS_Price_DATA2, 6)
909 Q12_ATM_prices$Sigma_DATA1 <- round(Q12_ATM_prices$Sigma_DATA1, 6)

```

```

900 Q12_ATM_prices$Tau_DATA2 <- round(Q12_ATM_prices$Tau_DATA2, 6)
901
902 # Final output
903 rownames(Q12_ATM_prices) <- NULL
904 View(Q12_ATM_prices)
905 write.csv(Q12_ATM_prices, file.path(table_folder, "Q12_ATM_prices.csv"),
           row.names = FALSE)

```

### A.3 Part 3: Numerical Integration and AMM Fee Analysis (Questions 13–15)

Listing 3: Part 3: AMM Fee Revenue (Trapezoidal Rule) and Optimal Fee Rate

```

1
2 # Part 3
3 #####
4 # (b) Expected fee revenue (minimal version)
5
6 # Given
7 x0 <- 1000
8 y0 <- 1000
9 St <- 1
10 dt <- 1/365
11
12 sigma <- 0.2
13 gamma <- 0.003
14
15 # Trapezoid rule
16 trapz <- function(a, b, n, f) {
17   h <- (b - a) / n
18   s <- a + h * (0:n)
19   vals <- f(s)
20   h * (0.5 * vals[1] + sum(vals[2:n]) + 0.5 * vals[n + 1])
21 }
22
23 # CASE 1: s > P / (1-gamma)
24 case1 <- function(s, x, y, gamma) {
25   k <- x * y
26   dx <- x - sqrt(k / ((1 - gamma) * s))
27   dy <- (sqrt(k * (1 - gamma) * s) - y) / (1 - gamma)
28   list(dx = dx, dy = dy)
29 }
30
31 # CASE 2: s < P * (1-gamma)
32 case2 <- function(s, x, y, gamma) {

```

```

33 k <- x * y
34 dx <- (sqrt(k * (1 - gamma) / s) - x) / (1 - gamma)
35 dy <- y - sqrt(k * s / (1 - gamma))
36 list(dx = dx, dy = dy)
37 }
38
39 # Lognormal density for S_{t+1} given S_t = St
40 log_density <- function(s, sigma, dt) {
41   mu <- log(St) - 0.5 * sigma^2 * dt
42   var <- sigma^2 * dt
43   (1 / (s * sqrt(2 * pi * var))) * exp(-(log(s) - mu)^2 / (2 * var))
44 }
45
46 # Piecewise revenue function R(s)
47 R_func <- function(s, x, y, gamma) {
48   P <- y / x
49   upper <- P / (1 - gamma)
50   lower <- P * (1 - gamma)
51
52   R_values <- numeric(length(s))
53
54   for (i in seq_along(s)) {
55     if (s[i] > upper) {
56       result <- case1(s[i], x, y, gamma)
57       R_values[i] <- gamma * result$dy
58     } else if (s[i] < lower) {
59       result <- case2(s[i], x, y, gamma)
60       R_values[i] <- gamma * result$dx * s[i]
61     } else {
62       R_values[i] <- 0
63     }
64   }
65
66   R_values
67 }
68
69 # Expected Revenue E[R(S_{t+1})]
70 expected_revenue <- function(x, y, sigma, gamma, dt, a = 0.1, b = 2.0, n
  = 20000) {
71   integrand <- function(s) {
72     R_func(s, x, y, gamma) * log_density(s, sigma, dt)
73   }
74   trapz(a, b, n, integrand)
75 }

```

```

76
77 #Computing ER for one (sigma, gamma)
78 ER <- expected_revenue(x = x0, y = y0, sigma = sigma, gamma = gamma, dt =
    dt,
79                             a = 0.1, b = 2.0, n = 20000)
80 message("Expected Revenue (Part b): ", ER)
81
82 #####
83 # Part 3 (c): Optimal Fee R\te under different volatilities
84
85 # Given sets in the problem
86 sigmas <- c(0.2, 0.6, 1.0)
87 gammas <- c(0.001, 0.003, 0.01)
88
89 # Generate Grid
90 grid <- expand.grid(sigma = sigmas, gamma = gammas)
91 grid$ER <- numeric(nrow(grid))
92
93 # Populate expected revenue values
94 for (row in 1:nrow(grid)) {
95     grid$ER[row] <- expected_revenue(x = x0, y = y0,
96                                     sigma = grid$sigma[row],
97                                     gamma = grid$gamma[row],
98                                     dt = dt,
99                                     a = 0.1, b = 2.0, n = 20000)
100 }
101
102 # Best gamma*(sigma) among the discrete gamma options
103 best <- data.frame(sigma = numeric(),
104                   gamma_star = numeric(),
105                   ER_max = numeric())
106
107 for (s in sigmas) {
108     sub <- grid[grid$sigma == s, ]
109     idx <- which.max(sub$ER)
110
111     best <- rbind(best, data.frame(sigma = s,
112                                   gamma_star = sub$gamma[idx],
113                                   ER_max = sub$ER[idx]))
114 }
115
116 cat("\nPart (c) Table of E[R] values:\n")
117 print(grid)
118

```

```

119 cat("\nPart (c) Best gamma*(sigma) among the 3 options:\n")
120 print(best)
121
122 # Saving tables
123 table_folder <- "./tables"
124 if (!dir.exists(table_folder)) dir.create(table_folder, recursive = TRUE)
125
126 write.csv(grid, file.path(table_folder, "ER_grid_table.csv"), row.names =
127   FALSE)
128 write.csv(best, file.path(table_folder, "best_gamma_table.csv"),
129   row.names = FALSE)
130
131 # Plotting gamma*(sigma) over a sigma grid using the same discrete gamma
132   set
133
134 sigma_grid <- seq(0.1, 1.0, by = 0.01)
135 gamma_star_grid <- numeric(length(sigma_grid))
136
137 for (ii in seq_along(sigma_grid)) {
138   ERs <- numeric(length(gammas))
139
140   for (jj in seq_along(gammas)) {
141     ERs[jj] <- expected_revenue(x = x0, y = y0,
142       sigma = sigma_grid[ii],
143       gamma = gammas[jj],
144       dt = dt,
145       a = 0.1, b = 2.0, n = 20000)
146   }
147
148   gamma_star_grid[ii] <- gammas[which.max(ERs)]
149 }
150
151 out <- data.frame(sigma = sigma_grid, gamma_star = gamma_star_grid)
152
153 # Saving plot
154 plot_folder <- "./figures"
155 if (!dir.exists(plot_folder)) dir.create(plot_folder, recursive = TRUE)
156
157 full_path <- file.path(plot_folder, "optimal_fee.png")
158 png(full_path, width = 6, height = 4.5, units = "in", res = 300)
159
160 plot(out$sigma, out$gamma_star,
161   xlab = expression(sigma),
162   ylab = expression(gamma^"*"(sigma)),

```



```
160     main = expression("Volatility " * sigma * " vs Optimal Fee Rate " *  
161         gamma^"*(sigma)),  
162     type = "o", pch = 16, cex = 0.6)  
163 grid()  
164 invisible(dev.off())
```