Hands-on Lab: Working with Multiple Tables



Estimated time needed: 20 minutes

Objectives

After completing this lab, you will be able to:

- · Write SQL queries that access more than one table
- Compose queries that access multiple tables using a nested statement in the WHERE clause
 Build queries with multiple tables in the FROM clause
- Write Implicit Join queries with join criteria specified in the WHERE clause
 Specify aliases for table names and qualify column names with table aliases

In this lab, you will complete SQL practice problems that will provide hands-on experience with SQL queries that access multiple tables. You will be:

- Accessing Multiple Tables with Sub-Queries
- · Accessing Multiple Tables with Implicit Joins

Software used in this lab

In this lab, you will use MySQL. MySQL is a Relational Database Management System (RDBMS) designed to store, manipulate, and retrieve data efficiently.



To complete this lab, you will utilize MySQL relational database service available as part of IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

Database used in this lab

The database used in this lab is internal. You will be working on a sample HR database. This HR database schema consists of 5 tables called EMPLOYEES, JOB_HISTORY, JOBS, DEPARTMENTS and LOCATIONS. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

SAMPLE HR DATABASE TABLES

EMP_ID	F_NAME	L_NAME		SSN	B_DATE			ADDRESS		108 ^T ID	SALAF	1 YS	MANAGE	CID.	DEP_ID	
E1001	John	Thomas		123456	1976-01-09		м	5631 Rice, OakPark,IL		100	100000 300		30001		2	
E1002	Alice	James		123457	1972-0	1972-07-31		980 Berry In, Elgin,IL		200	80000		30002		5	
E1003	Steve	teve Wells		123458	1980-0	8-10	м	291 Springs, Gary,JL		300	50000 30002			5		
IOB_HIST	ORY						JO	OBS								
EMPL_ID	START_D	START_DATE JOBS		_ID DEPT_II		ID	JC	OB_IDENT JOB_TIT		LE N		MIN_	IIN_SALARY MA		X_SALARY	
E1001	2000-01	2000-01-30 100		2			10	00 Sr. Archi		itect		60000	60000		100000	
E1002	2010-08	2010-08-16			5		20	200 Sr.Softw		vareDeveloper 6		60000	50000 8		00	
E1003	2016-08	2016-08-10 300		5			30	00 Jr.Softw		vareDeveloper 40		40000	0000 600		00	
DEPARTM	ENTS							LOCATI	ONS							
DEPT_ID_DE	P DEP_NA	DEP_NAME			MANAGER_ID			LOCT_ID		DEP_ID_LOC						
2	Archite	Architect Group			30001			L0001		2						
5	Softwar	Software Development			30002			L0002		5						
7	Davis 1	Design Team			30003			L0003		7						

Load the database

Using the skills acquired in the previous modules, you should first create the database in MySQL. Follow the steps below:

- 1. Open the phpMyAdmin interface from the Skills Network Toolbox in Cloud IDE.
- 2. Create a blank database named HR. Use the script shared in the link below to create the required tables. Script Create Tables.sql
- 3. Download the files in the links below to your local machine (if not already done in previous labs).

Jobs. csv JobsHistory.csv

Locations. csv Employees. csv

4. Use these files to the interface as data for respective tables in the HR database.

Accessing multiple tables with sub-queries

Let us see some examples of queries requiring multiple table access using sub-queries.

1. Retrieve only the EMPLOYEES records corresponding to jobs in the JOBS table.

For such a question, you can implement the sub-query in the WHERE clause, such that the overlapping column of JOD ID can identify the required entries.

1. SELECT * FROM EMPLOYEES WHERE JOB_ID IN (SELECT JOB_IDENT FROM JOBS);

Copied!

The expected output would look as shown below.

1/2/2024, 6:18 PM 1 of 4



2. Retrieve JOB information for employees earning over \$70,000.

For this example, retrieve the details from the JOBS table, which has common IDs with those available in the EMPLOYEES table, provided the salary in the EMPLOYEES table is greater than \$70,000. You can write the query as:

- 2. 2
- 1. SELECT JOB_TITLE, MIN_SALARY, MAX_SALARY, JOB_IDENT
- WHERE JOB_IDENT IN (select JOB_ID from EMPLOYEES where SALARY > 70000);

Copied!

The expected output would look as shown below.



Accessing multiple tables with Implicit Joins

Let us see some examples of queries that require access of multiple tables using Implicit Joins.


1. Retrieve only the EMPLOYEES records corresponding to jobs in the JOBS table.

The same question as before, but now we will use Implicit Join to retrieve the required information. For this, you will combine the tables based on job IDs. Using the following query for this:

- 2. 2 3. 3 1. SELECT *
- FROM EMPLOYEES, JOBS
 WHERE EMPLOYEES.JOB_ID = JOBS.JOB_IDENT;

Copied!

The expected output is shown below.



2. Redo the previous query using shorter aliases for table names.

Note that the tables in question can be assigned shorter aliases. This is especially helpful in cases where specific columns are to be accessed from different tables. The query would be modified to:

- 1. 1
- 3. 3


2 of 4 1/2/2024, 6:18 PM

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refre

```
1. SELECT *
2. FROM EMPLOYEES E, JOBS J
3. WHERE E.JOB_ID = J.JOB_IDENT;
```

Copied!

The output would look like:




Notice that the two queries are giving the same response.

3. In the previous query, retrieve only the Employee ID, Name, and Job Title.

Notice that Job Title is a column of the JOBS table, and other details are coming from the EMPLOYEES table. The two tables will be joined on Job ID. The query would be as follows:

- 1. SELECT EMP_ID,F_NAME,L_NAME, JOB_TITLE
 2. FROM EMPLOYEES E, JOBS J
 3. WHERE E.JOB_ID = J.JOB_IDENT;
- Copied!

The output would look as shown below.



4. Redo the previous query, but specify the fully qualified column names with aliases in the SELECT clause.

The column names can also be prefixed with table aliases to keep track of where each column is coming from. The above query will be modified as shown below.

- 1. 1 2. 2 3. 3
- 1. SELECT E.EMP_ID, E.F_NAME, E.L_NAME, J.JOB_TITLE
 2. FROM EMPLOYEES E, JOBS J
 3. WHERE E.JOB_ID = J.JOB_IDENT;

Copied!

The expected output is:

3 of 4 1/2/2024, 6:18 PM



Practice problems

- 1. Retrieve only the list of employees whose JOB_TITLE is Jr. Designer.
- a. Using sub-queries
- b. Using Implicit Joins
- ► Solution
 - 2. Retrieve JOB information and a list of employees whose birth year is after 1976.
- a. Using sub-queries
- b. Using implicit join
- ► Solution

Conclusion

Congratulations! You have completed this lab and are ready for the next topic.

At the end of this lab, you are now able to:

- Write SQL queries that access more than one table
- write SQL queries that access multiple tables using a nested statement in the WHERE clause
 Build queries with multiple tables in the FROM clause
 Write Implicit Join queries with join criteria specified in the WHERE clause
 Specify aliases for table names and qualify column names with table aliases

Author(s)

Abhishek Gagneja

Lakshmi Holla

Malika Singla

Changelog

Date	Version	Changed by	Change Description
2023-10-13	0.6	Mary Stenberg	QA pass with edits
2023-10-13	0.5	Misty Taylor	ID Check
2023-10-10	0.4	Abhishek Gagneja	Instructions updated
2023-05-10	0.3	Eric Hao & Vladislav Boyko	Updated Page Frames
2023-05-04	0.2	Rahul Jaideep	Updated Markdown file
2021-11-01	0.1	Lakshmi Holla, Malika Singla	Initial Version

© IBM Corporation 2023. All rights reserved.

1/2/2024, 6:18 PM 4 of 4