CNT 4704
Analysis of Computer Communication Networks

Computer Networks and the Internet (Cont'd)

Lecture-2

Mesut Ozdag, Ph.D.

Department of Computer Science

Fall 2023

HOUSEKEEPING & ACKNOWLEDGEMENT

This class session is
being recorded

- An ample portion of the material is derived/borrowed from Copyrighted ppt. slides of J.F. Kurose, K.W. Ross 1996-2020. All Rights Reserved.
- Original material can be found on: https://gaia.cs.umass.edu/kurose_ross/ppt.htm

UCF

Chapter 1: Introduction roadmap

1.1 What is the Internet?

1.2 Network edge

- end systems, access networks, links

1.3 Network core

- Packet switching, circuit switching, network structure

1.4 Delay, loss, throughput in networks

1.5 Protocol layers, service models

1.6 Networks under attack: security

1.7 History

The Network Core

- mesh of interconnected routers
- packet-switching: hosts break application-layer messages into ***packets***
  - **forward** packets from one router to the next, across links on path from source to destination
  - each packet transmitted at full link **capacity**



Host: sends packets of data (reminder)

host sending function:

- takes application message
- breaks into smaller chunks, known as *packets*, of length *L* bits
- transmits packet into access network at *transmission rate R*
  - link transmission rate, aka link *capacity, aka link bandwidth*



$$\text{packet transmission delay} = \text{time needed to transmit } L\text{-bit packet into link} = \frac{L \text{ (bits)}}{R \text{ (bits/sec)}}$$

Two key network-core functions

Forwarding:

- aka "switching"
- *local* action: move arriving packets from router's input link to appropriate router output link



destination address in arriving packet's header

Routing:

- *global* action: determine source-destination paths taken by packets
- routing algorithms


routing
45 h
3,053 miles
48 h
3,309 miles
San Jose
Northampton
United States

forwarding
forwarding
45 h
3,053 miles
48 h
3,309 miles
United States
San Jose
Northampton
Sacramento
Cleveland

Packet-switching: store-and-forward



- Transmission delay: takes L/R seconds to transmit (push out) L-bit packet into link at R bps
- *Store and forward: entire* packet must arrive at router before it can be transmitted on next link

One-hop numerical example:

- L = 10 Kbits
- R = 100 Mbps
- one-hop transmission delay = 0.1 msec

Packet-switching: queueing delay, loss



Packet queuing and loss: if arrival rate (in bps) to link exceeds transmission rate (bps) of link for a period of time:

- packets will queue, waiting to be transmitted on output link
- packets can be dropped (lost) if memory (buffer) in router fills up

Alternative to packet switching: circuit switching

end-end resources allocated to, reserved for "call" between source and destination

- in diagram, each link has four circuits.
  - call gets 2nd circuit in top link and 1st circuit in right link.
- dedicated resources: no sharing
  - circuit-like (guaranteed) performance
- circuit segment idle if not used by call (no sharing)
- commonly used in traditional telephone networks



Circuit Switching: FDM and TDM

Frequency Division Multiplexing (FDM)

- optical, electromagnetic frequencies divided into (narrow) frequency bands
- each call allocated its own band, can transmit at max rate of that narrow band



Time Division Multiplexing (TDM)

- time divided into slots
- each call allocated periodic slot(s), can transmit at maximum rate of (wider) frequency band, but only during its time slot(s)



GSM

Circuit Switching: FDM and TDM



Packet switching versus circuit switching

packet switching allows more users to use network!

Example:

- 1 Gb/s link
- each user:
  - 100 Mb/s when "active"
  - active 10% of time



- *circuit-switching:* 10 users
- *packet switching:* with 35 users, probability > 10 active at same time is less than .0004 *

Q: how did we get value 0.0004?

A: Hw problem

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive

Packet switching versus circuit switching

Is packet switching a "slam dunk winner"?

- great for "bursty" data – sometimes has data to send, but at other times not
  - resource sharing
  - simpler, no call setup
- excessive congestion possible: packet delay and loss due to buffer overflow
  - protocols needed for reliable data transfer, congestion control
- *Q:* How to provide circuit-like behavior with packet-switching?
  - bandwidth guarantees traditionally used for audio/video applications

Internet structure: a "network of networks"

- Hosts connect to Internet via access Internet Service Providers (ISPs)
  - residential, enterprise (company, university, commercial) ISPs
- Access ISPs in turn must be interconnected
  - so that any two hosts can send packets to each other
- Resulting network of networks is very complex
  - evolution was driven by economics and national policies
- Let's take a stepwise approach to describe current Internet structure

Internet structure: a "network of networks"

Question: given *millions* of access ISPs, how to connect them together?



Internet structure: a "network of networks"

Question: given *millions* of access ISPs, how to connect them together?



Internet structure: a "network of networks"

Option: connect each access ISP to one global transit ISP?
Customer and provider ISPs have economic agreement.



Internet structure: a “network of networks”

But if one global ISP is viable business, there will be competitors ….



Internet structure: a "network of networks"

But if one global ISP is viable business, there will be competitors …. who will want to be connected



Internet structure: a "network of networks"

… and regional networks may arise to connect access nets to ISPs



Internet structure: a "network of networks"

… and content provider networks (e.g., Google, Microsoft, Akamai) may run their own network, to bring services, content close to end users



Internet structure: a "network of networks"



At "center": small # of well-connected large networks

- "tier-1" commercial ISPs (e.g., Level 3, Sprint, AT&T, NTT), national & international coverage
- content provider networks (e.g., Google, Facebook): private network that connects its data centers to Internet, often bypassing tier-1, regional ISPs

CHAPTER 1: INTRODUCTION ROADMAP

1.1 What is the Internet?

1.2 Network edge

- end systems, access networks, links

1.3 Network core

- Packet switching, circuit switching, network structure

1.4 Delay, loss, throughput in networks

1.5 Protocol layers, service models

1.6 Networks under attack: security

1.7 History

How do packet loss and delay occur?

packets *queue* in router buffers

- packets queue, wait for turn
- arrival rate to link (temporarily) exceeds output link capacity: packet loss



Packet delay: four sources



$$d_{\text{nodal}} = d_{\text{proc}} + d_{\text{queue}} + d_{\text{trans}} + d_{\text{prop}}$$

d_{proc}: nodal processing

- check bit errors
- determine output link
- typically < msec

d_{queue}: queueing delay

- time waiting at output link for transmission
- depends on congestion level of router

Packet delay: four sources



$$d_{nodal} = d_{proc} + d_{queue} + d_{trans} + d_{prop}$$

d_{trans}: transmission delay:

- L: packet length (bits)
- R: link *transmission rate (bps)*
- $d_{trans} = L/R$

d_{prop}: propagation delay:

- d: length of physical link
- s: propagation speed (~2x10^8 m/sec)
- $d_{prop} = d/s$

d_{trans} and d_{prop}
very different

* Check out the online interactive exercises:
http://gaia.cs.umass.edu/kurose_ross

Questions?