

UiO : **Department of Physics**  
University of Oslo

# **Application of Supervised Machine Learning to the Search for New Physics in ATLAS data**

A Study of Ordinary Dense, Parameterized  
and Ensemble Networks and their Application  
to High Energy Physics

**William Hirst**

**May 25, 2023**

## 1 Introduction & Motivation

## 2 The Implementation

## 3 Methods & Results

## 4 Conclusion & Outlook

## 1 Introduction & Motivation



## 2 The Implementation

## 3 Methods & Results

## 4 Conclusion & Outlook



# Why apply machine learning to HEP problems?

- The standard model (SM) of particle physics is very successful, but not complete
  - Neutrino masses
  - Hierarchy problem
- Large amount of data
- Machine learning (ML)
  - Event reconstruction
  - Particle classification
  - Creating search regions



# How do we search for new physics?

- Compare theory with experiment
  - Experiment: Measured
  - Theory: Simulated (background and signal)
- Search regions
- Expected significance
  - $Z_{\text{exp}} \approx \frac{\text{signal}}{\sqrt{\text{background}}}$
- Difficult to separate  $\rightarrow$  ML



# The Implementation

**1** Introduction & Motivation


**2** The Implementation

**3** Methods & Results

**4** Conclusion & Outlook

# The SUSY signal

- Chargino-neutralino production
- Free parameters → masses
- Nr-of-Events(Mass)





# A summary of the applied methods

## ■ Three neural network variants

- Ordinary dense neural network
- Ensemble networks utilizing Local-Winner-Takes-All (LWTA) layers
- Parameterized neural networks (PNN)

## ■ One boosted decision tree method



# Training strategy

- Objective
  - Background → 0
  - Signal → 1
- 80% training and 20% validation
- Early stopping criteria
  - Train as long as performance on validation set improves
  - Patience 10 epochs
  - Reset weights to best epoch

## 1 Introduction & Motivation

## 2 The Implementation



## 3 Methods & Results

## 4 Conclusion & Outlook

# Ordinary dense neural network




# Compare one-mass approach to several-masses approach




# Parameterized neural network

- Long-term memory
- PNN → signal includes mass parameter in feature set
- Background assigned parameters randomly using same distribution as signal
- Motivation
  - Network will associate parameters with trends in the data




# Ensemble methods - LWTA

- Local-Winner-Takes-All
- Competing nodes - Units
- Encode information in pattern specific pathways





# Channel-Out, SCO and Maxout

Layer	Separate weights	Static units
Channel-Out	✓	✓
SCO	✓	X
Maxout	X	✓





# Visualization and study of sparse pathways

- Visualize the activation and paths of randomly sampled events
- The bolder the line the more frequently the path is used.
- Color of lines
  - Pink: SM background
  - Blue: SUSY signal




# Visualization and study of sparse pathways


- Visualize the activation and paths of randomly sampled events
- The bolder the line the more frequently the path is used.
- Color of lines
  - Pink: SM background
  - Blue: SUSY signal



# Comparing activation of Maxout with SCO




Maxout



SCO

# Ensemble network architecture

**MaxOut:**




# Comparing sensitivity of channel-out, SCO and maxout


■ Maxout: 24/30

■ SCO: 6/30

- No trend for preferred masses
- Possibly improve without layer on prediction




# Comparing the sensitivity on a subset of the signal




# Increasing sensitivity through a PCA

- Dimensionality reduction
- This analysis
  - Demand conservation of 99.9% of variance/spread
  - 5 features removed




Maxout




PNN

# Comparing methods on full signal grid



# Comparing the methods to previous analysis

- Compare the expected limits to analysis made by ATLAS in 2021 [4]
- Introduce flat uncertainty (20%, 10%, < 1%)
- Why not better sensitivity?



# Conclusion & Outlook

## 1 Introduction & Motivation

## 2 The Implementation

## 3 Methods & Results

## 4 Conclusion & Outlook

## Conclusion & Outlook

- 1 Including a diverse signal set can improve performance
- 2 The LWTA layers improve long-term memory via pattern specific pathways
- 3 PCA increased sensitivity of PNN and maxout model in original signal set
- 4 None of the networks extended expected limit past previous ATLAS analysis
- 5 PNN exhibited bias towards lower masses, whereas maxout model achieved a more balanced sensitivity
- 6 Long-term memory of LWTA layers is promising in future analysis where higher masses are studied

# References

-  Maximilien Brice.  
‘Installing the ATLAS calorimeter. Vue centrale du détecteur ATLAS avec ses huit toroides entourant le calorimètre avant son déplacement au centre du détecteur’.  
<https://cds.cern.ch/record/910381>  
Figure on front page
-  Joao Pequenao.  
‘Event Cross Section in a computer generated image of the ATLAS detector.’.  
<https://cds.cern.ch/record/1096081>  
Figure on slide 3
-  ATLAS Collaboration.  
‘ATLAS event at 900 GeV - 6 May 2015 - Run 264034 lb 659 event 11526514’.  
<https://cds.cern.ch/record/2015238>  
Figure on slide 4
-  ATLAS Collaboration [4].  
‘Search for chargino–neutralino pair production in final states with three leptons and missing transverse momentum in  $\sqrt{s} = 13$  TeV pp collisions with the ATLAS detector’.  
<http://arxiv.org/abs/2106.01676>



**William Hirst**



**Application of Supervised Machine Learning  
to the Search for New Physics in ATLAS data**

A Study of Ordinary Dense, Parameterized and Ensemble Networks and their Application to High Energy Physics