

STANDARD ARRIVAL CHART-INSTRUMENT

VAR4° W

ATIS 127.05
APP 119.625(132.15)
TWR 118.875(118.2)

ZSWZ WENZHOU/Longwan
RWY21

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM



NOT TO SCALE

SHENGZHOU
113.4 SHZ
... ..
CH 81X
N29 36.0E120 49.0

TL 3600
TA 3000
3300(QNH \geq 1031HPA)
2700(QNH \leq 979HPA)

Note:

1. Holding MAX IAS 400kmH. Initial approach MAX IAS 380kmH.
2. ❶ It is available to gain the ALT for holding pattern if cannot get the required ALT by ATC: BEGMO-02A, OKATO-02A.
❷ ALT less than 2100m, use BEGMO-04A.

YUNHE
244 BZ
....
N28 06.1E119 33.7

F
D14.5DST
N27 59.4
E120 39.2

IAF
D15.0DST
1800

WENZHOUS
116.4 WNZ
CH 111X
N27 55.8E120 51.8

IAF
D12.5WNZ
N28 00.0
E121 05.0

BEGMO
D65.7DST
N28 00.0
E121 50.0
8400
or by ATC

BEGMO-044
(by ATC)
D12.5WNZ

D 2 BEG
D27.0DS

N27 51.2
E121 07.5
5500
or by AT

OKATO
D51.3DST
N27 35.1
E121 34.6
6300
or by ATC

OKATO
7.0DST
7 39.8
1.07.5

by ATC


[DONGSHAN
 109.2 DST
 -.. -.. -
 CH 29X
 N27 45.0E120 37.8

RUPOX
D44.2DST
N27 07.6
E120 11.3

BZ-02A
LJG-02A
SHZ-02A

LIANJIANG
117.6 L JG

CH 123X
N26 13.2E119 32.9



Changes: APP FREQ.