

# STANDARD ARRIVAL CHART-INSTRUMENT

VAR 4° W

ATIS 127.05  
APP 119.625(132.15)  
TWR 118.875(118.2)

ZSWZ WENZHOU/Longwan  
RNAV RWY03

BEARINGS ARE MAGNETIC  
ALTITUDES, ELEVATIONS  
AND HEIGHTS IN METERS  
DME DISTANCES IN  
NAUTICAL MILES  
DISTANCES IN KM

TL 3600  
TA 3000  
3300(QNH≥1031HPA)  
2700(QNH≤979HPA)

1. GNSS REQUIRED
2. RNP1



YUNHE  
244 BZ  
N28 06.1E119 33.7

SHENGZHOU  
113.4 SHZ  
CH 81X  
N29 36.0E120 49.0

SHZ-5/F  
83  
190°  
REMIM

SHZ-5/F  
97  
190°  
WZ402  
1800

SHZ-5/F  
27  
190°  
WZ403  
2100

SHZ-5/F  
27  
190°  
WZ405  
1800

SHZ-5/F  
27  
190°  
WZ406  
5500

SHZ-5/F  
27  
190°  
WZ509  
1800

SHZ-5/F  
27  
190°  
WZ508  
1800

SHZ-5/F  
27  
190°  
WZ505  
1800

SHZ-5/F  
27  
190°  
WZ508  
1800

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

DONGSHAN  
109.2 DST  
CH 29X  
N27 45.0E120 37.8

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ509  
1800  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ401  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ406  
5500  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ505  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC

WZ508  
1800  
or by ATC


MAX 400kmH (for holding)

Note:

1. "WZ508" and "DST" are fly-over point for holding procedure.

RUPOX

LIANJIANG  
117.6 LJG  
CH 123X  
N26 13.2E119 32.9



Changes: APP FREQ.