STANDARD ARRIVAL CHART-INSTRUMENT VAR5° W

ATIS 127.85 APP01 120.45(124.75) APP02 119.125(124.75) TWR 118.35(123.65)

ZBSJ SHIJIAZHUANG/Zhengding RNAV RWY33

BEARINGS ARE MAGNETIC ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS DME DISTANCES IN NAUTICAL MILES DISTANCES IN KM 3600 3000 3300(QNH≥1031hPa) 2700(QNH≤979hPa) TL TA 1. RNAV1 2. GNSS REQUIRED 3. RADAR REQUIRED N NOT TO SCALE ZANGANGZHEN 403 JB LARAD N39 02.6E116 11.9 8 LA723 JB-16A,18A LA601 3000 3000 **ENGIL** 1 JB602 1500 2400 6 SAKOD MAX 425kmH XINGTANG 1200 〜 ご 235 OC N38 27.3E114 33.3 WUJI 272 FL N38 14.8E114 53.4 1200 MAX 340kmH \bigcirc ISGOD 2700 900 MAX 340kmH -ZHENGDING-117.7 SJW 1 CH 124X 1200 TAIYUAN N38 16.8E114 41.9 MAX 425kmH 113.1 TYN CH 78X N37 44.9E112 37.2 Note: NDB "OC" and "FL" are fly-over points for holding procedure. 1150 SJW ₅₀₀ MSA 46km Changes: APPOI, APPO2.