ATIS 126.4 TWR 118.45 (124.35) GND 121.60(124.35) APN 121.725 ZSFZ FUZHOU/Changle AERODROME CHART BEARINGS ARE MAGNETIC ALTITUDES, DISTANCES, ELEVATIONS AND HEIGHTS IN METERS RWY Direction Bearing strength(PCN) TWY A4-A7, E, A(N of A10), Nroth&South apron: 51/R/B/W/T 030° 03 210° 21 RWY, TWYs: 83/R/B/W/T - ILS/LOC 110.7 ICL ELEV14.3/ North APRON ILS/GP 335.0 Note: 1. A/C are forbidden to enter RWY via TWY A4, A5, A6, A7. 2. Taxiing speed shall not exceed 15km/h while aircraft with wing span 65m taxiing along B between B8 and B9. -ILS/GP 330.2 ELEV6. 720 1080m 360 360 South APRON - ILS/LOC-110.3 INN PAPI. · PALS CAT I 3 PALS CAT I

TAKE-OFF MINIMA(WITH RELIABLE ALTN)(m) RWY03/21			LIGHTS	
			DWV07	DWV01
	REDL	NIL(Day only)	RWY03	RWY21
A B C	RVR 400 VIS 800	RVR 500 VIS 800	PALS CAT I SFL PAPI REDL RCLL	PALS CAT I SFL PAPI REDL RCLL
Changes: Apron		•		