

STANDARD ARRIVAL CHART-INSTRUMENT

VAR3° W

ATIS 126.4
APP 119.45(133.05) AP01
124.85(133.05) AP02
TWR 118.45(124.35)


ZSFZ FUZHOU/Changle

RNAV RWY21

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM

TL 3600
TA 3000
3300(QNH≥1031HPA)
2700(QNH≤979HPA)

1. RNAV1
2. GNSS REQUIRED
3. RADAR REQUIRED



FZ011, FZ015, LYG, FQG are fly over points for holding procedure.

(MAX 450km/h for holding procedure)

(MAX 450km/h for holding procedure)

(MAX 450km/h for holding procedure)

(MAX 450km/h for holding procedure)

XINGLIN
114.7 XLN
CH 94X
N24 33.9E118 00.9

LIANJIANG
117.6 LYG
CH 123X
N26 13.2E119 32.9

FUQING
117.4 FQG
CH 121X
N25 44.4E119 23.1

FUZHOU
116.8 FOC
CH 115X
N25 56.6E119 39.8

1750
FQG
1250
MSA 46km

Changes: Speed limits, holding procedure.