

AERODROME CHART


RWY	Direction	Bearing strength(PCN)
03	032°	TWYs A10, D3-D5, 77/R/B/W/T T1&T2&T3(apron 3), cargo apron, south deicing apron:
21	212°	TWYs A2,A4,A8: 73/F/B/X/T TWYs A, A1, A3, A7, A9, 72/R/B/W/T T1&T2(apron 2): RWY, TWYs A5, A6, D1, D2, 66/R/B/W/T T1&T2(apron 1):

ATIS 126.65
TWR 118.35(130.0)
GND 121.6
EMG 121.5

ZLIC YINCHUAN/Hedong


N38°19.2'E106°23.6' ELEV 1141m

BEARINGS ARE MAGNETIC
ALTITUDES, DISTANCES,
ELEVATIONS AND HEIGHTS
IN METERS



Note:

1. A/C are strictly forbidden to enter RWY by TWYs A3, A4, A5, A6, A7 without ATC clearance.
2. HS1-HS2: Hot Spots.
3. Under construction



TAKE-OFF MINIMA(WITH RELIABLE ALTN)(M)					LIGHTS	
RWY	ACFT Type		REDL	NIL(Day only)	RWY03	RWY21
03/21	2 TURB ENG	CAT A.B.C	RVR 400 VIS 800	RVR 500 VIS 800	PALS CAT I SFL PAPI REDL RCLL	PALS CAT I PAPI REDL RCLL
	or 3&4 ENG	CAT D				
	Other		VIS 1600			

Changes: ARP position.