TCP Server-Client implementation in C

Prerequisites – Socket Programming in C/C++, TCP and UDP server using select, UDP Server-Client implementation in C

If we are creating a connection between client and server using TCP then it has a few functionalities like, TCP is suited for applications that require high reliability, and transmission time is relatively less critical. It is used by other protocols like HTTP, HTTPs, FTP, SMTP, Telnet. TCP rearranges data packets in the order specified. There is absolute guarantee that the data transferred remains intact and arrives in the same order in which it was sent. TCP does Flow Control and requires three packets to set up a socket connection before any user data can be sent. TCP handles reliability and congestion control. It also does error checking and error recovery. Erroneous packets are retransmitted from the source to the destination.

The entire process can be broken down into the following steps:



The entire process can be broken down into following steps:

TCP Server –

1. using create(), Create TCP socket.
2. using bind(), Bind the socket to server address.
3. using listen(), put the server socket in a passive mode, where it waits for the client to approach the server to make a connection
4. using accept(), At this point, connection is established between client and server, and they are ready to transfer data.
5. Go back to Step 3.

TCP Client –

1. Create TCP socket.
2. connect newly created client socket to server.

TCP Server:

C

```
#include <stdio.h>
#include <netdb.h>
#include <netinet/in.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <unistd.h> // read(), write(), close()
#define MAX 80
#define PORT 8080
#define SA struct sockaddr
```

```c
// Function designed for chat between client and server.
void func(int connfd)
{
    char buff[MAX];
    int n;
    // infinite loop for chat
    for (;;) {
        bzero(buff, MAX);

        // read the message from client and copy it in buffer
        read(connfd, buff, sizeof(buff));
        // print buffer which contains the client contents
        printf("From client: %s\t To client : ", buff);
        bzero(buff, MAX);
        n = 0;
        // copy server message in the buffer
        while ((buff[n++] = getchar()) != '\n')
            ;

        // and send that buffer to client
        write(connfd, buff, sizeof(buff));

        // if msg contains "Exit" then server exit and chat ended.
        if (strncmp("exit", buff, 4) == 0) {
            printf("Server Exit...\n");
            break;
        }
    }
}

// Driver function
int main()
{
    int sockfd, connfd, len;
    struct sockaddr_in servaddr, cli;

    // socket create and verification
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
    if (sockfd == -1) {
        printf("socket creation failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully created..\n");
    bzero(&servaddr, sizeof(servaddr));

    // assign IP, PORT
    servaddr.sin_family = AF_INET;
    servaddr.sin_addr.s_addr = htonl(INADDR_ANY);
    servaddr.sin_port = htons(PORT);

    // Binding newly created socket to given IP and verification
    if ((bind(sockfd, (SA*)&servaddr, sizeof(servaddr))) != 0) {
```

```
        printf("socket bind failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully binded..\n");

    // Now server is ready to listen and verification
    if ((listen(sockfd, 5)) != 0) {
        printf("Listen failed...\n");
        exit(0);
    }
    else
        printf("Server listening..\n");
    len = sizeof(cli);

    // Accept the data packet from client and verification
    connfd = accept(sockfd, (SA*)&cli, &len);
    if (connfd < 0) {
        printf("server accept failed...\n");
        exit(0);
    }
    else
        printf("server accept the client...\n");

    // Function for chatting between client and server
    func(connfd);

    // After chatting close the socket
    close(sockfd);
}
```

TCP Client:

C

```
#include <arpa/inet.h> // inet_addr()
#include <netdb.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <strings.h> // bzero()
#include <sys/socket.h>
#include <unistd.h> // read(), write(), close()
#define MAX 80
#define PORT 8080
#define SA struct sockaddr
void func(int sockfd)
{
    char buff[MAX];
    int n;
```

```c
    for (;;) {
        bzero(buff, sizeof(buff));
        printf("Enter the string : ");
        n = 0;
        while ((buff[n++] = getchar()) != '\n')
            ;
        write(sockfd, buff, sizeof(buff));
        bzero(buff, sizeof(buff));
        read(sockfd, buff, sizeof(buff));
        printf("From Server : %s", buff);
        if ((strncmp(buff, "exit", 4)) == 0) {
            printf("Client Exit...\n");
            break;
        }
    }
}

int main()
{
    int sockfd, connfd;
    struct sockaddr_in servaddr, cli;

    // socket create and verification
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
    if (sockfd == -1) {
        printf("socket creation failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully created..\n");
    bzero(&servaddr, sizeof(servaddr));

    // assign IP, PORT
    servaddr.sin_family = AF_INET;
    servaddr.sin_addr.s_addr = inet_addr("127.0.0.1");
    servaddr.sin_port = htons(PORT);

    // connect the client socket to server socket
    if (connect(sockfd, (SA*)&servaddr, sizeof(servaddr))
        != 0) {
        printf("connection with the server failed...\n");
        exit(0);
    }
    else
        printf("connected to the server..\n");

    // function for chat
    func(sockfd);

    // close the socket
    close(sockfd);
}
```

Compilation –

Server side:

gcc server.c -o server

./server

Client side:

gcc client.c -o client

./client

Output –

Server side:

```
Socket successfully created..
Socket successfully binded..
Server listening..
server accept the client...
From client: hi
     To client : hello
From client: exit
     To client : exit
Server Exit...
```

Client side:

```
Socket successfully created..
connected to the server..
Enter the string : hi
From Server : hello
Enter the string : exit
From Server : exit
Client Exit...
```

Last Updated : 18 Nov, 2022

Similar Reads


TCP Client-Server Program to Check if a Given String is Palindrome


UDP Server-Client implementation in C++

UDP Client Server using connect | C implementation



Java Implementation of Diffie-Hellman Algorithm between Client and Server



Setting up local DNS server between client-server machines



TCP with explicit link failure notification (TCP-ELFN)



TCP Tahoe and TCP Reno



Reverse a string in C/C++ using Client Server model

Difference between Client-Server and Peer-to-Peer Network



Two way communication between Client and Server using Win32 Threads

Previous

wmemset() in C/C++ with Examples

Next

Open shortest path first (OSPF) - Set 2

Article Contributed By :

Yogesh Shukla 1

Yogesh Shukla 1

+ Follow

Vote for difficulty

Current difficulty : Hard

Easy | Normal | Medium | Hard | Expert

Improved By : Anviti_Sr, sweetyty, simmytarika5, sumitgumber28, arubrahjo, harendrakumar123, armanbaig012

Article Tags : c-network-programming , system-programming , C Language , Computer Networks , Linux-Unix

Practice Tags : Computer Networks

Improve Article | Report Issue

201305

feedback@geeksforgeeks.org

Lodash

Computer Science

GATE CS Notes

Operating Systems

Computer Network

Database Management System

Software Engineering

Digital Logic Design

Engineering Maths

Python

Python Programming Examples

Django Tutorial

Python Projects

Python Tkinter

OpenCV Python Tutorial

Python Interview Question

Data Science & ML

Data Science With Python

Data Science For Beginner

Machine Learning Tutorial

Maths For Machine Learning

Pandas Tutorial

NumPy Tutorial

NLP Tutorial

Deep Learning Tutorial

DevOps

Git

AWS

Docker

Kubernetes

Azure

GCP

Competitive Programming

Top DSA for CP

Top 50 Tree Problems

Top 50 Graph Problems

Top 50 Array Problems

Top 50 String Problems

Top 50 DP Problems

Top 15 Websites for CP

System Design

What is System Design

Monolithic and Distributed SD

Scalability in SD

Databases in SD

High Level Design or HLD

Low Level Design or LLD

Top SD Interview Questions

Interview Corner

Company Wise Preparation

Preparation for SDE

Experienced Interviews

Internship Interviews

Competitive Programming

Aptitude Preparation

GfG School

CBSE Notes for Class 8

CBSE Notes for Class 9

CBSE Notes for Class 10

CBSE Notes for Class 11

CBSE Notes for Class 12

English Grammar

Commerce

Accountancy

Business Studies

Economics

Management

Income Tax

Finance

Statistics for Economics

UPSC

Polity Notes

Geography Notes

History Notes

Science and Technology Notes

Economics Notes

Important Topics in Ethics

UPSC Previous Year Papers

SSC/ BANKING

SSC CGL Syllabus

SBI PO Syllabus

SBI Clerk Syllabus

IBPS PO Syllabus

IBPS Clerk Syllabus

Aptitude Questions

SSC CGL Practice Papers

Write & Earn

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships