

Using Microsoft Windows Command Prompt Tools for Administration

Estimated time needed: **10** minutes

After reading this article, you will be able to:

- List and describe several Windows OS features and their associated commands.

The Command Line Interface (CLI) tool, or the CMD prompt tool, is a text-based interface in the Microsoft Windows operating system that lets users interact with the system by executing commands. It provides a way to perform various tasks, run programs, manage files and folders, configure system settings, and troubleshoot issues through typed commands.

Group Policy Management

Group Policy is a feature in Windows OS that lets system administrators manage and control user and computer settings on a network. Two essential commands for managing and troubleshooting Group Policy in Windows are `gpupdate` and `gpresult`.

Command: `gpupdate`

The `gpupdate` command ensures policy changes are applied immediately, allowing for the timely enforcement of new policies. It's used to update Group Policy settings on a Windows computer.

When you run `gpupdate` in the command prompt, it refreshes the Group Policy settings, immediately applying any changes or new policies to the system. The command has various options to specify the update, such as `/target:user` for updating user policies or `/target:computer` for updating computer policies.

Command: `gpresult`

The `gpresult` command provides visibility into the applied policies, helping administrators verify policy settings and diagnose any issues related to Group Policy application. The `gpresult` command displays Group Policy result information for a user or computer in a Windows OS.

By running `gpresult` in the command prompt, you can view the applied Group Policy settings and their sources and details about the applied policies and their results. The command provides insights into which Group Policies are in effect and helps troubleshoot policy-related issues. The `/r` option generates a summary report, while the `/v` option provides verbose output with detailed policy information.

Drive Letters in Windows

Drive letters in Windows identify storage devices like hard drives, SSDs, USB drives, and network drives. Working with different drives using command line tools enables users to manage files and directories across various storage devices. By understanding drive letters and using commands like `vol`, `chdir`, and `cd`, you can access, explore, and manipulate data on different drives from the command line interface, providing greater flexibility and control over your file management tasks.

Command: `vol`

Using CMD prompt, the `vol` command displays the volume information of a particular drive. By specifying the drive letter, such as `vol C:`, you can view details such as the volume label, serial number, file system type, and the total available and free space on that drive. This command is helpful for quickly gathering information about a specific drive before performing file management tasks.

Command: `chdir`

The `chdir` command, or `cd`, lets users change the current directory to a different drive. By specifying the drive letter followed by a colon, such as `cd D:`, you can switch to the selected drive.

Command: `cd`

The `cd` command is used to navigate through directories within the current drive. It lets you change the working directory to a different folder within the same drive.

By typing `cd` followed by the directory path, you can move to a specific folder. For example, `cd Documents` will switch to the "Documents" folder within the current drive.

System Maintenance and Information

The following essential system maintenance and information commands provide valuable tools for managing and maintaining a Windows system. They let users control system power, diagnose and repair system files and disk errors, manage disk partitions, and obtain information about the Windows version installed on the computer. Understanding these commands can help ensure system stability, performance, and compatibility.

Command: `shutdown`

The `shutdown` command is used to shut down or restart a computer in Windows OS. This command lets you make a graceful system shutdown, restart the computer, or schedule a shutdown or restart at a specific time.

By specifying different options and parameters, you can control the shutdown behavior, display a custom message, and select a time delay before the shutdown or restart occurs. The `shutdown` command provides a convenient way to manage the system's power state.

Command: `sfc`

The `sfc` (System File Checker) command is used to check and repair system files in Windows. Running `sfc/scannow` in the command prompt scans the system files for integrity violations and attempts to repair any corrupted or missing files. It is a useful command for resolving issues related to system file corruption, which can cause

various problems, such as application crashes or system instability.

Command: chkdsk

The `chkdsk` command is used to scan and repair disk errors in Windows. When you run `chkdsk` followed by a drive letter (e.g., `chkdsk C:`), it checks the file system and disk for errors and tries to fix them if found.

This command can identify and repair bad sectors, file system inconsistencies, and other disk-related issues. Running `chkdsk` with no parameters displays the status of the disk and file system.

Command: diskpart

The `diskpart` command is a disk partitioning and management tool in Windows. It interfaces creating, deleting, formatting, and managing disk partitions. By running `diskpart` in the command prompt, you enter the diskpart utility, where you can execute commands to manage disks, partitions, and volumes.

Diskpart allows for advanced disk management operations, such as extending or shrinking partitions, converting disk formats, and assigning drive letters.

Command: winver

The `winver` command is used to check the Windows version and build information. When executed in the command prompt, it opens a dialog box that displays the version number, build number, and release information of the installed Windows OS.

This command is helpful for quickly verifying the Windows version and ensuring compatibility with specific software or troubleshooting issues that might be version specific.

Command: format

In Windows, the `format` command is used to format disks or drives, letting you prepare a chosen disk or drive for storage by erasing all existing data. It effectively wipes out all data on the selected disk or drive and readies it for storing fresh data.

When executing the `format` command, specify the drive letter or the volume name followed by the file system type (for example, NTFS, FAT32).

- An example that formats the C drive with the NTFS file system is:
`format c:/FS:NTFS`
- Another example that formats the D drive with the FAT32 file system is:
`format d:/FS:FAT32`

A disk or drive should be formatted cautiously, as it permanently deletes all data on the selected storage device.

Managing Files and Directories

Managing files and directories is essential to organizing and maintaining your computer file system. Using commands like `dir`, `md`, `rd`, `ren`, and `del` in the CMD prompt tool, you can efficiently navigate through directories, create new directories, remove unwanted directories, rename directories, and delete files.

Command: dir

The `dir` command is used to display a list of files and directories located in the current directory. It displays information like file names, sizes, and change dates. By default, it shows the contents of the current directory, but you can specify the directory path to view its contents.

The `dir` command is helpful for quickly assessing the files and directories in a particular location.

Command: md

The `md` command is used to create directories or folders. It's followed by the name of the directory you want to make. For example, `md Documents` will create a directory named "Documents" in the current directory.

Command: rd

The `rd` command enables users to remove or delete directories by specifying the directory name they want to remove. For example, if it's empty, `rd Documents` will delete the "Documents" directory file in the current directory.

If the directory has files or subdirectories, you'll need to add the `/s` parameter to remove them recursively. For example, `rd /s Documents` will delete the "Documents" directory and its contents.

Command: ren

The `ren` command is used to rename files and directories. It's followed by the current name of the file or directory, followed by the desired new name.

For example, `ren file.txt newfile.txt` will rename "file.txt" to "newfile.txt" in the current directory.

Similarly, `ren folder oldfolder` will rename the directory "folder" to "oldfolder."

Command: del

The `del` command is used to delete files. It's followed by the name of the file(s) you want to delete. For example, `del file.txt` will delete the file named "file.txt" in the current directory. You can also use wildcards (*) to specify a group of files to delete, such as `del *.txt`, to delete all files with the .txt extension in the current

directory.

File Copying and Backup

File copying and backup tools like `copy`, `xcopy`, and `robocopy` provide various functionality and options for file copying and backup in Windows. Whether you need to copy files or perform advanced file-copying tasks, these command-line tools offer flexibility and control over file management operations.

It's a good idea to use caution when using file copying and backup tools, especially when performing operations that involve data deletion or overwriting.

Command: `copy`

The `copy` command is used to copy files between directories and to other systems. It lets you duplicate or transfer files to a different directory or drive. You can perform file copying operations by specifying the source file(s) and the destination directory or file name.

The `/v` option verifies the integrity of the copied files, while the `/y` option suppresses confirmation prompts when overwriting existing files during the copying process. An example that copies the file "File.txt" from the C drive to the D drive in the specified folder is: `copy C:\Folder\File.txt D:\Folder`

Command: `xcopy`

The `xcopy` command is an advanced file-copying tool that provides more options and flexibility than the basic `copy` command. It lets you copy files and directories with various options, such as:

- Copying subdirectories: `/s`
- Copying empty directories: `/e`
- Preserving file attributes and timestamps: `/a`
- Copying hidden and system files: `/h`

An example that copies the entire contents of the source folder to the destination folder, including subdirectories and empty directories, is:

- `xcopy C:\SourceFolder D:\DestinationFolder /S /E`

The `xcopy` command helps perform advanced file-copying operations, including recursive copies and mirroring directory structures.

Command: `robocopy`

Robust File Copy, or `robocopy`, is a powerful command-line tool for advanced file copying and synchronization in Windows. It offers extensive features, including multi-threading, mirroring, retrying on failed copies, preserving file attributes, and copying NTFS security permissions.

`robocopy` is designed for handling complex file copying scenarios and is especially useful for tasks such as backing up data, migrating files, and synchronizing directories across different drives or network locations.

An example that copies the contents of the source folder to the destination folder is: `robocopy C:\SourceFolder D:\DestinationFolder /MIR`

Hostname and Network

Hostname and network commands provide valuable information and tools for managing and troubleshooting network connections and identifying devices on a network. Using commands such as `hostname`, `ipconfig`, and `ping`, users can gain insights into their network configuration, verify connectivity, and diagnose network-related issues efficiently from the command line interface.

Command: `hostname`

The `hostname` command is used to display the hostname of the computer. When this is entered into the command prompt, it will show you the name assigned to the computer on the network. The hostname is a unique identifier that helps identify and locate devices within a network.

Command: `ipconfig`

The `ipconfig` command checks IP configuration information on a Windows computer. Running `ipconfig` in the command prompt provides details like the IP address, subnet mask, default gateway, and DNS servers for all network interfaces on the system.

The `ipconfig` command is helpful in troubleshooting network connectivity issues, verifying network settings, and gathering information about your computer's network configuration.

Command: `ping`

The `ping` command tests network connectivity between your computer and another device or server on the network. By entering `ping` followed by the IP address or hostname of the target device, the command sends Internet Control Message Protocol (ICMP) echo requests to the specified destination. If the target device responds, the `ping` command displays round-trip time information, suggesting that network connectivity is established.

The `ping` command is commonly used to diagnose network connectivity problems, check if a device is reachable, and measure network latency.

Summary

In this article, you learned that:

- The Group Policy feature allows system administrators to manage and control user and computer settings on a network. The two essential commands for Group Policy are `gpupdate` and `gpresult`.
- Drive Letters identify storage devices like hard drives, SSDs, USB drives, and network drives. The main commands for Drive Letters are `vol`, `chdir`, and `cd`.

- System maintenance and information commands provide tools for managing and maintaining a Windows system. These commands include `shutdown`, `sfc`, `chkdsk`, `diskpart`, `winver`, and `format`.
- Managing files and directories helps to organize and maintain your computer file system. The commands used are `dir`, `md`, `rd`, `ren`, and `del`.
- File copying and backup tools like `copy`, `xcopy`, and `robocopy` allow you to have control over file copying and backup options in Windows.
- Hostname and network commands provide information and tools for managing and troubleshooting network connections and identifying devices on a network. These commands include `hostname`, `ipconfig`, and `ping`.



Skills Network