



Just for Fun - Hands-on Lab: Hacker Typer

Estimated time needed: **10** minutes

About the Lab Instructions and Solutions

Hacker Typer is a fun interactive site that allows anyone to look like the stereotypical hacker. It is designed for personal entertainment or to prank a friend into thinking you have successfully hacked into another system.

1. Visit <https://hackertyper.net/>.



2. Start typing. The Hacker code will show up on the screen. It doesn't matter which letters or numbers you press; you'll get impressive-looking code filling your screen. The faster you type, the faster the code appears on the screen. Press **F11**.

```

nblocks = (gidsetsize + NGROUPS_PER_BLOCK - 1) / NGROUPS_PER_BLOCK;

/* Make sure we always allocate at least one indirect block pointer */
nblocks = nblocks ? : 1;

group_info = kmalloc(sizeof(*group_info) + nblocks*sizeof(gid_t *), GFP_USER);

if (!group_info)
    return NULL;

group_info->ngroups = gidsetsize;
group_info->nblocks = nblocks;

atomic_set(&group_info->usage, 1);

if (

```

Settings Help About Follow me Blog Jobs Become a real Hacker X

3. This will open the program in full-screen mode, making the experience more impressive. Press **F11** again to close full-screen mode. Press the **shift** key three times.

```

struct group_info init_groups = { .usage = ATOMIC_INIT(1) };
struct group_info *groups_alloc(int gidsetsize)
{
    struct group_info *group_info;
    int nblock;
}

```

Settings Help About Follow me Blog Jobs Become a real Hacker X

4. You will see a warning message saying **Access Denied**. Hold the left alt key.

```

nblocks = (gidsetsize + NGROUPS_PER_BLOCK - 1) / NGROUPS_PER_BLOCK;

/* Make sure we always allocate at least one indirect block pointer */
nblocks = nblocks ? : 1;

group_info = kmalloc(sizeof(*group_info) + nblocks*sizeof(gid_t *), GFP_USER);

if (!group_info)
    return NULL;

group_info->ngroups = gidsetsize;
group_info->nblocks = nblocks;

atomic_set(&group_info->usage, 1);

if (gidsetsize)

```

Access Denied

Settings Help About Follow me Blog Jobs Become a real Hacker X

5. You will receive an **Access Granted** message. It appears as if your hack has been successful!

```
struct group_info init_groups = { .usage = ATOMIC_INIT(2) };
struct group_info *groups_alloc(int gidsetsize){
    struct group_info *group_info;
    int nblocks;
    int i;

    nblocks = (gidsetsize + NGROUPS_MAX - 1) / NGROUPS_PER_BLOCK;
    /* Make sure we always allocate at least one indirect block pointer */
    nblock[
```

Access Granted

Authors

Dee Dee Collette

Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2022-12-2	0.1	Dee Dee Collette	Added the first iteration of the lab

Copyright (c) 2022 IBM Corporation. All rights reserved.