Definition

For real-valued nets f and g,

$\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M\,|g(x)|$ iff $f(x) \in O(g(x))$ and $|g(x)|$ is an asymptotic upper bound of $|f(x)|$.

$\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \geq M\,|g(x)|$ iff $f(x) \in \Omega(g(x))$ and $|g(x)|$ is an asymptotic lower bound of $|f(x)|$.

$\exists M_1, M_2 > 0, T \in \mathbb{R} : x \geq T \implies M_1\,|g(x)| \leq |f(x)| \leq M_2\,|g(x)|$ iff $f(x) \in \Theta(g(x))$.

$\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| < M\,|g(x)|$ iff $f(x) \in o(g(x))$.

$\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| > M\,|g(x)|$ iff $f(x) \in \omega(g(x))$.

$\in$ is also denoted as $=$ for them.

Limit

If $\exists k \in \mathbb{R} : x \geq k \implies g(x) \neq 0$,

$\lim\sup \left|\frac{f(x)}{g(x)}\right| < \infty$ iff $f(x) \in O(g(x))$.

Proof. $|f(x)| \leq M\,|g(x)|,\ x \geq T;\ \left|\frac{f(x)}{g(x)}\right| \leq M,\ x \geq T;\ \sup\left|\frac{f(x)}{g(x)}\right| \leq M,\ x \geq T;\ \lim\sup\left|\frac{f(x)}{g(x)}\right| \leq M < \infty;$ □

$\liminf \left|\frac{f(x)}{g(x)}\right| > 0$ iff $f(x) \in \Omega(g(x))$.

Proof. $|f(x)| \geq M\,|g(x)|,\ x \geq T;\ \left|\frac{f(x)}{g(x)}\right| \geq M,\ x \geq T;\ \inf\left|\frac{f(x)}{g(x)}\right| \geq M,\ x \geq T;\ \liminf\left|\frac{f(x)}{g(x)}\right| \geq M > 0;$ □

$\infty > \lim\sup \left|\frac{f(x)}{g(x)}\right| \geq \liminf \left|\frac{f(x)}{g(x)}\right| > 0$ iff $f(x) \in \Theta(g(x))$.

Proof. $|f(x)| \geq M_1\,|g(x)|,\ x \geq T;\ \left|\frac{f(x)}{g(x)}\right| \geq M_1,\ x \geq T;\ \inf\left|\frac{f(x)}{g(x)}\right| \geq M_1,\ x \geq T;\ \liminf\left|\frac{f(x)}{g(x)}\right| \geq M_1 > 0;\ |f(x)| \leq M_2\,|g(x)|,\ x \geq T;\ \left|\frac{f(x)}{g(x)}\right| \leq M_2,\ x \geq T;\ \sup\left|\frac{f(x)}{g(x)}\right| \leq M_2,\ x \geq T;\ \lim\sup\left|\frac{f(x)}{g(x)}\right| \leq M_2 < \infty;$ □

$\lim_{x\to\infty}\left|\frac{f(x)}{g(x)}\right| = 0$ iff $f(x) \in o(g(x))$. $|f(x)| < M\,|g(x)|$; $\left|\frac{f(x)}{g(x)}\right| < M$; $\lim_{x\to\infty}\left|\frac{f(x)}{g(x)}\right| = 0$;

$\lim_{x\to\infty}\left|\frac{f(x)}{g(x)}\right| = \infty$ iff $f(x) \in \omega(g(x))$. $|f(x)| > M\,|g(x)|$; $\left|\frac{f(x)}{g(x)}\right| > M$; $\lim_{x\to\infty}\left|\frac{f(x)}{g(x)}\right| = \infty$;

Relation

For any fixed $g(x)$, $o(g(x))$, $\Theta(g(x))$, and $\omega(g(x))$ are mutually exclusive.

Proof. Prove by contradiction. If $f \in o(g(x)) \cap \Theta(g(x))$, $\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| < M\,|g(x)|$; $\exists M_1, M_2 > 0, U \in \mathbb{R} : x \geq U \implies M_1\,|g(x)| \leq |f(x)| \leq M_2\,|g(x)|$; then set $M = M_1$, for $x \geq \max\{T, U\}$ $M_1\,|g(x)| \leq |f(x)| < M_1\,|g(x)|$.; which can't happen. If $f \in \omega(g(x)) \cap \Theta(g(x))$, $\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| > M\,|g(x)|$; $\exists M_1, M_2 > 0, U \in \mathbb{R} : x \geq U \implies M_1\,|g(x)| \leq |f(x)| \leq M_2\,|g(x)|$; then set $M = M_2$, for $x \geq \max\{T, U\}$ $M_2\,|g(x)| \geq |f(x)| > M_2\,|g(x)|$.; which can't happen. If $f \in o(g(x)) \cap \omega(g(x))$, $\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| < M\,|g(x)|$; $\forall M > 0 : \exists U \in \mathbb{R} : x \geq U \implies |f(x)| > M\,|g(x)|$; then set any fixed M, $M\,|g(x)| < |f(x)| < M\,|g(x)|$.; which can't happen. □

For any fixed $g(x)$, $o(g(x)) \subseteq O(g(x))$;

Proof. Peak any $M > 0$. □

For any fixed $g(x)$, $\omega(g(x)) \subseteq \Omega(g(x))$;

Proof. Peak any $M > 0$. □

For any fixed $g(x)$, $\Theta(g(x)) = O(g(x)) \cap \Omega(g(x))$;

Proof. Prove $\Theta(g(x)) \subseteq O(g(x)) \cap \Omega(g(x))$; $\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M\,|g(x)|$; $\exists N > 0, U \in \mathbb{R} : x \geq U \implies |f(x)| \geq N\,|g(x)|$; then $\exists M, N > 0, \max\{T, U\} \in \mathbb{R} : x \geq \max\{T, U\} \implies N\,|g(x)| \leq |f(x)| \leq M\,|g(x)|$;

Prove $\Theta(g(x)) \supseteq O(g(x)) \cap \Omega(g(x))$; $\exists M_1, M_2 > 0, T \in \mathbb{R} : x \geq T \implies M_1\,|g(x)| \leq |f(x)| \leq M_2\,|g(x)|$; then $\exists M_2 > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M_2\,|g(x)|$; $\exists M_1 > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \geq M_1\,|g(x)|$; □

For any fixed $g(x)$, $O(g(x)) \setminus (o(g(x)) \cup \Theta(g(x))) \neq \varnothing$;

Proof. Counterexample: $f(x) = \begin{cases} 1, & x \in \mathbb{Q} \\ 0, & x \notin \mathbb{Q} \end{cases}$; $g(x) = 1$; $f \in O(g(x))$: $\exists 1 > 0, 1 \in \mathbb{R} : x \geq 1 \implies |f(x)| \leq |g(x)|$; $f \notin o(g(x))$: $\forall 1 > 0, T \in \mathbb{R} : \exists x \geq T, x \in \mathbb{Q} : |f(x)| = |g(x)|$; $f \notin \Theta(g(x))$: $\forall M_1 > 0, x \in \mathbb{R}, x \notin \mathbb{Q} : M_1\,|g(x)| = M_1 > |f(x)| = 0$; □

For any fixed $g(x)$, $\Omega(g(x)) \setminus (\omega(g(x)) \cup \Theta(g(x))) \neq \varnothing$;

Proof. Counterexample: $f(x) = 1$; $g(x) = \begin{cases} 1, & x \in \mathbb{Q} \\ 0, & x \notin \mathbb{Q} \end{cases}$; $f \in \Omega(g(x))$: $\exists 1 > 0, 1 \in \mathbb{R} : x \geq 1 \implies |f(x)| \geq |g(x)|$; $f \notin \omega(g(x))$: $\forall 1 > 0, T \in \mathbb{R} : \exists x \geq T, x \in \mathbb{Q} : |f(x)| = |g(x)|$; $f \notin \Theta(g(x))$: $\forall M_2 > 0, x \in \mathbb{R}, x \notin \mathbb{Q} : M_2\,|g(x)| = 0 < |f(x)| = 1$; □

$f(x) \in O(g(x)) \iff g(x) \in \Omega(f(x))$;

Proof. $\implies$: $\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M\,|g(x)|$; then $\exists \frac{1}{M} > 0, T \in \mathbb{R} : x \geq T \implies |g(x)| \geq \frac{1}{M}\,|g(x)|$; $\impliedby$: $\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \geq M\,|g(x)|$; then $\exists \frac{1}{M} > 0, T \in \mathbb{R} : x \geq T \implies |g(x)| \leq \frac{1}{M}\,|g(x)|$; □

$f(x) \in o(g(x)) \iff g(x) \in \omega(f(x))$;

Proof. $\implies$: $\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| < M\,|g(x)|$; then $\forall \frac{1}{M} > 0 : \exists T \in \mathbb{R} : x \geq T \implies |g(x)| > \frac{1}{M}\,|f(x)|$; $\impliedby$: $\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| > M\,|g(x)|$; then $\forall \frac{1}{M} > 0 : \exists T \in \mathbb{R} : x \geq T \implies |g(x)| < \frac{1}{M}\,|f(x)|$; □

For any fixed $g(x)$, $\exists f(x) : f(x) \notin O(g(x)) \cup \Omega(g(x))$;

Proof. $f(x) = \begin{cases} 1, & x \in \mathbb{Q} \\ x, & x \notin \mathbb{Q} \end{cases}$; $g(x) = \begin{cases} x, & x \in \mathbb{Q} \\ 1, & x \notin \mathbb{Q} \end{cases}$; For $x \in \mathbb{R} \setminus \mathbb{Q}$, $\nexists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M\,|g(x)|$; For $x \in \mathbb{Q}$, $\nexists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \geq M\,|g(x)|$; □

Binary relation

$\Theta(g(x))$ is an equivalence class.

Proof. Transitive: $\exists M_1, M_2 > 0, T \in \mathbb{R} : x \geq T \implies M_1\,|g(x)| \leq |f(x)| \leq M_2\,|g(x)|$; $\exists N_1, N_2 > 0, U \in \mathbb{R} : x \geq U \implies N_1\,|h(x)| \leq |g(x)| \leq N_2\,|h(x)|$; then $\exists M_1 N_1, M_2 N_2 > 0, \max\{T, U\} \in \mathbb{R} : x \geq \max\{T, U\} \implies M_1 N_1\,|h(x)| \leq |f(x)| \leq M_2 N_2\,|h(x)|$; Reflexive: $f(x) \in \Theta(f(x))$; $\exists 1, 1 > 0, a \in \mathbb{R} : x \in \mathbb{R} \implies 1\,|f(x)| \leq |f(x)| \leq 1\,|f(x)|$; Symmetric: $\exists M_1, M_2 > 0, T \in \mathbb{R} : x \geq T \implies M_1\,|g(x)| \leq |f(x)| \leq M_2\,|g(x)|$; then $\exists \frac{1}{M_2}, \frac{1}{M_1} > 0, T \in \mathbb{R} : x \geq T \implies \frac{1}{M_2}\,|f(x)| \leq |f(x)| \leq \frac{1}{M_1}\,|f(x)|$; □

$O(g(x))$ is partial-ordered set with Θ as $=$.

Proof. Transitive: $\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M\,|g(x)|$; $\exists N > 0, U \in \mathbb{R} : x \geq U \implies |g(x)| \leq N\,|h(x)|$; then $\exists MN > 0, \max\{T, U\} \in \mathbb{R} : x \geq \max\{T, U\} \implies |f(x)| \leq MN\,|h(x)|$; Reflexive: $\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M\,|g(x)|$; then $\exists \frac{1}{M} > 0, T \in \mathbb{R} : x \geq T \implies |g(x)| \leq \frac{1}{M}\,|f(x)|$; Antisymmetric: $\exists M > 0, T \in \mathbb{R} : x \geq T \implies |f(x)| \leq M\,|g(x)|$; $\exists N > 0, U \in \mathbb{R} : x \geq U \implies |g(x)| \leq N\,|f(x)|$; then $\exists M, \frac{1}{N} > 0, \max\{T, U\} \in \mathbb{R} : x \geq \max\{T, U\} \implies \frac{1}{N}\,|g(x)| \leq |f(x)| \leq M\,|g(x)|$; □

$\Omega(g(x))$ is partial-ordered set with Θ as $=$.

Proof. Similar to that of O. □

$o(g(x))$ is a strictly partially-ordered set.

Proof. Asymmetry: $f(x) \in o(g(x)) \iff g(x) \in \omega(f(x)) \implies g \notin o(f(x))$; Transitivity: $\forall M > 0 : \exists T \in \mathbb{R} : x \geq T \implies |f(x)| < M\,|g(x)|$; $\exists U \in \mathbb{R} : x \geq U \implies |g(x)| < |h(x)|$; then $\forall M > 0 : \exists \max\{T, U\} \in \mathbb{R} : x \geq \max\{T, U\} \implies |f(x)| < M\,|h(x)|$; □

$\omega(g(x))$ is a strictly partially-ordered set.

Proof. Similar to that of o. □

Integral test (for convergence) or Maclaurin – Cauchy test

Suppose $f(x) : [a, \infty) \to \mathbb{R}$ for some $a \in \mathbb{N}$ is monotone and $\lim_{x\to\infty} f(x) = 0$. Then $\int_a^\infty f(x)\,\mathrm{d}x$ is convergent iff $\sum_{k=a}^{\infty} f(k)$ is convergent. And,

If $\int_a^\infty f(x)\,\mathrm{d}x$ is convergent and $f(x)$ is monotone decreasing, for any $n \in \mathbb{N}_{\geq a}$, $\int_n^\infty f(x)\,\mathrm{d}x \leq \sum_{k=n}^{\infty} f(k) \leq f(n) + \int_n^\infty f(x)\,\mathrm{d}x$.; called remainder estimate for integral test. Note that for $n \in \mathbb{N}_{>a}$, $f(n) + \int_n^\infty f(x)\,\mathrm{d}x \geq \int_{n-1}^\infty f(x)\,\mathrm{d}x$.

If $\int_a^\infty f(x)\,\mathrm{d}x$ is convergent and $f(x)$ is monotone increasing, for any $n \in \mathbb{N}_{\geq a}$, $\int_n^\infty f(x)\,\mathrm{d}x \geq \sum_{k=n}^{\infty} f(k) \geq f(n) + \int_n^\infty f(x)\,\mathrm{d}x$.; called remainder estimate for integral test. Note that for $n \in \mathbb{N}_{>a}$, $f(n) + \int_n^\infty f(x)\,\mathrm{d}x \geq \int_{n-1}^\infty f(x)\,\mathrm{d}x$.

Proof. Consider the case where $f(x)$ is monotone increasing. The case where $f(x)$ is monotone decreasing can be proven similarly. First consider the case where $\int_a^\infty f(x)\,\mathrm{d}x$ is convergent. This implies that $f(x)$ is non-positive. Thus, for any fixed $n \in \mathbb{N}_{\geq a}$, $\int_n^{n+1} f(x)\,\mathrm{d}x \geq f(n)$.; and for any $k \geq n+1$, $\int_k^{k+1} f(x)\,\mathrm{d}x \geq f(k) \geq \int_{k-1}^{k} f(x)\,\mathrm{d}x$.; For any $N \in \mathbb{N}_{\geq n}$, summing over all $k \in \mathbb{N}_{\geq n}$, we obtain, $\int_n^{N+1} f(x)\,\mathrm{d}x \geq \sum_{k=n}^{N} f(k) \geq f(n) + \int_n^N f(x)\,\mathrm{d}x$.; Take limit $\lim_{N\to\infty}$, we obtain $\int_n^\infty f(x)\,\mathrm{d}x \geq \sum_{k=n}^{\infty} f(n) \geq f(n) + \int_n^\infty f(x)\,\mathrm{d}x$.; Second, consider the case where $\int_a^\infty f(x)\,\mathrm{d}x$ is divergent. Since $f(x)$ is monotone. Either $\int_a^\infty f(x)\,\mathrm{d}x = -\infty$ or $\int_a^\infty f(x)\,\mathrm{d}x = \infty$. For the former, the supremum of $f(x)$ is non-positive, and $\sum_{k=a}^{\infty} f(k) = -\infty$. For the latter, there exists $x_0 > a$ such that $f(x) > 0$ for all $x \geq x_0$, and thus $\sum_{k=a}^{\infty} f(k) = \infty$. □

p-test (for improper integral)

For any fixed $a > 0$, $\int_a^\infty \frac{1}{x^p}\,\mathrm{d}x$ converges iff $p > 1$, and if so, $\int_a^\infty \frac{1}{x^p}\,\mathrm{d}x = \frac{1}{(p-1)\,a^{p-1}}$.; $\int_0^a \frac{1}{x^p}\,\mathrm{d}x$ converges iff $p < 1$, and if so, $\int_0^a \frac{1}{x^p}\,\mathrm{d}x = -\frac{1}{(p-1)\,a^{p-1}}$.;

Proof. $\int \frac{1}{x^p}\,\mathrm{d}x = \begin{cases} -\frac{1}{(p-1)\,x^{p-1}}, & p \neq 1 \\ \ln(x), & p = 1 \end{cases}$; $\forall p < 1 : \nexists \lim_{x\to\infty} -\frac{1}{(p-1)\,x^{p-1}}$; $\nexists \lim_{x\to\infty} \ln(x)$; $\forall p > 1 : \lim_{x\to\infty} -\frac{1}{(p-1)\,x^{p-1}} = 0 \int_a^\infty \frac{1}{x^p}\,\mathrm{d}x = \frac{1}{(p-1)\,a^{p-1}}$; $\forall p > 1 : \nexists \lim_{x\to 0^+} -\frac{1}{(p-1)\,x^{p-1}}$; $\nexists \lim_{x\to 0^+} \ln(x)$; $\forall p < 1 : \lim_{x\to 0^+} -\frac{1}{(p-1)\,x^{p-1}} = 0 \int_0^a \frac{1}{x^p}\,\mathrm{d}x = -\frac{1}{(p-1)\,a^{p-1}}$; □

Generalized p-test (for improper integral)

Define iterated logarithmic function $L_n(x)$ as $L_0(x) = x,\ x \in \mathbb{R}_{>0}$; $L_n(x) = \ln\left(L_{n-1}(x)\right),\ n \in \mathbb{N}, x \in \mathbb{R}_{>0}$.; For any fixed $a > 1, k \in \mathbb{N}$, $\int_a^\infty \frac{1}{\left(\prod_{i=0}^{k-1} L_i(x)\right)\left(L_k(x)\right)^m}\,\mathrm{d}x$; converges iff $m > 1$.

Proof. Let $u = L_k(x)$; $\mathrm{d}u = \frac{\mathrm{d}x}{\prod_{i=0}^{k-1} L_i(x)}$; $\int \frac{1}{\left(\prod_{i=0}^{k-1} L_i(x)\right)\left(L_k(x)\right)^m}\,\mathrm{d}x = \int \frac{1}{u^m}\,\mathrm{d}u$; By p-test, the statement holds. □

For any fixed $0 < a < 1$, $\int_0^a \frac{1}{x(\ln x)^m}\,\mathrm{d}x$; converges iff $m < 1$.

Proof. By substitution of $u = \ln x$. □

Generalized p-test for series or generalized p-series test

Define iterated logarithmic function $L_n(x)$ as $L_0(x) = x,\ x \in \mathbb{R}_{>0}$; $L_n(x) = \ln\left(L_{n-1}(x)\right),\ n \in \mathbb{N}, x \in \mathbb{R}_{>0}$.; For any fixed $a \in \mathbb{N}$, $\sum_{n=a}^{\infty} \frac{1}{\left(\prod_{i=0}^{k-1} L_i(n)\right)\left(L_k(n)\right)^m}$; converges iff $m > 1$.

Proof. By integral test and generalized p-test for improper integral, the statement holds. □

Generalized Master Theorem

For a positive valued net $T(n)$ defined on $n = b^h$ for any $h \in \mathbb{N}_0$ as $T(n) = aT\left(\frac{n}{b}\right) + f(n)$; for some constants $a > 0$ and $b > 1$, and non-negative-valued function $f(n)$,

If for some $c < \log_b a$, $f(n) = O\left(n^c\right)$.; then $T(n) = \Theta\left(n^{\log_b a}\right)$.;

Define iterated logarithmic function $L_n(x)$ as $L_0(x) = x,\ x \in \mathbb{R}_{>0}$; $L_n(x) = \ln\left(L_{n-1}(x)\right),\ n \in \mathbb{N}, x \in \mathbb{R}_{>0}$.;

If for some positive integers k and positive number m, $f(n) = \Theta\left(n^{\log_b a}\left(\prod_{i=1}^{k-1}\left(L_i(n)\right)^{-1}\right)\left(L_k(n)\right)^{m-1}\right)$.; then $T(n) = \Theta\left(n^{\log_b a}\left(L_k(n)\right)^m\right)$.;

If for some positive integer k, $f(n) = \Theta\left(n^{\log_b a}\prod_{i=1}^{k}\left(L_i(n)\right)^{-1}\right)$.; then $T(n) = \Theta\left(n^{\log_b a} L_{k-1}(n)\right)$.;

If for some positive integers k and some positive number m, $f(n) = \Theta\left(n^{\log_b a}\left(\prod_{i=1}^{k-1}\left(L_i(n)\right)^{-1}\right)\left(L_k(n)\right)^{-m-1}\right)$.; then $T(n) = \Theta\left(n^{\log_b a}\right)$.;

If $f(n) = \Omega\left(n^c\right)$ for some $c > \log_b a$, and the regularity condition that $\exists m \in \mathbb{R}, k < 1$ such that $n \geq m$ implies $af\left(\frac{n}{b}\right) \leq kf(n)$; is satisfied, then $T(n) = \Theta\left(f(n)\right)$.;

Proof. Let $s = \log_b a$, $n = b^h$, and $f(x) = x^s g(x)$. At level j, there are a^j nodes, each of size $\frac{n}{b^j}$. Thus, the total non-recursive work at level j is $a^j f\left(\frac{n}{b^j}\right)$.; Hence $T(n) = \sum_{j=0}^{h-1} a^j f\left(\frac{n}{b^j}\right) + n^s T(1) = \sum_{j=0}^{h-1} b^{sj} f\left(\frac{b^h}{b^j}\right) + \Theta\left(n^s\right) = n^s \sum_{j=0}^{h-1} g\left(b^{h-j}\right) + \Theta\left(n^s\right) = n^s \sum_{r=1}^{h} g\left(b^r\right) + \Theta\left(n^s\right)$; Case 1: If for some $c < \log_b a$, $f(n) = O\left(n^c\right)$.; then $T(n) = \Theta\left(n^{\log_b a}\right)$.; Case 2: $L_k\left(b^x\right) = \Theta\left(L_{k-1}(x)\right)$; $f(n) = \Theta\left(n^{\log_b a}\left(\prod_{i=1}^{k-1}\left(L_i(n)\right)^{-1}\right)\left(L_k(n)\right)^{m-1}\right)$; $g\left(b^r\right) = \Theta\left(\left(\prod_{i=1}^{k-2}\left(L_i(r)\right)^{-1}\right)\left(L_{k-1}(r)\right)^{m-1}\right)$; By generalized p-test for series: Sub-case 1 $m > 0$: $T(n) = \Theta\left(n^{\log_b a}\left(L_k(n)\right)^m\right)$.; Sub-case 2 $m = 0$: $T(n) = \Theta\left(n^{\log_b a} L_{k-1}(n)\right)$.; Sub-case 3 $m = 0$: $T(n) = \Theta\left(n^{\log_b a}\right)$.; Case 3: If $f(n) = \Omega\left(n^c\right)$ for some $c > \log_b a$, and the regularity condition that $\exists m \in \mathbb{R}, 0 < k < 1$ such that $n \geq m$ implies $af\left(\frac{n}{b}\right) \leq kf(n)$; is satisfied, then $af\left(\frac{n}{b}\right) \leq kf(n)$; $a^j f\left(\frac{n}{b^j}\right) \leq a^{j-1} kf\left(\frac{n}{b^{j-1}}\right) \leq k^j f(n)$; $T(n) = \sum_{j=0}^{h-1} a^j f\left(\frac{n}{b^j}\right) + n^s T(1) = f(n) + \sum_{j=1}^{h-1} O\left(k^j f(n)\right) + \Theta\left(n^s\right)$; $\sum_{j=1}^{\infty} k^j f(n) = \frac{f(n)}{1-k}$; $T(n) = f(n) + O\left(f(n)\right) + \Theta\left(n^s\right) = \Theta\left(f(n)\right)$; □

Terms:

h is called recursion level.

$\log_b a$ is called critical exponent c_{crit}.

$T(1)$ is called leaf cost.

At each node, the first term is called recursive work, and the second term is called non-recursive work.

For original master theorem, the second case is

If for some positive integers m, $f(n) = \Theta\left(n^{\log_b a}(\ln n)^{m-1}\right)$.; then $T(n) = \Theta\left(n^{\log_b a}(\ln n)^m\right)$.;

If $f(n) = o\left(n^{\log_b a}(\ln n)^{-1}\right)$.; then $T(n) = \Theta\left(n^{\log_b a}\ln(\ln n)\right)$.;

If for some positive integers m, $f(n) = \Theta\left(n^{\log_b a}(\ln n)^{-m-1}\right)$.; then $T(n) = \Theta\left(n^{\log_b a}\right)$.;

Stirling's approximation

$n! = \sqrt{2\pi n}\left(\frac{n}{e}\right)^n\left(1 + O\left(\frac{1}{n}\right)\right)$;

特徵方程式

定義：對一個給定 k 階常係數線性遞迴數列：

$$< a_n >: a_n = \sum_{i=1}^{k} c_i \cdot a_{n-i} + f(n)$$

，其特徵方程式為 $x^k - \sum_{i=1}^{k} c_i \cdot x^{k-i} = 0$，特徵方程式的根稱其特徵根。

若一個給定 k 階常係數線性齊次遞迴數列 $< a_n >$ 有 a 相異特徵根 $q_1, q_2, q_3, \ldots, q_a$，其中第 i 個根 $(1 \leq i \leq a)$ 為 m_i 重根，則 $< a_n >$ 之一般式為：

$$a_n = \sum_{i=1}^{a}\left(\sum_{j=1}^{m_i}\left(A_{i,j} \cdot n^{j-1}\right) \cdot {q_i}^n\right)$$

若給定一個 k 階常係數線性非齊次遞迴數列：$< a_n >: a_n = \sum_{i=1}^{k} c_i \cdot a_{n-i} + f(n)$; 則令：$a_n = a'_n + a''_n$; 使得 $< a'_n >$ 為 k 階常係數線性齊次遞迴數列，$< a''_n >$ 為 k 階常係數線性非齊次遞迴數列且一次項同 $< a'_n >$ 且 $f(n)$ 項同 $< a_n >$。$a''_n = g(n)$, $\deg(g(n)) \leq \deg(f(n))$; 解出 k 階常係數線性非齊次遞迴數列 $< a'_n >$ 與 $g(n)$，即可解出 $< a_n >$。

Linear Data Structures

Stack is last-in-first-out (LIFO) O(1) with push as inputting an element, pop as removing and returning the last inputted element, top as peaking the last inputted element, and bottom as the first inputted element. list is a stack with append as push, pop as pop, and [-1] as top. SinglyLinkedList is a stack with prepend as push, pop_front as pop, and peak_front as top.

Queue is first-in-first-out (FIFO) O(1) with enqueue as inputting an element, dequeue as removing and returning the first inputted element, peak as peaking the first inputted element, front as the first inputted element, and back or rear as the last inputted element. SinglyLinkedList is a queue with append as enqueue, pop_front as dequeue, and peak_front as top.

To keep track of the extreme element of a stack or queue in O(1) time with O(n) extra space. One can maintain the original stack of elements and an extra stack of extrema. When an element is pushed to the original stack, it is compared with the top of the extrema stack and the extreme one is pushed to the extrema stack (for the first element, it is pushed to the extrema stack). When an element is popped from the original stack, an element is popped from the extrema stack. This way, the top of the extrema stack is always the extreme of the elements in the original stack.

Doubly-ended queue (Deque) is both-end-in-out O(1) and is a stack and a queue.

An unordered list is a collection of items where each item holds a relative position with respect to the others, such as SinglyLinkedList and DoublyLinkedList.

An ordered list is a collection of items which are ordered based upon some underlying characteristic of the item, which can be implemented with a stack or a queue if O(1) pop of one end is needed and a deque if O(1) pop of both ends is needed.

```
# Python operator precedence order: \texttt
        {()} > \texttt{**} > \texttt{+x} \
        texttt{-x} \texttt{~x} (bitwise NOT)
        > \texttt{*} \texttt{/} \texttt{//} \
        texttt{\%} > \texttt{+} \texttt{-} >
        \texttt{<<} \texttt{>>} (preserve
        sign) > \texttt{\&} (bitwise AND) > \
        texttt{^} (bitwise XOR) > \texttt{|}
          (bitwise OR) > \texttt{==} \texttt
        {!=} \texttt{>} \texttt{>=} \texttt
        {<} \texttt{<=} (value comparison) \
        texttt{is} \texttt{is not} (identity)
          \texttt{in} \texttt{not in} > \
        texttt{not} > \texttt{and} > \texttt{
        or}

bool(0)  # False, only 0 False, other numbers
        True
2**72  # int is of infinite precision, ** is
        power
pow(2, 72)  # same as 2**72
float("inf")  # infinite float
(1).__add__(2)  # 3, must use (1). since 1.
        is treated as decimal
3 // 2  # 1, floor quotient
3 / 2  # 1.5, quotient
divmod(3, 2)  # (1, 1), the pair (x // y, x %
        y)
abs(-2)  # 2
c = complex(1, 2)  # (1+2j), complex(re, im)
c.conjugate()  # (1-2j)
a = 0.5  # a == 0.5
type(True)  # <class 'bool'>
type(1)  # <class 'int'>
type(1.0)  # <class 'float'>
type(complex(1, 1))  # <class 'complex'>
a = None
a is None  # True
a = [1]
b = a
a == b  # True
a != b  # False
a is b  # True, i.e., id(a) == id(b)
a is not b  # False
b = a.copy()  # Shallow copy
a == b  # True
a is b  # False
a[0] is b[0]  # True
c, d = b
c, d = d, c  # swap
3 if 2 > 1 else 2  # 3
sradius = input("Please enter the radius of
        the circle ")
# ...
# Please enter the radius of the circle (
        input here, say 1)
# sradius == 1
# print(obj[, obj ,...], sep=' ', end='\n',
        file=sys.stdout, flush=False)
# obj: Arbitrary number of objects that can
        be converted to str. Will be
        converted to str and printed.
# sep: Separator between objects
# end: What to print at end
# file: An object with a write method to
        print to
# flush: True for flushed, False for buffered
print("a")  # a
print(1, [1])  # 1 [1]
print(1, 2, sep=", ", end="1")  # 1,21<
        no_newline>
print(1, 2, sep=", ", end="")  # 1, 2<
        no_newline>
```

```
a = "a"
type(a)  # <class 'str'>
a += "b"  # a == 'ab'
"He".__add__("llo")  # 'Hello'
str(1)  # '1'
"g" in "egg"  # True
"f" in "egg"  # False
len("Hello")  # 5
"Hello World".capitalize()  # 'Hello world', first capitalize, other lowercase
# str.center(width, fillchar=' '), Return centered in a string of length width. Padding is done using the specified fillchar (default is an ASCII space). The original string is returned if width is less than or equal to len(s).
"Python".center(10)  # '  Python  '
"Python".center(10, "-")  # '--Python--'
"Python".center(4)  # 'Python'
# str.count(sub[, start[, end]])
"spam, spam, spam".count("spam")  # 3
"spam, spam, spam".count("spam", 5)  # 2
"spam, spam, spam".count("spam", 5, 10)  # 1
"spam, spam, spam".count("eggs")  # 0
"spam, spam, spam".count("") # 17
# str.endswith(suffix[, start[, end]]), Return True if the string ends with the specified suffix, otherwise return False. suffix can also be a tuple of suffixes to look for. With optional start, test beginning at that position. With optional end, stop comparing at that position. Using start and end is equivalent to str[start:end].endswith(suffix).
# suffix can also be a tuple of suffixes to look for.
"Python".endswith("on")  # True
"a tuple of suffixes".endswith(("at", "in"))  # False
"a tuple of suffixes".endswith(("at", "es"))  # True
"Python is amazing".endswith("is", 0, 9)  # True
# str.startswith(prefix[, start[, end]]), endswith but startswith
# str.expandtabs(tabsize=8)
"01\t012\t0123\t01234".expandtabs()  # '01      012     0123    01234'
"01\t012\t0123\t01234".expandtabs(4)  # '01  012 0123  01234'
# str.find(sub[, start[, end]]), Return the lowest index in the string where substring sub is found within the slice s[start:end]. Optional arguments start and end are interpreted as in slice notation. Return -1 if sub is not found.
"spam, spam, spam".find("sp")  # 0
"spam, spam, spam".find("sp", 5)  # 6
# str.rfind(sub[, start[, end]]), find but highest index
# str.index(sub[, start[, end]]), Like find(), but raise ValueError when the substring is not found.
"spam, spam, spam".index("spam")  # 0
# 'spam, spam, spam'.index('eggs')  # ValueError: substring not found
# str.rindex(sub[, start[, end]]), index but highest index
# str.join(iterable), Return a string which is the concatenation of the strings in iterable. A TypeError will be raised if there are any non-string values in iterable, including bytes objects. The separator between elements is the string providing this method.
", ".join(["spam", "spam", "spam"])  # 'spam, spam, spam'
"-".join("Python")  # 'P-y-t-h-o-n'
"".join(["a", "b", "c"]) # 'abc'
"Hello World".lower()  # 'hello world', all lowercase
# str.lstrip(chars=None), Return a copy of the string with leading characters removed. The chars argument is a string specifying the set of characters to be removed. If omitted or None, the chars argument defaults to removing whitespace. The chars argument is not a prefix; rather, all combinations of its values are stripped.
"   spacious   ".lstrip()  # 'spacious   '
"www.example.com".lstrip("cmowz.")  # 'example.com'
# str.rstrip(chars=None), lstrip but trailing
# str.strip(chars=None), lstrip and rstrip
# str.partition(sep), Split the string at the first occurrence of sep, and return a 3-tuple containing the part before the separator, the separator itself, and the part after the separator. If the separator is not found, return a 3-tuple containing the string itself, followed by two empty strings.
"Monty Python".partition(" ")  # ('Monty', ' ', 'Python')
"Monty Python's Flying Circus".partition(" ")  # ('Monty', ' ', "Python's Flying Circus")
"Monty Python".partition("-")  # ('Monty Python', '', '')
# str.rpartition(sep), partition but last occurrence
# str.removeprefix(prefix), If the string starts with the prefix string, return string[len(prefix):]. Otherwise, return a copy of the original string:
"Arthur: three!".removeprefix("Arthur: ")  # 'three!'
# str.removesuffix(suffix, /), If the string ends with the suffix string and that suffix is not empty, return string[:-len(suffix)]. Otherwise, return a copy of the original string
# str.replace(old, new, count=-1), Return a copy of the string with all occurrences of substring old replaced by new. If count is given, only the first count occurrences are replaced. If count is not specified or -1, then all occurrences are replaced.
"spam, spam, spam".replace("spam", "eggs")  # 'eggs, eggs, eggs'
"spam, spam, spam".replace("spam", "eggs", 1)  # 'eggs, spam, spam'
# str.split(sep=None, maxsplit=-1), Return a list of the words in the string, using sep as the delimiter string. If maxsplit is given, at most maxsplit splits are done, the leftmost ones (thus, the list will have at most maxsplit+1 elements). If maxsplit is not specified or -1, then there is no limit on the number of splits (all possible splits are made). If sep is given, consecutive delimiters are not grouped together and are deemed to delimit empty strings (for example, '1,,2'.split(',') returns ['1', '', '2']). The sep argument may consist of multiple characters as a single delimiter. Splitting an empty string with a specified separator returns ['']. If sep is not specified or is None, a different splitting algorithm is applied: runs of consecutive whitespace are regarded as a single separator, and the result will contain no empty strings at the start or end if the string has leading or trailing whitespace. Consequently, splitting an empty string or a string consisting of just whitespace with a None separator returns [].
"1,2,3".split(",")  # ['1', '2', '3']
"1,2,3".split(",", maxsplit=1)  # ['1', '2,3']
"1,2,,3,".split(",")  # ['1', '2', '', '3', '']
"1<>2<>3<4".split("<>")  # ['1', '2', '3<4']
# str.rsplit(sep=None, maxsplit=-1), split but rightmost
# str.swapcase()  # 'hELLO WORLD'
"Hello World".swapcase()  # 'hELLO wORLD'
# str.title(), Return a titlecased version of the string where words start with an uppercase character and the remaining characters are lowercase. The algorithm uses a simple language-independent definition of a word as groups of consecutive letters.
"Hello world".title()  # 'Hello World'
"they're bill's friends from the UK".title()  # "They'Re Bill'S Friends From The Uk"
# str.upper(), all uppercase



# A list is a dynamic array of elements of arbitrary types
a = [10, 20, 30]
type(a)  # <class 'list'>
a[0]  # 10, O(1)
a[1]  # 20, O(1)
a[-1]  # 30, O(1)
a[-2]  # 20, O(1)
len(a)  # 3, O(1)
a.__len__()  # 3, O(1)
a.append(40)  # a == [10, 20, 30, 40], amortized O(1)
a.pop()  # a == [10, 20, 30], O(1)
a.insert(1, 50)  # a == [10, 50, 20, 30], O(n)
a.pop(0)  # a == [50, 20, 30], O(n)
a[0] = 0  # a == [0, 20, 30], O(1)
b, c, d = a  # b == 0, c == 20, d == 30
a.clear()  # a == []
a = [0, 1, 2]
b = a  # id(a) == id(b)
b.pop()  # a == b == [0, 1], id(a) == id(b)
b = [1, 2]  # id(a) != id(b), a == [0, 1]
a = [1, 1, 1]
a.count(1)  # 3, O(n)
b = a.copy()  # a == b but id(a) != id(b)
a.index(1)  # 0, first occurrence, O(n)
a.extend([0, 4, 3, 4])  # a == [1, 1, 1, 0, 4, 3, 4], O(k)
a.remove(4)  # a.pop(a.index(x))
a.reverse()  # a == [4, 3, 0, 1, 1, 1], O(n)
a.sort()  # [0, 1, 1, 1, 3, 4], O(n log n) worst-case O(n) best-case, Powersort
sorted(a)  # same as a.sort()
del a[0:5:2]  # a == [1, 1, 4]
1 in a  # True
0 not in a  # True
a = [None] * 5  # a == [None, None, None, None, None]
del a  # a is now not defined
a = [1, '1', [1], True]  # arbitrary types
a.__getitem__(0)  # a same as a[0]
a.__setitem__(0, (1,))  # a == [(1,), '1', [1], True], same as a[0] = (1,)
it = iter([1, 2, 3])  # also it = [1, 2, 3].__iter__()
iter(a) is iter(a)  # False
next(it)  # 1, also it.__next__()
# Return of __next__ is defined by the yield clause in the method.
# __next__ is used by for loop.
# range(start, stop, step), all are integers, start + k step, k = [0, (stop - start) / step - 1] integers
reversed(a)  # a reversed iterator of a, also a.__reversed__()
next(a)  # True
list(range(0, 10, 1))  # [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
list(range(9, -1, -2))  # [9, 7, 5, 3, 1]
# List comprehensions provide a concise way to create lists. Common applications are to make new lists where each element is the result of some operations applied to each member of another sequence or iterable, or to create a subsequence of those elements that satisfy a certain condition.
list(map(lambda x: x**2, range(10)))  # [0, 1, 4, 9, 16, 25, 36, 49, 64, 81]
[x**2 for x in range(10)] # [0, 1, 4, 9, 16, 25, 36, 49, 64, 81]
[(x, y) for x in [1, 2, 3] for y in [3, 1, 4] if x != y]  # [(1, 3), (1, 4), (2, 3), (2, 1), (2, 4), (3, 1), (3, 4)]
[w.strip() for w in [" banana", "  loganberry ", "passion fruit  "]]  # ['banana', 'loganberry', 'passion fruit']
[num for elem in [[1, 2, 3], [4, 5, 6], [7, 8, 9]] for num in elem]  # [1, 2, 3, 4, 5, 6, 7, 8, 9]
[
    [
        row[i]
        for row in [
            [1, 2, 3, 4],
            [5, 6, 7, 8],
            [9, 10, 11, 12],
        ]
    ]
    for i in range(4)
]  # [[1, 5, 9], [2, 6, 10], [3, 7, 11], [4, 8, 12]]
# zip(*iterables, strict=False), Iterate over several iterables in parallel, producing tuples with an item from each one, similar to transposing a matrix. By default, zip() stops when the shortest iterable is exhausted. With strict=True, it raises a ValueError if one iterable is exhausted before the others.
list(
    zip(
        *[
            [1, 2, 3, 4],
            [5, 6, 7, 8],
            [9, 10, 11, 12],
        ]
    )
)  # [(1, 5, 9), (2, 6, 10), (3, 7, 11), (4, 8, 12)]
list(zip(range(3), ["fee", "fi", "fo", "fum"]))  # [(0, 'fee'), (1, 'fi'), (2, 'fo')]
# list(zip(range(3), ['fee', 'fi', 'fo', 'fum'], strict=True))  # ValueError: zip() argument 2 is longer than argument 1
[0, *[1, 2, 3], 4, 5, 6]  # [0, 1, 2, 3, 4, 5, 6]



# A tuple is an immutable ordered collection of arbitrary number of elements of arbitrary types
a = (
    1,
    "a",
    "a",
    [0],
)
type(a)  # <class 'tuple'>
a = 1, "a", "a", [0]  # can also be created without the parentheses
a[0]  # 1
a[-1]  # [0]
# a[0] = 0  # TypeError: 'tuple' object does not support item assignment
a[3][0] = 1  # allowed
a = ("a",)  # a == ('a',), a tuple. One-item tuple requires comma
a = ("a",)  # a == ('a',), a tuple
a = "a"  # a == 'a', a string
a = (1, 1, 1)
a.count(1)  # 3
a.index(1)  # 0, first occurrence
1 in a  # True
0 not in a  # True



# A set is an immutable unordered collection of arbitrary number of elements of hashable types with duplicates ignored
a = {
    1,
    "a",
    "a",
}  # t == {1, 'a'}
"a".__hash__()  # -8760825294024040742, a hashable type has __hash__ method that returns an int
# a = {[0]} # TypeError: cannot use 'list' as a set element (unhashable type: 'list')
type(a)  # <class 'set'>
type({})  # <class 'dict'>
a = {True, 1}  # t == {True}
a = {1, True}  # t == {1}
a = {False, 0}  # t == {False}
a = {0, False}  # t == {0}
len(a)  # 1
a.clear()  # a == set()
a = {1, 0, 2}  # a == {0, 1, 2}
b = a.copy()  # id(a) != id(b)
a.add(3)  # a == {0, 1, 2, 3}
a.remove(3)  # a == {0, 1, 2}, remove if present, KeyError if not
# a.remove(3)  # KeyError: 3
a.discard(2)  # a == {0, 1}, remove if present
a.discard(2)  # a == {0, 1}
a.pop()  # 0, a == {1}, Remove and return an arbitrary element from the set. Raises KeyError if the set is empty.
a.pop()  # 1
# a.pop  # KeyError: 'pop from an empty set'
a = {0, 1, 2, 3}
# arg is any iterable, denoted as b below
a.isdisjoint({0})  # False, a\cap b == \varnothing
a.isdisjoint({0})
a.isdisjoint((0,))
a.issubset(a)  # True, a\subseteq b
a <= a  # True, a\subseteq b
a < a  # False, a\subsetneq b
a.issuperset(a)  # True, a\supseteq b
a >= a  # True, a\supseteq b
a > a  # False, a\supsetneq b
a.union({4})  # {0, 1, 2, 3, 4}, a\cup b
a | {4}  # {0, 1, 2, 3, 4}, a\cup b
a.update({1})  # a == {0, 1, 2, 3}, assign a\cup b to a
a |= {4}  # a == {0, 1, 2, 3, 4}, assign a\cup b to a
a.intersection({3})  # {3}, a\cap b
a & {3}  # {3}, a\cap b
a & {6}  # set(), a\cap b
a.intersection_update(a)  # a == {0, 1, 2, 3, 4}, assign a\cap b to a
a &= {-1, 0, 1, 2, 3}  # a == {0, 1, 2, 3}, assign a\cap b to a
a.difference({1})  # {0, 2, 3}, a\setminus b
a - {1}  # {0, 2, 3}, a\setminus b
a.difference_update({1})  # a == {0, 2, 3}, assign a\setminus b to a
a -= {2}  # a == {0, 3}, assign a\setminus b to a
a.symmetric_difference({1, 3})  # {0, 1}, a\cup b\setminus(a\cap b)
a ^ {1, 3}  # {0, 1}, a\cup b\setminus(a\cap b)
a.symmetric_difference_update({1, 3})  # a == {0, 1}, assign a\cup b\setminus(a\cap b) to a
a ^= {1, 3}  # a == {0, 3}, assign a\cup b\setminus(a\cap b) to a
{c for c in "abracadabra" if c not in "abc"}  # {'d', 'r'}, set comprehension



# A dict is a mapping object maps hashable values to arbitrary objects
a = dict(one=1, two=2, three=3)
b = {"one": 1, "two": 2, "three": 3}
c = dict(zip(["one", "two", "three"], [1, 2, 3]))
d = dict([("two", 2), ("one", 1), ("three", 3)])
e = dict({"three": 3, "one": 1, "two": 2})
f = dict({"one": 1, "three": 3}, two=2)
a == b == c == d == e == f  # True
type(d)  # <class 'dict'>
type({})  # <class 'dict'>
list(d)  # ['two', 'one', 'three'], list of keys
len(d)  # 3, len(list(d))
d["two"]  # 2
# d["a"]  # KeyError: 'a'
d["four"] = 5  # d == {'two': 2, 'one': 1, 'three': 3, 'four': 5}
d["four"] = 4  # d == {'two': 2, 'one': 1, 'three': 3, 'four': 4}
# del d["four"]  # d == {'two': 2, 'one': 1, 'three': 3}
# del d["five"]  # KeyError: 'five'
"one" in d  # True
"five" in d  # False
iter(d)  # iter(d.keys())
e.clear()  # e == {}
c = d.copy()
# items(), Return a new view of the dictionary's items ((key, value) pairs).
i = d.items()  # i == dict_items([('two', 2), ('one', 1), ('three', 3)])
list(i)  # [('two', 2), ('one', 1), ('three', 3)]
# keys(), Return a new view of the dictionary's keys.
k = d.keys()  # k == dict_keys(['two', 'one', 'three'])
list(k)  # ['two', 'one', 'three']
# values(), Return a new view of the dictionary's values.
v = d.values()  # v == dict_values([2, 1, 3])
list(v)  # [2, 1, 3]
# iter(dictview), Return an iterator over the keys, values or items (represented as tuples of (key, value)) in the dictionary.
# Keys and values are iterated over in insertion order since 3.7. This allows the creation of (value, key) pairs using zip(): pairs = zip(d.values(), d.keys()). Another way to create the same list is pairs = [(v, k) for (k, v) in d.items()].
# x in dictview
# reversed(dictview), reverse iterator
# classmethod fromkeys(iterable, value=None), Return a new dictionary with keys from iterable and values set to value.
d.fromkeys([1, 2, 3])  # {1: None, 2: None, 3: None}
dict.fromkeys([1, 2, 3])  # {1: None, 2: None, 3: None}
# get(key, default=None), Return the value for key if key is in the dictionary, else default.
d.get("two")  # 2
d.get("four")  # (None)
# pop(key), pop(key, default), If key is in the dictionary, remove it and return its value, else return default. If default is not given and key is not in the dictionary, a KeyError is raised.
d.pop("one")  # d == {'two': 2, 'three': 3}
d.pop("one", 10)  # 10
# d.pop("one")  # KeyError: 'one'
# popitem(), Remove and return a (key, value) pair from the dictionary. Pairs are returned in LIFO order since 3.7.
d.popitem()  # ('three', 3), d == {'two': 2}
reversed(d)  # reversed(list(d))
# setdefault(key, default=None), If key is in the dictionary, return its value. If not, insert key with a value of default and return default.
d.setdefault("two")  # 2, d == {'two': 2}
d.setdefault("one", 1)  # 1, d == {'two': 2, 'one': 1}
# update(**kwargs), update(mapping, **kwargs), update(iterable, **kwargs), update the dictionary with the key/value pairs from mapping or iterable and kwargs, overwriting existing keys. Return None. update() accepts either another object with a keys() method (in which case __getitem__() is called with every key returned from the method) or an iterable of key/value pairs (as tuples or other iterables of length two). If keyword arguments are specified, the dictionary is then updated with those key/value pairs: d.update(red=1, blue=2).
d.update(four=4, three=3)  # d == {'two': 2, 'one': 1, 'four': 4, 'three': 3}
d.update(two=0)  # d == {'two': 0, 'one': 1, 'four': 4, 'three': 3}
d.update([("two", 2)])  # d == {'two': 2, 'one': 1, 'four': 4, 'three': 3}
d.update(((("two", 2),)))
d.update((((("two", 2),))))
d.update([("two", 2)])
d | {
    "one": 0,
    "five": 5,
}  # {'two': 2, 'one': 0, 'four': 4, 'three': 3, 'five': 5}, Create a new dictionary with the merged keys and values of d and other, which must both be dictionaries. The values of other take priority when d and other share keys.
d |= {
    "one": 0,
    "five": 5,
}  # d == {'two': 2, 'one': 0, 'four': 4, 'three': 3, 'five': 5}



class _SNode:
    def __init__(self, data, next=None):
        self.data = data
        self.next = next


class SinglyLinkedList:
    def __init__(self):
        self.head = None
        self.tail = None
        self.size = 0

    def __len__(self):  # O(1)
        return self.size

    def is_empty(self):  # O(1)
        return self.head is None

    def __getitem__(self, num):  # O(num)
        if not 0 <= num < self.size:
            raise IndexError("list assignment index out of range")
        cur = self.head
        for _ in range(0, num):
            cur = cur.next
        return cur.data

    def __setitem__(self, num, x):  # O(num)
        if not 0 <= num < self.size:
            raise IndexError("list assignment index out of range")
        cur = self.head
        for _ in range(0, num):
            cur = cur.next
        cur.data = x

    def prepend(self, x):  # O(1)
        self.head = _SNode(x, self.head)
        if self.tail is None:
            self.tail = self.head
        self.size += 1

    def append(self, x):  # O(1)
        node = _SNode(x)
        if self.tail is None:
            self.head = self.tail = node
        else:
            self.tail.next = node
            self.tail = node
        self.size += 1

    def pop_front(self):  # O(1)
        if self.head is None:
            raise IndexError("pop from empty list")
        x = self.head.data
        self.head = self.head.next
        self.size -= 1
        if self.head is None:
            self.tail = None
        return x

    def pop_back(self):  # O(1)
        if self.tail is None:
            raise IndexError("pop from empty list")
        x = self.tail.data
        if self.head is self.tail:
            self.head = self.tail = None
        else:
            cur = self.head
            while cur.next is not self.tail:
                cur = cur.next
            cur.next = None
            self.tail = cur
        self.size -= 1
        return x

    def remove_front(self):  # O(1)
        if self.head is None:
            raise IndexError("remove from empty list")
        if self.head is self.tail:
            self.head = self.tail = None
        else:
            self.head = self.head.next
        self.size -= 1

    def remove_back(self):  # O(1)
        if self.tail is None:
            raise IndexError("remove from empty list")
        if self.head is self.tail:
            self.head = self.tail = None
        else:
            cur = self.head
            while cur.next is not self.tail:
                cur = cur.next
            cur.next = None
            self.tail = cur
        self.size -= 1

    def __iter__(self):
        cur = self.head
        while cur is not None:
            yield cur.data
            cur = cur.next

    def __reversed__(self):
        cur = self.tail
        while cur is not None:
            yield cur.data
            cur = cur.prev


class _DNode:
    def __init__(self, data, prev=None, next=None):
        self.data = data
        self.prev = prev
        self.next = next


class DoublyLinkedList:
    def __init__(self):
        self.head = None
        self.tail = None
        self.size = 0

    def __len__(self):  # O(1)
        return self.size

    def is_empty(self):  # O(1)
        return self.size == 0

    def __getitem__(self, num):  # O(min(n, size - n)), n = num if num > 0 else num + size
        if not -self.size <= num < self.size:
            raise IndexError("list assignment index out of range")
        if num * 2 >= self.size:
            num = self.size - num - 1
        elif num < 0:
            num += self.size
        if num >= 0:
            cur = self.head
            for _ in range(0, num):
                cur = cur.next
        else:
            cur = self.tail
            for _ in range(-1, num, -1):
                cur = cur.prev
        return cur.data

    def __setitem__(self, num, x):  # O(min(n, size - n)), n = num if num > 0 else num + size
        if not -self.size <= num < self.size:
            raise IndexError("list assignment index out of range")
        if num * 2 >= self.size:
            num = self.size - num - 1
        elif num < 0:
            num += self.size
        if num >= 0:
            cur = self.head
            for _ in range(0, num):
                cur = cur.next
        else:
            cur = self.tail
            for _ in range(-1, num, -1):
                cur = cur.prev
        cur.data = x

    def prepend(self, x):  # O(1)
        node = _DNode(None, self.head)
        if self.head is None:
            self.head = self.tail = node
        else:
            self.head.prev = node
            self.head = node
        self.size += 1

    def append(self, x):  # O(1)
        node = _DNode(x, self.tail, None)
        if self.tail is None:
            self.head = self.tail = node
        else:
            self.tail.next = node
            self.tail = node
        self.size += 1

    def pop_front(self):  # O(1)
        if self.head is None:
            raise IndexError("pop from empty list")
        x = self.head.data
        self.head = self.head.next
        self.size -= 1
        if self.head is None:
            self.tail = None
        else:
            self.head.prev = None
        return x

    def pop_back(self):  # O(1)
        if self.tail is None:
            raise IndexError("pop from empty list")
        x = self.tail.data
        self.tail = self.tail.prev
        self.size -= 1
        if self.tail is None:
            self.head = None
        else:
            self.tail.next = None
        return x

    def pop_node(self, node):  # O(1)
        if self.head is None:
            raise IndexError("remove from empty list")
        if self.head is node:
            return self.pop_front()
        elif self.tail is node:
            return self.pop_back()
        node.prev.next = node.next
        node.next.prev = node.prev
        self.size -= 1
        return node.data

    def peek_front(self):  # O(1)
        if self.is_empty():
            raise IndexError("peek at empty list")
        return self.head.data

    def peek_back(self):  # O(1)
        if self.is_empty():
            raise IndexError("peek at empty list")
        return self.tail.data

    def clear(self):  # O(1)
        self.head = None
        self.tail = None
        self.size = 0

    def __iter__(self):
        cur = self.head
        while cur is not None:
            yield cur.data
            cur = cur.next

    def __reversed__(self):
        cur = self.tail
        while cur is not None:
            yield cur.data
            cur = cur.prev


class BlockListDeque:  # Both ends IO amortized O(1)
    def __init__(self, block_size=64, front_step=1, back_step=1):
        if block_size <= 0:
            raise ValueError("deque block_size must >0")
        if front_step <= 0:
            raise ValueError("deque front_step must >0")
        if back_step <= 0:
            raise ValueError("deque back_step must >0")
        self.block_size = block_size
        self.front_step = front_step
        self.back_step = back_step
        self.data = [[None] * self.block_size for _ in range(self.front_step + self.back_step - 1)]
        self.block_begin = 0
        self.block_end = self.block_begin + 1
        self.in_begin = (self.block_size - 1) // 2
        self.in_end = self.in_begin
        self.size = 0

    def __len__(self):
        return self.size

    def is_empty(self):
        return self.size == 0

    def capacity(self):
        return self.block_size * len(self.data)

    def is_valid(self):
        return self.size == self.block_size * (self.block_end - self.block_begin - 1) + self.in_end - self.in_begin

    def __getitem__(self, index):  # O(1)
        if not -self.size <= index < self.size:
            raise IndexError("deque index out of range")
        if index < 0:
            index += self.size
        block_offset, in_block = divmod(self.in_begin + index, self.block_size)
        return self.data[self.block_begin + block_offset][in_block]

    def __setitem__(self, index, x):  # O(1)
        if not -self.size <= index < self.size:
            raise IndexError("deque assignment index out of range")
        if index < 0:
            index += self.size
        block_offset, in_block = divmod(self.in_begin + index, self.block_size)
        self.data[self.block_begin + block_offset][in_block] = x

    def reserve_front(self, blocks=None):
        if blocks is None:
            blocks = self.front_step
        new = [[None] * self.block_size for _ in range(blocks)]
        new.extend(self.data)
        self.data = new
        self.block_begin += blocks
        self.block_end += blocks

    def reserve_back(self, blocks=None):
        if blocks is None:
            blocks = self.back_step
        self.data.extend([[None] * self.block_size for _ in range(blocks)])

    def shrink_front_to_fit(self):
        new = self.data[self.block_begin :]
        self.data = new
        self.block_end -= self.block_begin
        self.block_begin = 0

    def shrink_back_to_fit(self):
        for i in range(self.block_end, len(self.data)):
            self.data.pop()

    def prepend(self, x):
        if self.in_begin != 0:
            self.in_begin -= 1
        else:
            if self.block_begin == 0:
                self.reserve_front()
            self.block_begin -= 1
            self.in_begin = self.block_size - 1
        self.data[self.block_begin][self.in_begin] = x
        self.size += 1

    def append(self, x):
        if self.in_end != self.block_size:
            self.in_end += 1
        else:
            if self.block_end == len(self.data):
                self.reserve_back()
            self.block_end += 1
            self.in_end = 1
        self.data[self.block_end - 1][self.in_end - 1] = x
        self.size += 1

    def pop_front(self):
        if self.is_empty():
            raise IndexError("pop from empty deque")
        x = self.data[self.block_begin][self.in_begin]
        self.data[self.block_begin][self.in_begin] = None
        self.size -= 1
        if self.in_begin != self.block_size - 1:
            self.in_begin += 1
        else:
            self.block_begin += 1
            self.in_begin = 0
        return x

    def pop_back(self):
        if self.is_empty():
            raise IndexError("pop from empty deque")
        x = self.data[self.block_end - 1][self.in_end - 1]
        self.data[self.block_end - 1][self.in_end - 1] = None
        self.size -= 1
        if self.in_end != 1:
            self.in_end -= 1
        else:
            self.block_end -= 1
            self.in_end = self.block_size
        return x

    def peek_front(self):
        if self.is_empty():
            raise IndexError("peek from empty deque")
        return self.data[self.block_begin][self.in_begin]

    def peek_back(self):
        if self.is_empty():
            raise IndexError("peek from empty deque")
        return self.data[self.block_end - 1][self.in_end - 1]

    def clear(self):
        for _ in range(self.size):
            self.pop_back()

    def __iter__(self):
        block = self.block_begin
        index = self.in_begin
        for _ in range(self.size):
            yield self.data[block][index]
            index += 1
            if index == self.block_size:
                index = 0
                block += 1

    def __reversed__(self):  # O(n)
        block = self.block_end - 1
        index = self.in_end - 1
        for _ in range(self.size):
            yield self.data[block][index]
            index -= 1
            if index < 0:
                index = self.block_size - 1
                block -= 1
```