

# Assignment 3 for CS224d

Lifu Huang

April 2016

## 1 RNN's(Recursive Neural Network)

(a)

$$\begin{aligned}\delta^{(s)} &= \hat{y} - y \\ \delta^{(1)} &= f'(h^{(1)}) \circ (U^T \delta^{(s)} + \delta_{above}) \\ \delta_{below} &= (W^{(1)})^T \delta^{(1)} \\ \nabla_U J &= \delta^{(s)} (h^{(1)})^T \\ \nabla_{b^{(s)}} J &= \delta^{(s)} \\ \nabla_{W^{(1)}} J &= \delta^{(1)} \begin{bmatrix} h_{left}^{(1)}; h_{right}^{(1)} \end{bmatrix}^T \\ \nabla_{b^{(1)}} J &= \delta^{(1)} \\ \nabla_{[L_{left}; L_{right}]} J &= \delta_{below}\end{aligned}$$

(b)

Please see code files for details.

(c)  
(a)




Figure 1: Accuracy on Training and Dev Set over Epochs

(b)  
Beacause training for too many epochs may lead to the problem of over fitting.  
(c)




Figure 2: Confusion Matrix on Training Set




Figure 3: Confusion Matrix on Dev Set

(d)




Figure 4: Accuracy on Training and Dev Set over wvecDims

## 2 2-Layer Deep RNN's

(a)

$$\begin{aligned}\delta^{(s)} &= \hat{y} - y \\ \nabla_U J &= \delta^{(s)} (h^{(2)})^T \\ \nabla_{b^{(s)}} J &= \delta^{(s)}\end{aligned}$$

$$\begin{aligned}\delta^{(2)} &= f'(h^{(2)}) \circ (U^T \delta^{(s)}) \\ \nabla_{W^{(2)}} J &= \delta^{(2)} (h^{(1)})^T \\ \nabla_{b^{(2)}} J &= \delta^{(2)}\end{aligned}$$

$$\begin{aligned}\delta^{(1)} &= f'(h^{(1)}) \circ ((W^{(2)})^T \delta^{(2)} + \delta_{above}) \\ \nabla_{W^{(1)}} J &= \delta^{(1)} \begin{bmatrix} h_{left}^{(1)}; h_{right}^{(1)} \end{bmatrix}^T \\ \nabla_{b^{(1)}} J &= \delta^{(1)}\end{aligned}$$

$$\begin{aligned}\delta_{below} &= (W^{(1)})^T \delta^{(1)} \\ \nabla_{[L_{left}; L_{right}]} J &= \delta_{below}\end{aligned}$$

(b)

Please see code files for details.

(c)

(a)




Figure 5:

(b)




Figure 6: Confusion Matrix on Training Set




Figure 7: Confusion Matrix on Dev Set

(c)

Model RNN2 performs better on training set while worse on dev set, which indicates a typical problem of over fitting.

(d)




Figure 8: Accuracy on Training and Dev Set over middleDims

(d)

To be updated.

(e)

To be updated.

(f)

To be updated.

### **3 Extra Credit: Recursive Neural Tensor Networks**

To be updated.