

## Министерство науки и высшего образования Российской Федерации Федеральное государственное бюджетное образовательное учреждение высшего образования

## «Московский государственный технический университет имени Н.Э. Баумана» (МГТУ им. Н.Э. Баумана)

ФАКУЛЬТЕТ «Информатика и системы управления»

КАФЕДРА «Программное обеспечение ЭВМ и информационные технологии»

## Лабораторная работа $\mathbb{N}$ 8

Дисциплина Операционые системы.

Тема Создание виртуальной файловой системы.

Студент Степанов А. О.

Группа ИУ7-63Б

Оценка (баллы)

Преподаватель Рязанова Н.Ю.

## Листинг 1: Текст программы

```
1 #include linux/module.h>
2 #include linux/kernel.h>
3 #include ux/init.h>
4 \# include < linux / fs.h >
5 #include ux/time.h>
6 #include ux/slab.h>
7 #include ux/version.h>
9 #define wfs MAGIC NUMBER 0x13131313
10 #define SLABNAME "wfs_cache"
11
12 MODULE LICENSE("GPL");
13 MODULE AUTHOR("Alexander_Stepanov");
  MODULE_DESCRIPTION("BMSTU_operating_systems_VFS");
15
16 static int size = 7;
17 module param(size, int, 0);
18 static int number = 31;
19 module_param(number, int, 0);
20 static int sco = 0;
21
   static void* *line = NULL;
22
23
   static void co(void* p)
24
   {
25
       *(\mathbf{int}*)p = (\mathbf{int})p;
26
27
       sco++;
28
   }
29
   struct kmem cache *cache = NULL;
30
31
32
   static struct wfs_inode
33
   {
34
        int i_mode;
35
        unsigned long i ino;
   } wfs inode;
36
37
38 static struct inode *wfs_make_inode(struct super_block *sb, int mode)
39
40
       struct inode *ret = new inode(sb);
41
```

```
if (ret)
42
43
       {
44
            inode init owner(ret, NULL, mode);
            ret->i size = PAGE SIZE;
45
            ret->i atime = ret->i mtime = ret->i ctime = current time(ret);
46
            ret->i private = &wfs inode;
47
48
       }
49
50
       return ret;
51
  }
52
53 static void wfs_put_super(struct super_block * sb)
54
       printk(KERN DEBUG "[wfs]_super_block_destroyed!\n");
55
56
  }
57
58 static struct super operations const wfs super ops = {
59
       .put super = wfs put super,
       .statfs = simple statfs,
60
       .drop_inode = generic_delete_inode,
61
62
  };
63
64 static int wfs fill sb(struct super block *sb, void *data, int silent)
65 {
66
       struct inode* root = NULL;
67
68
       sb->s blocksize = PAGE SIZE;
       sb->s blocksize bits = PAGE SHIFT;
69
70
       sb->s magic = wfs MAGIC NUMBER;
       sb->s op = \&wfs\_super\_ops;
71
72
       root = wfs make inode(sb, S IFDIR | 0755);
73
74
       if (!root)
75
       {
            printk \ (KERN\_ERR \ "[wfs]\_inode\_allocation\_failed! \ "");
76
77
            return -ENOMEM;
       }
78
79
80
                     = &simple_dir_inode_operations;
       root->i op
       root->i fop = &simple dir operations;
81
82
83
       sb->s root = d make root(root);
```

```
84
        if (!sb->s root)
85
        {
             printk(KERN ERR "[wfs]_root_creation_failed!\n");
86
             iput(root);
87
             return -ENOMEM;
88
89
        }
90
        return 0;
91
92 }
93
94
    static struct dentry* wfs mount(
        struct file_system_type *type, int flags, char const *dev, void *data
95
96
   {
97
98
        struct dentry* const entry = mount nodev(type, flags, data, wfs fill sb);
99
        if (IS ERR(entry))
100
             printk(KERN_ERR "[wfs]_mounting_failed!\n");
101
        else
102
             printk(KERN\_DEBUG "[wfs]\_mounted! \ n");
103
104
105
        return entry;
106
   }
107
    static struct file system type wfs type = {
108
109
        .owner = THIS MODULE,
        .name = "wfs",
110
        .mount = wfs mount,
111
        .kill sb = kill litter super,
112
113
    };
114
    static int init wfs init (void)
115
116
   {
117
        int i;
        int ret;
118
119
        if (size < 0)
120
121
        {
             printk(KERN_ERR "[wfs]_invalid_argument\n");
122
             return -EINVAL;
123
124
        }
```

125

```
line = kmalloc(sizeof(void*), GFP KERNEL);
126
127
        if (line == NULL)
128
129
        {
             printk(KERN ERR "[wfs]_kmalloc_error\n");
130
             kfree(line);
131
             return -ENOMEM;
132
        }
133
134
        cache = kmem cache create(SLABNAME, size, 0, SLAB HWCACHE ALIGN, co);
135
136
        if (cache == NULL)
137
138
        {
             printk(KERN ERR "[wfs]_kmem cache create_error\n");
139
             kmem cache destroy(cache);
140
             kfree(line);
141
             return -ENOMEM;
142
        }
143
144
        *line = kmem cache alloc(cache, GFP KERNEL)
145
        if (*line == NULL)
146
147
        {
             printk(KERN_ERR "[wfs]_kmem cache alloc_error\n");
148
149
             kmem cache free (cache, *line);
150
151
             kmem cache destroy(cache);
152
             kfree(*line);
153
154
             return -ENOMEM;
155
        }
156
157
        printk (KERN INFO "[wfs]_allocate_%d_objects_into_slab:_%s\n",
158
             1, SLABNAME);
159
        printk(KERN INFO "[wfs]_object_size_%d_bytes,_full_size_%ld_bytes\n",
160
161
             size, size);
        printk(KERN INFO "[wfs]_constructor_called_%d_times\n", sco);
162
163
164
        ret = register filesystem(&wfs type);
165
        if (ret!= 0)
166
167
        {
```

```
printk(KERN ERR "[wfs]_module_cannot_register_filesystem!\n");
168
             return ret;
169
        }
170
171
        printk(KERN DEBUG "[wfs]_module_loaded!\n");
172
173
        return 0;
174 }
175
176
    static void exit wfs exit(void)
177
    {
        int i;
178
179
        int ret;
180
        for (i = 0; i < number; i++)
181
            kmem cache free(cache, line[i]);
182
183
        kmem cache destroy(cache);
184
        kfree(line);
185
186
        ret = unregister filesystem(&wfs type);
187
188
        if (ret!= 0)
189
190
             printk(KERN ERR "[wfs]_module_cannot_unregister_filesystem!\n");
191
        printk(KERN DEBUG "[wfs]_module_unloaded!\n");
192
193
    }
194
    module init(wfs init);
195
196
    module exit (wfs exit);
```

```
~/Repositories/operating-systems/sem_02/lab_08/src 💆 🇗 feature/lab_08_sem_02 ❶
 -» make
make -C /lib/modules/5.6.10-3-MANJARO/build M=/home/alex/Repositories/operating-systems/sem_02/lab_08/src models
make[1]: вход в каталог «/usr/lib/modules/5.6.10-3-MANJARO/build»
  CC [M] /home/alex/Repositories/operating-systems/sem_02/lab_08/src/wfs.o
/home/alex/Repositories/operating-systems/sem_02/lab_08/src/wfs.c: В функции «co»:
/home/alex/Repositories/operating-systems/sem_02/lab_08/src/wfs.c:26:16: предупреждение: приведение указател
              *(int*)p = (int)p;
  MODPOST 1 modules
  CC [M] /home/alex/Repositories/operating-systems/sem_02/lab_08/src/wfs.mod.o
  LD [M] /home/alex/Repositories/operating-systems/sem_02/lab_08/src/wfs.ko
make[1]: выход из каталога «/usr/lib/modules/5.6.10-3-MANJARO/build»
  😕 ~/Repositories/operating-systems/sem_02/lab_08/src 💆 🗗 feature/lab_08_sem_02 🛭
» <u>sudo</u> insmod <u>wfs.ko</u>
~/Repositories/operating-systems/sem_02/lab_08/src ♥ 1/2 feature/lab_08_sem_02 ● sudo lsmod | grep wfs
                           16384 0
wfs
  😕 ~/Repositories/operating-systems/sem_02/lab_08/src 💆 🧗 feature/lab_08_sem_02 ❶
L» sudo dmesg | grep "\[wfs\]'
[17308.793430] [wfs] allocate 31 objects into slab: wfs_cache [17308.793432] [wfs] object size 7 bytes, full size 217 bytes [17308.793433] [wfs] constructor called 256 times [17308.793437] [wfs] module loaded!
  😕 ~/Repositories/operating-systems/sem_02/lab_08/src 💆 🗗 feature/lab_08_sem_02 🛭
L» sudo cat /proc/slabinfo| grep wfs
wfs_cache
                         256
                                  256
                                           16 256
                                                        1 : tunables
                                                                                       0 : slabdata
```

Рис. 1: Загрузка модуля

```
~/Repositories/operating-systems/sem_02/lab_08/src/test
L<sub>»</sub> touch image
  ~/Repositories/operating-systems/sem_02/lab_08/src/test
L_{
m w} md dir
  - > ~/Repositories/operating-systems/sem_02/lab_08/src/test
L<sub>»</sub> <u>sudo</u> mount -o loop -t wfs <u>./image</u> <u>./dir</u>
~/Repositories/operating-systems/sem_02/lab_08/src/test
» sudo dmesg | grep "\[wfs\]"
[17308.793430] [wfs] allocate 31 objects into slab: wfs_cache
[17308.793432] [wfs] object size 7 bytes, full size 217 bytes
[17308.793433] [wfs] constructor called 256 times
[17308.793437] [wfs] module loaded!
[17434.946328] [wfs] mounted!
  ~/Repositories/operating-systems/sem_02/lab_08/src/test
L<sub>» sudo</sub> umount <u>./dir</u>
  ~/Repositories/operating-systems/sem_02/lab_08/src/test
L<sub>» sudo</sub> dmesg | grep "\[wfs\]"
[17308.793430] [wfs] allocate 31 objects into slab: wfs_cache [17308.793432] [wfs] object size 7 bytes, full size 217 bytes
[17308.793433] [wfs] constructor called 256 times
[17308.793437] [wfs] module loaded!
[17434.946328] [wfs] mounted!
[17455.783357] [wfs] super block destroyed!
```

Рис. 2: Монтирование файловой системы

Рис. 3: Файловая система в дереве каталогов

Рис. 4: Выгрузка модуля

```
~/Repositories/operating-systems/sem_02/lab_08/src
L» sudo insmod wfs.ko size=64 number=128
 - 🖙 ~/Repositories/operating-systems/sem_02/lab_08/src 💆 🧗 fea
<sup>L</sup>» sudo dmesg | grep "\[wfs\]" | tail -4
[17580.157306] [wfs] allocate 128 objects into slab: wfs_cache
[17580.157308] [wfs] object size 64 bytes, full size 8192 bytes
[17580.157308] [wfs] constructor called 128 times
[17580.157313] [wfs] module loaded!
 - 🝃 ~/Repositories/operating-systems/sem_02/lab_08/src
                                                              జ ు౭fea
L<sub>»</sub> <u>sudo</u> cat <u>/proc/slabinfo</u>| grep wfs
wfs_cache
                      128
                              128
                                     128
                                            32
                                                  1 : tunables
                                                                   0
```

Рис. 5: Загрузка модуля с заданием параметров