



FMS Harness for 5th Gen Devices

Install GPS trackers faster and easier with **FMS Harness**.

FMS Harness is used to install advanced trackers into trucks. An additional connector for K-Line is provided in case the user would like to use K-Line with Tacho harness. CANbus and tachograph data are available with the FMS harness.

Applications

- CANbus data reading
- Tachograph data reading

Key Features

- Faster and easier installation
- Professional installation
- Minimize risk of faulty installations

Compatibility

✓ HCV5	✗ LCV5	✓ Pro5	✓ HCV5 Lite/Pro5 Lite	✗ Trace5
--------	--------	--------	-----------------------	----------

Environmental specifications

Temperature range	-35 to +75 °C
-------------------	---------------

Electrical specifications


Voltage range	Up to 32 V DC
Fuse type	ATO, 1A

Physical properties

Wire cross sectional area	0.5 mm ² (20 AWG)
Cable length	0.5 m
Open cable length	1 m
K-Line cable length	0.1 m


Pinout

FMS connector




Pin no.	Wire color	Function
1	Black	Ground
6	White	Device-specific*
7	Brown	K-Line
9	Blue	Device-specific*
10	Yellow	Ignition
12	Red	Power supply

14 pin connector




Pin no.	Wire color	Function
1	Red	Power supply (9-32 V)
2	Purple	DOUT1
3	Green/Yellow	1-Wire data
4	Pink	DIN3
5	Yellow	Device-specific*
6	Blue	Device-specific*
7	Brown	K-Line
8	Black	Ground
9	Orange	DOUT2
10	Red/Yellow	1-Wire power
11	Green	Device-specific*
12	Grey	AIN1
13	White	Device-specific*
14	Green/White	Device-specific*

K-Line connector from the FMS connector



Pin no.	Wire color	Function
1	Brown	K-Line
2	-	NC

K-Line connector from the 14 pin connector



Pin no.	Wire color	Function
1	Brown	K-Line
2	-	NC

*Pinout depends on the device type

Ordering information

K00090

0.5 m FMS harness with fuse, 8 open wires and additional K-Line connectors

Contact information:

Perkūnkiemio g. 6
LT-12130 Vilnius, Lithuania
Phone: +370 520 451 88
Web: www.ruptela.com

Datasheet v1.4
2022-05-20