Long text	Quantity	Item number
Primostar 3, full-K, HD Cam 8MP, SF22, 5 pos, 40x Ph2, ABBE 0.9 turret, 75x50 Complete configuration with full-Köhler stand including - transmitted-light slide-in modules with 6V 30W halogen lamp and LED 3W white light, 5600K - 5-position nosepiece, tilted backwards - mechanical rackless stage 75x50, drive right and specimen holder for two slides, with spring clip left - binocular tube 25°/22 with integrated camera 8MP - eyepieces 10x/22 Br.foc. with eyecups - objective iPlan-Achromat 40x Ph2 - ABBE condenser 0.9 with turret disk BF, DF, Ph1, Ph2, Ph3 - pinhole diaphragm, d=30mm - light manager - ECO-Mode - color filter set blue, green, yellow - 6V 30W halogen lamp (spare part) - country-specific power cable - dust cover Camera specification - Sensor: Sony CMOS image sensor Color, Rolling Shutter - Number of Pixel: 3840 (H) x 2160 (V) = 8.3MP, Ultra HD (4K) - Selectable Resolution: 3840 x 2160 = Ultra HD (4K) and 1920 x 1080 = Full HD (1080p) - Pixel size: 1.85 µm x 1.85 µm - Effective Area: 7.1 mm x 4.0 mm, equivalent to 1/2.1" (8.15 mm diagonal) - Spectral range: approx. 400 nm – 700 nm, IR filter - Stand-alone image storage format: TIFF or JPG - Video stream format: mp4 - Live frame rate via HDMI: 30 fps @ 4K/1080p (also with HDR) - Live frame rate through software via Ethernet or USB 3.0 (depending on hardware and software configuration), Exp. Time 1 ms: 3840 x 2160 up to 15 fps (ZEN blue edition) 1920 x 1080 up to 27 fps (ZEN blue edition) 1920 x 1080 up to 30 fps (Labscope) - Digitization: 8-bit/pixel - Integration time: 0.06 ms up to 1 s - Interfaces for Communication: HDMI for monitor USB 3.0 Type C for USB hub, flash drive, Wi-Fi adapter or PC connection Ethernet (RJ45) for LAN connection - Optical interface: integrated adapter - Max. file size per image: .tiff up to: 24 MB (not content dependent) .jpg up to: approx. 0.5 MB – 3.3 MB (content dependent) - Size/Weight: approx. 135 x 97 x 54 mm / 590 g - Passive cooling by aluminium cooling fins on the cover plate - Environmental conditions: +10°C to +40°C, max. 75% relative air humidity at 35°C, no condensation, free air circulation required - Operating systems for Labscope: Windows® 7/10 x64 Prof./Ultimate and iOS® v11 and higher/Android® 9.0 and higher Supported Application Software: Labscope v4.0 (Win, iOS® and Android®) and later and higher The camera is network-enabled and can be used with the ZEISS iOS® App/Android® App on Google® or Zeiss Portal and Labscope software. The App is available as a free download from the Apple® App Store or Google® Store. Unless otherwise stated by the distributor, iPad® and WLAN router are not supplied by ZEISS. Apple®, iPad®, iPad Pro®, iPhone® are registered trademarks of Apple Inc.	1	415501-0231-000
Objective iPlan-Achromat 4x/0.10 for Primostar 3 (WD=30.7mm)	1	415501-1600-000
Objective iPlan-Achromat 10x/0.25 Ph1 for Primostar 3 (WD=18.4mm)	1	415501-1615-000
Objective iPlan-Achromat 100x/1.25 Oil for Primostar 3 (WD=0.27mm), incl. Immersion oil, 5 ml	1	415501-1641-000
Power cord ZA/3-H03 2x0,75mm²-C7/1,8m bk	1	000000-0613-454
Includes shipping to Maputo		
Grand total with 10% reseller Discount	**€ 6 531,97**	