Long text	Quantity	Item number
Primostar 1, fix-K, tri, FOV20, 4 pos, ABBE 0.9, 75x40, pointer Complete configuration with fixed-Köhler stand including - Transmitted-light illumination LED 3W warm-light, 3200K - 4-position nosepiece, tilted backwards - mechanical rackless stage 75x40, drive right and specimen holder for one slide with spring clip left - trinocular tube 30°/20 - eyepieces 10x/20 Br.foc. with eyecups, 1x with pointer - objectives Plan-Achromat 4x, 10x, 40x - Abbe condenser 0.9/1.25 - external power unit 100...240VAC/50...60Hz/30VA with country-specific adapters - dust cover	1	415501-0131-000
Objective Plan-Achromat 100x/1.25 Oil for Primostar 1 (WD=0.14mm), incl. Immersion oil, 5 ml	1	415501-1653-000
Microscopy Camera Axiocam 212 color Most versatile color camera for education, documentation and routine applications with standalone capability, USB 3.0 and Ethernet connectivity with 64bit driver software for: ZEN (blue and core), Labscope and TWAIN plugin. Camera package contains the following accessories: - USB 3.0 flash drive, Type-C and Type-A - USB 3.0 cable Type-C to Type-A - Power & signal cable camera to microscope stand compatible with Axiolab 5 and Axioscope 5/7/Vario - Power adapter with country-specific plug Sensor: Sony CMOS image sensor Color, Rolling Shutter Number of Pixel (max): 4032 (H) x 3044 (V) = 12.3 MP, Full Sensor Selectable Resolution: 4032 (H) x 3044 (V) = 12.3 MP, Full Sensor 3840 (H) x 2160 (V) = 8.1 MP, Ultra HD (4K) 1920 (H) x 1080 (V) = 2.1 MP, Full HD (1080p) Pixel size: 1.85 µm x 1.85 µm (resolution 4032 x 3044 and 3840 x 2160) 3.70 µm x 3.70 µm (binned, resolution 1920 x 1080) Effective Sensor Area: 4032 x 3044: 7.4 mm x 5.7 mm, equivalent to 1/1.7" (9.3 mm diagonal) 3840 x 2160: 7.2 mm x 4.0 mm, equivalent to 1/2.1" (8.2 mm diagonal) 1920 x 1080: 7.2 mm x 4.0 mm, equivalent to 1/2.1" (8.2 mm diagonal) Spectral range: approx. 400 nm - 700 nm, IR filter; RGBBayer color mask Control buttons on camera: 1x Power on/off switch 1x Camera factory reset Status-LED for camera: color coded operation status Stand-alone: Image storage format: TIFF or JPG Video stream format: mp4 Live frame rate viaHDMI: 30 fps @ 4K/1080p Live frame rate through software via Ethernet or USB 3.0 (depending on hardware and software configuration), Exp. Time 1 ms: H x V Frame rate 4032 x 3044 up to 11 fps (ZEN (blue) / ZEN core) 3840 x 2160 up to 17 fps (ZEN (blue) / ZEN core) 1920 x 1080 up to 30 fps (ZEN (blue) / ZEN core) 1920 x 1080 up to 30 fps (Labscope) Digitization: 24-bit (3 x 8-bit RGB) A/D conversion Integration time: 0.1msup to 1 s Gain: 0x - 27x Interfaces for Communication and for Power: 1x HDMI for monitor 1x USB 3.0 Type C for USB flash drive, Wi-Fi adapter or PC connection 2x USB 2.0 Type A for mouse and keyboard 1x RJ45 (Ethernet) for LAN connection 1x M8 for power and communication with dedicated stands Optical interface: C-mount Size/Weight: approx. 125 x 92 x 78mm / 700 g Housing: Blue painted aluminum and cooling fins Registration: CE, CSA, UKCA Power supply: via M8interface Power consumption: max. 36 W (24 V DC,1.5 A) Environmental conditions: +5°C to +35°C, max. 75% relative air humidity at 35°C, no condensation, free air circulation required, CATII, pollution degree 2, altitude <2000m, indoor use Supported Operating systems: for ZEN: Windows 10 / Windows 11 for Labscope: Windows 10 and 11 x64 and higher, iOS v15 and higher, Android 12 and higher Supported Application Software: ZEN 3.11 (blue edition) and higher ZEN core 3.11 and higher Labscope v4.4 and higher (Windows, iOS and Android) TWAIN plugin: Software interface to control camera by 3rd party application software The camera is network-enabled and can be used with the ZEISSiOS App, Android APP and ZEISS Labscope software. The Apps are available as a free download from the Apple® App Store, Google Play Store or ZEISS Portal. Unless otherwise stated by the distributor, iPad® and WLAN router are not supplied by ZEISS. Apple®, Apple iPad® are registered trademarks of Apple Inc.	1	426570-9901-000
Camera Adapter P95-C 1/2" 0.5x for Primo Star and Primostar 1	1	415500-1811-000
Includes shipping to Maputo		
Grand total with 10% reseller Discount	**€ 4 007,67**	